

HepMC Reference Manual

2.06.05

Generated by Doxygen 1.4.7

Thu Apr 21 16:31:24 2011

Contents

1	HepMC Directory Hierarchy	1
1.1	HepMC Directories	1
2	HepMC Namespace Index	3
2.1	HepMC Namespace List	3
3	HepMC Hierarchical Index	5
3.1	HepMC Class Hierarchy	5
4	HepMC Class Index	7
4.1	HepMC Class List	7
5	HepMC File Index	11
5.1	HepMC File List	11
6	HepMC Page Index	13
6.1	HepMC Related Pages	13
7	HepMC Directory Documentation	15
7.1	/home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/examples/ Directory Reference	15
7.2	/home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/fio/ Directory Reference	16
7.3	/home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/HepMC/ Directory Reference	17
7.4	/home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/src/ Directory Reference	18
7.5	/home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/test/ Directory Reference	19
8	HepMC Namespace Documentation	21
8.1	CLHEP Namespace Reference	21
8.2	detail Namespace Reference	22
8.3	HepMC Namespace Reference	23
8.4	HepMC::detail Namespace Reference	35
8.5	HepMC::Units Namespace Reference	39

8.6	Units Namespace Reference	41
9	HepMC Class Documentation	43
9.1	HepMC::ConstGenEventParticleRange Class Reference	43
9.2	HepMC::ConstGenEventVertexRange Class Reference	45
9.3	HepMC::ConstGenParticleEndRange Class Reference	46
9.4	HepMC::ConstGenParticleProductionRange Class Reference	47
9.5	HepMC::detail::disable_if<, > Struct Template Reference	48
9.6	HepMC::detail::disable_if< false, T > Struct Template Reference	49
9.7	HepMC::detail::enable_if<, > Struct Template Reference	50
9.8	HepMC::detail::enable_if< true, T > Struct Template Reference	51
9.9	HepMC::Flow Class Reference	52
9.10	HepMC::FourVector Class Reference	59
9.11	HepMC::GenCrossSection Class Reference	69
9.12	HepMC::GenEvent Class Reference	73
9.13	HepMC::GenEvent::particle_const_iterator Class Reference	96
9.14	HepMC::GenEvent::particle_iterator Class Reference	99
9.15	HepMC::GenEvent::vertex_const_iterator Class Reference	102
9.16	HepMC::GenEvent::vertex_iterator Class Reference	105
9.17	HepMC::GenEventParticleRange Class Reference	109
9.18	HepMC::GenEventVertexRange Class Reference	110
9.19	HepMC::GenParticle Class Reference	111
9.20	HepMC::GenParticleEndRange Class Reference	122
9.21	HepMC::GenParticleProductionRange Class Reference	124
9.22	HepMC::GenVertex Class Reference	126
9.23	HepMC::GenVertex::edge_iterator Class Reference	141
9.24	HepMC::GenVertex::particle_iterator Class Reference	144
9.25	HepMC::GenVertex::vertex_iterator Class Reference	147
9.26	HepMC::GenVertexParticleRange Class Reference	151
9.27	HepMC::HeavyIon Class Reference	152
9.28	HepMC::HEPEVT_Wrapper Class Reference	160
9.29	hwgev Struct Reference	173
9.30	HepMC::IO_AsciiParticles Class Reference	176
9.31	HepMC::IO_BaseClass Class Reference	179
9.32	HepMC::IO_Exception Class Reference	182
9.33	HepMC::IO_GenEvent Class Reference	184
9.34	HepMC::IO_HEPEVT Class Reference	188

9.35	HepMC::IO_HERWIG Class Reference	193
9.36	HepMC::detail::is_arithmetic< T > Struct Template Reference	200
9.37	HepMC::detail::is_arithmetic< char > Struct Template Reference	201
9.38	HepMC::detail::is_arithmetic< double > Struct Template Reference	202
9.39	HepMC::detail::is_arithmetic< float > Struct Template Reference	203
9.40	HepMC::detail::is_arithmetic< int > Struct Template Reference	204
9.41	HepMC::detail::is_arithmetic< long > Struct Template Reference	205
9.42	HepMC::detail::is_arithmetic< long double > Struct Template Reference	206
9.43	HepMC::detail::is_arithmetic< short > Struct Template Reference	207
9.44	HepMC::detail::is_arithmetic< signed char > Struct Template Reference	208
9.45	HepMC::detail::is_arithmetic< unsigned char > Struct Template Reference	209
9.46	HepMC::detail::is_arithmetic< unsigned int > Struct Template Reference	210
9.47	HepMC::detail::is_arithmetic< unsigned long > Struct Template Reference	211
9.48	HepMC::detail::is_arithmetic< unsigned short > Struct Template Reference	212
9.49	IsEventGood Class Reference	213
9.50	IsFinalState Class Reference	214
9.51	IsGoodEvent Class Reference	215
9.52	IsGoodEventMyPythia Class Reference	216
9.53	IsPhoton Class Reference	217
9.54	IsStateFinal Class Reference	218
9.55	IsW_Boson Class Reference	219
9.56	HepMC::PdfInfo Class Reference	220
9.57	pin3 Struct Reference	227
9.58	pin5 Struct Reference	228
9.59	pin7 Struct Reference	229
9.60	pin8 Struct Reference	230
9.61	pin9 Struct Reference	231
9.62	HepMC::Polarization Class Reference	232
9.63	PrintChildren Class Reference	237
9.64	PrintDescendants Class Reference	238
9.65	PrintParticle Class Reference	239
9.66	PrintPhoton Class Reference	240
9.67	prvvnv Struct Reference	241
9.68	prvpm Struct Reference	243
9.69	pssm Struct Reference	244
9.70	HepMC::StreamInfo Class Reference	245

9.71 HepMC::TempParticleMap Class Reference	251
9.72 HepMC::ThreeVector Class Reference	254
9.73 HepMC::WeightContainer Class Reference	260
10 HepMC File Documentation	267
10.1 CompareGenEvent.cc File Reference	267
10.2 CompareGenEvent.h File Reference	268
10.3 enable_if.h File Reference	269
10.4 example_BuildEventFromScratch.cc File Reference	270
10.5 example_EventSelection.cc File Reference	271
10.6 example_MyHerwig.cc File Reference	272
10.7 example_MyPythia.cc File Reference	273
10.8 example_MyPythiaOnlyToHepMC.cc File Reference	276
10.9 example_PythiaStreamIO.cc File Reference	277
10.10example_UsingIterators.cc File Reference	279
10.11filterEvent.cc File Reference	280
10.12Flow.cc File Reference	281
10.13Flow.h File Reference	282
10.14GenCrossSection.cc File Reference	283
10.15GenCrossSection.h File Reference	284
10.16GenEvent.cc File Reference	285
10.17GenEvent.h File Reference	286
10.18GenEventStreamIO.cc File Reference	288
10.19GenParticle.cc File Reference	290
10.20GenParticle.h File Reference	291
10.21GenRanges.cc File Reference	292
10.22GenRanges.h File Reference	293
10.23GenVertex.cc File Reference	294
10.24GenVertex.h File Reference	295
10.25HeavyIon.cc File Reference	296
10.26HeavyIon.h File Reference	297
10.27HEPEVT_Wrapper.cc File Reference	298
10.28HEPEVT_Wrapper.h File Reference	299
10.29HepMCDefs.h File Reference	301
10.30HerwigWrapper.cc File Reference	302
10.31HerwigWrapper.h File Reference	303
10.32initPythia.cc File Reference	318

10.33IO_AsciiParticles.cc File Reference	319
10.34IO_AsciiParticles.h File Reference	320
10.35IO_BaseClass.h File Reference	321
10.36IO_Exception.h File Reference	322
10.37IO_GenEvent.cc File Reference	323
10.38IO_GenEvent.h File Reference	324
10.39IO_HEPEVT.cc File Reference	325
10.40IO_HEPEVT.h File Reference	326
10.41IO_HERWIG.cc File Reference	327
10.42IO_HERWIG.h File Reference	328
10.43is_arithmetic.h File Reference	329
10.44IsGoodEvent.h File Reference	330
10.45IteratorRange.h File Reference	331
10.46list_of_examples.cc File Reference	332
10.47list_of_examples.cc File Reference	333
10.48PdfInfo.cc File Reference	334
10.49PdfInfo.h File Reference	335
10.50Polarization.cc File Reference	336
10.51Polarization.h File Reference	337
10.52PythiaHelper.h File Reference	338
10.53PythiaWrapper.cc File Reference	339
10.54PythiaWrapper.h File Reference	341
10.55PythiaWrapper6_4.h File Reference	342
10.56PythiaWrapper6_4_WIN32.h File Reference	355
10.57SearchVector.cc File Reference	356
10.58SearchVector.h File Reference	357
10.59SimpleVector.h File Reference	358
10.60StreamHelpers.cc File Reference	359
10.61StreamHelpers.h File Reference	360
10.62StreamInfo.cc File Reference	361
10.63StreamInfo.h File Reference	362
10.64TempParticleMap.h File Reference	363
10.65testFlow.cc File Reference	364
10.66testHepMCIteration.h File Reference	365
10.67testHepMCMethods.cc File Reference	366
10.68testHepMCMethods.h File Reference	367

10.69testHerwigCopies.cc File Reference	368
10.70testPolarization.cc File Reference	369
10.71testPrintBug.cc File Reference	370
10.72testPythiaCopies.cc File Reference	371
10.73testSimpleVector.cc File Reference	372
10.74testUnits.cc File Reference	373
10.75testWeights.cc File Reference	374
10.76Units.h File Reference	375
10.77VectorConversion.h File Reference	376
10.78Version.h File Reference	377
10.79WeightContainer.cc File Reference	378
10.80WeightContainer.h File Reference	379
11 HepMC Example Documentation	381
11.1 example_BuildEventFromScratch.cc	381
11.2 example_EventSelection.cc	384
11.3 example_MyHerwig.cc	386
11.4 example_MyPythia.cc	388
11.5 example_MyPythiaOnlyToHepMC.cc	393
11.6 example_PythiaStreamIO.cc	395
11.7 example_UsingIterators.cc	398
11.8 testFlow.cc	401
11.9 testHepMC.cc.in	405
11.10testHepMCIteration.cc.in	412
11.11testHerwigCopies.cc	418
11.12testMass.cc.in	420
11.13testMultipleCopies.cc.in	423
11.14testPrintBug.cc	426
11.15testPythiaCopies.cc	427
11.16testSimpleVector.cc	429
11.17testStreamIO.cc.in	432
11.18testUnits.cc	437
11.19VectorConversion.h	439
12 HepMC Page Documentation	441
12.1 Todo List	441

Chapter 1

HepMC Directory Hierarchy

1.1 HepMC Directories

This directory hierarchy is sorted roughly, but not completely, alphabetically:

examples	15
fio	16
HepMC	17
src	18
test	19

Chapter 2

HepMC Namespace Index

2.1 HepMC Namespace List

Here is a list of all namespaces with brief descriptions:

CLHEP	21
detail	22
HepMC	23
HepMC::detail	35
HepMC::Units	39
Units	41

Chapter 3

HepMC Hierarchical Index

3.1 HepMC Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

HepMC::ConstGenEventParticleRange	43
HepMC::ConstGenEventVertexRange	45
HepMC::ConstGenParticleEndRange	46
HepMC::ConstGenParticleProductionRange	47
HepMC::detail::disable_if<, >	48
HepMC::detail::disable_if< false, T >	49
HepMC::detail::enable_if<, >	50
HepMC::detail::enable_if< true, T >	51
std::exception	
std::runtime_error	
HepMC::IO_Exception	182
HepMC::Flow	52
HepMC::FourVector	59
HepMC::GenCrossSection	69
HepMC::GenEvent	73
HepMC::GenEvent::particle_const_iterator	96
HepMC::GenEvent::particle_iterator	99
HepMC::GenEvent::vertex_const_iterator	102
HepMC::GenEvent::vertex_iterator	105
HepMC::GenEventParticleRange	109
HepMC::GenEventVertexRange	110
HepMC::GenParticle	111
HepMC::GenParticleEndRange	122
HepMC::GenParticleProductionRange	124
HepMC::GenVertex	126
HepMC::GenVertex::edge_iterator	141
HepMC::GenVertex::particle_iterator	144
HepMC::GenVertex::vertex_iterator	147
HepMC::GenVertexParticleRange	151
HepMC::HeavyIon	152
HepMC::HEPEVT_Wrapper	160
hwgev	173
HepMC::IO_BaseClass	179

HepMC::IO_AsciiParticles	176
HepMC::IO_GenEvent	184
HepMC::IO_HEPEVT	188
HepMC::IO_HERWIG	193
HepMC::detail::is_arithmetic< T >	200
HepMC::detail::is_arithmetic< char >	201
HepMC::detail::is_arithmetic< double >	202
HepMC::detail::is_arithmetic< float >	203
HepMC::detail::is_arithmetic< int >	204
HepMC::detail::is_arithmetic< long >	205
HepMC::detail::is_arithmetic< long double >	206
HepMC::detail::is_arithmetic< short >	207
HepMC::detail::is_arithmetic< signed char >	208
HepMC::detail::is_arithmetic< unsigned char >	209
HepMC::detail::is_arithmetic< unsigned int >	210
HepMC::detail::is_arithmetic< unsigned long >	211
HepMC::detail::is_arithmetic< unsigned short >	212
IsEventGood	213
IsFinalState	214
IsGoodEvent	215
IsGoodEventMyPythia	216
IsPhoton	217
IsStateFinal	218
IsW_Boson	219
HepMC::PdfInfo	220
pin3	227
pin5	228
pin7	229
pin8	230
pin9	231
HepMC::Polarization	232
PrintChildren	237
PrintDescendants	238
PrintParticle	239
PrintPhoton	240
prvnm	241
prvpm	243
pssm	244
HepMC::StreamInfo	245
HepMC::TempParticleMap	251
HepMC::ThreeVector	254
HepMC::WeightContainer	260

Chapter 4

HepMC Class Index

4.1 HepMC Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

HepMC::ConstGenEventParticleRange (ConstGenEventParticleRange (p. 43) acts like a collection of particles)	43
HepMC::ConstGenEventVertexRange (ConstGenEventVertexRange (p. 45) acts like a collection of vertices)	45
HepMC::ConstGenParticleEndRange	46
HepMC::ConstGenParticleProductionRange	47
HepMC::detail::disable_if<, > (Internal - used by SimpleVector to decide if a class is arithmetic)	48
HepMC::detail::disable_if< false, T > (Internal - used by SimpleVector to decide if a class is arithmetic)	49
HepMC::detail::enable_if<, > (Internal - used to decide if a class is arithmetic)	50
HepMC::detail::enable_if< true, T > (Internal - use if class T is arithmetic)	51
HepMC::Flow (The flow object)	52
HepMC::FourVector (FourVector (p. 59) is a simple representation of a physics 4 vector)	59
HepMC::GenCrossSection (The GenCrossSection (p. 69) class stores the generated cross section)	69
HepMC::GenEvent (The GenEvent (p. 73) class is the core of HepMC (p. 23))	73
HepMC::GenEvent::particle_const_iterator (Const particle iterator)	96
HepMC::GenEvent::particle_iterator (Non-const particle iterator)	99
HepMC::GenEvent::vertex_const_iterator (Const vertex iterator)	102
HepMC::GenEvent::vertex_iterator (Non-const vertex iterator)	105
HepMC::GenEventParticleRange (GenEventParticleRange (p. 109) acts like a collection of particles)	109
HepMC::GenEventVertexRange (GenEventVertexRange (p. 110) acts like a collection of vertices)	110
HepMC::GenParticle (The GenParticle (p. 111) class contains information about generated particles)	111
HepMC::GenParticleEndRange (GenParticleEndRange (p. 122) acts like a collection of particles)	122
HepMC::GenParticleProductionRange (GenParticleProductionRange (p. 124) acts like a collection of particles)	124
HepMC::GenVertex (GenVertex (p. 126) contains information about decay vertices)	126
HepMC::GenVertex::edge_iterator (Edge iterator)	141

HepMC::GenVertex::particle_iterator (Particle iterator)	144
HepMC::GenVertex::vertex_iterator (Vertex iterator)	147
HepMC::GenVertexParticleRange (GenVertexParticleRange (p. 151) acts like a collection of particles)	151
HepMC::HeavyIon (The HeavyIon (p. 152) class stores information about heavy ions) . . .	152
HepMC::HEPEVT_Wrapper (Generic Wrapper for the fortran HEPEVT common block)	160
hwgev	173
HepMC::IO_AsciiParticles (Event input/output in ascii format for eye and machine reading)	176
HepMC::IO_BaseClass (All input/output classes inherit from IO_BaseClass (p. 179)) . . .	179
HepMC::IO_Exception (IO exception handling)	182
HepMC::IO_GenEvent (IO_GenEvent (p. 184) also deals with HeavyIon (p. 152) and Pdf-Info (p. 220))	184
HepMC::IO_HEPEVT (HEPEVT IO class)	188
HepMC::IO_HERWIG (IO_HERWIG (p. 193) is used to get Herwig information)	193
HepMC::detail::is_arithmetic< T > (Undefined and therefore non-arithmetic)	200
HepMC::detail::is_arithmetic< char > (Character is arithmetic)	201
HepMC::detail::is_arithmetic< double > (Double is arithmetic)	202
HepMC::detail::is_arithmetic< float > (Float is arithmetic)	203
HepMC::detail::is_arithmetic< int > (Int is arithmetic)	204
HepMC::detail::is_arithmetic< long > (Long is arithmetic)	205
HepMC::detail::is_arithmetic< long double > (Long double is arithmetic)	206
HepMC::detail::is_arithmetic< short > (Short is arithmetic)	207
HepMC::detail::is_arithmetic< signed char > (Signed character is arithmetic)	208
HepMC::detail::is_arithmetic< unsigned char > (Unsigned character is arithmetic)	209
HepMC::detail::is_arithmetic< unsigned int > (Unsigned int is arithmetic)	210
HepMC::detail::is_arithmetic< unsigned long > (Unsigned long is arithmetic)	211
HepMC::detail::is_arithmetic< unsigned short > (Unsigned short is arithmetic)	212
IsEventGood (Example class)	213
IsFinalState	214
IsGoodEvent (Used in the tests)	215
IsGoodEventMyPythia (Example class)	216
IsPhoton (Example class)	217
IsStateFinal (Example class)	218
IsW_Boson (Example class)	219
HepMC::PdfInfo (The PdfInfo (p. 220) class stores PDF information)	220
pin3	227
pin5	228
pin7	229
pin8	230
pin9	231
HepMC::Polarization (The Polarization (p. 232) class stores theta and phi for a GenParticle (p. 111))	232
PrintChildren (Test class)	237
PrintDescendants (Test class)	238
PrintParticle	239
PrintPhoton	240
prvrv	241
prvpm	243
pssm	244
HepMC::StreamInfo (StreamInfo (p. 245) contains extra information needed when using streaming IO)	245
HepMC::TempParticleMap (TempParticleMap (p. 251) is a temporary GenParticle* container used during input)	251

HepMC::ThreeVector (ThreeVector (p. 254) is a simple representation of a position or displacement 3 vector)	254
HepMC::WeightContainer (Container for the Weights associated with an event or vertex)	260

Chapter 5

HepMC File Index

5.1 HepMC File List

Here is a list of all files with brief descriptions:

CompareGenEvent.cc	267
CompareGenEvent.h	268
enable_if.h	269
example_BuildEventFromScratch.cc	270
example_EventSelection.cc	271
example_MyHerwig.cc	272
example_MyPythia.cc	273
example_MyPythiaOnlyToHepMC.cc	276
example_PythiaStreamIO.cc	277
example_UsingIterators.cc	279
filterEvent.cc	280
Flow.cc	281
Flow.h	282
GenCrossSection.cc	283
GenCrossSection.h	284
GenEvent.cc	285
GenEvent.h	286
GenEventStreamIO.cc	288
GenParticle.cc	290
GenParticle.h	291
GenRanges.cc	292
GenRanges.h	293
GenVertex.cc	294
GenVertex.h	295
HeavyIon.cc	296
HeavyIon.h	297
HEPEVT_Wrapper.cc	298
HEPEVT_Wrapper.h	299
HepMCDefs.h	301
HerwigWrapper.cc	302
HerwigWrapper.h	303
initPythia.cc	318
IO_AsciiParticles.cc	319

IO_AsciiParticles.h	320
IO_BaseClass.h	321
IO_Exception.h	322
IO_GenEvent.cc	323
IO_GenEvent.h	324
IO_HEPEVT.cc	325
IO_HEPEVT.h	326
IO_HERWIG.cc	327
IO_HERWIG.h	328
is_arithmetic.h	329
IsGoodEvent.h	330
IteratorRange.h	331
examples/list_of_examples.cc	332
test/list_of_examples.cc	333
PdfInfo.cc	334
PdfInfo.h	335
Polarization.cc	336
Polarization.h	337
PythiaHelper.h	338
PythiaWrapper.cc	339
PythiaWrapper.h	341
PythiaWrapper6_4.h	342
PythiaWrapper6_4_WIN32.h	355
SearchVector.cc	356
SearchVector.h	357
SimpleVector.h	358
StreamHelpers.cc	359
StreamHelpers.h	360
StreamInfo.cc	361
StreamInfo.h	362
TempParticleMap.h	363
testFlow.cc	364
testHepMCIteration.h	365
testHepMCMethods.cc	366
testHepMCMethods.h	367
testHerwigCopies.cc	368
testPolarization.cc	369
testPrintBug.cc	370
testPythiaCopies.cc	371
testSimpleVector.cc	372
testUnits.cc	373
testWeights.cc	374
Units.h	375
VectorConversion.h	376
Version.h	377
WeightContainer.cc	378
WeightContainer.h	379

Chapter 6

HepMC Page Index

6.1 HepMC Related Pages

Here is a list of all related documentation pages:

Todo List	441
---------------------	-----

Chapter 7

HepMC Directory Documentation

7.1 `/home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/examples/` Directory Reference

Files

- file `example_BuildEventFromScratch.cc`
- file `example_EventSelection.cc`
- file `example_MyHerwig.cc`
- file `example_MyPythia.cc`
- file `example_MyPythiaOnlyToHepMC.cc`
- file `example_PythiaStreamIO.cc`
- file `example_UsingIterators.cc`
- file `initPythia.cc`
- file `examples/list_of_examples.cc`
- file `PythiaHelper.h`
- file `testHerwigCopies.cc`
- file `testPythiaCopies.cc`
- file `VectorConversion.h`

7.2 /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/fio/ Directory Reference

Files

- file **HEPEVT_Wrapper.cc**
- file **HerwigWrapper.cc**
- file **IO_HEPEVT.cc**
- file **IO_HERWIG.cc**
- file **PythiaWrapper.cc**

7.3 /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/HepMC/ Directory Reference

Files

- file CompareGenEvent.h
- file enable_if.h
- file Flow.h
- file GenCrossSection.h
- file GenEvent.h
- file GenParticle.h
- file GenRanges.h
- file GenVertex.h
- file HeavyIon.h
- file HEPEVT_Wrapper.h
- file HepMCDefs.h
- file HerwigWrapper.h
- file IO_AsciiParticles.h
- file IO_BaseClass.h
- file IO_Exception.h
- file IO_GenEvent.h
- file IO_HEPEVT.h
- file IO_HERWIG.h
- file is_arithmetic.h
- file IteratorRange.h
- file PdfInfo.h
- file Polarization.h
- file PythiaWrapper.h
- file PythiaWrapper6_4.h
- file PythiaWrapper6_4_WIN32.h
- file SearchVector.h
- file SimpleVector.h
- file StreamHelpers.h
- file StreamInfo.h
- file TempParticleMap.h
- file Units.h
- file Version.h
- file WeightContainer.h

7.4 /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/src/ Directory Reference

Files

- file CompareGenEvent.cc
- file filterEvent.cc
- file Flow.cc
- file GenCrossSection.cc
- file GenEvent.cc
- file GenEventStreamIO.cc
- file GenParticle.cc
- file GenRanges.cc
- file GenVertex.cc
- file HeavyIon.cc
- file IO_AsciiParticles.cc
- file IO_GenEvent.cc
- file PdfInfo.cc
- file Polarization.cc
- file SearchVector.cc
- file StreamHelpers.cc
- file StreamInfo.cc
- file WeightContainer.cc

7.5 /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/test/ Directory Reference

Files

- file `IsGoodEvent.h`
- file `test/list_of_examples.cc`
- file `testFlow.cc`
- file `testHepMCIteration.h`
- file `testHepMCMethods.cc`
- file `testHepMCMethods.h`
- file `testPolarization.cc`
- file `testPrintBug.cc`
- file `testSimpleVector.cc`
- file `testUnits.cc`
- file `testWeights.cc`

Chapter 8

HepMC Namespace Documentation

8.1 CLHEP Namespace Reference

8.1.1 Detailed Description

CLHEP (p. 21) Vector classes are used in one of the examples

8.2 detail Namespace Reference

8.2.1 Detailed Description

internal namespace

8.3 HepMC Namespace Reference

Classes

- class **Flow**
The flow object.
- class **GenCrossSection**
The GenCrossSection (p. 69) class stores the generated cross section.
- class **GenEvent**
The GenEvent (p. 73) class is the core of HepMC (p. 23).
- class **GenParticle**
The GenParticle (p. 111) class contains information about generated particles.
- class **GenEventVertexRange**
GenEventVertexRange (p. 110) acts like a collection of vertices.
- class **ConstGenEventVertexRange**
ConstGenEventVertexRange (p. 45) acts like a collection of vertices.
- class **GenEventParticleRange**
GenEventParticleRange (p. 109) acts like a collection of particles.
- class **ConstGenEventParticleRange**
ConstGenEventParticleRange (p. 43) acts like a collection of particles.
- class **GenVertexParticleRange**
GenVertexParticleRange (p. 151) acts like a collection of particles.
- class **GenParticleProductionRange**
GenParticleProductionRange (p. 124) acts like a collection of particles.
- class **ConstGenParticleProductionRange**
- class **GenParticleEndRange**
GenParticleEndRange (p. 122) acts like a collection of particles.
- class **ConstGenParticleEndRange**
- class **GenVertex**
GenVertex (p. 126) contains information about decay vertices.
- class **HeavyIon**
The HeavyIon (p. 152) class stores information about heavy ions.
- class **HEPEVT_Wrapper**
Generic Wrapper for the fortran HEPEVT common block.
- class **IO_AsciiParticles**
event input/output in ascii format for eye and machine reading

- **class IO_BaseClass**
all input/output classes inherit from IO_BaseClass (p. 179)
- **class IO_Exception**
IO exception handling.
- **class IO_GenEvent**
IO_GenEvent (p. 184) also deals with HeavyIon (p. 152) and PdfInfo (p. 220).
- **class IO_HEPEVT**
HEPEVT IO class.
- **class IO_HERWIG**
IO_HERWIG (p. 193) is used to get Herwig information.
- **class PdfInfo**
The PdfInfo (p. 220) class stores PDF information.
- **class Polarization**
The Polarization (p. 232) class stores theta and phi for a GenParticle (p. 111).
- **class FourVector**
FourVector (p. 59) is a simple representation of a physics 4 vector.
- **class ThreeVector**
ThreeVector (p. 254) is a simple representation of a position or displacement 3 vector.
- **class StreamInfo**
StreamInfo (p. 245) contains extra information needed when using streaming IO.
- **class TempParticleMap**
TempParticleMap (p. 251) is a temporary GenParticle container used during input.*
- **class WeightContainer**
Container for the Weights associated with an event or vertex.

Namespaces

- namespace **detail**
- namespace **Units**

Enumerations

- enum **IteratorRange** {
 parents, children, family, ancestors,
 descendants, relatives }

type of iteration

- `enum known_io {
 gen = 1, ascii, extascii, ascii_pdt,
 extascii_pdt }`

The known_io enum is used to track which type of input is being read.

Functions

- `GenCrossSection getHerwigCrossSection (int ngen)`
- `HepMC::GenCrossSection getPythiaCrossSection ()`
calculate the Pythia cross section and statistical error
- `bool compareGenEvent (GenEvent *, GenEvent *)`
- `bool compareSignalProcessVertex (GenEvent *, GenEvent *)`
- `bool compareBeamParticles (GenEvent *, GenEvent *)`
- `bool compareWeights (GenEvent *, GenEvent *)`
- `bool compareVertices (GenEvent *, GenEvent *)`
- `bool compareParticles (GenEvent *, GenEvent *)`
- `bool compareVertex (GenVertex *v1, GenVertex *v2)`
- `std::ostream & operator<< (std::ostream &os, GenCrossSection &xs)`
- `std::istream & operator>> (std::istream &is, GenCrossSection &xs)`
- `template<class InputIterator, class OutputIterator, class Predicate> void copy_if (Input-
 Iterator first, InputIterator last, OutputIterator out, Predicate pred)`
define the type of iterator to use
- `std::ostream & operator<< (std::ostream &, GenEvent &)`
standard streaming IO output operator
- `std::istream & operator>> (std::istream &, GenEvent &)`
standard streaming IO input operator
- `std::istream & set_input_units (std::istream &, Units::MomentumUnit, Units::LengthUnit)`
set the units for this input stream
- `std::ostream & write_HepMC_IO_block_begin (std::ostream &)`
Explicitly write the begin block lines that IO_GenEvent (p. 184) uses.
- `std::ostream & write_HepMC_IO_block_end (std::ostream &)`
Explicitly write the end block line that IO_GenEvent (p. 184) uses.
- `GenEvent & convert_units (GenEvent &evt, Units::MomentumUnit m, Units::LengthUnit l)`
- `std::ostream & operator<< (std::ostream &, HeavyIon const *)`
Write the contents of HeavyIon (p. 152) to an output stream.
- `std::istream & operator>> (std::istream &, HeavyIon *)`
Read the contents of HeavyIon (p. 152) from an input stream.

- `std::ostream & operator<< (std::ostream &, PdfInfo const *)`
- `std::istream & operator>> (std::istream &, PdfInfo *)`
- `bool not_in_vector (std::vector< HepMC::GenParticle * > *, GenParticle *)`
returns true if it cannot find GenParticle in the vector*
- `std::vector< HepMC::GenParticle * >::iterator already_in_vector (std::vector< GenParticle * > *v, GenParticle *p)`
returns true if GenParticle (p. 111) is in the vector
- `void version (std::ostream &os=std::cout)`
print HepMC (p. 23) version
- `void writeVersion (std::ostream &os)`
write HepMC (p. 23) version to os
- `std::string versionName ()`
return HepMC (p. 23) version
- `std::ostream & operator<< (std::ostream &ostr, const Flow &f)`
for printing
- `void HepMCStreamCallback (std::ios_base::event e, std::ios_base &b, int i)`
- `template<class IO> StreamInfo & get_stream_info (IO &iost)`
- `std::ostream & establish_output_stream_info (std::ostream &os)`
used by IO_GenEvent (p. 184) constructor
- `std::istream & establish_input_stream_info (std::istream &is)`
used by IO_GenEvent (p. 184) constructor
- `std::ostream & operator<< (std::ostream &ostr, const GenParticle &part)`
print particle
- `std::ostream & operator<< (std::ostream &ostr, const GenVertex &vtx)`
print vertex information
- `std::ostream & operator<< (std::ostream &ostr, const Polarization &polar)`
print polarization information

Variables

- static const double `HepMC_pi = 3.14159265358979323846`

8.3.1 Detailed Description

All classes in the `HepMC` (p. 23) packages are in the `HepMC` (p. 23) namespace

8.3.2 Enumeration Type Documentation

8.3.2.1 enum HepMC::IteratorRange

type of iteration

Enumerator:

parents
children
family
ancestors
descendants
relatives

Definition at line 17 of file IteratorRange.h.

8.3.2.2 enum HepMC::known_io

The known_io enum is used to track which type of input is being read.

Enumerator:

gen
ascii
extascii
ascii_pdt
extascii_pdt

Definition at line 17 of file StreamInfo.h.

8.3.3 Function Documentation

8.3.3.1 GenCrossSection HepMC::getHerwigCrossSection (int *ngen*)

Examples:

example_MyHerwig.cc, and testHerwigCopies.cc.

Definition at line 24 of file HerwigWrapper.cc.

References hwevnt, and HepMC::GenCrossSection::set_cross_section().

Referenced by main().

8.3.3.2 GenCrossSection HepMC::getPythiaCrossSection ()

calculate the Pythia cross section and statistical error

Examples:

example_MyPythia.cc, example_MyPythiaOnlyToHepMC.cc, example_PythiaStreamIO.cc, and testPythiaCopies.cc.

Definition at line 31 of file PythiaWrapper.cc.

References pyint5, and HepMC::GenCrossSection::set_cross_section().

Referenced by event_selection(), main(), pythia_in_out(), pythia_out(), pythia_particle_out(), and write-PythiaStreamIO().

8.3.3.3 bool HepMC::compareGenEvent (GenEvent *, GenEvent *)**Examples:**

testHerwigCopies.cc, testMultipleCopies.cc.in, and testPythiaCopies.cc.

Definition at line 16 of file CompareGenEvent.cc.

References HepMC::GenEvent::alphaQCD(), HepMC::GenEvent::alphaQED(), compareBeamParticles(), compareParticles(), compareSignalProcessVertex(), compareVertices(), compareWeights(), HepMC::GenEvent::event_number(), HepMC::GenEvent::event_scale(), HepMC::GenEvent::heavy_ion(), HepMC::GenEvent::mpi(), HepMC::GenEvent::pdf_info(), HepMC::GenEvent::random_states(), and HepMC::GenEvent::signal_process_id().

Referenced by main().

8.3.3.4 bool HepMC::compareSignalProcessVertex (GenEvent *, GenEvent *)

Definition at line 64 of file CompareGenEvent.cc.

References HepMC::GenEvent::signal_process_vertex().

Referenced by compareGenEvent().

8.3.3.5 bool HepMC::compareBeamParticles (GenEvent *, GenEvent *)

Definition at line 77 of file CompareGenEvent.cc.

References HepMC::GenEvent::beam_particles().

Referenced by compareGenEvent().

8.3.3.6 bool HepMC::compareWeights (GenEvent *, GenEvent *)

Definition at line 92 of file CompareGenEvent.cc.

References HepMC::GenEvent::weights().

Referenced by compareGenEvent().

8.3.3.7 bool HepMC::compareVertices (GenEvent *, GenEvent *)

Definition at line 120 of file CompareGenEvent.cc.

References HepMC::GenEvent::barcode_to_vertex(), compareVertex(), v, HepMC::GenEvent::vertices_begin(), HepMC::GenEvent::vertices_end(), and HepMC::GenEvent::vertices_size().

Referenced by compareGenEvent().

8.3.3.8 bool HepMC::compareParticles (GenEvent *, GenEvent *)

Definition at line 98 of file CompareGenEvent.cc.

References HepMC::GenEvent::particles_begin(), HepMC::GenEvent::particles_end(), and HepMC::GenEvent::particles_size().

Referenced by compareGenEvent().

8.3.3.9 bool HepMC::compareVertex (GenVertex * v1, GenVertex * v2)

Definition at line 141 of file CompareGenEvent.cc.

References HepMC::GenVertex::barcode(), HepMC::GenVertex::particles_in_const_begin(), HepMC::GenVertex::particles_in_const_end(), HepMC::GenVertex::particles_in_size(), HepMC::GenVertex::particles_out_const_begin(), HepMC::GenVertex::particles_out_const_end(), HepMC::GenVertex::particles_out_size(), and HepMC::GenVertex::position().

Referenced by compareVertices().

8.3.3.10 std::ostream& HepMC::operator<< (std::ostream & os, GenCrossSection & xs) [inline]

Definition at line 89 of file GenCrossSection.h.

References HepMC::GenCrossSection::write().

8.3.3.11 std::istream& HepMC::operator>> (std::istream & is, GenCrossSection & xs) [inline]

Definition at line 92 of file GenCrossSection.h.

References HepMC::GenCrossSection::read().

8.3.3.12 template<class InputIterator, class OutputIterator, class Predicate> void HepMC::copy_if (InputIterator *first*, InputIterator *last*, OutputIterator *out*, Predicate *pred*)

define the type of iterator to use

Examples:

example_UsingIterators.cc, and testHepMCIteration.cc.in.

Definition at line 50 of file GenEvent.h.

Referenced by main().

8.3.3.13 `std::ostream & HepMC::operator<< (std::ostream &, GenEvent &)`

standard streaming IO output operator

Writes evt to an output stream.

Definition at line 348 of file GenEventStreamIO.cc.

References HepMC::GenEvent::write().

8.3.3.14 `std::istream & HepMC::operator>> (std::istream &, GenEvent &)`

standard streaming IO input operator

Definition at line 355 of file GenEventStreamIO.cc.

References HepMC::GenEvent::read().

8.3.3.15 `std::istream & HepMC::set_input_units (std::istream &, Units::MomentumUnit, Units::LengthUnit)`

set the units for this input stream

Examples:

`testStreamIO.cc.in.`

Definition at line 363 of file GenEventStreamIO.cc.

References `get_stream_info()`, and `HepMC::StreamInfo::use_input_units()`.

Referenced by `HepMC::IO_GenEvent::use_input_units()`.

8.3.3.16 `std::ostream & HepMC::write_HepMC_IO_block_begin (std::ostream &)`

Explicitly write the begin block lines that `IO_GenEvent` (p. 184) uses.

Examples:

`example_PythiaStreamIO.cc`, and `testStreamIO.cc.in.`

Definition at line 375 of file GenEventStreamIO.cc.

References `HepMC::StreamInfo::finished_first_event()`, `get_stream_info()`, `HepMC::StreamInfo::IO_GenEvent_Key()`, and `versionName()`.

Referenced by `readPythiaStreamIO()`, `HepMC::IO_GenEvent::write_event()`, and `writePythiaStreamIO()`.

8.3.3.17 `std::ostream & HepMC::write_HepMC_IO_block_end (std::ostream &)`

Explicitly write the end block line that `IO_GenEvent` (p. 184) uses.

Examples:

`example_PythiaStreamIO.cc`, and `testStreamIO.cc.in.`

Definition at line 388 of file GenEventStreamIO.cc.

References HepMC::StreamInfo::finished_first_event(), get_stream_info(), and HepMC::StreamInfo::IO_GenEvent_End().

Referenced by readPythiaStreamIO(), HepMC::IO_GenEvent::write_comment(), writePythiaStreamIO(), and HepMC::IO_GenEvent::~~IO_GenEvent().

8.3.3.18 GenEvent& HepMC::convert_units (GenEvent & evt, Units::MomentumUnit m, Units::LengthUnit l) [inline]

Definition at line 655 of file GenEvent.h.

References HepMC::GenEvent::use_units().

8.3.3.19 std::ostream & HepMC::operator<< (std::ostream & os, HeavyIon const * ion)

Write the contents of **HeavyIon** (p. 152) to an output stream.

Write the contents of **HeavyIon** (p. 152) to an output stream. **GenEvent** (p. 73) stores a pointer to a **HeavyIon** (p. 152).

Definition at line 23 of file HeavyIon.cc.

References HepMC::HeavyIon::eccentricity(), HepMC::HeavyIon::event_plane_angle(), HepMC::HeavyIon::impact_parameter(), HepMC::HeavyIon::N_Nwounded_collisions(), HepMC::HeavyIon::Ncoll(), HepMC::HeavyIon::Ncoll_hard(), HepMC::HeavyIon::Npart_proj(), HepMC::HeavyIon::Npart_targ(), HepMC::HeavyIon::Nwounded_N_collisions(), HepMC::HeavyIon::Nwounded_Nwounded_collisions(), HepMC::detail::output(), HepMC::HeavyIon::sigma_inel_NN(), HepMC::HeavyIon::spectator_neutrons(), and HepMC::HeavyIon::spectator_protons().

8.3.3.20 std::istream & HepMC::operator>> (std::istream & is, HeavyIon * ion)

Read the contents of **HeavyIon** (p. 152) from an input stream.

Read the contents of **HeavyIon** (p. 152) from an input stream. **GenEvent** (p. 73) stores a pointer to a **HeavyIon** (p. 152).

Definition at line 71 of file HeavyIon.cc.

References HepMC::HeavyIon::set_eccentricity(), HepMC::HeavyIon::set_event_plane_angle(), HepMC::HeavyIon::set_impact_parameter(), HepMC::HeavyIon::set_N_Nwounded_collisions(), HepMC::HeavyIon::set_Ncoll(), HepMC::HeavyIon::set_Ncoll_hard(), HepMC::HeavyIon::set_Npart_proj(), HepMC::HeavyIon::set_Npart_targ(), HepMC::HeavyIon::set_Nwounded_N_collisions(), HepMC::HeavyIon::set_Nwounded_Nwounded_collisions(), HepMC::HeavyIon::set_sigma_inel_NN(), HepMC::HeavyIon::set_spectator_neutrons(), and HepMC::HeavyIon::set_spectator_protons().

8.3.3.21 std::ostream & HepMC::operator<< (std::ostream &, PdfInfo const *)

Definition at line 21 of file PdfInfo.cc.

References HepMC::PdfInfo::id1(), HepMC::PdfInfo::id2(), HepMC::detail::output(), HepMC::PdfInfo::pdf1(), HepMC::PdfInfo::pdf2(), HepMC::PdfInfo::pdf_id1(), HepMC::PdfInfo::pdf_id2(), HepMC::PdfInfo::scalePDF(), HepMC::PdfInfo::x1(), and HepMC::PdfInfo::x2().

8.3.3.22 `std::istream & HepMC::operator>> (std::istream &, PdfInfo *)`

Definition at line 59 of file PdfInfo.cc.

References `HepMC::PdfInfo::set_id1()`, `HepMC::PdfInfo::set_id2()`, `HepMC::PdfInfo::set_pdf1()`, `HepMC::PdfInfo::set_pdf2()`, `HepMC::PdfInfo::set_pdf_id1()`, `HepMC::PdfInfo::set_pdf_id2()`, `HepMC::PdfInfo::set_scalePDF()`, `HepMC::PdfInfo::set_x1()`, `HepMC::PdfInfo::set_x2()`, and `x1`.

8.3.3.23 `bool HepMC::not_in_vector (std::vector< HepMC::GenParticle * > *, GenParticle *)`

returns true if it cannot find `GenParticle*` in the vector

Definition at line 11 of file SearchVector.cc.

References `already_in_vector()`, and `p`.

Referenced by `HepMC::Flow::connected_partners()`, and `HepMC::Flow::dangling_connected_partners()`.

8.3.3.24 `std::vector< HepMC::GenParticle * >::iterator HepMC::already_in_vector (std::vector< HepMC::GenParticle * > *, GenParticle *)`

returns true if **GenParticle** (p. 111) is in the vector

Returns the index of a `GenParticle*` within a vector. Returns -1 if `GenParticle*` is not in the vector.

Definition at line 18 of file SearchVector.cc.

References `p`.

Referenced by `not_in_vector()`, `HepMC::GenVertex::remove_particle_in()`, and `HepMC::GenVertex::remove_particle_out()`.

8.3.3.25 `void HepMC::version (std::ostream & os = std::cout) [inline]`

print **HepMC** (p. 23) version

Examples:

`testMass.cc.in.`

Definition at line 27 of file Version.h.

References `versionName()`.

8.3.3.26 `void HepMC::writeVersion (std::ostream & os) [inline]`

write **HepMC** (p. 23) version to `os`

Definition at line 33 of file Version.h.

References `versionName()`.

Referenced by `HepMC::GenEvent::print_version()`.

8.3.3.27 `std::string HepMC::versionName () [inline]`

return **HepMC** (p. 23) version

Definition at line 22 of file Version.h.

References HEPMC_VERSION.

Referenced by version(), HepMC::IO_AsciiParticles::write_event(), write_HepMC_IO_block_begin(), and writeVersion().

8.3.3.28 std::ostream& HepMC::operator<< (std::ostream & ostr, const Flow & f)

for printing

Definition at line 190 of file Flow.cc.

References HepMC::Flow::m_icode.

8.3.3.29 void HepMC::HepMCStreamCallback (std::ios_base::event e, std::ios_base & b, int i)

This method is called by the stream destructor. It does cleanup on stored user data (**StreamInfo** (p. 245)) and is registered by the first call to **get_stream_info**() (p. 33).

Definition at line 29 of file GenEventStreamIO.cc.

References HepMC::StreamInfo::stream_id().

Referenced by get_stream_info().

8.3.3.30 template<class IO> StreamInfo& HepMC::get_stream_info (IO & iost)

A custom iomanip that allows us to store and access user data (**StreamInfo** (p. 245)) associated with the stream. This method creates the **StreamInfo** (p. 245) object the first time it is called.

Definition at line 51 of file GenEventStreamIO.cc.

References HepMCStreamCallback().

Referenced by HepMC::detail::establish_input_stream_info(), establish_input_stream_info(), HepMC::detail::establish_output_stream_info(), establish_output_stream_info(), HepMC::GenEvent::read(), HepMC::detail::read_particle(), HepMC::detail::read_units(), set_input_units(), HepMC::GenEvent::write(), write_HepMC_IO_block_begin(), and write_HepMC_IO_block_end().

8.3.3.31 std::ostream& HepMC::establish_output_stream_info (std::ostream & os)

used by **IO_GenEvent** (p. 184) constructor

Definition at line 646 of file GenEventStreamIO.cc.

References HepMC::StreamInfo::finished_first_event(), and get_stream_info().

Referenced by HepMC::IO_GenEvent::IO_GenEvent().

8.3.3.32 std::istream& HepMC::establish_input_stream_info (std::istream & is)

used by **IO_GenEvent** (p. 184) constructor

Definition at line 660 of file GenEventStreamIO.cc.

References HepMC::StreamInfo::finished_first_event(), and get_stream_info().

Referenced by HepMC::IO_GenEvent::IO_GenEvent().

8.3.3.33 `std::ostream& HepMC::operator<< (std::ostream & ostr, const GenParticle & part)`

print particle

Definition at line 189 of file GenParticle.cc.

References HepMC::GenVertex::barcode(), HepMC::GenParticle::barcode(), HepMC::FourVector::e(), HepMC::GenParticle::end_vertex(), HepMC::GenParticle::momentum(), HepMC::GenParticle::pdg_id(), HepMC::FourVector::px(), HepMC::FourVector::py(), HepMC::FourVector::pz(), and HepMC::GenParticle::status().

8.3.3.34 `std::ostream& HepMC::operator<< (std::ostream & ostr, const GenVertex & vtx)`

print vertex information

Definition at line 440 of file GenVertex.cc.

References HepMC::GenVertex::barcode(), HepMC::GenVertex::position(), and HepMC::FourVector::x().

8.3.3.35 `std::ostream& HepMC::operator<< (std::ostream & ostr, const Polarization & polar)`

print polarization information

Definition at line 129 of file Polarization.cc.

References HepMC::Polarization::phi(), and HepMC::Polarization::theta().

8.3.4 Variable Documentation**8.3.4.1 `const double HepMC::HepMC_pi = 3.14159265358979323846` `[static]`**

Definition at line 19 of file Polarization.h.

8.4 HepMC::detail Namespace Reference

Classes

- struct **enable_if**
internal - used to decide if a class is arithmetic
- struct **enable_if**< true, T >
internal - use if class T is arithmetic
- struct **disable_if**
internal - used by SimpleVector to decide if a class is arithmetic
- struct **disable_if**< false, T >
internal - used by SimpleVector to decide if a class is arithmetic
- struct **is_arithmetic**
undefined and therefore non-arithmetic
- struct **is_arithmetic**< char >
character is arithmetic
- struct **is_arithmetic**< unsigned char >
unsigned character is arithmetic
- struct **is_arithmetic**< signed char >
signed character is arithmetic
- struct **is_arithmetic**< short >
short is arithmetic
- struct **is_arithmetic**< unsigned short >
unsigned short is arithmetic
- struct **is_arithmetic**< int >
int is arithmetic
- struct **is_arithmetic**< unsigned int >
unsigned int is arithmetic
- struct **is_arithmetic**< long >
long is arithmetic
- struct **is_arithmetic**< unsigned long >
unsigned long is arithmetic
- struct **is_arithmetic**< float >
float is arithmetic
- struct **is_arithmetic**< double >

double is arithmetic

- **struct is_arithmetic< long double >**

long double is arithmetic

Functions

- **std::ostream & establish_output_stream_info (std::ostream &)**
used by IO_GenEvent (p. 184) constructor
- **std::istream & establish_input_stream_info (std::istream &)**
used by IO_GenEvent (p. 184) constructor
- **std::istream & read_vertex (std::istream &, TempParticleMap &, GenVertex *)**
- **std::istream & read_particle (std::istream &, TempParticleMap &, GenParticle *)**
- **std::ostream & output (std::ostream &os, const double &d)**
write a double - for internal use by streaming IO
- **std::ostream & output (std::ostream &os, const float &d)**
write a float - for internal use by streaming IO
- **std::ostream & output (std::ostream &os, const int &i)**
write an int - for internal use by streaming IO
- **std::ostream & output (std::ostream &os, const long &l)**
write a long - for internal use by streaming IO
- **std::ostream & output (std::ostream &os, const char &c)**
write a single char - for internal use by streaming IO
- **std::istream & find_event_end (std::istream &)**
used to read to the end of a bad event
- **std::istream & read_units (std::istream &is, GenEvent &evt)**

8.4.1 Function Documentation

8.4.1.1 std::ostream & HepMC::detail::establish_output_stream_info (std::ostream &)

used by **IO_GenEvent** (p. 184) constructor

Definition at line 789 of file GenEventStreamIO.cc.

References HepMC::StreamInfo::finished_first_event(), and HepMC::get_stream_info().

Referenced by HepMC::IO_GenEvent::IO_GenEvent().

8.4.1.2 std::istream & HepMC::detail::establish_input_stream_info (std::istream &)

used by **IO_GenEvent** (p. 184) constructor

Definition at line 803 of file GenEventStreamIO.cc.

References HepMC::StreamInfo::finished_first_event(), and HepMC::get_stream_info().

Referenced by HepMC::IO_GenEvent::IO_GenEvent().

8.4.1.3 std::istream & HepMC::detail::read_vertex (std::istream &, TempParticleMap &, GenVertex *)

get a **GenVertex** (p. 126) from ASCII input **TempParticleMap** (p. 251) is used to track the associations of particles with vertices

Definition at line 23 of file StreamHelpers.cc.

References read_particle(), and v.

Referenced by HepMC::GenEvent::read().

8.4.1.4 std::istream & HepMC::detail::read_particle (std::istream &, TempParticleMap &, GenParticle *)

get a **GenParticle** (p. 111) from ASCII input **TempParticleMap** (p. 251) is used to track the associations of particles with vertices

Definition at line 681 of file GenEventStreamIO.cc.

References HepMC::TempParticleMap::addEndParticle(), HepMC::ascii, HepMC::get_stream_info(), HepMC::StreamInfo::io_type(), p, and HepMC::Flow::set_icode().

Referenced by read_vertex().

8.4.1.5 std::ostream& HepMC::detail::output (std::ostream & os, const double & d) [inline]

write a double - for internal use by streaming IO

Definition at line 35 of file StreamHelpers.h.

Referenced by HepMC::Flow::connected_partners(), HepMC::Flow::dangling_connected_partners(), HepMC::operator<(), HepMC::GenEvent::write(), and HepMC::IO_AsciiParticles::write_event().

8.4.1.6 std::ostream& HepMC::detail::output (std::ostream & os, const float & d) [inline]

write a float - for internal use by streaming IO

Definition at line 47 of file StreamHelpers.h.

8.4.1.7 std::ostream& HepMC::detail::output (std::ostream & os, const int & i) [inline]

write an int - for internal use by streaming IO

Definition at line 59 of file StreamHelpers.h.

8.4.1.8 `std::ostream& HepMC::detail::output (std::ostream & os, const long & i)` `[inline]`

write a long - for internal use by streaming IO

Definition at line 71 of file StreamHelpers.h.

8.4.1.9 `std::ostream& HepMC::detail::output (std::ostream & os, const char & c)` `[inline]`

write a single char - for internal use by streaming IO

Definition at line 83 of file StreamHelpers.h.

8.4.1.10 `std::istream & HepMC::detail::find_event_end (std::istream &)`

used to read to the end of a bad event

Definition at line 98 of file StreamHelpers.cc.

Referenced by `HepMC::GenEvent::read()`.

8.4.1.11 `std::istream& HepMC::detail::read_units (std::istream & is, GenEvent & evt)`

Definition at line 762 of file GenEventStreamIO.cc.

References `HepMC::get_stream_info()`, `HepMC::StreamInfo::io_momentum_unit()`, `HepMC::StreamInfo::io_position_unit()`, and `HepMC::GenEvent::use_units()`.

8.5 HepMC::Units Namespace Reference

Enumerations

- enum **MomentumUnit** { MEV, GEV }
- enum **LengthUnit** { MM, CM }

Functions

- **LengthUnit default_length_unit ()**
default unit is defined by configure
- **MomentumUnit default_momentum_unit ()**
default unit is defined by configure
- **std::string name (MomentumUnit)**
convert enum to string
- **std::string name (LengthUnit)**
convert enum to string
- **double conversion_factor (MomentumUnit from, MomentumUnit to)**
scaling factor relative to MeV
- **double conversion_factor (LengthUnit from, LengthUnit to)**

8.5.1 Enumeration Type Documentation

8.5.1.1 enum HepMC::Units::MomentumUnit

Enumerator:

MEV

GEV

Definition at line 25 of file Units.h.

8.5.1.2 enum HepMC::Units::LengthUnit

Enumerator:

MM

CM

Definition at line 26 of file Units.h.

8.5.2 Function Documentation

8.5.2.1 LengthUnit HepMC::Units::default_length_unit ()

default unit is defined by configure

Examples:

`testUnits.cc.`

Referenced by HepMC::GenEvent::clear(), and main().

8.5.2.2 MomentumUnit HepMC::Units::default_momentum_unit ()

default unit is defined by configure

Examples:

`testUnits.cc.`

Referenced by HepMC::GenEvent::clear(), and main().

8.5.2.3 std::string HepMC::Units::name (MomentumUnit)

convert enum to string

Examples:

`testHepMC.cc.in, testStreamIO.cc.in, and testUnits.cc.`

Referenced by main(), HepMC::GenEvent::write(), and HepMC::GenEvent::write_units().

8.5.2.4 std::string HepMC::Units::name (LengthUnit)

convert enum to string

8.5.2.5 double HepMC::Units::conversion_factor (MomentumUnit *from*, MomentumUnit *to*)

scaling factor relative to MeV

Examples:

`testUnits.cc.`

Referenced by main(), and repairUnits().

8.5.2.6 double HepMC::Units::conversion_factor (LengthUnit *from*, LengthUnit *to*)

8.6 Units Namespace Reference

8.6.1 Detailed Description

Allow units to be specified within **HepMC** (p. 23). The default units are set at compile time.

Chapter 9

HepMC Class Documentation

9.1 HepMC::ConstGenEventParticleRange Class Reference

ConstGenEventParticleRange (p. 43) acts like a collection of particles.

```
#include <GenRanges.h>
```

Public Member Functions

- **ConstGenEventParticleRange (GenEvent const &e)**
the constructor requires a const GenEvent (p. 73)
- **GenEvent::particle_const_iterator begin () const**
- **GenEvent::particle_const_iterator end () const**

9.1.1 Detailed Description

ConstGenEventParticleRange (p. 43) acts like a collection of particles.

HepMC::ConstGenEventParticleRange (p. 43) is used to mimic a collection of particles for ease of use - especially with utilities such as the Boost foreach function. This is the const partner of **GenEventParticleRange** (p. 109)

Definition at line 112 of file GenRanges.h.

9.1.2 Constructor & Destructor Documentation

9.1.2.1 HepMC::ConstGenEventParticleRange::ConstGenEventParticleRange (GenEvent const &e) [inline]

the constructor requires a const **GenEvent** (p. 73)

Definition at line 117 of file GenRanges.h.

9.1.3 Member Function Documentation

9.1.3.1 `GenEvent::particle_const_iterator HepMC::ConstGenEventParticleRange::begin () const` [inline]

Definition at line 119 of file GenRanges.h.

References `HepMC::GenEvent::particles_begin()`.

9.1.3.2 `GenEvent::particle_const_iterator HepMC::ConstGenEventParticleRange::end () const` [inline]

Definition at line 120 of file GenRanges.h.

References `HepMC::GenEvent::particles_end()`.

The documentation for this class was generated from the following file:

- **GenRanges.h**

9.2 HepMC::ConstGenEventVertexRange Class Reference

ConstGenEventVertexRange (p. 45) acts like a collection of vertices.

```
#include <GenRanges.h>
```

Public Member Functions

- **ConstGenEventVertexRange (GenEvent const &e)**
the constructor requires a const GenEvent (p. 73)
- **GenEvent::vertex_const_iterator begin () const**
- **GenEvent::vertex_const_iterator end () const**

9.2.1 Detailed Description

ConstGenEventVertexRange (p. 45) acts like a collection of vertices.

HepMC::ConstGenEventVertexRange (p. 45) is used to mimic a collection of vertices for ease of use - especially with utilities such as the Boost foreach function. This is the const partner of **GenEventVertexRange** (p. 110)

Definition at line 55 of file GenRanges.h.

9.2.2 Constructor & Destructor Documentation

9.2.2.1 HepMC::ConstGenEventVertexRange::ConstGenEventVertexRange (GenEvent const &e) [inline]

the constructor requires a const **GenEvent** (p. 73)

Definition at line 60 of file GenRanges.h.

9.2.3 Member Function Documentation

9.2.3.1 GenEvent::vertex_const_iterator HepMC::ConstGenEventVertexRange::begin () const [inline]

Definition at line 62 of file GenRanges.h.

References HepMC::GenEvent::vertices_begin().

9.2.3.2 GenEvent::vertex_const_iterator HepMC::ConstGenEventVertexRange::end () const [inline]

Definition at line 63 of file GenRanges.h.

References HepMC::GenEvent::vertices_end().

The documentation for this class was generated from the following file:

- **GenRanges.h**

9.3 HepMC::ConstGenParticleEndRange Class Reference

```
#include <GenRanges.h>
```

Public Member Functions

- **ConstGenParticleEndRange** (GenParticle const &p, IteratorRange range=relatives)
the constructor requires a GenParticle (p. 111)
- **GenVertex::particle_iterator** begin ()
begin iterator throws an error if the particle end_vertex is undefined
- **GenVertex::particle_iterator** end ()
end iterator throws an error if the particle end_vertex is undefined

9.3.1 Detailed Description

Definition at line 247 of file GenRanges.h.

9.3.2 Constructor & Destructor Documentation

9.3.2.1 HepMC::ConstGenParticleEndRange::ConstGenParticleEndRange (GenParticle const &p, IteratorRange range = relatives) [inline]

the constructor requires a **GenParticle** (p. 111)

Definition at line 252 of file GenRanges.h.

9.3.3 Member Function Documentation

9.3.3.1 GenVertex::particle_iterator HepMC::ConstGenParticleEndRange::begin () [inline]

begin iterator throws an error if the particle end_vertex is undefined

Definition at line 313 of file GenRanges.h.

References HepMC::GenParticle::end_vertex(), and HepMC::GenVertex::particles_begin().

9.3.3.2 GenVertex::particle_iterator HepMC::ConstGenParticleEndRange::end () [inline]

end iterator throws an error if the particle end_vertex is undefined

Definition at line 319 of file GenRanges.h.

References HepMC::GenParticle::end_vertex(), and HepMC::GenVertex::particles_end().

The documentation for this class was generated from the following file:

- **GenRanges.h**

9.4 HepMC::ConstGenParticleProductionRange Class Reference

```
#include <GenRanges.h>
```

Public Member Functions

- **ConstGenParticleProductionRange** (GenParticle const &p, IteratorRange range=relatives)
the constructor requires a GenParticle (p. 111)
- **GenVertex::particle_iterator** begin ()
begin iterator throws an error if the particle production_vertex is undefined
- **GenVertex::particle_iterator** end ()
end iterator throws an error if the particle production_vertex is undefined

9.4.1 Detailed Description

Definition at line 193 of file GenRanges.h.

9.4.2 Constructor & Destructor Documentation

9.4.2.1 HepMC::ConstGenParticleProductionRange::ConstGenParticleProductionRange (GenParticle const &p, IteratorRange range = relatives) [inline]

the constructor requires a **GenParticle** (p. 111)

Definition at line 198 of file GenRanges.h.

9.4.3 Member Function Documentation

9.4.3.1 GenVertex::particle_iterator HepMC::ConstGenParticleProductionRange::begin () [inline]

begin iterator throws an error if the particle production_vertex is undefined

Definition at line 286 of file GenRanges.h.

References HepMC::GenVertex::particles_begin(), and HepMC::GenParticle::production_vertex().

9.4.3.2 GenVertex::particle_iterator HepMC::ConstGenParticleProductionRange::end () [inline]

end iterator throws an error if the particle production_vertex is undefined

Definition at line 293 of file GenRanges.h.

References HepMC::GenVertex::particles_end(), and HepMC::GenParticle::production_vertex().

The documentation for this class was generated from the following file:

- **GenRanges.h**

9.5 HepMC::detail::disable_if<, > Struct Template Reference

internal - used by SimpleVector to decide if a class is arithmetic

```
#include <enable_if.h>
```

9.5.1 Detailed Description

template<bool, class> struct HepMC::detail::disable_if<, >

internal - used by SimpleVector to decide if a class is arithmetic

Definition at line 33 of file enable_if.h.

The documentation for this struct was generated from the following file:

- **enable_if.h**

9.6 HepMC::detail::disable_if< false, T > Struct Template Reference

internal - used by SimpleVector to decide if a class is arithmetic

```
#include <enable_if.h>
```

Public Types

- `typedef T type`
check type of class T

9.6.1 Detailed Description

```
template<class T> struct HepMC::detail::disable_if< false, T >
```

internal - used by SimpleVector to decide if a class is arithmetic

Definition at line 38 of file enable_if.h.

9.6.2 Member Typedef Documentation

9.6.2.1 `template<class T> typedef T HepMC::detail::disable_if< false, T >::type`

check type of class T

Definition at line 40 of file enable_if.h.

The documentation for this struct was generated from the following file:

- `enable_if.h`

9.7 HepMC::detail::enable_if<, > Struct Template Reference

internal - used to decide if a class is arithmetic

```
#include <enable_if.h>
```

9.7.1 Detailed Description

template<bool, class> struct HepMC::detail::enable_if<, >

internal - used to decide if a class is arithmetic

Definition at line 17 of file enable_if.h.

The documentation for this struct was generated from the following file:

- **enable_if.h**

9.8 HepMC::detail::enable_if< true, T > Struct Template Reference

internal - use if class T is arithmetic

```
#include <enable_if.h>
```

Public Types

- **typedef T type**
check type of class T

9.8.1 Detailed Description

template<class T> struct HepMC::detail::enable_if< true, T >

internal - use if class T is arithmetic

Definition at line 22 of file enable_if.h.

9.8.2 Member Typedef Documentation

9.8.2.1 **template<class T> typedef T HepMC::detail::enable_if< true, T >::type**

check type of class T

Definition at line 24 of file enable_if.h.

The documentation for this struct was generated from the following file:

- **enable_if.h**

9.9 HepMC::Flow Class Reference

The flow object.

```
#include <Flow.h>
```

Public Types

- `typedef std::map< int, int >::iterator iterator`
iterator for flow pattern container
- `typedef std::map< int, int >::const_iterator const_iterator`
const iterator for flow pattern container

Public Member Functions

- `Flow (GenParticle *particle_owner=0)`
default constructor
- `Flow (const Flow &)`
copy
- `virtual ~Flow ()`
- `void swap (Flow &other)`
swap
- `Flow & operator= (const Flow &)`
make a copy
- `bool operator== (const Flow &a) const`
equality
- `bool operator!= (const Flow &a) const`
inequality
- `void print (std::ostream &ostr=std::cout) const`
print Flow (p. 52) information to ostr
- `std::vector< HepMC::GenParticle * > connected_partners (int code, int code_index=1, int num_indices=2) const`
- `std::vector< HepMC::GenParticle * > dangling_connected_partners (int code, int code_index=1, int num_indices=2) const`
- `const GenParticle * particle_owner () const`
find particle owning this Flow (p. 52)
- `int icode (int code_index=1) const`
flow code
- `Flow set_icode (int code_index, int code)`

set flow code

- **Flow set_unique_icode (int code_index=1)**

set unique flow code

- **bool empty () const**

return true if there is no flow container

- **int size () const**

size of flow pattern container

- **void clear ()**

clear flow patterns

- **bool erase (int code_index)**

empty flow pattern container

- **iterator begin ()**

beginning of flow pattern container

- **iterator end ()**

end of flow pattern container

- **const_iterator begin () const**

beginning of flow pattern container

- **const_iterator end () const**

end of flow pattern container

Protected Member Functions

- **void connected_partners (std::vector< HepMC::GenParticle * > *output, int code, int code_index, int num_indices) const**

for internal use only

- **void dangling_connected_partners (std::vector< HepMC::GenParticle * > *output, std::vector< HepMC::GenParticle * > *visited_particles, int code, int code_index, int num_indices) const**

for internal use only

Friends

- **std::ostream & operator<< (std::ostream &ostr, const Flow &f)**

for printing

9.9.1 Detailed Description

The flow object.

The particle's flow object keeps track of an arbitrary number of flow patterns within a graph (i.e. color flow, charge flow, lepton number flow, ...) **Flow** (p. 52) patterns are coded with an integer, in the same manner as in Herwig.

Examples:

testFlow.cc.

Definition at line 66 of file Flow.h.

9.9.2 Member Typedef Documentation

9.9.2.1 `typedef std::map<int,int>::const_iterator HepMC::Flow::const_iterator`

const iterator for flow pattern container

Definition at line 128 of file Flow.h.

9.9.2.2 `typedef std::map<int,int>::iterator HepMC::Flow::iterator`

iterator for flow pattern container

Definition at line 126 of file Flow.h.

9.9.3 Constructor & Destructor Documentation

9.9.3.1 `HepMC::Flow::Flow (GenParticle * particle_owner = 0)`

default constructor

Definition at line 13 of file Flow.cc.

9.9.3.2 `HepMC::Flow::Flow (const Flow &)`

copy

copies both the m_icode AND the m_particle_owner

Definition at line 17 of file Flow.cc.

9.9.3.3 `HepMC::Flow::~~Flow ()` `[virtual]`

Definition at line 24 of file Flow.cc.

9.9.4 Member Function Documentation

9.9.4.1 `Flow::const_iterator HepMC::Flow::begin () const` `[inline]`

beginning of flow pattern container

Definition at line 186 of file Flow.h.

9.9.4.2 Flow::iterator HepMC::Flow::begin () [inline]

beginning of flow pattern container

Definition at line 184 of file Flow.h.

9.9.4.3 void HepMC::Flow::clear () [inline]

clear flow patterns

Definition at line 179 of file Flow.h.

9.9.4.4 void HepMC::Flow::connected_partners (std::vector< HepMC::GenParticle * > * output, int code, int code_index, int num_indices) const [protected]

for internal use only

protected: for recursive use by **Flow::connected_partners()** (p. 55)

Definition at line 60 of file Flow.cc.

References HepMC::GenParticle::end_vertex(), HepMC::family, HepMC::not_in_vector(), p, HepMC::GenVertex::particles_begin(), HepMC::GenVertex::particles_end(), and HepMC::GenParticle::production_vertex().

9.9.4.5 std::vector< GenParticle * > HepMC::Flow::connected_partners (int code, int code_index = 1, int num_indices = 2) const

returns all connected particles which have "code" in any of the num_indices beginning with index code_index.

Returns all flow partners which have "code" in any of the num_indices beginning with index code_index. m_particle_owner is included in the result. Return is by value since the set should never be very big. EXAMPLE: if you want to find all flow partners that have the same code in indices 2,3,4 as particle p has in index 2, you would use: set<GenParticle*> result = p->flow().connected_partners(p->flow().icode(2),2,3);

Definition at line 38 of file Flow.cc.

References icode(), and HepMC::detail::output().

9.9.4.6 void HepMC::Flow::dangling_connected_partners (std::vector< HepMC::GenParticle * > * output, std::vector< HepMC::GenParticle * > * visited_particles, int code, int code_index, int num_indices) const [protected]

for internal use only

protected: for recursive use by **Flow::dangling_connected_partners** (p. 56)

Definition at line 123 of file Flow.cc.

References HepMC::GenParticle::end_vertex(), HepMC::family, HepMC::not_in_vector(), p, HepMC::GenVertex::particles_begin(), HepMC::GenVertex::particles_end(), and HepMC::GenParticle::production_vertex().

9.9.4.7 `std::vector< GenParticle * > HepMC::Flow::dangling_connected_partners (int code, int code_index = 1, int num_indices = 2) const`

same as `connected_partners`, but returns only those particles which are connected to ≤ 1 other particles (i.e. the flow line "dangles" at these particles)

Definition at line 108 of file `Flow.cc`.

References `icode()`, and `HepMC::detail::output()`.

9.9.4.8 `bool HepMC::Flow::empty () const` `[inline]`

return true if there is no flow container

Definition at line 177 of file `Flow.h`.

9.9.4.9 `Flow::const_iterator HepMC::Flow::end () const` `[inline]`

end of flow pattern container

Definition at line 187 of file `Flow.h`.

9.9.4.10 `Flow::iterator HepMC::Flow::end ()` `[inline]`

end of flow pattern container

Definition at line 185 of file `Flow.h`.

9.9.4.11 `bool HepMC::Flow::erase (int code_index)` `[inline]`

empty flow pattern container

Examples:

`testFlow.cc`.

Definition at line 180 of file `Flow.h`.

Referenced by `main()`.

9.9.4.12 `int HepMC::Flow::icode (int code_index = 1) const` `[inline]`

flow code

Definition at line 163 of file `Flow.h`.

Referenced by `connected_partners()`, `dangling_connected_partners()`, and `HepMC::GenParticle::flow()`.

9.9.4.13 `bool HepMC::Flow::operator!= (const Flow & a) const` `[inline]`

inequality

Definition at line 199 of file `Flow.h`.

9.9.4.14 Flow & HepMC::Flow::operator= (const Flow &) [inline]

make a copy

copies only the m_icode ... not the particle_owner this is intuitive behaviour so you can do oneparticle->flow() = otherparticle->flow()

Definition at line 202 of file Flow.h.

References m_icode.

9.9.4.15 bool HepMC::Flow::operator==(const Flow & a) const [inline]

equality

equivalent flows have the same flow codes for all flow_numbers (i.e. their m_icode maps are identical), but they need not have the same m_particle owner

Definition at line 193 of file Flow.h.

References m_icode.

9.9.4.16 const GenParticle * HepMC::Flow::particle_owner () const [inline]

find particle owning this **Flow** (p. 52)

Definition at line 160 of file Flow.h.

9.9.4.17 void HepMC::Flow::print (std::ostream & ostr = std::cout) const

print **Flow** (p. 52) information to ostr

Definition at line 34 of file Flow.cc.

9.9.4.18 Flow HepMC::Flow::set_icode (int code_index, int code) [inline]

set flow code

Definition at line 167 of file Flow.h.

Referenced by HepMC::detail::read_particle(), and HepMC::GenParticle::set_flow().

9.9.4.19 Flow HepMC::Flow::set_unique_icode (int code_index = 1) [inline]

set unique flow code

use this method if you want to assign a unique flow code, but do not want the burden of choosing it yourself

Definition at line 171 of file Flow.h.

Referenced by HepMC::GenParticle::set_flow().

9.9.4.20 int HepMC::Flow::size () const [inline]

size of flow pattern container

Definition at line 178 of file Flow.h.

9.9.4.21 void HepMC::Flow::swap (Flow & *other*)

swap

Definition at line 28 of file Flow.cc.

References m_icode, and m_particle_owner.

Referenced by HepMC::GenParticle::swap().

9.9.5 Friends And Related Function Documentation

9.9.5.1 std::ostream& operator<< (std::ostream & *ostr*, const Flow & *f*) [friend]

for printing

Definition at line 190 of file Flow.cc.

The documentation for this class was generated from the following files:

- **Flow.h**
- **Flow.cc**

9.10 HepMC::FourVector Class Reference

FourVector (p. 59) is a simple representation of a physics 4 vector.

```
#include <SimpleVector.h>
```

Public Member Functions

- **FourVector (double xin, double yin, double zin, double tin=0)**
constructor requiring at least x, y, and z
- **FourVector (double t)**
constructor requiring only t
- **FourVector ()**
- **template<class T> FourVector (const T &v, typename detail::disable_if< detail::is_arithmetic< T >::value, void >::type *=0)**
- **FourVector (const FourVector &v)**
copy constructor
- **void swap (FourVector &other)**
swap
- **double px () const**
return px
- **double py () const**
return py
- **double pz () const**
return pz
- **double e () const**
return E
- **double x () const**
return x
- **double y () const**
return y
- **double z () const**
return z
- **double t () const**
return t
- **double m2 () const**
Invariant mass squared.

- **double m () const**
Invariant mass. If $m2()$ (p. 62) is negative then $-\sqrt{-m2()}$ is returned.
- **double perp2 () const**
Transverse component of the spatial vector squared.
- **double perp () const**
Transverse component of the spatial vector (R in cylindrical system).
- **double theta () const**
The polar angle.
- **double phi () const**
The azimuth angle.
- **double rho () const**
spatial vector component magnitude
- **FourVector & operator= (const FourVector &)**
make a copy
- **bool operator== (const FourVector &) const**
equality
- **bool operator!= (const FourVector &) const**
inequality
- **double pseudoRapidity () const**
Returns the pseudo-rapidity, i.e. $-\ln(\tan(\theta/2))$.
- **double eta () const**
Pseudorapidity (of the space part).
- **void set (double x, double y, double z, double t)**
set x , y , z , and t
- **void setX (double x)**
set x
- **void setY (double y)**
set y
- **void setZ (double z)**
set z
- **void setT (double t)**
set t
- **void setPx (double x)**
set px

- **void setPy (double y)**

set py

- **void setPz (double z)**

set pz

- **void setE (double t)**

set E

9.10.1 Detailed Description

FourVector (p. 59) is a simple representation of a physics 4 vector.

For compatibility with existing code, the basic expected geometrical access methods are provided. Also, there is a templated constructor that will take another vector (HepLorentzVector, GenVector, ...) which must have the following methods: **x()** (p. 67), **y()** (p. 67), **z()** (p. 67), **t()** (p. 67).

Examples:

testFlow.cc, testPrintBug.cc, testSimpleVector.cc, and VectorConversion.h.

Definition at line 42 of file SimpleVector.h.

9.10.2 Constructor & Destructor Documentation

9.10.2.1 HepMC::FourVector::FourVector (double *xin*, double *yin*, double *zin*, double *tin* = 0) [inline]

constructor requiring at least x, y, and z

Definition at line 47 of file SimpleVector.h.

9.10.2.2 HepMC::FourVector::FourVector (double *t*) [inline]

constructor requiring only t

Definition at line 51 of file SimpleVector.h.

9.10.2.3 HepMC::FourVector::FourVector () [inline]

Definition at line 54 of file SimpleVector.h.

9.10.2.4 template<class T> HepMC::FourVector::FourVector (const T & v, typename detail::disable_if< detail::is_arithmetic< T >::value, void >::type * = 0) [inline]

templated constructor this is used ONLY if T is not arithmetic

Definition at line 60 of file SimpleVector.h.

9.10.2.5 HepMC::FourVector::FourVector (const FourVector & v) [inline]

copy constructor

Definition at line 65 of file SimpleVector.h.

9.10.3 Member Function Documentation**9.10.3.1 double HepMC::FourVector::e () const [inline]**

return E

Examples:

testSimpleVector.cc.

Definition at line 73 of file SimpleVector.h.

Referenced by HepMC::GenParticle::convert_momentum(), main(), HepMC::operator<<(), HepMC::GenParticle::print(), repairUnits(), and HepMC::IO_HEPEVT::write_event().

9.10.3.2 double HepMC::FourVector::eta () const

Pseudorapidity (of the space part).

Examples:

testSimpleVector.cc.

Referenced by main().

9.10.3.3 double HepMC::FourVector::m () const

Invariant mass. If **m2()** (p. 62) is negative then $-\sqrt{-m2()}$ is returned.

Examples:

testSimpleVector.cc.

Referenced by main().

9.10.3.4 double HepMC::FourVector::m2 () const

Invariant mass squared.

Examples:

testSimpleVector.cc.

Referenced by main().

9.10.3.5 bool HepMC::FourVector::operator!= (const FourVector &) const

inequality

9.10.3.6 FourVector& HepMC::FourVector::operator= (const FourVector &)

make a copy

9.10.3.7 bool HepMC::FourVector::operator== (const FourVector &) const

equality

9.10.3.8 double HepMC::FourVector::perp () const

Transverse component of the spatial vector (R in cylindrical system).

Examples:

`testSimpleVector.cc.`

Referenced by `main()`.

9.10.3.9 double HepMC::FourVector::perp2 () const

Transverse component of the spatial vector squared.

Examples:

`testSimpleVector.cc.`

Referenced by `main()`.

9.10.3.10 double HepMC::FourVector::phi () const

The azimuth angle.

Examples:

`testSimpleVector.cc.`

Referenced by `main()`.

9.10.3.11 double HepMC::FourVector::pseudoRapidity () const

Returns the pseudo-rapidity, i.e. $-\ln(\tan(\theta/2))$.

Examples:

`testSimpleVector.cc.`

Referenced by `main()`.

9.10.3.12 double HepMC::FourVector::px () const [inline]

return px

Examples:

testSimpleVector.cc.

Definition at line 70 of file SimpleVector.h.

Referenced by HepMC::GenParticle::convert_momentum(), main(), HepMC::operator<<(), HepMC::GenParticle::print(), and HepMC::IO_HEPEVT::write_event().

9.10.3.13 double HepMC::FourVector::py () const [inline]

return py

Examples:

testSimpleVector.cc.

Definition at line 71 of file SimpleVector.h.

Referenced by HepMC::GenParticle::convert_momentum(), main(), HepMC::operator<<(), HepMC::GenParticle::print(), repairUnits(), and HepMC::IO_HEPEVT::write_event().

9.10.3.14 double HepMC::FourVector::pz () const [inline]

return pz

Examples:

testSimpleVector.cc.

Definition at line 72 of file SimpleVector.h.

Referenced by HepMC::GenParticle::convert_momentum(), main(), HepMC::operator<<(), HepMC::GenParticle::print(), repairUnits(), and HepMC::IO_HEPEVT::write_event().

9.10.3.15 double HepMC::FourVector::rho () const

spatial vector component magnitude

Examples:

testSimpleVector.cc.

Referenced by main().

9.10.3.16 void HepMC::FourVector::set (double x, double y, double z, double t)

set x, y, z, and t

Examples:

testSimpleVector.cc.

Referenced by main().

9.10.3.17 void HepMC::FourVector::setE (double *t*) [inline]

set E

Examples:

testSimpleVector.cc.

Definition at line 110 of file SimpleVector.h.

Referenced by main().

9.10.3.18 void HepMC::FourVector::setPx (double *x*) [inline]

set px

Examples:

testSimpleVector.cc.

Definition at line 107 of file SimpleVector.h.

Referenced by main().

9.10.3.19 void HepMC::FourVector::setPy (double *y*) [inline]

set py

Examples:

testSimpleVector.cc.

Definition at line 108 of file SimpleVector.h.

Referenced by main().

9.10.3.20 void HepMC::FourVector::setPz (double *z*) [inline]

set pz

Examples:

testSimpleVector.cc.

Definition at line 109 of file SimpleVector.h.

Referenced by main().

9.10.3.21 void HepMC::FourVector::setT (double *t*) [inline]

set t

Examples:

testSimpleVector.cc.

Definition at line 105 of file SimpleVector.h.

Referenced by main().

9.10.3.22 void HepMC::FourVector::setX (double *x*) [inline]

set x

Examples:

testSimpleVector.cc.

Definition at line 102 of file SimpleVector.h.

Referenced by main().

9.10.3.23 void HepMC::FourVector::setY (double *y*) [inline]

set y

Examples:

testSimpleVector.cc.

Definition at line 103 of file SimpleVector.h.

Referenced by main().

9.10.3.24 void HepMC::FourVector::setZ (double *z*) [inline]

set z

Examples:

testSimpleVector.cc.

Definition at line 104 of file SimpleVector.h.

Referenced by main().

9.10.3.25 void HepMC::FourVector::swap (FourVector & *other*)

swap

Referenced by HepMC::GenVertex::swap(), and HepMC::GenParticle::swap().

9.10.3.26 double HepMC::FourVector::t () const [inline]

return t

Examples:

testSimpleVector.cc.

Definition at line 78 of file SimpleVector.h.

Referenced by HepMC::GenVertex::convert_position(), main(), and HepMC::GenVertex::print().

9.10.3.27 double HepMC::FourVector::theta () const

The polar angle.

Examples:

testSimpleVector.cc.

Referenced by main().

9.10.3.28 double HepMC::FourVector::x () const [inline]

return x

Examples:

testSimpleVector.cc.

Definition at line 75 of file SimpleVector.h.

Referenced by HepMC::GenVertex::convert_position(), main(), HepMC::operator<<(), HepMC::GenVertex::point3d(), and HepMC::GenVertex::print().

9.10.3.29 double HepMC::FourVector::y () const [inline]

return y

Examples:

testSimpleVector.cc.

Definition at line 76 of file SimpleVector.h.

Referenced by HepMC::GenVertex::convert_position(), main(), HepMC::GenVertex::point3d(), and HepMC::GenVertex::print().

9.10.3.30 double HepMC::FourVector::z () const [inline]

return z

Examples:

testSimpleVector.cc.

Definition at line 77 of file SimpleVector.h.

Referenced by HepMC::GenVertex::convert_position(), main(), HepMC::GenVertex::point3d(), and HepMC::GenVertex::print().

The documentation for this class was generated from the following file:

- **SimpleVector.h**

9.11 HepMC::GenCrossSection Class Reference

The **GenCrossSection** (p. 69) class stores the generated cross section.

```
#include <GenCrossSection.h>
```

Public Member Functions

- **GenCrossSection ()**
- **~GenCrossSection ()**
- **GenCrossSection (GenCrossSection const &orig)**
copy
- **void swap (GenCrossSection &other)**
swap
- **GenCrossSection & operator= (GenCrossSection const &rhs)**
- **bool operator== (const GenCrossSection &) const**
check for equality
- **bool operator!= (const GenCrossSection &) const**
check for inequality
- **double cross_section () const**
cross section in pb
- **double cross_section_error () const**
error associated with this cross section in pb
- **bool is_set () const**
True if the cross section has been set. False by default.
- **void set_cross_section (double xs, double xs_err)**
Set cross section and error in pb.
- **void set_cross_section (double)**
set cross section in pb
- **void set_cross_section_error (double)**
set error associated with this cross section in pb
- **void clear ()**
- **std::ostream & write (std::ostream &) const**
write to an output stream
- **std::istream & read (std::istream &)**
read from an input stream

9.11.1 Detailed Description

The **GenCrossSection** (p. 69) class stores the generated cross section.

HepMC::GenCrossSection (p. 69) is used to store the generated cross section. This class is meant to be used to pass, on an event by event basis, the current best guess of the total cross section. It is expected that the final cross section will be stored elsewhere.

- double cross_section; // cross section in pb
- double cross_section_error; // error associated with this cross section

The units of cross_section and cross_section_error are expected to be pb.

GenCrossSection (p. 69) information will be written if **GenEvent** (p. 73) contains a pointer to a valid **GenCrossSection** (p. 69) object.

Examples:

testHepMC.cc.in.

Definition at line 32 of file GenCrossSection.h.

9.11.2 Constructor & Destructor Documentation

9.11.2.1 HepMC::GenCrossSection::GenCrossSection () [inline]

Definition at line 35 of file GenCrossSection.h.

9.11.2.2 HepMC::GenCrossSection::~~GenCrossSection () [inline]

Definition at line 40 of file GenCrossSection.h.

9.11.2.3 HepMC::GenCrossSection::GenCrossSection (GenCrossSection const & orig)

copy

Definition at line 19 of file GenCrossSection.cc.

9.11.3 Member Function Documentation

9.11.3.1 void HepMC::GenCrossSection::clear ()

Clear all **GenCrossSection** (p. 69) info (disables output of **GenCrossSection** (p. 69) until the cross section is set again)

Definition at line 52 of file GenCrossSection.cc.

9.11.3.2 double HepMC::GenCrossSection::cross_section () const [inline]

cross section in pb

Definition at line 55 of file GenCrossSection.h.

Referenced by operator==(), and HepMC::GenEvent::write_cross_section().

9.11.3.3 double HepMC::GenCrossSection::cross_section_error () const [inline]

error associated with this cross section in pb

Definition at line 57 of file GenCrossSection.h.

Referenced by operator==(), and HepMC::GenEvent::write_cross_section().

9.11.3.4 bool HepMC::GenCrossSection::is_set () const [inline]

True if the cross section has been set. False by default.

Definition at line 60 of file GenCrossSection.h.

Referenced by HepMC::GenEvent::read(), and write().

9.11.3.5 bool HepMC::GenCrossSection::operator!= (const GenCrossSection &) const

check for inequality

Definition at line 46 of file GenCrossSection.cc.

9.11.3.6 GenCrossSection & HepMC::GenCrossSection::operator= (GenCrossSection const & rhs)

shallow

Definition at line 32 of file GenCrossSection.cc.

References swap().

9.11.3.7 bool HepMC::GenCrossSection::operator== (const GenCrossSection &) const

check for equality

Definition at line 39 of file GenCrossSection.cc.

References cross_section(), and cross_section_error().

9.11.3.8 std::istream & HepMC::GenCrossSection::read (std::istream &)

read from an input stream

Definition at line 76 of file GenCrossSection.cc.

References set_cross_section().

Referenced by HepMC::operator>>(), and HepMC::GenEvent::read().

9.11.3.9 void HepMC::GenCrossSection::set_cross_section (double) [inline]

set cross section in pb

Definition at line 103 of file GenCrossSection.h.

9.11.3.10 void HepMC::GenCrossSection::set_cross_section (double xs, double xs_err)
[inline]

Set cross section and error in pb.

Examples:

testHepMC.cc.in.

Definition at line 98 of file GenCrossSection.h.

References set_cross_section_error().

Referenced by HepMC::getHerwigCrossSection(), HepMC::getPythiaCrossSection(), and read().

9.11.3.11 void HepMC::GenCrossSection::set_cross_section_error (double) [inline]

set error associated with this cross section in pb

Definition at line 109 of file GenCrossSection.h.

Referenced by set_cross_section().

9.11.3.12 void HepMC::GenCrossSection::swap (GenCrossSection & other)

swap

Definition at line 25 of file GenCrossSection.cc.

References m_cross_section, m_cross_section_error, and m_is_set.

Referenced by operator=().

9.11.3.13 std::ostream & HepMC::GenCrossSection::write (std::ostream &) const

write to an output stream

Definition at line 59 of file GenCrossSection.cc.

References is_set().

Referenced by HepMC::operator<<(), and HepMC::GenEvent::write().

The documentation for this class was generated from the following files:

- **GenCrossSection.h**
- **GenCrossSection.cc**

9.12 HepMC::GenEvent Class Reference

The **GenEvent** (p. 73) class is the core of **HepMC** (p. 23).

```
#include <GenEvent.h>
```

Public Member Functions

- **GenEvent** (int signal_process_id=0, int event_number=0, GenVertex *signal_vertex=0, const WeightContainer &weights=std::vector< double >(), const std::vector< long > &randomstates=std::vector< long >(), Units::MomentumUnit=Units::default_momentum_unit(), Units::LengthUnit=Units::default_length_unit())
default constructor creates null pointers to HeavyIon (p.152), PdfInfo (p.220), and GenCrossSection (p.69)
- **GenEvent** (int signal_process_id, int event_number, GenVertex *signal_vertex, const WeightContainer &weights, const std::vector< long > &randomstates, const HeavyIon &ion, const PdfInfo &pdf, Units::MomentumUnit=Units::default_momentum_unit(), Units::LengthUnit=Units::default_length_unit())
explicit constructor that takes HeavyIon (p.152) and PdfInfo (p.220)
- **GenEvent** (Units::MomentumUnit, Units::LengthUnit, int signal_process_id=0, int event_number=0, GenVertex *signal_vertex=0, const WeightContainer &weights=std::vector< double >(), const std::vector< long > &randomstates=std::vector< long >())
constructor requiring units - all else is default
- **GenEvent** (Units::MomentumUnit, Units::LengthUnit, int signal_process_id, int event_number, GenVertex *signal_vertex, const WeightContainer &weights, const std::vector< long > &randomstates, const HeavyIon &ion, const PdfInfo &pdf)
explicit constructor with units first that takes HeavyIon (p.152) and PdfInfo (p.220)
- **GenEvent** (const GenEvent &inevent)
deep copy
- **GenEvent & operator=** (const GenEvent &inevent)
make a deep copy
- **virtual ~GenEvent** ()
deletes all vertices/particles in this evt
- **void swap** (GenEvent &other)
swap
- **void print** (std::ostream &ostr=std::cout) const
dumps to ostr
- **void print_version** (std::ostream &ostr=std::cout) const
dumps release version to ostr
- **GenParticle * barcode_to_particle** (int barCode) const
assign a barcode to a particle

- **GenVertex * barcode_to_vertex (int barCode) const**
assign a barcode to a vertex
- **int signal_process_id () const**
unique signal process id
- **int event_number () const**
event number
- **int mpi () const**
number of multi parton interactions
- **double event_scale () const**
energy scale, see hep-ph/0109068
- **double alphaQCD () const**
QCD coupling, see hep-ph/0109068.
- **double alphaQED () const**
- **GenVertex * signal_process_vertex () const**
pointer to the vertex containing the signal process
- **bool valid_beam_particles () const**
test to see if we have two valid beam particles
- **std::pair< HepMC::GenParticle *, HepMC::GenParticle * > beam_particles () const**
pair of pointers to the two incoming beam particles
- **bool is_valid () const**
- **WeightContainer & weights ()**
direct access to WeightContainer (p. 260)
- **const WeightContainer & weights () const**
direct access to WeightContainer (p. 260)
- **GenCrossSection const * cross_section () const**
access the GenCrossSection (p. 69) container if it exists
- **GenCrossSection * cross_section ()**
- **HeavyIon const * heavy_ion () const**
access the HeavyIon (p. 152) container if it exists
- **HeavyIon * heavy_ion ()**
- **PdfInfo const * pdf_info () const**
access the PdfInfo (p. 220) container if it exists
- **PdfInfo * pdf_info ()**
- **const std::vector< long > & random_states () const**
vector of integers containing information about the random state

- **int particles_size () const**
how many particle barcodes exist?
- **bool particles_empty () const**
return true if there are no particle barcodes
- **int vertices_size () const**
how many vertex barcodes exist?
- **bool vertices_empty () const**
return true if there are no vertex barcodes
- **void write_units (std::ostream &os=std::cout) const**
- **void write_cross_section (std::ostream &ostr=std::cout) const**
- **Units::MomentumUnit momentum_unit () const**
Units (p. 39) used by the GenParticle (p. 111) momentum FourVector (p. 59).
- **Units::LengthUnit length_unit () const**
Units (p. 39) used by the GenVertex (p. 126) position FourVector (p. 59).
- **std::ostream & write (std::ostream &)**
- **std::istream & read (std::istream &)**
- **bool add_vertex (GenVertex *vtx)**
adds to evt and adopts
- **bool remove_vertex (GenVertex *vtx)**
erases vtx from evt
- **void clear ()**
empties the entire event
- **void set_signal_process_id (int id)**
set unique signal process id
- **void set_event_number (int eventno)**
set event number
- **void set_mpi (int)**
Use this to set the number of multi parton interactions in each event.
- **void set_event_scale (double scale)**
set energy scale
- **void set_alphaQCD (double a)**
set QCD coupling
- **void set_alphaQED (double a)**
set QED coupling

- **void set_signal_process_vertex (GenVertex *)**
set pointer to the vertex containing the signal process
- **bool set_beam_particles (GenParticle *, GenParticle *)**
set incoming beam particles
- **bool set_beam_particles (std::pair< HepMC::GenParticle *, HepMC::GenParticle * > const &)**
use a pair of GenParticle's to set incoming beam particles*
- **void set_random_states (const std::vector< long > &randomstates)**
provide random state information
- **void set_cross_section (const GenCrossSection &)**
provide a pointer to the GenCrossSection (p. 69) container
- **void set_heavy_ion (const HeavyIon &ion)**
provide a pointer to the HeavyIon (p. 152) container
- **void set_pdf_info (const PdfInfo &p)**
provide a pointer to the PdfInfo (p. 220) container
- **void use_units (Units::MomentumUnit, Units::LengthUnit)**
set the units using enums
- **void use_units (std::string &, std::string &)**
- **GenEventVertexRange vertex_range ()**
vertex range
- **ConstGenEventVertexRange vertex_range () const**
vertex range
- **GenEventParticleRange particle_range ()**
particle range
- **ConstGenEventParticleRange particle_range () const**
particle range
- **vertex_const_iterator vertices_begin () const**
begin vertex iteration
- **vertex_const_iterator vertices_end () const**
end vertex iteration
- **vertex_iterator vertices_begin ()**
begin vertex iteration
- **vertex_iterator vertices_end ()**
end vertex iteration

- **particle_const_iterator particles_begin () const**
begin particle iteration
- **particle_const_iterator particles_end () const**
end particle iteration
- **particle_iterator particles_begin ()**
begin particle iteration
- **particle_iterator particles_end ()**
end particle iteration

Protected Member Functions

- **bool set_barcode (GenParticle *p, int suggested_barcode=false)**
set the barcode - intended for use by GenParticle (p. 111)
- **bool set_barcode (GenVertex *v, int suggested_barcode=false)**
set the barcode - intended for use by GenVertex (p. 126)
- **void remove_barcode (GenParticle *p)**
intended for use by GenParticle (p. 111)
- **void remove_barcode (GenVertex *v)**
intended for use by GenVertex (p. 126)
- **void delete_all_vertices ()**
delete all vertices owned by this event

Friends

- **class GenParticle**
- **class GenVertex**
- **class vertex_const_iterator**
- **class vertex_iterator**
- **class particle_const_iterator**
- **class particle_iterator**

Classes

- **class particle_const_iterator**
const particle iterator
- **class particle_iterator**
non-const particle iterator
- **class vertex_const_iterator**

const vertex iterator

- **class vertex_iterator**

non-const vertex iterator

9.12.1 Detailed Description

The **GenEvent** (p. 73) class is the core of **HepMC** (p. 23).

HepMC::GenEvent (p. 73) contains information about generated particles. **GenEvent** (p. 73) is structured as a set of vertices which contain the particles.

Examples:

example_BuildEventFromScratch.cc, example_EventSelection.cc, example_MyHerwig.cc, example_MyPythia.cc, example_MyPythiaOnlyToHepMC.cc, example_PythiaStreamIO.cc, example_UsingIterators.cc, testFlow.cc, testHepMC.cc.in, testHepMCIteration.cc.in, test-HerwigCopies.cc, testMass.cc.in, testMultipleCopies.cc.in, testPrintBug.cc, testPythiaCopies.cc, and testStreamIO.cc.in.

Definition at line 155 of file GenEvent.h.

9.12.2 Constructor & Destructor Documentation

9.12.2.1 HepMC::GenEvent::GenEvent (int signal_process_id = 0, int event_number = 0, GenVertex * signal_vertex = 0, const WeightContainer & weights = std::vector< double >(), const std::vector< long > & randomstates = std::vector< long >(), Units::MomentumUnit = Units::default_momentum_unit(), Units::LengthUnit = Units::default_length_unit())

default constructor creates null pointers to **HeavyIon** (p. 152), **PdfInfo** (p. 220), and **GenCrossSection** (p. 69)

This constructor only allows null pointers to **HeavyIon** (p. 152) and **PdfInfo** (p. 220)

note: default values for m_event_scale, m_alphaQCD, m_alphaQED are as suggested in hep-ph/0109068, "Generic Interface..."

Definition at line 22 of file GenEvent.cc.

9.12.2.2 HepMC::GenEvent::GenEvent (int signal_process_id, int event_number, GenVertex * signal_vertex, const WeightContainer & weights, const std::vector< long > & randomstates, const HeavyIon & ion, const PdfInfo & pdf, Units::MomentumUnit = Units::default_momentum_unit(), Units::LengthUnit = Units::default_length_unit())

explicit constructor that takes **HeavyIon** (p. 152) and **PdfInfo** (p. 220)

GenEvent (p. 73) makes its own copy of **HeavyIon** (p. 152) and **PdfInfo** (p. 220)

note: default values for m_event_scale, m_alphaQCD, m_alphaQED are as suggested in hep-ph/0109068, "Generic Interface..."

Definition at line 55 of file GenEvent.cc.

9.12.2.3 HepMC::GenEvent::GenEvent (Units::MomentumUnit, Units::LengthUnit, int *signal_process_id* = 0, int *event_number* = 0, GenVertex * *signal_vertex* = 0, const WeightContainer & *weights* = std::vector< double >(), const std::vector< long > & *randomstates* = std::vector< long >())

constructor requiring units - all else is default

constructor requiring units - all else is default This constructor only allows null pointers to **HeavyIon** (p. 152) and **PdfInfo** (p. 220)

note: default values for *m_event_scale*, *m_alphaQCD*, *m_alphaQED* are as suggested in hep-ph/0109068, "Generic Interface..."

Definition at line 88 of file GenEvent.cc.

9.12.2.4 HepMC::GenEvent::GenEvent (Units::MomentumUnit, Units::LengthUnit, int *signal_process_id*, int *event_number*, GenVertex * *signal_vertex*, const WeightContainer & *weights*, const std::vector< long > & *randomstates*, const HeavyIon & *ion*, const PdfInfo & *pdf*)

explicit constructor with units first that takes **HeavyIon** (p. 152) and **PdfInfo** (p. 220)

explicit constructor with units first that takes **HeavyIon** (p. 152) and **PdfInfo** (p. 220) **GenEvent** (p. 73) makes its own copy of **HeavyIon** (p. 152) and **PdfInfo** (p. 220)

note: default values for *m_event_scale*, *m_alphaQCD*, *m_alphaQED* are as suggested in hep-ph/0109068, "Generic Interface..."

Definition at line 122 of file GenEvent.cc.

9.12.2.5 HepMC::GenEvent::GenEvent (const GenEvent & *inevent*)

deep copy

deep copy - makes a copy of all vertices!

Definition at line 156 of file GenEvent.cc.

References `add_vertex()`, `beam_particles()`, `GenParticle`, `GenVertex`, `p`, `particles_begin()`, `particles_end()`, `random_states()`, `set_beam_particles()`, `set_random_states()`, `set_signal_process_vertex()`, `signal_process_vertex()`, `v`, `vertices_begin()`, `vertices_end()`, and `weights()`.

9.12.2.6 HepMC::GenEvent::~~GenEvent () [virtual]

deletes all vertices/particles in this evt

Deep destructor. deletes all vertices/particles in this **GenEvent** (p. 73) deletes the associated **HeavyIon** (p. 152) and **PdfInfo** (p. 220)

Definition at line 258 of file GenEvent.cc.

References `delete_all_vertices()`.

9.12.3 Member Function Documentation

9.12.3.1 `bool HepMC::GenEvent::add_vertex (GenVertex * vtx)`

adds to evt and adopts

returns true if successful - generally will only return false if the inserted vertex is already included in the event.

Examples:

example_BuildEventFromScratch.cc, testFlow.cc, and testPrintBug.cc.

Definition at line 334 of file GenEvent.cc.

References `HepMC::GenVertex::barcode()`, `HepMC::GenVertex::parent_event()`, `remove_vertex()`, and `HepMC::GenVertex::set_parent_event_()`.

Referenced by `HepMC::IO_HERWIG::build_end_vertex()`, `HepMC::IO_HEPEVT::build_end_vertex()`, `HepMC::IO_HERWIG::build_production_vertex()`, `HepMC::IO_HEPEVT::build_production_vertex()`, `HepMC::IO_HERWIG::fill_next_event()`, `HepMC::IO_HEPEVT::fill_next_event()`, `GenEvent()`, `main()`, `read()`, and `set_signal_process_vertex()`.

9.12.3.2 `double HepMC::GenEvent::alphaQCD () const` `[inline]`

QCD coupling, see hep-ph/0109068.

Definition at line 680 of file GenEvent.h.

Referenced by `HepMC::compareGenEvent()`, `print()`, `write()`, and `HepMC::IO_AsciiParticles::write_event()`.

9.12.3.3 `double HepMC::GenEvent::alphaQED () const` `[inline]`

QED coupling, see hep-ph/0109068

Definition at line 682 of file GenEvent.h.

Referenced by `HepMC::compareGenEvent()`, `print()`, `write()`, and `HepMC::IO_AsciiParticles::write_event()`.

9.12.3.4 `GenParticle * HepMC::GenEvent::barcode_to_particle (int barCode) const` `[inline]`

assign a barcode to a particle

Each vertex or particle has a barcode, which is just an integer which uniquely identifies it inside the event (i.e. there is a one to one mapping between particle memory addresses and particle barcodes... and the same applied for vertices).

The value of a barcode has NO MEANING and NO ORDER! For the user's convenience, when an event is read in via an IO_method from an indexed list (like the HEPEVT common block), then the index will become the barcode for that particle.

Particle barcodes are always positive integers. The barcodes are chosen and set automatically when a vertex or particle comes under the ownership of an event (i.e. it is contained in an event).

Please note that the barcodes are intended for internal use within **HepMC** (p. 23) as a unique identifier for the particles and vertices. Using the barcode to encode extra information is an abuse of the barcode data

member and causes confusion among users.

Definition at line 788 of file GenEvent.h.

9.12.3.5 GenVertex * HepMC::GenEvent::barcode_to_vertex (int *barCode*) const [inline]

assign a barcode to a vertex

Each vertex or particle has a barcode, which is just an integer which uniquely identifies it inside the event (i.e. there is a one to one mapping between particle memory addresses and particle barcodes... and the same applied for vertices).

The value of a barcode has NO MEANING and NO ORDER! For the user's convenience, when an event is read in via an IO_method from an indexed list (like the HEPEVT common block), then the index will become the barcode for that particle.

Vertex barcodes are always negative integers. The barcodes are chosen and set automatically when a vertex or particle comes under the ownership of an event (i.e. it is contained in an event).

Please note that the barcodes are intended for internal use within **HepMC** (p. 23) as a unique identifier for the particles and vertices. Using the barcode to encode extra information is an abuse of the barcode data member and causes confusion among users.

Definition at line 813 of file GenEvent.h.

Referenced by HepMC::compareVertices(), and read().

9.12.3.6 std::pair< HepMC::GenParticle *, HepMC::GenParticle * > HepMC::GenEvent::beam_particles () const [inline]

pair of pointers to the two incoming beam particles

Examples:

testMass.cc.in.

Definition at line 834 of file GenEvent.h.

Referenced by HepMC::compareBeamParticles(), filterEvent(), GenEvent(), print(), and write().

9.12.3.7 void HepMC::GenEvent::clear ()

empties the entire event

remove all information from the event deletes all vertices/particles in this evt

Examples:

testHepMCIteration.cc.in, and testStreamIO.cc.in.

Definition at line 365 of file GenEvent.cc.

References HepMC::Units::default_length_unit(), HepMC::Units::default_momentum_unit(), and delete_all_vertices().

Referenced by HepMC::IO_GenEvent::fill_next_event(), and read().

9.12.3.8 GenCrossSection * HepMC::GenEvent::cross_section () [inline]

Definition at line 697 of file GenEvent.h.

9.12.3.9 GenCrossSection const * HepMC::GenEvent::cross_section () const [inline]

access the **GenCrossSection** (p. 69) container if it exists

Examples:

example_PythiaStreamIO.cc, and testHepMC.cc.in.

Definition at line 694 of file GenEvent.h.

Referenced by readPythiaStreamIO(), and write_cross_section().

9.12.3.10 void HepMC::GenEvent::delete_all_vertices () [protected]

delete all vertices owned by this event

deletes all vertices in the vertex container (i.e. all vertices owned by this event) The vertices are the "owners" of the particles, so as we delete the vertices, the vertex destructors are automatically deleting their particles.

Definition at line 403 of file GenEvent.cc.

References particles_empty(), and vertices_empty().

Referenced by clear(), and ~GenEvent().

9.12.3.11 int HepMC::GenEvent::event_number () const [inline]

event number

Examples:

example_EventSelection.cc, example_MyPythia.cc, testHepMC.cc.in, testHepMCIteration.cc.in, testHerwigCopies.cc, testMass.cc.in, testMultipleCopies.cc.in, testPythiaCopies.cc, and test-StreamIO.cc.in.

Definition at line 672 of file GenEvent.h.

Referenced by HepMC::compareGenEvent(), main(), particleTypes(), print(), pythia_in(), pythia_in_out(), write(), HepMC::IO_HEPEVT::write_event(), and HepMC::IO_AsciiParticles::write_event().

9.12.3.12 double HepMC::GenEvent::event_scale () const [inline]

energy scale, see hep-ph/0109068

Definition at line 678 of file GenEvent.h.

Referenced by HepMC::compareGenEvent(), print(), write(), and HepMC::IO_AsciiParticles::write_event().

9.12.3.13 HeavyIon * HepMC::GenEvent::heavy_ion () [inline]

Definition at line 703 of file GenEvent.h.

9.12.3.14 HeavyIon const * HepMC::GenEvent::heavy_ion () const [inline]

access the **HeavyIon** (p. 152) container if it exists

Definition at line 700 of file GenEvent.h.

Referenced by HepMC::compareGenEvent(), and write().

9.12.3.15 bool HepMC::GenEvent::is_valid () const

check **GenEvent** (p. 73) for validity A **GenEvent** (p. 73) is presumed valid if it has particles and/or vertices.

A **GenEvent** (p. 73) is presumed valid if it has both associated particles and vertices. No other information is checked.

Examples:

example_PythiaStreamIO.cc, and testStreamIO.cc.in.

Definition at line 665 of file GenEvent.cc.

References particles_empty(), and vertices_empty().

Referenced by HepMC::IO_GenEvent::fill_next_event(), and readPythiaStreamIO().

9.12.3.16 Units::LengthUnit HepMC::GenEvent::length_unit () const [inline]

Units (p. 39) used by the **GenVertex** (p. 126) position **FourVector** (p. 59).

Definition at line 842 of file GenEvent.h.

Referenced by write(), and write_units().

9.12.3.17 Units::MomentumUnit HepMC::GenEvent::momentum_unit () const [inline]

Units (p. 39) used by the **GenParticle** (p. 111) momentum **FourVector** (p. 59).

Definition at line 839 of file GenEvent.h.

Referenced by write(), and write_units().

9.12.3.18 int HepMC::GenEvent::mpi () const [inline]

number of multi parton interactions

Returns the number of multi parton interactions in the event. This number is -1 if it is not set.

Definition at line 676 of file GenEvent.h.

Referenced by HepMC::compareGenEvent(), and write().

9.12.3.19 GenEvent & HepMC::GenEvent::operator= (const GenEvent & *inevent*)

make a deep copy

best practices implementation

Definition at line 269 of file GenEvent.cc.

References swap().

9.12.3.20 ConstGenEventParticleRange HepMC::GenEvent::particle_range () const

particle range

Definition at line 31 of file GenRanges.cc.

9.12.3.21 GenEventParticleRange HepMC::GenEvent::particle_range ()

particle range

Examples:

testHepMCIteration.cc.in.

Definition at line 26 of file GenRanges.cc.

9.12.3.22 particle_iterator HepMC::GenEvent::particles_begin () [inline]

begin particle iteration

Definition at line 555 of file GenEvent.h.

9.12.3.23 particle_const_iterator HepMC::GenEvent::particles_begin () const [inline]

begin particle iteration

Examples:

example_BuildEventFromScratch.cc, example_EventSelection.cc, example_MyPythia.cc, example_UsingIterators.cc, testHepMCIteration.cc.in, testMass.cc.in, and testMultiple-Copies.cc.in.

Definition at line 497 of file GenEvent.h.

Referenced by HepMC::ConstGenEventParticleRange::begin(), HepMC::GenEventParticleRange::begin(), HepMC::compareParticles(), filterEvent(), findPiZero(), GenEvent(), main(), IsGoodEvent::operator(), IsGoodEventMyPythia::operator(), IsEventGood::operator(), particleTypes(), repairUnits(), valid_beam_particles(), and HepMC::IO_AsciiParticles::write_event().

9.12.3.24 bool HepMC::GenEvent::particles_empty () const [inline]

return true if there are no particle barcodes

Definition at line 823 of file GenEvent.h.

Referenced by delete_all_vertices(), and is_valid().

9.12.3.25 particle_iterator HepMC::GenEvent::particles_end () [inline]

end particle iteration

Definition at line 559 of file GenEvent.h.

9.12.3.26 particle_const_iterator HepMC::GenEvent::particles_end () const [inline]

end particle iteration

Examples:

example_BuildEventFromScratch.cc, example_EventSelection.cc, example_MyPythia.cc, example_UsingIterators.cc, testHepMCIteration.cc.in, testMass.cc.in, and testMultipleCopies.cc.in.

Definition at line 501 of file GenEvent.h.

Referenced by HepMC::compareParticles(), HepMC::ConstGenEventParticleRange::end(), HepMC::GenEventParticleRange::end(), filterEvent(), findPiZero(), GenEvent(), main(), IsGoodEvent::operator>(), IsGoodEventMyPythia::operator>(), IsEventGood::operator>(), particleTypes(), repairUnits(), valid_beam_particles(), and HepMC::IO_AsciiParticles::write_event().

9.12.3.27 int HepMC::GenEvent::particles_size () const [inline]

how many particle barcodes exist?

Examples:

testMultipleCopies.cc.in.

Definition at line 820 of file GenEvent.h.

Referenced by HepMC::compareParticles(), particleTypes(), print(), and HepMC::IO_AsciiParticles::write_event().

9.12.3.28 PdfInfo * HepMC::GenEvent::pdf_info () [inline]

Definition at line 709 of file GenEvent.h.

9.12.3.29 PdfInfo const * HepMC::GenEvent::pdf_info () const [inline]

access the PdfInfo (p. 220) container if it exists

Definition at line 706 of file GenEvent.h.

Referenced by HepMC::compareGenEvent(), and write().

9.12.3.30 void HepMC::GenEvent::print (std::ostream & ostr = std::cout) const

dumps to ostr

dumps the content of this event to ostr to dump to cout use: event.print(); if you want to write this event to file outfile.txt you could use: std::ofstream outfile("outfile.txt"); event.print(outfile);

Examples:

example_BuildEventFromScratch.cc, example_MyHerwig.cc, testFlow.cc, testHepMC.cc.in, testHerwigCopies.cc, testMultipleCopies.cc.in, testPrintBug.cc, and testPythiaCopies.cc.

Definition at line 277 of file GenEvent.cc.

References alphaQCD(), alphaQED(), HepMC::GenVertex::barcode(), beam_particles(), event_number(), event_scale(), particles_size(), HepMC::WeightContainer::print(), signal_process_id(), signal_process_vertex(), HepMC::WeightContainer::size(), vertices_end(), vertices_size(), weights(), write_cross_section(), and write_units().

Referenced by main().

9.12.3.31 void HepMC::GenEvent::print_version (std::ostream & ostr = std::cout) const

dumps release version to ostr

Definition at line 328 of file GenEvent.cc.

References HepMC::writeVersion().

9.12.3.32 const std::vector< long > & HepMC::GenEvent::random_states () const [inline]

vector of integers containing information about the random state

Vector of integers which specify the random number generator's state for this event. It is left to the generator to make use of this. We envision a vector of RndmStatesTags to be included with a run class which would specify the meaning of the random_states.

Definition at line 717 of file GenEvent.h.

Referenced by HepMC::compareGenEvent(), GenEvent(), and HepMC::IO_AsciiParticles::write_event().

9.12.3.33 std::istream & HepMC::GenEvent::read (std::istream &)**Examples:**

example_PythiaStreamIO.cc, and testStreamIO.cc.in.

Definition at line 155 of file GenEventStreamIO.cc.

References HepMC::GenVertex::add_particle_in(), add_vertex(), barcode_to_vertex(), clear(), HepMC::TempParticleMap::end_vertex(), HepMC::extascii, HepMC::detail::find_event_end(), HepMC::StreamInfo::finished_first_event(), HepMC::gen, GenVertex, HepMC::get_stream_info(), HepMC::StreamInfo::has_key(), HepMC::StreamInfo::io_type(), HepMC::GenCrossSection::is_set(), HepMC::TempParticleMap::order_begin(), HepMC::TempParticleMap::order_end(), p, HepMC::GenCrossSection::read(), HepMC::detail::read_vertex(), HepMC::StreamInfo::reading_event_header(), set_beam_particles(), set_cross_section(), HepMC::StreamInfo::set_finished_first_event(), set_heavy_ion(), set_pdf_info(), HepMC::StreamInfo::set_reading_event_header(), set_signal_process_vertex(), signal_process_vertex(), and v.

Referenced by HepMC::operator>>(), and readPythiaStreamIO().

9.12.3.34 void HepMC::GenEvent::remove_barcode (GenVertex * *v*) [inline, protected]

intended for use by **GenVertex** (p. 126)

Definition at line 767 of file GenEvent.h.

References *v*.

9.12.3.35 void HepMC::GenEvent::remove_barcode (GenParticle * *p*) [inline, protected]

intended for use by **GenParticle** (p. 111)

Definition at line 764 of file GenEvent.h.

References *p*.

Referenced by HepMC::GenParticle::set_end_vertex_(), HepMC::GenVertex::set_parent_event_(), HepMC::GenParticle::set_production_vertex_(), HepMC::GenParticle::~~GenParticle(), and HepMC::GenVertex::~~GenVertex().

9.12.3.36 bool HepMC::GenEvent::remove_vertex (GenVertex * *vtx*)

erases *vtx* from evt

this removes *vtx* from the event but does NOT delete it. returns True if an entry *vtx* existed in the table and was erased

Definition at line 357 of file GenEvent.cc.

References HepMC::GenVertex::barcode(), HepMC::GenVertex::parent_event(), and HepMC::GenVertex::set_parent_event_().

Referenced by add_vertex().

9.12.3.37 void HepMC::GenEvent::set_alphaQCD (double *a*) [inline]

set QCD coupling

Definition at line 733 of file GenEvent.h.

9.12.3.38 void HepMC::GenEvent::set_alphaQED (double *a*) [inline]

set QED coupling

Definition at line 735 of file GenEvent.h.

9.12.3.39 bool HepMC::GenEvent::set_barcode (GenVertex * *v*, int *suggested_barcode* = false) [protected]

set the barcode - intended for use by **GenVertex** (p. 126)

Definition at line 501 of file GenEvent.cc.

References *v*.

9.12.3.40 `bool HepMC::GenEvent::set_barcode (GenParticle * p, int suggested_barcode = false)`
`[protected]`

set the barcode - intended for use by **GenParticle** (p. 111)

Definition at line 430 of file GenEvent.cc.

References `p`.

Referenced by `HepMC::GenVertex::set_parent_event()`, `HepMC::GenVertex::suggest_barcode()`, and `HepMC::GenParticle::suggest_barcode()`.

9.12.3.41 `bool HepMC::GenEvent::set_beam_particles (std::pair< HepMC::GenParticle *, HepMC::GenParticle * > const & bp)`

use a pair of `GenParticle*`'s to set incoming beam particles

construct the beam particle information using a `std::pair` of pointers to **GenParticle** (p. 111) returns false if either `GenParticle*` is null

Definition at line 595 of file GenEvent.cc.

References `set_beam_particles()`.

9.12.3.42 `bool HepMC::GenEvent::set_beam_particles (GenParticle * bp1, GenParticle * bp2)`

set incoming beam particles

construct the beam particle information using pointers to **GenParticle** (p. 111) returns false if either `GenParticle*` is null

Definition at line 586 of file GenEvent.cc.

Referenced by `HepMC::IO_HERWIG::fill_next_event()`, `HepMC::IO_HEPEVT::fill_next_event()`, `GenEvent()`, `read()`, and `set_beam_particles()`.

9.12.3.43 `void HepMC::GenEvent::set_cross_section (const GenCrossSection &) [inline]`

provide a pointer to the **GenCrossSection** (p. 69) container

Examples:

`example_MyHerwig.cc`, `example_MyPythia.cc`, `example_MyPythiaOnlyToHepMC.cc`,
`example_PythiaStreamIO.cc`, `testHepMC.cc.in`, `testHerwigCopies.cc`, and `testPythiaCopies.cc`.

Definition at line 742 of file GenEvent.h.

Referenced by `event_selection()`, `main()`, `pythia_in_out()`, `pythia_out()`, `pythia_particle_out()`, `read()`, and `writePythiaStreamIO()`.

9.12.3.44 `void HepMC::GenEvent::set_event_number (int eventno) [inline]`

set event number

Examples:

`example_MyHerwig.cc`, `example_MyPythia.cc`, `example_PythiaStreamIO.cc`, and `testHerwigCopies.cc`.

Definition at line 723 of file GenEvent.h.

Referenced by HepMC::IO_HERWIG::fill_next_event(), HepMC::IO_HEPEVT::fill_next_event(), main(), pythia_in_out(), pythia_out(), pythia_particle_out(), and writePythiaStreamIO().

9.12.3.45 void HepMC::GenEvent::set_event_scale (double *scale*) [inline]

set energy scale

Definition at line 731 of file GenEvent.h.

9.12.3.46 void HepMC::GenEvent::set_heavy_ion (const HeavyIon & *ion*) [inline]

provide a pointer to the **HeavyIon** (p. 152) container

Examples:

testMass.cc.in.

Definition at line 748 of file GenEvent.h.

Referenced by read().

9.12.3.47 void HepMC::GenEvent::set_mpi (int) [inline]

Use this to set the number of multi parton interactions in each event.

Examples:

example_MyPythia.cc, example_MyPythiaOnlyToHepMC.cc, example_PythiaStreamIO.cc, and testPythiaCopies.cc.

Definition at line 727 of file GenEvent.h.

Referenced by event_selection(), main(), pythia_out(), and writePythiaStreamIO().

9.12.3.48 void HepMC::GenEvent::set_pdf_info (const PdfInfo & *p*) [inline]

provide a pointer to the **PdfInfo** (p. 220) container

Examples:

testMass.cc.in.

Definition at line 754 of file GenEvent.h.

References p.

Referenced by read().

9.12.3.49 void HepMC::GenEvent::set_random_states (const std::vector< long > & *randomstates*) [inline]

provide random state information

Definition at line 760 of file GenEvent.h.

Referenced by GenEvent().

9.12.3.50 void HepMC::GenEvent::set_signal_process_id (int *id*) [inline]

set unique signal process id

Examples:

example_MyHerwig.cc, example_MyPythia.cc, example_PythiaStreamIO.cc, and testHerwig-Copies.cc.

Definition at line 720 of file GenEvent.h.

Referenced by main(), pythia_in_out(), pythia_out(), pythia_particle_out(), and writePythiaStreamIO().

9.12.3.51 void HepMC::GenEvent::set_signal_process_vertex (GenVertex *) [inline]

set pointer to the vertex containing the signal process

Examples:

example_BuildEventFromScratch.cc, and testFlow.cc.

Definition at line 737 of file GenEvent.h.

References add_vertex().

Referenced by HepMC::IO_HERWIG::fill_next_event(), GenEvent(), main(), and read().

9.12.3.52 int HepMC::GenEvent::signal_process_id () const [inline]

unique signal process id

The integer ID that uniquely specifies this signal process, i.e. MSUB in Pythia. It is necessary to package this with each event rather than with the run because many processes may be generated within one run.

Definition at line 669 of file GenEvent.h.

Referenced by HepMC::compareGenEvent(), print(), write(), and HepMC::IO_AsciiParticles::write_event().

9.12.3.53 GenVertex * HepMC::GenEvent::signal_process_vertex () const [inline]

pointer to the vertex containing the signal process

returns a (mutable) pointer to the signal process vertex

Definition at line 684 of file GenEvent.h.

Referenced by HepMC::compareSignalProcessVertex(), GenEvent(), print(), read(), write(), and HepMC::IO_AsciiParticles::write_event().

9.12.3.54 void HepMC::GenEvent::swap (GenEvent & *other*)

swap

Definition at line 226 of file GenEvent.cc.

References m_alphaQCD, m_alphaQED, m_beam_particle_1, m_beam_particle_2, m_cross_section, m_event_number, m_event_scale, m_heavy_ion, m_momentum_unit, m_mpi, m_particle_barcodes, m_pdf_info, m_position_unit, m_random_states, m_signal_process_id, m_signal_process_vertex, m_vertex_barcodes, m_weights, HepMC::WeightContainer::swap(), vertices_begin(), and vertices_end().

Referenced by operator=().

9.12.3.55 void HepMC::GenEvent::use_units (std::string &, std::string &) [inline]

set the units using strings the string must match the enum exactly

Definition at line 851 of file GenEvent.h.

9.12.3.56 void HepMC::GenEvent::use_units (Units::MomentumUnit, Units::LengthUnit) [inline]

set the units using enums

Examples:

example_BuildEventFromScratch.cc, example_MyHerwig.cc, example_MyPythia.cc, example_MyPythiaOnlyToHepMC.cc, example_PythiaStreamIO.cc, testFlow.cc, testHerwigCopies.cc, testPrintBug.cc, and testPythiaCopies.cc.

Definition at line 846 of file GenEvent.h.

Referenced by HepMC::convert_units(), event_selection(), main(), pythia_in_out(), pythia_out(), pythia_particle_out(), HepMC::detail::read_units(), and writePythiaStreamIO().

9.12.3.57 bool HepMC::GenEvent::valid_beam_particles () const

test to see if we have two valid beam particles

Examples:

testMass.cc.in.

Definition at line 568 of file GenEvent.cc.

References p, particles_begin(), and particles_end().

9.12.3.58 ConstGenEventVertexRange HepMC::GenEvent::vertex_range () const

vertex range

Definition at line 21 of file GenRanges.cc.

9.12.3.59 GenEventVertexRange HepMC::GenEvent::vertex_range ()

vertex range

Examples:

testHepMCIteration.cc.in.

Definition at line 16 of file GenRanges.cc.

9.12.3.60 vertex_iterator HepMC::GenEvent::vertices_begin () [inline]

begin vertex iteration

Definition at line 430 of file GenEvent.h.

9.12.3.61 vertex_const_iterator HepMC::GenEvent::vertices_begin () const [inline]

begin vertex iteration

Examples:

example_UsingIterators.cc, and testHepMCIteration.cc.in.

Definition at line 367 of file GenEvent.h.

Referenced by HepMC::ConstGenEventVertexRange::begin(), HepMC::GenEventVertexRange::begin(), HepMC::compareVertices(), filterEvent(), GenEvent(), main(), swap(), write(), and HepMC::IO_HEPEVT::write_event().

9.12.3.62 bool HepMC::GenEvent::vertices_empty () const [inline]

return true if there are no vertex barcodes

Definition at line 829 of file GenEvent.h.

Referenced by delete_all_vertices(), and is_valid().

9.12.3.63 vertex_iterator HepMC::GenEvent::vertices_end () [inline]

end vertex iteration

Definition at line 434 of file GenEvent.h.

9.12.3.64 vertex_const_iterator HepMC::GenEvent::vertices_end () const [inline]

end vertex iteration

Examples:

example_UsingIterators.cc, and testHepMCIteration.cc.in.

Definition at line 371 of file GenEvent.h.

Referenced by HepMC::compareVertices(), HepMC::ConstGenEventVertexRange::end(), HepMC::GenEventVertexRange::end(), filterEvent(), GenEvent(), main(), print(), swap(), write(), and HepMC::IO_HEPEVT::write_event().

9.12.3.65 int HepMC::GenEvent::vertices_size () const [inline]

how many vertex barcodes exist?

Examples:

testMultipleCopies.cc.in.

Definition at line 826 of file GenEvent.h.

Referenced by HepMC::compareVertices(), print(), write(), and HepMC::IO_AsciiParticles::write_event().

9.12.3.66 const WeightContainer & HepMC::GenEvent::weights () const [inline]

direct access to **WeightContainer** (p. 260)

Definition at line 691 of file GenEvent.h.

9.12.3.67 WeightContainer & HepMC::GenEvent::weights () [inline]

direct access to **WeightContainer** (p. 260)

direct access to the weights container is allowed. Thus you can use myevt.weights()[2]; to access element 2 of the weights. or use myevt.weights().push_back(mywgt); to add an element. and you can set the weights with myevt.weights() = myvector;

Examples:

testHepMC.cc.in, testMass.cc.in, and testPythiaCopies.cc.

Definition at line 689 of file GenEvent.h.

Referenced by HepMC::compareWeights(), GenEvent(), main(), print(), write(), and HepMC::IO_AsciiParticles::write_event().

9.12.3.68 std::ostream & HepMC::GenEvent::write (std::ostream &)

Examples:

example_PythiaStreamIO.cc, testFlow.cc, and testStreamIO.cc.in.

Definition at line 72 of file GenEventStreamIO.cc.

References alphaQCD(), alphaQED(), beam_particles(), event_number(), event_scale(), HepMC::StreamInfo::finished_first_event(), HepMC::get_stream_info(), heavy_ion(), length_unit(), HepMC::WeightContainer::map_end(), momentum_unit(), mpi(), HepMC::Units::name(), HepMC::detail::output(), pdf_info(), HepMC::StreamInfo::set_finished_first_event(), signal_process_id(), signal_process_vertex(), HepMC::WeightContainer::size(), v, vertices_begin(), vertices_end(), vertices_size(), weights(), and HepMC::GenCrossSection::write().

Referenced by `main()`, `HepMC::operator<<()`, and `readPythiaStreamIO()`.

9.12.3.69 `void HepMC::GenEvent::write_cross_section (std::ostream & ostr = std::cout) const`

If the cross section is defined, write the cross section information to an output stream. If the output stream is not defined, use `std::cout`.

Examples:

`testHepMC.cc.in.`

Definition at line 605 of file `GenEvent.cc`.

References `HepMC::GenCrossSection::cross_section()`, `cross_section()`, and `HepMC::GenCrossSection::cross_section_error()`.

Referenced by `print()`.

9.12.3.70 `void HepMC::GenEvent::write_units (std::ostream & os = std::cout) const`

Write the unit information to an output stream. If the output stream is not defined, use `std::cout`.

Examples:

`testHepMC.cc.in`, and `testStreamIO.cc.in`.

Definition at line 599 of file `GenEvent.cc`.

References `length_unit()`, `momentum_unit()`, and `HepMC::Units::name()`.

Referenced by `print()`.

9.12.4 Friends And Related Function Documentation

9.12.4.1 `friend class GenParticle` [friend]

Definition at line 156 of file `GenEvent.h`.

Referenced by `GenEvent()`.

9.12.4.2 `friend class GenVertex` [friend]

Definition at line 157 of file `GenEvent.h`.

Referenced by `GenEvent()`, and `read()`.

9.12.4.3 `friend class particle_const_iterator` [friend]

Definition at line 495 of file `GenEvent.h`.

Referenced by `HepMC::GenEvent::particle_iterator::operator particle_const_iterator()`.

9.12.4.4 `friend class particle_iterator` [friend]

Definition at line 553 of file `GenEvent.h`.

9.12.4.5 friend class vertex_const_iterator [friend]

Definition at line 365 of file GenEvent.h.

Referenced by HepMC::GenEvent::vertex_iterator::operator vertex_const_iterator().

9.12.4.6 friend class vertex_iterator [friend]

Definition at line 428 of file GenEvent.h.

The documentation for this class was generated from the following files:

- **GenEvent.h**
- **GenEvent.cc**
- **GenEventStreamIO.cc**
- **GenRanges.cc**

9.13 HepMC::GenEvent::particle_const_iterator Class Reference

const particle iterator

```
#include <GenEvent.h>
```

Public Member Functions

- **particle_const_iterator** (const std::map< int, HepMC::GenParticle * >::const_iterator &i)
iterate over particles
- **particle_const_iterator** ()
- **particle_const_iterator** (const particle_const_iterator &i)
copy constructor
- **virtual ~particle_const_iterator** ()
- **particle_const_iterator & operator=** (const particle_const_iterator &i)
make a copy
- **GenParticle * operator *** (void) const
return a pointer to GenParticle (p. 111)
- **particle_const_iterator & operator++** (void)
Pre-fix increment.
- **particle_const_iterator operator++** (int)
Post-fix increment.
- **bool operator==** (const particle_const_iterator &a) const
equality
- **bool operator!=** (const particle_const_iterator &a) const
inequality

Protected Attributes

- std::map< int, HepMC::GenParticle * >::const_iterator m_map_iterator
const iterator to the GenParticle (p. 111) map

9.13.1 Detailed Description

const particle iterator

HepMC::GenEvent::particle_const_iterator (p. 96) is used to iterate over all particles in the event.

Examples:

`example_BuildEventFromScratch.cc`, `example_EventSelection.cc`, `example_MyPythia.cc`, `test-Mass.cc.in`, and `testMultipleCopies.cc.in`.

Definition at line 454 of file GenEvent.h.

9.13.2 Constructor & Destructor Documentation

9.13.2.1 HepMC::GenEvent::particle_const_iterator::particle_const_iterator (const std::map< int, HepMC::GenParticle * >::const_iterator & i) [inline]

iterate over particles

Definition at line 459 of file GenEvent.h.

9.13.2.2 HepMC::GenEvent::particle_const_iterator::particle_const_iterator () [inline]

Definition at line 462 of file GenEvent.h.

9.13.2.3 HepMC::GenEvent::particle_const_iterator::particle_const_iterator (const particle_const_iterator & i) [inline]

copy constructor

Definition at line 464 of file GenEvent.h.

9.13.2.4 virtual HepMC::GenEvent::particle_const_iterator::~~particle_const_iterator () [inline, virtual]

Definition at line 466 of file GenEvent.h.

9.13.3 Member Function Documentation

9.13.3.1 GenParticle* HepMC::GenEvent::particle_const_iterator::operator * (void) const [inline]

return a pointer to **GenParticle** (p. 111)

Definition at line 472 of file GenEvent.h.

References `m_map_iterator`.

9.13.3.2 bool HepMC::GenEvent::particle_const_iterator::operator!= (const particle_const_iterator & a) const [inline]

inequality

Definition at line 484 of file GenEvent.h.

References `m_map_iterator`.

9.13.3.3 particle_const_iterator HepMC::GenEvent::particle_const_iterator::operator++ (int) [inline]

Post-fix increment.

Definition at line 478 of file GenEvent.h.

9.13.3.4 `particle_const_iterator& HepMC::GenEvent::particle_const_iterator::operator++ (void)`
`[inline]`

Pre-fix increment.

Definition at line 475 of file GenEvent.h.

References `m_map_iterator`.

9.13.3.5 `particle_const_iterator& HepMC::GenEvent::particle_const_iterator::operator= (const particle_const_iterator & i)` `[inline]`

make a copy

Definition at line 468 of file GenEvent.h.

References `m_map_iterator`.

9.13.3.6 `bool HepMC::GenEvent::particle_const_iterator::operator== (const particle_const_iterator & a) const` `[inline]`

equality

Definition at line 481 of file GenEvent.h.

References `m_map_iterator`.

9.13.4 Member Data Documentation

9.13.4.1 `std::map<int,HepMC::GenParticle*>::const_iterator HepMC::GenEvent::particle_const_iterator::m_map_iterator` `[protected]`

const iterator to the **GenParticle** (p. 111) map

Definition at line 488 of file GenEvent.h.

Referenced by `operator*()`, `operator!=()`, `operator++()`, `operator=()`, and `operator==()`.

The documentation for this class was generated from the following file:

- **GenEvent.h**

9.14 HepMC::GenEvent::particle_iterator Class Reference

non-const particle iterator

```
#include <GenEvent.h>
```

Public Member Functions

- **particle_iterator (const std::map< int, HepMC::GenParticle * >::iterator &i)**
iterate over particles
- **particle_iterator ()**
- **particle_iterator (const particle_iterator &i)**
copy constructor
- **virtual ~particle_iterator ()**
- **particle_iterator & operator= (const particle_iterator &i)**
make a copy
- **operator particle_const_iterator () const**
const particle iterator
- **GenParticle * operator * (void) const**
return pointer to GenParticle (p. 111)
- **particle_iterator & operator++ (void)**
Pre-fix increment.
- **particle_iterator operator++ (int)**
Post-fix increment.
- **bool operator== (const particle_iterator &a) const**
equality
- **bool operator!= (const particle_iterator &a) const**
inequality

Protected Attributes

- **std::map< int, HepMC::GenParticle * >::iterator m_map_iterator**
iterator for GenParticle (p. 111) map

9.14.1 Detailed Description

non-const particle iterator

HepMC::GenEvent::particle_iterator (p. 99) is used to iterate over all particles in the event.

Examples:

example_UsingIterators.cc, and testHepMCIteration.cc.in.

Definition at line 510 of file GenEvent.h.

9.14.2 Constructor & Destructor Documentation**9.14.2.1 HepMC::GenEvent::particle_iterator::particle_iterator (const std::map< int, HepMC::GenParticle * >::iterator & i) [inline]**

iterate over particles

Definition at line 515 of file GenEvent.h.

9.14.2.2 HepMC::GenEvent::particle_iterator::particle_iterator () [inline]

Definition at line 517 of file GenEvent.h.

9.14.2.3 HepMC::GenEvent::particle_iterator::particle_iterator (const particle_iterator & i) [inline]

copy constructor

Definition at line 519 of file GenEvent.h.

9.14.2.4 virtual HepMC::GenEvent::particle_iterator::~~particle_iterator () [inline, virtual]

Definition at line 520 of file GenEvent.h.

9.14.3 Member Function Documentation**9.14.3.1 GenParticle* HepMC::GenEvent::particle_iterator::operator * (void) const [inline]**

return pointer to **GenParticle** (p. 111)

Definition at line 530 of file GenEvent.h.

References m_map_iterator.

9.14.3.2 HepMC::GenEvent::particle_iterator::operator particle_const_iterator () const [inline]

const particle iterator

Definition at line 527 of file GenEvent.h.

References m_map_iterator, and HepMC::GenEvent::particle_const_iterator.

9.14.3.3 `bool HepMC::GenEvent::particle_iterator::operator!=(const particle_iterator & a) const` `[inline]`

inequality

Definition at line 542 of file GenEvent.h.

References `m_map_iterator`.

9.14.3.4 `particle_iterator HepMC::GenEvent::particle_iterator::operator++(int)` `[inline]`

Post-fix increment.

Definition at line 536 of file GenEvent.h.

9.14.3.5 `particle_iterator& HepMC::GenEvent::particle_iterator::operator++(void)` `[inline]`

Pre-fix increment.

Definition at line 533 of file GenEvent.h.

References `m_map_iterator`.

9.14.3.6 `particle_iterator& HepMC::GenEvent::particle_iterator::operator=(const particle_iterator & i)` `[inline]`

make a copy

Definition at line 522 of file GenEvent.h.

References `m_map_iterator`.

9.14.3.7 `bool HepMC::GenEvent::particle_iterator::operator==(const particle_iterator & a) const` `[inline]`

equality

Definition at line 539 of file GenEvent.h.

References `m_map_iterator`.

9.14.4 Member Data Documentation

9.14.4.1 `std::map<int,HepMC::GenParticle*>::iterator HepMC::GenEvent::particle_iterator::m_map_iterator` `[protected]`

iterator for **GenParticle** (p. 111) map

Definition at line 546 of file GenEvent.h.

Referenced by `operator*()`, `operator particle_const_iterator()`, `operator!=()`, `operator++()`, `operator=()`, and `operator==(())`.

The documentation for this class was generated from the following file:

- **GenEvent.h**

9.15 HepMC::GenEvent::vertex_const_iterator Class Reference

const vertex iterator

```
#include <GenEvent.h>
```

Public Member Functions

- **vertex_const_iterator** (const std::map< int, HepMC::GenVertex *, std::greater< int > >::const_iterator &i)
constructor requiring vertex information
- **vertex_const_iterator** ()
- **vertex_const_iterator** (const vertex_const_iterator &i)
copy constructor
- **virtual ~vertex_const_iterator** ()
- **vertex_const_iterator & operator=** (const vertex_const_iterator &i)
make a copy
- **GenVertex * operator *** (void) const
return a pointer to a GenVertex (p. 126)
- **vertex_const_iterator & operator++** (void)
Pre-fix increment.
- **vertex_const_iterator operator++** (int)
Post-fix increment.
- **bool operator==** (const vertex_const_iterator &a) const
equality
- **bool operator!=** (const vertex_const_iterator &a) const
inequality

Protected Attributes

- std::map< int, HepMC::GenVertex *, std::greater< int > >::const_iterator m_map_iterator
const iterator to a vertex map

9.15.1 Detailed Description

const vertex iterator

HepMC::GenEvent::vertex_const_iterator (p. 102) is used to iterate over all vertices in the event.

Definition at line 324 of file GenEvent.h.

9.15.2 Constructor & Destructor Documentation

9.15.2.1 HepMC::GenEvent::vertex_const_iterator::vertex_const_iterator (const std::map< int, HepMC::GenVertex *, std::greater< int > >::const_iterator & i) [inline]

constructor requiring vertex information

Definition at line 329 of file GenEvent.h.

9.15.2.2 HepMC::GenEvent::vertex_const_iterator::vertex_const_iterator () [inline]

Definition at line 333 of file GenEvent.h.

9.15.2.3 HepMC::GenEvent::vertex_const_iterator::vertex_const_iterator (const vertex_const_iterator & i) [inline]

copy constructor

Definition at line 335 of file GenEvent.h.

9.15.2.4 virtual HepMC::GenEvent::vertex_const_iterator::~~vertex_const_iterator () [inline, virtual]

Definition at line 337 of file GenEvent.h.

9.15.3 Member Function Documentation

9.15.3.1 GenVertex* HepMC::GenEvent::vertex_const_iterator::operator * (void) const [inline]

return a pointer to a **GenVertex** (p. 126)

Definition at line 342 of file GenEvent.h.

References m_map_iterator.

9.15.3.2 bool HepMC::GenEvent::vertex_const_iterator::operator!= (const vertex_const_iterator & a) const [inline]

inequality

Definition at line 353 of file GenEvent.h.

References m_map_iterator.

9.15.3.3 vertex_const_iterator HepMC::GenEvent::vertex_const_iterator::operator++ (int) [inline]

Post-fix increment.

Definition at line 347 of file GenEvent.h.

9.15.3.4 `vertex_const_iterator& HepMC::GenEvent::vertex_const_iterator::operator++ (void)` [inline]

Pre-fix increment.

Definition at line 344 of file GenEvent.h.

References `m_map_iterator`.

9.15.3.5 `vertex_const_iterator& HepMC::GenEvent::vertex_const_iterator::operator= (const vertex_const_iterator & i)` [inline]

make a copy

Definition at line 339 of file GenEvent.h.

References `m_map_iterator`.

9.15.3.6 `bool HepMC::GenEvent::vertex_const_iterator::operator== (const vertex_const_iterator & a) const` [inline]

equality

Definition at line 350 of file GenEvent.h.

References `m_map_iterator`.

9.15.4 Member Data Documentation

9.15.4.1 `std::map<int,HepMC::GenVertex*,std::greater<int> >::const_iterator HepMC::GenEvent::vertex_const_iterator::m_map_iterator` [protected]

const iterator to a vertex map

Definition at line 358 of file GenEvent.h.

Referenced by `operator*()`, `operator!=()`, `operator++()`, `operator=()`, and `operator==()`.

The documentation for this class was generated from the following file:

- **GenEvent.h**

9.16 HepMC::GenEvent::vertex_iterator Class Reference

non-const vertex iterator

```
#include <GenEvent.h>
```

Public Member Functions

- **vertex_iterator (const std::map< int, HepMC::GenVertex *, std::greater< int > >::iterator &i)**

constructor requiring vertex information

- **vertex_iterator ()**
- **vertex_iterator (const vertex_iterator &i)**

copy constructor

- **virtual ~vertex_iterator ()**
- **vertex_iterator & operator= (const vertex_iterator &i)**

make a copy

- **operator vertex_const_iterator () const**

const vertex iterator

- **GenVertex * operator * (void) const**

return a pointer to a GenVertex (p. 126)

- **vertex_iterator & operator++ (void)**

Pre-fix increment.

- **vertex_iterator operator++ (int)**

Post-fix increment.

- **bool operator== (const vertex_iterator &a) const**

equality

- **bool operator!= (const vertex_iterator &a) const**

inequality

Protected Attributes

- **std::map< int, HepMC::GenVertex *, std::greater< int > >::iterator m_map_iterator**

iterator to the vertex map

9.16.1 Detailed Description

non-const vertex iterator

HepMC::GenEvent::vertex_iterator (p. 105) is used to iterate over all vertices in the event.

Examples:

example_UsingIterators.cc, and testHepMCIteration.cc.in.

Definition at line 381 of file GenEvent.h.

9.16.2 Constructor & Destructor Documentation

9.16.2.1 HepMC::GenEvent::vertex_iterator::vertex_iterator (const std::map< int, HepMC::GenVertex *, std::greater< int > >::iterator & i) [inline]

constructor requiring vertex information

Definition at line 386 of file GenEvent.h.

9.16.2.2 HepMC::GenEvent::vertex_iterator::vertex_iterator () [inline]

Definition at line 390 of file GenEvent.h.

9.16.2.3 HepMC::GenEvent::vertex_iterator::vertex_iterator (const vertex_iterator & i) [inline]

copy constructor

Definition at line 392 of file GenEvent.h.

9.16.2.4 virtual HepMC::GenEvent::vertex_iterator::~~vertex_iterator () [inline, virtual]

Definition at line 393 of file GenEvent.h.

9.16.3 Member Function Documentation

9.16.3.1 GenVertex* HepMC::GenEvent::vertex_iterator::operator * (void) const [inline]

return a pointer to a **GenVertex** (p. 126)

Definition at line 403 of file GenEvent.h.

References m_map_iterator.

9.16.3.2 HepMC::GenEvent::vertex_iterator::operator vertex_const_iterator () const [inline]

const vertex iterator

Definition at line 400 of file GenEvent.h.

References `m_map_iterator`, and `HepMC::GenEvent::vertex_const_iterator`.

9.16.3.3 `bool HepMC::GenEvent::vertex_iterator::operator!=(const vertex_iterator & a) const`
[inline]

inequality

Definition at line 415 of file GenEvent.h.

References `m_map_iterator`.

9.16.3.4 `vertex_iterator HepMC::GenEvent::vertex_iterator::operator++(int)` [inline]

Post-fix increment.

Definition at line 409 of file GenEvent.h.

9.16.3.5 `vertex_iterator& HepMC::GenEvent::vertex_iterator::operator++(void)` [inline]

Pre-fix increment.

Definition at line 406 of file GenEvent.h.

References `m_map_iterator`.

9.16.3.6 `vertex_iterator& HepMC::GenEvent::vertex_iterator::operator=(const vertex_iterator & i)` [inline]

make a copy

Definition at line 395 of file GenEvent.h.

References `m_map_iterator`.

9.16.3.7 `bool HepMC::GenEvent::vertex_iterator::operator==(const vertex_iterator & a) const`
[inline]

equality

Definition at line 412 of file GenEvent.h.

References `m_map_iterator`.

9.16.4 Member Data Documentation

9.16.4.1 `std::map<int,HepMC::GenVertex*,std::greater<int>>::iterator`
`HepMC::GenEvent::vertex_iterator::m_map_iterator` [protected]

iterator to the vertex map

Definition at line 420 of file GenEvent.h.

Referenced by `operator*()`, `operator vertex_const_iterator()`, `operator!=()`, `operator++()`, `operator=()`, and `operator==()`.

The documentation for this class was generated from the following file:

- **GenEvent.h**

9.17 HepMC::GenEventParticleRange Class Reference

GenEventParticleRange (p. 109) acts like a collection of particles.

```
#include <GenRanges.h>
```

Public Member Functions

- **GenEventParticleRange (GenEvent &e)**
the constructor requires a GenEvent (p. 73)
- **GenEvent::particle_iterator begin ()**
- **GenEvent::particle_iterator end ()**

9.17.1 Detailed Description

GenEventParticleRange (p. 109) acts like a collection of particles.

HepMC::GenEventParticleRange (p. 109) is used to mimic a collection of particles for ease of use - especially with utilities such as the Boost foreach funtion

Examples:

```
testHepMCIteration.cc.in.
```

Definition at line 83 of file GenRanges.h.

9.17.2 Constructor & Destructor Documentation

9.17.2.1 HepMC::GenEventParticleRange::GenEventParticleRange (GenEvent & e) [inline]

the constructor requires a **GenEvent** (p. 73)

Definition at line 88 of file GenRanges.h.

9.17.3 Member Function Documentation

9.17.3.1 GenEvent::particle_iterator HepMC::GenEventParticleRange::begin () [inline]

Definition at line 90 of file GenRanges.h.

References HepMC::GenEvent::particles_begin().

9.17.3.2 GenEvent::particle_iterator HepMC::GenEventParticleRange::end () [inline]

Definition at line 91 of file GenRanges.h.

References HepMC::GenEvent::particles_end().

The documentation for this class was generated from the following file:

- **GenRanges.h**

9.18 HepMC::GenEventVertexRange Class Reference

GenEventVertexRange (p. 110) acts like a collection of vertices.

```
#include <GenRanges.h>
```

Public Member Functions

- **GenEventVertexRange (GenEvent &e)**
the constructor requires a GenEvent (p. 73)
- **GenEvent::vertex_iterator begin ()**
- **GenEvent::vertex_iterator end ()**

9.18.1 Detailed Description

GenEventVertexRange (p. 110) acts like a collection of vertices.

HepMC::GenEventVertexRange (p. 110) is used to mimic a collection of vertices for ease of use - especially with utilities such as the Boost foreach funtion

Examples:

```
testHepMCIteration.cc.in.
```

Definition at line 26 of file GenRanges.h.

9.18.2 Constructor & Destructor Documentation

9.18.2.1 HepMC::GenEventVertexRange::GenEventVertexRange (GenEvent & e) [inline]

the constructor requires a **GenEvent** (p. 73)

Definition at line 31 of file GenRanges.h.

9.18.3 Member Function Documentation

9.18.3.1 GenEvent::vertex_iterator HepMC::GenEventVertexRange::begin () [inline]

Definition at line 33 of file GenRanges.h.

References HepMC::GenEvent::vertices_begin().

9.18.3.2 GenEvent::vertex_iterator HepMC::GenEventVertexRange::end () [inline]

Definition at line 34 of file GenRanges.h.

References HepMC::GenEvent::vertices_end().

The documentation for this class was generated from the following file:

- **GenRanges.h**

9.19 HepMC::GenParticle Class Reference

The **GenParticle** (p. 111) class contains information about generated particles.

```
#include <GenParticle.h>
```

Public Member Functions

- **GenParticle (void)**
default constructor
- **GenParticle (const FourVector &momentum, int pdg_id, int status=0, const Flow &its-flow=Flow(), const Polarization &polar=Polarization(0, 0))**
constructor requires momentum and particle ID
- **GenParticle (const GenParticle &inparticle)**
shallow copy.
- **virtual ~GenParticle ()**
- **void swap (GenParticle &other)**
swap
- **GenParticle & operator= (const GenParticle &inparticle)**
- **bool operator== (const GenParticle &) const**
check for equality
- **bool operator!= (const GenParticle &) const**
check for inequality
- **void print (std::ostream &ostr=std::cout) const**
dump this particle's full info to ostr
- **operator HepMC::FourVector () const**
conversion operator
- **const FourVector & momentum () const**
standard 4 momentum
- **int pdg_id () const**
particle ID
- **int status () const**
HEPEVT decay status.
- **const Flow & flow () const**
particle flow
- **int flow (int code_index) const**
particle flow index

- **const Polarization & polarization () const**
polarization information
- **GenVertex * production_vertex () const**
pointer to the production vertex
- **GenVertex * end_vertex () const**
pointer to the decay vertex
- **GenEvent * parent_event () const**
pointer to the event that owns this particle
- **double generated_mass () const**
mass as generated
- **double generatedMass () const**
generatedMass() (p. 116) is included for backwards compatibility with CLHEP (p. 21) HepMC (p. 23)
- **int barcode () const**
particle barcode
- **bool is_undecayed () const**
Convenience method. Returns true if status==1.
- **bool has_decayed () const**
Convenience method. Returns true if status==2.
- **bool is_beam () const**
- **GenParticleProductionRange particles_in (IteratorRange range=relatives)**
incoming particle range
- **ConstGenParticleProductionRange particles_in (IteratorRange range=relatives) const**
incoming particle range
- **GenParticleEndRange particles_out (IteratorRange range=relatives)**
outgoing particle range
- **ConstGenParticleEndRange particles_out (IteratorRange range=relatives) const**
outgoing particle range
- **bool suggest_barcode (int the_bar_code)**
In general there is no reason to "suggest_barcode".
- **void set_momentum (const FourVector &vec4)**
set standard 4 momentum
- **void set_pdg_id (int id)**
set particle ID
- **void set_status (int status=0)**

set decay status

- **void set_flow (const Flow &f)**

set particle flow

- **void set_flow (int code_index, int code=0)**
- **void set_polarization (const Polarization &pol=Polarization(0, 0))**

set polarization

- **void set_generated_mass (const double &m)**

define the actual generated mass

- **void setGeneratedMass (const double &m)**

setGeneratedMass() (p. 120) is included for backwards compatibility with CLHEP (p. 21) HepMC (p. 23)

Protected Member Functions

- **void set_production_vertex_ (GenVertex *productionvertex=0)**

set production vertex - for internal use only

- **void set_end_vertex_ (GenVertex *decayvertex=0)**

set decay vertex - for internal use only

- **void set_barcode_ (int the_bar_code)**

for use by GenEvent (p. 73) only

- **void convert_momentum (const double &)**

Friends

- class GenVertex
- class GenEvent
- **std::ostream & operator<< (std::ostream &, const GenParticle &)**

print particle

9.19.1 Detailed Description

The **GenParticle** (p. 111) class contains information about generated particles.

HepMC::GenParticle (p. 111) contains momentum, generated mass, particle ID, decay status, flow, polarization, pointers to production and decay vertices and a unique barcode identifier.

Examples:

example_BuildEventFromScratch.cc, example_UsingIterators.cc, testFlow.cc, testHepMCIteration.cc.in, testMass.cc.in, and testPrintBug.cc.

Definition at line 60 of file GenParticle.h.

9.19.2 Constructor & Destructor Documentation

9.19.2.1 HepMC::GenParticle::GenParticle (void)

default constructor

Definition at line 14 of file GenParticle.cc.

9.19.2.2 HepMC::GenParticle::GenParticle (const FourVector & *momentum*, int *pdg_id*, int *status* = 0, const Flow & *itsflow* = Flow(), const Polarization & *polar* = Polarization(0, 0))

constructor requires momentum and particle ID

Definition at line 23 of file GenParticle.cc.

References set_flow().

9.19.2.3 HepMC::GenParticle::GenParticle (const GenParticle & *inparticle*)

shallow copy.

Shallow copy: does not copy the vertex pointers (note - impossible to copy vertex pointers which having the vertex and particles in/out point-back to one another – unless you copy the entire tree – which we don't want to do)

Definition at line 37 of file GenParticle.cc.

References barcode(), set_end_vertex_(), set_production_vertex_(), and suggest_barcode().

9.19.2.4 HepMC::GenParticle::~~GenParticle () [virtual]

Definition at line 58 of file GenParticle.cc.

References parent_event(), and HepMC::GenEvent::remove_barcode().

9.19.3 Member Function Documentation

9.19.3.1 int HepMC::GenParticle::barcode () const [inline]

particle barcode

The barcode is the particle's reference number, every vertex in the event has a unique barcode. Particle barcodes are positive numbers, vertex barcodes are negative numbers.

Please note that the barcodes are intended for internal use within **HepMC** (p. 23) as a unique identifier for the particles and vertices. Using the barcode to encode extra information is an abuse of the barcode data member and causes confusion among users.

Examples:

testFlow.cc.

Definition at line 252 of file GenParticle.h.

Referenced by GenParticle(), main(), HepMC::operator<<(), print(), set_end_vertex_(), and set_production_vertex_().

9.19.3.2 void HepMC::GenParticle::convert_momentum (const double &) [protected]

scale the momentum vector and generated mass this method is only for use by **GenEvent** (p. 73)

Definition at line 246 of file GenParticle.cc.

References HepMC::FourVector::e(), HepMC::FourVector::px(), HepMC::FourVector::py(), and HepMC::FourVector::pz().

9.19.3.3 GenVertex * HepMC::GenParticle::end_vertex () const [inline]

pointer to the decay vertex

Definition at line 221 of file GenParticle.h.

Referenced by HepMC::GenVertex::add_particle_in(), HepMC::ConstGenParticleEndRange::begin(), HepMC::GenParticleEndRange::begin(), HepMC::Flow::connected_partners(), HepMC::Flow::dangling_connected_partners(), HepMC::ConstGenParticleEndRange::end(), HepMC::GenParticleEndRange::end(), HepMC::operator<<(), parent_event(), print(), and HepMC::GenVertex::remove_particle().

9.19.3.4 int HepMC::GenParticle::flow (int code_index) const [inline]

particle flow index

Definition at line 225 of file GenParticle.h.

References HepMC::Flow::icode().

9.19.3.5 const Flow & HepMC::GenParticle::flow () const [inline]

particle flow

Examples:

testFlow.cc.

Definition at line 223 of file GenParticle.h.

Referenced by main().

9.19.3.6 double HepMC::GenParticle::generated_mass () const

mass as generated

Because of precision issues, the generated mass is not always the same as the mass calculated from the momentum 4 vector. If the generated mass has been set, then **generated_mass()** (p. 115) returns that value. If the generated mass has not been set, then **generated_mass()** (p. 115) returns the mass calculated from the momentum 4 vector.

Definition at line 236 of file GenParticle.cc.

Referenced by generatedMass(), and operator==(.).

9.19.3.7 double HepMC::GenParticle::generatedMass () const [inline]

generatedMass() (p. 116) is included for backwards compatibility with **CLHEP** (p. 21) **HepMC** (p. 23)

Definition at line 121 of file GenParticle.h.

References generated_mass().

9.19.3.8 bool HepMC::GenParticle::has_decayed () const [inline]

Convenience method. Returns true if status==2.

Definition at line 259 of file GenParticle.h.

9.19.3.9 bool HepMC::GenParticle::is_beam () const [inline]

Convenience method. Returns true if status==4 Note that using status 4 for beam particles is a new convention which may not have been implemented by the code originating this **GenEvent** (p. 73).

Definition at line 262 of file GenParticle.h.

9.19.3.10 bool HepMC::GenParticle::is_undecayed () const [inline]

Convenience method. Returns true if status==1.

Definition at line 256 of file GenParticle.h.

9.19.3.11 const FourVector & HepMC::GenParticle::momentum () const [inline]

standard 4 momentum

Definition at line 211 of file GenParticle.h.

Referenced by HepMC::operator<<(), operator==(), and print().

9.19.3.12 HepMC::GenParticle::operator HepMC::FourVector () const [inline]

conversion operator

Definition at line 208 of file GenParticle.h.

9.19.3.13 bool HepMC::GenParticle::operator!= (const GenParticle &) const

check for inequality

Definition at line 102 of file GenParticle.cc.

9.19.3.14 GenParticle & HepMC::GenParticle::operator= (const GenParticle & *inparticle*)

shallow.

Shallow: does not copy the vertex pointers (note - impossible to copy vertex pointers which having the vertex and particles in/out point-back to one another – unless you copy the entire tree – which we don't want to do)

Definition at line 77 of file GenParticle.cc.

References swap().

9.19.3.15 bool HepMC::GenParticle::operator==(const GenParticle &) const

check for equality

consistent with the definition of the copy constructor as a shallow constructor,.. this operator does not test the vertex pointers. Does not compare barcodes.

Definition at line 89 of file GenParticle.cc.

References generated_mass(), m_flow, momentum(), pdg_id(), polarization(), and status().

9.19.3.16 GenEvent * HepMC::GenParticle::parent_event () const

pointer to the event that owns this particle

Definition at line 123 of file GenParticle.cc.

References end_vertex(), HepMC::GenVertex::parent_event(), and production_vertex().

Referenced by set_end_vertex_(), set_production_vertex_(), suggest_barcode(), and ~GenParticle().

9.19.3.17 ConstGenParticleProductionRange HepMC::GenParticle::particles_in (IteratorRange *range* = relatives) const

incoming particle range

Definition at line 67 of file GenRanges.cc.

9.19.3.18 GenParticleProductionRange HepMC::GenParticle::particles_in (IteratorRange *range* = relatives)

incoming particle range

Definition at line 61 of file GenRanges.cc.

9.19.3.19 ConstGenParticleEndRange HepMC::GenParticle::particles_out (IteratorRange *range* = relatives) const

outgoing particle range

Definition at line 79 of file GenRanges.cc.

9.19.3.20 GenParticleEndRange HepMC::GenParticle::particles_out (IteratorRange *range* = relatives)

outgoing particle range

Definition at line 73 of file GenRanges.cc.

9.19.3.21 int HepMC::GenParticle::pdg_id () const [inline]

particle ID

Definition at line 214 of file GenParticle.h.

Referenced by PrintChildren::operator>(), HepMC::operator<<(), operator==(), and print().

9.19.3.22 const Polarization & HepMC::GenParticle::polarization () const [inline]

polarization information

Definition at line 228 of file GenParticle.h.

Referenced by operator==(), and print().

9.19.3.23 void HepMC::GenParticle::print (std::ostream & ostr = std::cout) const

dump this particle's full info to ostr

Dump this particle's full info to ostr, where by default particle.print(); will dump to cout.

Definition at line 106 of file GenParticle.cc.

References HepMC::GenVertex::barcode(), barcode(), HepMC::FourVector::e(), end_vertex(), momentum(), pdg_id(), polarization(), production_vertex(), HepMC::FourVector::px(), HepMC::FourVector::py(), HepMC::FourVector::pz(), and status().

9.19.3.24 GenVertex * HepMC::GenParticle::production_vertex () const [inline]

pointer to the production vertex

Definition at line 218 of file GenParticle.h.

Referenced by HepMC::GenVertex::add_particle_out(), HepMC::ConstGenParticleProductionRange::begin(), HepMC::GenParticleProductionRange::begin(), HepMC::Flow::connected_partners(), HepMC::Flow::dangling_connected_partners(), HepMC::ConstGenParticleProductionRange::end(), HepMC::GenParticleProductionRange::end(), parent_event(), print(), and HepMC::GenVertex::remove_particle().

9.19.3.25 void HepMC::GenParticle::set_barcode_ (int the_bar_code) [inline, protected]

for use by **GenEvent** (p. 73) only

Definition at line 254 of file GenParticle.h.

Referenced by suggest_barcode().

9.19.3.26 void HepMC::GenParticle::set_end_vertex_ (GenVertex * decayvertex = 0) [protected]

set decay vertex - for internal use only

Definition at line 142 of file GenParticle.cc.

References barcode(), parent_event(), and HepMC::GenEvent::remove_barcode().

Referenced by HepMC::GenVertex::add_particle_in(), GenParticle(), and HepMC::GenVertex::remove_particle().

9.19.3.27 void HepMC::GenParticle::set_flow (int *code_index*, int *code* = 0) [inline]

set particle flow index

Definition at line 240 of file GenParticle.h.

References HepMC::Flow::set_icode(), and HepMC::Flow::set_unique_icode().

9.19.3.28 void HepMC::GenParticle::set_flow (const Flow &f) [inline]

set particle flow

Examples:

testFlow.cc.

Definition at line 238 of file GenParticle.h.

Referenced by GenParticle(), and main().

9.19.3.29 void HepMC::GenParticle::set_generated_mass (const double &m)

define the actual generated mass

If you do not call **set_generated_mass()** (p. 119), then **generated_mass()** (p. 115) will simply return the mass calculated from **momentum()** (p. 116)

Definition at line 240 of file GenParticle.cc.

Referenced by setGeneratedMass().

9.19.3.30 void HepMC::GenParticle::set_momentum (const FourVector &vec4) [inline]

set standard 4 momentum

Definition at line 231 of file GenParticle.h.

9.19.3.31 void HepMC::GenParticle::set_pdg_id (int *id*) [inline]

set particle ID

Definition at line 234 of file GenParticle.h.

9.19.3.32 void HepMC::GenParticle::set_polarization (const Polarization &pol = Polarization(0, 0)) [inline]

set polarization

Definition at line 249 of file GenParticle.h.

Referenced by main().

9.19.3.33 `void HepMC::GenParticle::set_production_vertex_ (GenVertex * productionvertex = 0)`
[protected]

set production vertex - for internal use only

Definition at line 129 of file GenParticle.cc.

References barcode(), parent_event(), and HepMC::GenEvent::remove_barcode().

Referenced by HepMC::GenVertex::add_particle_out(), GenParticle(), and HepMC::GenVertex::remove_particle().

9.19.3.34 `void HepMC::GenParticle::set_status (int status = 0)` [inline]

set decay status

Definition at line 236 of file GenParticle.h.

9.19.3.35 `void HepMC::GenParticle::setGeneratedMass (const double & m)` [inline]

`setGeneratedMass()` (p. 120) is included for backwards compatibility with CLHEP (p. 21) HepMC (p. 23)

Definition at line 173 of file GenParticle.h.

References set_generated_mass().

9.19.3.36 `int HepMC::GenParticle::status () const` [inline]

HEPEVT decay status.

Definition at line 216 of file GenParticle.h.

Referenced by PrintChildren::operator>(), HepMC::operator<<(), operator==(), and print().

9.19.3.37 `bool HepMC::GenParticle::suggest_barcode (int the_bar_code)`

In general there is no reason to "suggest_barcode".

allows a barcode to be suggested for this particle. In general it is better to let the event pick the barcode for you, which is automatic. Returns TRUE if the suggested barcode has been accepted (i.e. the suggested barcode has not already been used in the event, and so it was used). Returns FALSE if the suggested barcode was rejected, or if the particle is not yet part of an event, such that it is not yet possible to know if the suggested barcode will be accepted).

Definition at line 153 of file GenParticle.cc.

References parent_event(), HepMC::GenEvent::set_barcode(), and set_barcode_().

Referenced by GenParticle().

9.19.3.38 `void HepMC::GenParticle::swap (GenParticle & other)`

swap

Definition at line 63 of file GenParticle.cc.

References `m_barcode`, `m_end_vertex`, `m_flow`, `m_generated_mass`, `m_momentum`, `m_pdg_id`, `m_polarization`, `m_production_vertex`, `m_status`, `HepMC::Polarization::swap()`, `HepMC::Flow::swap()`, and `HepMC::FourVector::swap()`.

Referenced by `operator=()`.

9.19.4 Friends And Related Function Documentation

9.19.4.1 friend class GenEvent [friend]

Definition at line 63 of file `GenParticle.h`.

9.19.4.2 friend class GenVertex [friend]

Definition at line 62 of file `GenParticle.h`.

9.19.4.3 std::ostream& operator<< (std::ostream & ostr, const GenParticle & part) [friend]

print particle

Definition at line 189 of file `GenParticle.cc`.

The documentation for this class was generated from the following files:

- `GenParticle.h`
- `GenParticle.cc`
- `GenRanges.cc`

9.20 HepMC::GenParticleEndRange Class Reference

GenParticleEndRange (p. 122) acts like a collection of particles.

```
#include <GenRanges.h>
```

Public Member Functions

- **GenParticleEndRange (GenParticle const &p, IteratorRange range=relatives)**
the constructor requires a GenParticle (p. 111)
- **GenVertex::particle_iterator begin ()**
begin iterator throws an error if the particle end_vertex is undefined
- **GenVertex::particle_iterator end ()**
end iterator throws an error if the particle end_vertex is undefined

9.20.1 Detailed Description

GenParticleEndRange (p. 122) acts like a collection of particles.

HepMC::GenParticleEndRange (p. 122) is used to mimic a collection of particles associated with the particle's end vertex for ease of use Utilities such as the Boost foreach funtion will want to use this class.

Definition at line 224 of file GenRanges.h.

9.20.2 Constructor & Destructor Documentation

9.20.2.1 HepMC::GenParticleEndRange::GenParticleEndRange (GenParticle const &p, IteratorRange range = relatives) [inline]

the constructor requires a **GenParticle** (p. 111)

Definition at line 229 of file GenRanges.h.

9.20.3 Member Function Documentation

9.20.3.1 GenVertex::particle_iterator HepMC::GenParticleEndRange::begin () [inline]

begin iterator throws an error if the particle end_vertex is undefined

Definition at line 300 of file GenRanges.h.

References HepMC::GenParticle::end_vertex(), and HepMC::GenVertex::particles_begin().

9.20.3.2 GenVertex::particle_iterator HepMC::GenParticleEndRange::end () [inline]

end iterator throws an error if the particle end_vertex is undefined

Definition at line 306 of file GenRanges.h.

References HepMC::GenParticle::end_vertex(), and HepMC::GenVertex::particles_end().

The documentation for this class was generated from the following file:

- **GenRanges.h**

9.21 HepMC::GenParticleProductionRange Class Reference

GenParticleProductionRange (p. 124) acts like a collection of particles.

```
#include <GenRanges.h>
```

Public Member Functions

- **GenParticleProductionRange** (**GenParticle** const &p, **IteratorRange** range=relatives)
the constructor requires a GenParticle (p. 111)
- **GenVertex::particle_iterator** begin ()
begin iterator throws an error if the particle production_vertex is undefined
- **GenVertex::particle_iterator** end ()
end iterator throws an error if the particle production_vertex is undefined

9.21.1 Detailed Description

GenParticleProductionRange (p. 124) acts like a collection of particles.

HepMC::GenParticleProductionRange (p. 124) is used to mimic a collection of particles associated with the particle's production vertex for ease of use Utilities such as the Boost foreach funtion will want to use this class.

Definition at line 170 of file GenRanges.h.

9.21.2 Constructor & Destructor Documentation

9.21.2.1 HepMC::GenParticleProductionRange::GenParticleProductionRange (**GenParticle** const &p, **IteratorRange** range = relatives) [inline]

the constructor requires a **GenParticle** (p. 111)

Definition at line 175 of file GenRanges.h.

9.21.3 Member Function Documentation

9.21.3.1 GenVertex::particle_iterator HepMC::GenParticleProductionRange::begin () [inline]

begin iterator throws an error if the particle production_vertex is undefined

Definition at line 271 of file GenRanges.h.

References HepMC::GenVertex::particles_begin(), and HepMC::GenParticle::production_vertex().

9.21.3.2 GenVertex::particle_iterator HepMC::GenParticleProductionRange::end () [inline]

end iterator throws an error if the particle production_vertex is undefined

Definition at line 278 of file GenRanges.h.

References HepMC::GenVertex::particles_end(), and HepMC::GenParticle::production_vertex().

The documentation for this class was generated from the following file:

- **GenRanges.h**

9.22 HepMC::GenVertex Class Reference

GenVertex (p. 126) contains information about decay vertices.

```
#include <GenVertex.h>
```

Public Types

- `typedef std::vector< HepMC::GenParticle * >::const_iterator particles_in_const_iterator`
const iterator for incoming particles
- `typedef std::vector< HepMC::GenParticle * >::const_iterator particles_out_const_iterator`
const iterator for outgoing particles

Public Member Functions

- `GenVertex (const FourVector &position=FourVector(0, 0, 0, 0), int id=0, const Weight-Container &weights=std::vector< double >())`
default constructor
- `GenVertex (const GenVertex &invertex)`
shallow copy
- `virtual ~GenVertex ()`
- `void swap (GenVertex &other)`
swap
- `GenVertex & operator= (const GenVertex &invertex)`
shallow
- `bool operator== (const GenVertex &a) const`
equality
- `bool operator!= (const GenVertex &a) const`
inequality
- `void print (std::ostream &ostr=std::cout) const`
print vertex information
- `double check_momentum_conservation () const`
|Sum (mom_in-mom_out)|
- `void add_particle_in (GenParticle *inparticle)`
add incoming particle
- `void add_particle_out (GenParticle *outparticle)`
add outgoing particle
- `GenParticle * remove_particle (GenParticle *particle)`

remove a particle

- **operator HepMC::FourVector () const**
conversion operator
- **operator HepMC::ThreeVector () const**
conversion operator
- **GenEvent * parent_event () const**
pointer to the event that owns this vertex
- **ThreeVector point3d () const**
vertex position
- **const FourVector & position () const**
vertex position and time
- **void set_position (const FourVector &position=FourVector(0, 0, 0, 0))**
set vertex position and time
- **int id () const**
vertex ID
- **void set_id (int id)**
set vertex ID
- **int barcode () const**
unique identifier
- **bool suggest_barcode (int the_bar_code)**
In general there is no reason to "suggest_barcode".
- **WeightContainer & weights ()**
direct access to the weights container is allowed.
- **const WeightContainer & weights () const**
const direct access to the weights container
- **GenVertexParticleRange particles (IteratorRange range=relatives)**
particle range
- **GenParticleProductionRange particles_in (GenParticle &, IteratorRange range=relatives)**
incoming particle range
- **ConstGenParticleProductionRange particles_in (GenParticle const &, IteratorRange range=relatives) const**
incoming particle range
- **GenParticleEndRange particles_out (GenParticle &, IteratorRange range=relatives)**
outgoing particle range

- **ConstGenParticleEndRange particles_out (GenParticle const &, IteratorRange range=relatives) const**
outgoing particle range
- **particles_in_const_iterator particles_in_const_begin () const**
begin iteration of incoming particles
- **particles_in_const_iterator particles_in_const_end () const**
end iteration of incoming particles
- **particles_out_const_iterator particles_out_const_begin () const**
begin iteration of outgoing particles
- **particles_out_const_iterator particles_out_const_end () const**
end iteration of outgoing particles
- **int particles_in_size () const**
number of incoming particles
- **int particles_out_size () const**
number of outgoing particles
- **vertex_iterator vertices_begin (IteratorRange range=relatives)**
begin vertex range
- **vertex_iterator vertices_end (IteratorRange)**
end vertex range
- **particle_iterator particles_begin (IteratorRange range=relatives)**
begin particle range
- **particle_iterator particles_end (IteratorRange)**
end particle range

Protected Member Functions

- **void set_parent_event_ (GenEvent *evt)**
set parent event
- **void set_barcode_ (int the_bar_code)**
set identifier
- **void change_parent_event_ (GenEvent *evt)**
for use with swap
- **int edges_size (IteratorRange range=family) const**
size

- **edge_iterator edges_begin** (IteratorRange range=family) const
begin range
- **edge_iterator edges_end** (IteratorRange) const
end range
- **void delete_adopted_particles** ()
for internal use only
- **void remove_particle_in** (GenParticle *)
for internal use only - remove particle from incoming list
- **void remove_particle_out** (GenParticle *)
for internal use only - remove particle from outgoing list
- **void convert_position** (const double &)

Friends

- class **GenEvent**
- class **edge_iterator**
- class **vertex_iterator**
- class **particle_iterator**
- **std::ostream & operator<<** (std::ostream &, const GenVertex &)
print vertex information

Classes

- class **edge_iterator**
edge iterator
- class **particle_iterator**
particle iterator
- class **vertex_iterator**
vertex iterator

9.22.1 Detailed Description

GenVertex (p. 126) contains information about decay vertices.

HepMC::GenVertex (p. 126) contains the position in space and time of a decay. It also contains lists of incoming and outgoing particles.

Examples:

example_BuildEventFromScratch.cc, **testFlow.cc**, and **testPrintBug.cc**.

Definition at line 52 of file GenVertex.h.

9.22.2 Member Typedef Documentation

9.22.2.1 `typedef std::vector<HepMC::GenParticle*>::const_iterator HepMC::GenVertex::particles_in_const_iterator`

const iterator for incoming particles

Definition at line 152 of file GenVertex.h.

9.22.2.2 `typedef std::vector<HepMC::GenParticle*>::const_iterator HepMC::GenVertex::particles_out_const_iterator`

const iterator for outgoing particles

Definition at line 155 of file GenVertex.h.

9.22.3 Constructor & Destructor Documentation

9.22.3.1 `HepMC::GenVertex::GenVertex (const FourVector & position = FourVector(0, 0, 0, 0), int id = 0, const WeightContainer & weights = std::vector< double >())`

default constructor

Definition at line 14 of file GenVertex.cc.

9.22.3.2 `HepMC::GenVertex::GenVertex (const GenVertex & invertex)`

shallow copy

Shallow copy: does not copy the FULL list of particle pointers. Creates a copy of - invertex

- outgoing particles of invertex, but sets the decay vertex of these particles to NULL
- all incoming particles which do not have a creation vertex. (i.e. it creates copies of all particles which it owns) (note - impossible to copy the FULL list of particle pointers while having the vertex and particles in/out point-back to one another – unless you copy the entire tree – which we don't want to do)

Definition at line 23 of file GenVertex.cc.

References `add_particle_in()`, `add_particle_out()`, `barcode()`, `particles_in_const_begin()`, `particles_in_const_end()`, `particles_out_const_begin()`, `particles_out_const_end()`, and `suggest_barcode()`.

9.22.3.3 `HepMC::GenVertex::~~GenVertex ()` [virtual]

Definition at line 63 of file GenVertex.cc.

References `delete_adopted_particles()`, `parent_event()`, and `HepMC::GenEvent::remove_barcode()`.

9.22.4 Member Function Documentation

9.22.4.1 `void HepMC::GenVertex::add_particle_in (GenParticle * inparticle)`

add incoming particle

Examples:

example_BuildEventFromScratch.cc, testFlow.cc, and testPrintBug.cc.

Definition at line 273 of file GenVertex.cc.

References HepMC::GenParticle::end_vertex(), remove_particle_in(), and HepMC::GenParticle::set_end_vertex().

Referenced by HepMC::IO_HERWIG::build_end_vertex(), HepMC::IO_HEPEVT::build_end_vertex(), HepMC::IO_HERWIG::build_production_vertex(), HepMC::IO_HEPEVT::build_production_vertex(), HepMC::IO_HERWIG::fill_next_event(), GenVertex(), main(), and HepMC::GenEvent::read().

9.22.4.2 void HepMC::GenVertex::add_particle_out (GenParticle * outparticle)

add outgoing particle

Examples:

example_BuildEventFromScratch.cc, testFlow.cc, and testPrintBug.cc.

Definition at line 284 of file GenVertex.cc.

References HepMC::GenParticle::production_vertex(), remove_particle_out(), and HepMC::GenParticle::set_production_vertex().

Referenced by HepMC::IO_HERWIG::build_end_vertex(), HepMC::IO_HEPEVT::build_end_vertex(), HepMC::IO_HERWIG::build_production_vertex(), HepMC::IO_HEPEVT::build_production_vertex(), HepMC::IO_HERWIG::fill_next_event(), HepMC::IO_HEPEVT::fill_next_event(), GenVertex(), and main().

9.22.4.3 int HepMC::GenVertex::barcode () const [inline]

unique identifier

The barcode is the vertex's reference number, every vertex in the event has a unique barcode. Vertex barcodes are negative numbers, particle barcodes are positive numbers.

Please note that the barcodes are intended for internal use within **HepMC** (p. 23) as a unique identifier for the particles and vertices. Using the barcode to encode extra information is an abuse of the barcode data member and causes confusion among users.

Definition at line 416 of file GenVertex.h.

Referenced by HepMC::GenEvent::add_vertex(), HepMC::compareVertex(), GenVertex(), HepMC::operator<<(), print(), HepMC::GenParticle::print(), HepMC::GenEvent::print(), HepMC::GenEvent::remove_vertex(), set_parent_event(), and HepMC::IO_AsciiParticles::write_event().

9.22.4.4 void HepMC::GenVertex::change_parent_event_ (GenEvent * evt) [protected]

for use with swap

Definition at line 419 of file GenVertex.cc.

9.22.4.5 double HepMC::GenVertex::check_momentum_conservation () const

|Sum (mom_in-mom_out)|

finds the difference between the total momentum out and the total momentum in vectors, and returns the magnitude of this vector i.e. returns $|\text{vec}\{p_{\text{in}}\} - \text{vec}\{p_{\text{out}}\}|$

Definition at line 253 of file GenVertex.cc.

References `particles_in_const_begin()`, `particles_in_const_end()`, `particles_out_const_begin()`, and `particles_out_const_end()`.

9.22.4.6 `void HepMC::GenVertex::convert_position (const double &) [protected]`

scale the position vector this method is only for use by **GenEvent** (p. 73)

Definition at line 918 of file GenVertex.cc.

References `HepMC::FourVector::t()`, `HepMC::FourVector::x()`, `HepMC::FourVector::y()`, and `HepMC::FourVector::z()`.

9.22.4.7 `void HepMC::GenVertex::delete_adopted_particles () [protected]`

for internal use only

deletes all particles which this vertex owns to be used by the vertex destructor and operator=

Definition at line 329 of file GenVertex.cc.

Referenced by `~GenVertex()`.

9.22.4.8 `GenVertex::edge_iterator HepMC::GenVertex::edges_begin (IteratorRange range = family) const [inline, protected]`

begin range

Definition at line 476 of file GenVertex.h.

Referenced by `HepMC::GenVertex::vertex_iterator::vertex_iterator()`.

9.22.4.9 `GenVertex::edge_iterator HepMC::GenVertex::edges_end (IteratorRange) const [inline, protected]`

end range

Definition at line 481 of file GenVertex.h.

Referenced by `HepMC::GenVertex::vertex_iterator::operator++()`, and `HepMC::GenVertex::vertex_iterator::vertex_iterator()`.

9.22.4.10 `int HepMC::GenVertex::edges_size (IteratorRange range = family) const [protected]`

size

Definition at line 595 of file GenVertex.cc.

References `HepMC::children`, `HepMC::family`, and `HepMC::parents`.

9.22.4.11 `int HepMC::GenVertex::id () const` `[inline]`

vertex ID

we don't define what you use the id for – but we imagine, for example it might code the meaning of the `weights()` (p. 139)

Definition at line 414 of file `GenVertex.h`.

Referenced by `print()`.

9.22.4.12 `HepMC::GenVertex::operator HepMC::FourVector () const` `[inline]`

conversion operator

Definition at line 402 of file `GenVertex.h`.

References `position()`.

9.22.4.13 `HepMC::GenVertex::operator HepMC::ThreeVector () const` `[inline]`

conversion operator

Definition at line 404 of file `GenVertex.h`.

References `point3d()`.

9.22.4.14 `bool HepMC::GenVertex::operator!= (const GenVertex & a) const`

inequality

Definition at line 140 of file `GenVertex.cc`.

9.22.4.15 `GenVertex & HepMC::GenVertex::operator= (const GenVertex & invertex)`

shallow

Shallow: does not copy the FULL list of particle pointers. Creates a copy of - *invertex*

- outgoing particles of *invertex*, but sets the decay vertex of these particles to NULL
- all incoming particles which do not have a creation vertex.
- it does not alter **this*'s `m_event` (!) (i.e. it creates copies of all particles which it owns) (note - impossible to copy the FULL list of particle pointers while having the vertex and particles in/out point-back to one another – unless you copy the entire tree – which we don't want to do)

Definition at line 82 of file `GenVertex.cc`.

References `swap()`.

9.22.4.16 `bool HepMC::GenVertex::operator== (const GenVertex & a) const`

equality

Returns true if the positions and the particles in the lists of `a` and `this` are identical. Does not compare barcodes. Note that it is impossible for two vertices to point to the same particle's address, so we need to do more than just compare the particle pointers

Definition at line 103 of file `GenVertex.cc`.

References `particles_in_const_begin()`, `particles_in_const_end()`, `particles_in_size()`, `particles_out_const_begin()`, `particles_out_const_end()`, `particles_out_size()`, and `position()`.

9.22.4.17 `GenEvent * HepMC::GenVertex::parent_event () const` `[inline]`

pointer to the event that owns this vertex

Definition at line 408 of file `GenVertex.h`.

Referenced by `HepMC::GenEvent::add_vertex()`, `HepMC::GenParticle::parent_event()`, `HepMC::GenEvent::remove_vertex()`, `suggest_barcode()`, and `~GenVertex()`.

9.22.4.18 `GenVertexParticleRange HepMC::GenVertex::particles (IteratorRange range = relatives)`

particle range

Definition at line 36 of file `GenRanges.cc`.

9.22.4.19 `GenVertex::particle_iterator HepMC::GenVertex::particles_begin (IteratorRange range = relatives)` `[inline]`

begin particle range

Definition at line 525 of file `GenVertex.h`.

References `particle_iterator`.

Referenced by `HepMC::ConstGenParticleEndRange::begin()`, `HepMC::GenParticleEndRange::begin()`, `HepMC::ConstGenParticleProductionRange::begin()`, `HepMC::GenParticleProductionRange::begin()`, `HepMC::GenVertexParticleRange::begin()`, `HepMC::Flow::connected_partners()`, and `HepMC::Flow::dangling_connected_partners()`.

9.22.4.20 `GenVertex::particle_iterator HepMC::GenVertex::particles_end (IteratorRange)` `[inline]`

end particle range

Definition at line 530 of file `GenVertex.h`.

References `particle_iterator`.

Referenced by `HepMC::Flow::connected_partners()`, `HepMC::Flow::dangling_connected_partners()`, `HepMC::ConstGenParticleEndRange::end()`, `HepMC::GenParticleEndRange::end()`, `HepMC::ConstGenParticleProductionRange::end()`, `HepMC::GenParticleProductionRange::end()`, and `HepMC::GenVertexParticleRange::end()`.

9.22.4.21 ConstGenParticleProductionRange HepMC::GenVertex::particles_in (GenParticle const &, IteratorRange *range* = relatives) const

incoming particle range

Definition at line 46 of file GenRanges.cc.

References p.

9.22.4.22 GenParticleProductionRange HepMC::GenVertex::particles_in (GenParticle &, IteratorRange *range* = relatives)

incoming particle range

Definition at line 41 of file GenRanges.cc.

References p.

9.22.4.23 GenVertex::particles_in_const_iterator HepMC::GenVertex::particles_in_const_begin () const [inline]

begin iteration of incoming particles

Definition at line 435 of file GenVertex.h.

Referenced by check_momentum_conservation(), HepMC::compareVertex(), GenVertex(), operator==(), print(), and set_parent_event_().

9.22.4.24 GenVertex::particles_in_const_iterator HepMC::GenVertex::particles_in_const_end () const [inline]

end iteration of incoming particles

Definition at line 440 of file GenVertex.h.

Referenced by check_momentum_conservation(), HepMC::compareVertex(), GenVertex(), operator==(), print(), and set_parent_event_().

9.22.4.25 int HepMC::GenVertex::particles_in_size () const [inline]

number of incoming particles

Definition at line 454 of file GenVertex.h.

Referenced by HepMC::compareVertex(), and operator==().

9.22.4.26 ConstGenParticleEndRange HepMC::GenVertex::particles_out (GenParticle const &, IteratorRange *range* = relatives) const

outgoing particle range

Definition at line 56 of file GenRanges.cc.

References p.

9.22.4.27 **GenParticleEndRange** HepMC::GenVertex::particles_out (GenParticle &, IteratorRange *range* = relatives)

outgoing particle range

Definition at line 51 of file GenRanges.cc.

References p.

9.22.4.28 **GenVertex::particles_out_const_iterator** HepMC::GenVertex::particles_out_const_begin () const [inline]

begin iteration of outgoing particles

Definition at line 445 of file GenVertex.h.

Referenced by check_momentum_conservation(), HepMC::compareVertex(), filterEvent(), GenVertex(), operator==(), print(), and set_parent_event_().

9.22.4.29 **GenVertex::particles_out_const_iterator** HepMC::GenVertex::particles_out_const_end () const [inline]

end iteration of outgoing particles

Definition at line 450 of file GenVertex.h.

Referenced by check_momentum_conservation(), HepMC::compareVertex(), filterEvent(), GenVertex(), operator==(), print(), and set_parent_event_().

9.22.4.30 **int** HepMC::GenVertex::particles_out_size () const [inline]

number of outgoing particles

Definition at line 458 of file GenVertex.h.

Referenced by HepMC::compareVertex(), filterEvent(), and operator==().

9.22.4.31 **ThreeVector** HepMC::GenVertex::point3d () const [inline]

vertex position

Definition at line 410 of file GenVertex.h.

References HepMC::FourVector::x(), HepMC::FourVector::y(), and HepMC::FourVector::z().

Referenced by operator HepMC::ThreeVector().

9.22.4.32 **const FourVector &** HepMC::GenVertex::position () const [inline]

vertex position and time

Definition at line 406 of file GenVertex.h.

Referenced by HepMC::IO_HERWIG::build_end_vertex(), HepMC::IO_HEPEVT::build_end_vertex(), HepMC::IO_HERWIG::build_production_vertex(), HepMC::IO_HEPEVT::build_production_vertex(), HepMC::compareVertex(), operator HepMC::FourVector(), HepMC::operator<<(), operator==(), print(), and set_position().

9.22.4.33 void HepMC::GenVertex::print (std::ostream & ostr = std::cout) const

print vertex information

Definition at line 145 of file GenVertex.cc.

References barcode(), HepMC::WeightContainer::end(), id(), particles_in_const_begin(), particles_in_const_end(), particles_out_const_begin(), particles_out_const_end(), position(), HepMC::WeightContainer::size(), HepMC::FourVector::t(), weights(), HepMC::FourVector::x(), HepMC::FourVector::y(), and HepMC::FourVector::z().

Referenced by HepMC::IO_HERWIG::build_production_vertex().

9.22.4.34 GenParticle * HepMC::GenVertex::remove_particle (GenParticle * particle)

remove a particle

remove_particle finds *particle in the in and/or out list and removes it from these lists ... it DOES NOT DELETE THE PARTICLE or its relations. You could delete the particle too as follows: delete vtx->remove_particle(particle);

this finds *particle in the in and/or out list and removes it from these lists ... it DOES NOT DELETE THE PARTICLE or its relations. you could delete the particle too as follows: delete vtx->remove_particle(particle); or if the particle has an end vertex, you could: delete vtx->remove_particle(particle)->end_vertex(); which would delete the particle's end vertex, and thus would also delete the particle, since the particle would be owned by the end vertex.

Definition at line 295 of file GenVertex.cc.

References HepMC::GenParticle::end_vertex(), HepMC::GenParticle::production_vertex(), remove_particle_in(), remove_particle_out(), HepMC::GenParticle::set_end_vertex(), and HepMC::GenParticle::set_production_vertex().

Referenced by filterEvent().

9.22.4.35 void HepMC::GenVertex::remove_particle_in (GenParticle *) [protected]

for internal use only - remove particle from incoming list

this finds *particle in m_particles_in and removes it from that list

Definition at line 317 of file GenVertex.cc.

References HepMC::already_in_vector().

Referenced by add_particle_in(), and remove_particle().

9.22.4.36 void HepMC::GenVertex::remove_particle_out (GenParticle *) [protected]

for internal use only - remove particle from outgoing list

this finds *particle in m_particles_out and removes it from that list

Definition at line 323 of file GenVertex.cc.

References HepMC::already_in_vector().

Referenced by add_particle_out(), and remove_particle().

9.22.4.37 void HepMC::GenVertex::set_barcode_ (int *the_bar_code*) [inline, protected]

set identifier

Definition at line 417 of file GenVertex.h.

Referenced by suggest_barcode().

9.22.4.38 void HepMC::GenVertex::set_id (int *id*) [inline]

set vertex ID

Definition at line 428 of file GenVertex.h.

9.22.4.39 void HepMC::GenVertex::set_parent_event_ (GenEvent * *evt*) [protected]

set parent event

only the **GenEvent** (p. 73) (friend) is allowed to set the parent_event, and barcode. It is done automatically anytime you add a vertex to an event

Definition at line 388 of file GenVertex.cc.

References barcode(), particles_in_const_begin(), particles_in_const_end(), particles_out_const_begin(), particles_out_const_end(), HepMC::GenEvent::remove_barcode(), and HepMC::GenEvent::set_barcode().

Referenced by HepMC::GenEvent::add_vertex(), and HepMC::GenEvent::remove_vertex().

9.22.4.40 void HepMC::GenVertex::set_position (const FourVector & *position* = FourVector(0, 0, 0, 0)) [inline]

set vertex position and time

Definition at line 424 of file GenVertex.h.

References position().

Referenced by HepMC::IO_HERWIG::build_end_vertex(), HepMC::IO_HEPEVT::build_end_vertex(), HepMC::IO_HERWIG::build_production_vertex(), and HepMC::IO_HEPEVT::build_production_vertex().

9.22.4.41 bool HepMC::GenVertex::suggest_barcode (int *the_bar_code*)

In general there is no reason to "suggest_barcode".

allows a barcode to be suggested for this vertex. In general it is better to let the event pick the barcode for you, which is automatic. Returns TRUE if the suggested barcode has been accepted (i.e. the suggested barcode has not already been used in the event, and so it was used). Returns FALSE if the suggested barcode was rejected, or if the vertex is not yet part of an event, such that it is not yet possible to know if the suggested barcode will be accepted).

Definition at line 363 of file GenVertex.cc.

References parent_event(), HepMC::GenEvent::set_barcode(), and set_barcode_().

Referenced by GenVertex().

9.22.4.42 void HepMC::GenVertex::swap (GenVertex & *other*)

swap

Definition at line 71 of file GenVertex.cc.

References m_barcode, m_event, m_id, m_particles_in, m_particles_out, m_position, m_weights, HepMC::WeightContainer::swap(), and HepMC::FourVector::swap().

Referenced by operator=().

9.22.4.43 GenVertex::vertex_iterator HepMC::GenVertex::vertices_begin (IteratorRange *range* = relatives) [inline]

begin vertex range

Definition at line 504 of file GenVertex.h.

References vertex_iterator.

9.22.4.44 GenVertex::vertex_iterator HepMC::GenVertex::vertices_end (IteratorRange) [inline]

end vertex range

Definition at line 510 of file GenVertex.h.

References vertex_iterator.

9.22.4.45 const WeightContainer & HepMC::GenVertex::weights () const [inline]

const direct access to the weights container

Definition at line 421 of file GenVertex.h.

9.22.4.46 WeightContainer & HepMC::GenVertex::weights () [inline]

direct access to the weights container is allowed.

Definition at line 419 of file GenVertex.h.

Referenced by print().

9.22.5 Friends And Related Function Documentation**9.22.5.1 friend class edge_iterator [friend]**

Definition at line 233 of file GenVertex.h.

9.22.5.2 friend class GenEvent [friend]

Definition at line 56 of file GenVertex.h.

9.22.5.3 `std::ostream& operator<< (std::ostream & ostr, const GenVertex & vtx)` `[friend]`

print vertex information

Definition at line 440 of file GenVertex.cc.

9.22.5.4 `friend class particle_iterator` `[friend]`

Definition at line 366 of file GenVertex.h.

Referenced by `particles_begin()`, and `particles_end()`.

9.22.5.5 `friend class vertex_iterator` `[friend]`

Definition at line 318 of file GenVertex.h.

Referenced by `vertices_begin()`, and `vertices_end()`.

The documentation for this class was generated from the following files:

- **GenVertex.h**
- **GenRanges.cc**
- **GenVertex.cc**

9.23 HepMC::GenVertex::edge_iterator Class Reference

edge iterator

```
#include <GenVertex.h>
```

Public Member Functions

- **edge_iterator ()**
- **edge_iterator (const GenVertex &vtx, IteratorRange range=family)**
used to set limits on the iteration
- **edge_iterator (const edge_iterator &p)**
copy
- **virtual ~edge_iterator ()**
- **edge_iterator & operator= (const edge_iterator &p)**
make a copy
- **GenParticle * operator * (void) const**
return a pointer to a particle
- **edge_iterator & operator++ (void)**
Pre-fix increment.
- **edge_iterator operator++ (int)**
Post-fix increment.
- **bool operator== (const edge_iterator &a) const**
equality
- **bool operator!= (const edge_iterator &a) const**
inequality
- **bool is_parent () const**
true if parent of root vtx
- **bool is_child () const**
true if child of root vtx
- **const GenVertex * vertex_root () const**
root vertex of this iteration

9.23.1 Detailed Description

edge iterator

iterate over the family of edges connected to m_vertex begins with parents (incoming particles) then children (outgoing) This is not a recursive iterator ... it is a building block for the public iterators and is intended for internal use only. The acceptable Iterator Ranges are: family, parents, children

Definition at line 194 of file GenVertex.h.

9.23.2 Constructor & Destructor Documentation

9.23.2.1 HepMC::GenVertex::edge_iterator::edge_iterator ()

Definition at line 462 of file GenVertex.cc.

9.23.2.2 HepMC::GenVertex::edge_iterator::edge_iterator (const GenVertex & vtx, IteratorRange range = family)

used to set limits on the iteration

Definition at line 466 of file GenVertex.cc.

References HepMC::ancestors, HepMC::children, HepMC::descendants, HepMC::family, HepMC::GenVertex::m_particles_in, HepMC::GenVertex::m_particles_out, and HepMC::parents.

9.23.2.3 HepMC::GenVertex::edge_iterator::edge_iterator (const edge_iterator & p)

copy

Definition at line 517 of file GenVertex.cc.

References p.

9.23.2.4 HepMC::GenVertex::edge_iterator::~~edge_iterator () [virtual]

Definition at line 521 of file GenVertex.cc.

9.23.3 Member Function Documentation

9.23.3.1 bool HepMC::GenVertex::edge_iterator::is_child () const

true if child of root vtx

Definition at line 590 of file GenVertex.cc.

9.23.3.2 bool HepMC::GenVertex::edge_iterator::is_parent () const

true if parent of root vtx

Definition at line 585 of file GenVertex.cc.

Referenced by HepMC::GenVertex::particle_iterator::advance_to_first_(), and HepMC::GenVertex::vertex_iterator::follow_edge_().

9.23.3.3 GenParticle * HepMC::GenVertex::edge_iterator::operator * (void) const

return a pointer to a particle

Definition at line 533 of file GenVertex.cc.

9.23.3.4 `bool HepMC::GenVertex::edge_iterator::operator!=(const edge_iterator & a) const`
[inline]

inequality

Definition at line 467 of file GenVertex.h.

9.23.3.5 `GenVertex::edge_iterator HepMC::GenVertex::edge_iterator::operator++ (int)`

Post-fix increment.

Definition at line 578 of file GenVertex.cc.

9.23.3.6 `GenVertex::edge_iterator & HepMC::GenVertex::edge_iterator::operator++ (void)`

Pre-fix increment.

Definition at line 538 of file GenVertex.cc.

References HepMC::family, HepMC::GenVertex::m_particles_in, HepMC::GenVertex::m_particles_out, and HepMC::parents.

9.23.3.7 `GenVertex::edge_iterator & HepMC::GenVertex::edge_iterator::operator= (const edge_iterator & p)`

make a copy

Definition at line 523 of file GenVertex.cc.

References p.

9.23.3.8 `bool HepMC::GenVertex::edge_iterator::operator==(const edge_iterator & a) const`
[inline]

equality

Definition at line 462 of file GenVertex.h.

9.23.3.9 `const GenVertex * HepMC::GenVertex::edge_iterator::vertex_root () const` [inline]

root vertex of this iteration

Definition at line 472 of file GenVertex.h.

The documentation for this class was generated from the following files:

- GenVertex.h
- GenVertex.cc

9.24 HepMC::GenVertex::particle_iterator Class Reference

particle iterator

```
#include <GenVertex.h>
```

Public Member Functions

- **particle_iterator ()**
- **particle_iterator (GenVertex &vertex_root, IteratorRange range)**
used to set limits on the iteration
- **particle_iterator (const particle_iterator &)**
copy
- **virtual ~particle_iterator ()**
- **particle_iterator & operator= (const particle_iterator &)**
make a copy
- **GenParticle * operator * (void) const**
return a pointer to a particle
- **particle_iterator & operator++ (void)**
Pre-fix increment.
- **particle_iterator operator++ (int)**
Post-fix increment.
- **bool operator== (const particle_iterator &) const**
equality
- **bool operator!= (const particle_iterator &) const**
inequality

Protected Member Functions

- **GenParticle * advance_to_first_ ()**
"first" particle

9.24.1 Detailed Description

particle iterator

Iterates over all particles connected via a graph. by iterating through all vertices in the m_range. For each vertex it returns orphaned parent particles (i.e. parents without production vertices) then children ... in this way each particle is associated to exactly one vertex and so it is returned exactly once. Is made friend so that it can access protected edge iterator

Examples:

example_UsingIterators.cc, and testHepMCIteration.cc.in.

Definition at line 339 of file GenVertex.h.

9.24.2 Constructor & Destructor Documentation**9.24.2.1 HepMC::GenVertex::particle_iterator::particle_iterator ()**

Definition at line 838 of file GenVertex.cc.

9.24.2.2 HepMC::GenVertex::particle_iterator::particle_iterator (GenVertex & *vertex_root*, IteratorRange *range*)

used to set limits on the iteration

Definition at line 840 of file GenVertex.cc.

References `advance_to_first_()`, `HepMC::family`, and `HepMC::GenVertex::vertex_iterator::range()`.

9.24.2.3 HepMC::GenVertex::particle_iterator::particle_iterator (const particle_iterator &)

copy

Definition at line 854 of file GenVertex.cc.

9.24.2.4 HepMC::GenVertex::particle_iterator::~~particle_iterator () [virtual]

Definition at line 859 of file GenVertex.cc.

9.24.3 Member Function Documentation**9.24.3.1 GenParticle * HepMC::GenVertex::particle_iterator::advance_to_first_ ()**
[protected]

"first" particle

if the current edge is not a suitable return value (because it is a parent of the vertex root that itself belongs to a different vertex) it advances to the first suitable return value

Definition at line 900 of file GenVertex.cc.

References `HepMC::GenVertex::edge_iterator::is_parent()`, `HepMC::GenVertex::vertex_iterator::range()`, and `HepMC::relatives`.

Referenced by `operator++()`, and `particle_iterator()`.

9.24.3.2 GenParticle * HepMC::GenVertex::particle_iterator::operator * (void) const

return a pointer to a particle

Definition at line 869 of file GenVertex.cc.

9.24.3.3 `bool HepMC::GenVertex::particle_iterator::operator!=(const particle_iterator &) const`
[inline]

inequality

Definition at line 520 of file GenVertex.h.

9.24.3.4 `GenVertex::particle_iterator HepMC::GenVertex::particle_iterator::operator++(int)`

Post-fix increment.

Definition at line 893 of file GenVertex.cc.

9.24.3.5 `GenVertex::particle_iterator & HepMC::GenVertex::particle_iterator::operator++(void)`

Pre-fix increment.

Definition at line 874 of file GenVertex.cc.

References `advance_to_first_()`, and `HepMC::GenVertex::vertex_iterator::range()`.

9.24.3.6 `GenVertex::particle_iterator & HepMC::GenVertex::particle_iterator::operator=(const particle_iterator &)`

make a copy

Definition at line 862 of file GenVertex.cc.

References `m_edge`, and `m_vertex_iterator`.

9.24.3.7 `bool HepMC::GenVertex::particle_iterator::operator==(const particle_iterator &) const`
[inline]

equality

Definition at line 515 of file GenVertex.h.

The documentation for this class was generated from the following files:

- **GenVertex.h**
- **GenVertex.cc**

9.25 HepMC::GenVertex::vertex_iterator Class Reference

vertex iterator

```
#include <GenVertex.h>
```

Public Member Functions

- **vertex_iterator ()**
- **vertex_iterator (GenVertex &vtx_root, IteratorRange range)**
used to set limits on the iteration
- **vertex_iterator (GenVertex &vtx_root, IteratorRange range, std::set< const HepMC::GenVertex * > &visited_vertices)**
next constructor is intended for internal use only
- **vertex_iterator (const vertex_iterator &v_iter)**
copy
- **virtual ~vertex_iterator ()**
- **vertex_iterator & operator= (const vertex_iterator &)**
make a copy
- **GenVertex * operator * (void) const**
return a pointer to a vertex
- **vertex_iterator & operator++ (void)**
Pre-fix increment.
- **vertex_iterator operator++ (int)**
Post-fix increment.
- **bool operator== (const vertex_iterator &) const**
equality
- **bool operator!= (const vertex_iterator &) const**
inequality
- **GenVertex * vertex_root () const**
vertex that this iterator begins from
- **IteratorRange range () const**
iterator range
- **void copy_with_own_set (const vertex_iterator &v_iter, std::set< const HepMC::GenVertex * > &visited_vertices)**
intended for internal use only.

Protected Member Functions

- **GenVertex * follow_edge_ ()**
non-null if recursive iter. created
- **void copy_recursive_iterator_ (const vertex_iterator *recursive_v_iter)**
copy recursive iterator

9.25.1 Detailed Description

vertex iterator

Iterates over all vertices connected via a graph to this vertex. this is made friend to that it can access protected edge iterator the range can be IteratorRange= (parents, children, family, ancestors, descendants, relatives) example for range=descendants the iterator will return all vertices which are children (connected by an outgoing particle edge), grandchildren, great-grandchildren, etc. of this vertex In all cases the iterator always returns this vertex (returned last). The algorithm is accomplished by converting the graph to a tree (by "chopping" the edges connecting to an already visited vertex) and returning the vertices in POST ORDER traversal.

Definition at line 263 of file GenVertex.h.

9.25.2 Constructor & Destructor Documentation

9.25.2.1 HepMC::GenVertex::vertex_iterator::vertex_iterator ()

Definition at line 607 of file GenVertex.cc.

Referenced by copy_recursive_iterator_(), and follow_edge_().

9.25.2.2 HepMC::GenVertex::vertex_iterator::vertex_iterator (GenVertex & vtx_root, IteratorRange range)

used to set limits on the iteration

Definition at line 612 of file GenVertex.cc.

References HepMC::GenVertex::edges_begin(), HepMC::GenVertex::edges_end(), and follow_edge_().

9.25.2.3 HepMC::GenVertex::vertex_iterator::vertex_iterator (GenVertex & vtx_root, IteratorRange range, std::set< const HepMC::GenVertex * > & visited_vertices)

next constructor is intended for internal use only

Definition at line 628 of file GenVertex.cc.

References HepMC::GenVertex::edges_begin(), HepMC::GenVertex::edges_end(), and follow_edge_().

9.25.2.4 HepMC::GenVertex::vertex_iterator::vertex_iterator (const vertex_iterator & v_iter)

copy

Definition at line 645 of file GenVertex.cc.

9.25.2.5 HepMC::GenVertex::vertex_iterator::~~vertex_iterator () [virtual]

Definition at line 652 of file GenVertex.cc.

9.25.3 Member Function Documentation**9.25.3.1 void HepMC::GenVertex::vertex_iterator::copy_recursive_iterator_ (const vertex_iterator * *recursive_v_iter*)** [protected]

copy recursive iterator

Definition at line 817 of file GenVertex.cc.

References copy_recursive_iterator_(), m_edge, m_it_owns_set, m_range, m_recursive_iterator, m_vertex, m_visited_vertices, and vertex_iterator().

Referenced by copy_recursive_iterator_(), copy_with_own_set(), and operator=().

9.25.3.2 void HepMC::GenVertex::vertex_iterator::copy_with_own_set (const vertex_iterator & *v_iter*, std::set< const HepMC::GenVertex * > & *visited_vertices*)

intended for internal use only.

intended for internal use only. (use with care!) this is the same as the operator= method, but it allows the user to specify which set container m_visited_vertices points to. in all cases, this vertex will NOT own its set.

Definition at line 758 of file GenVertex.cc.

References copy_recursive_iterator_(), m_edge, m_range, m_recursive_iterator, and m_vertex.

9.25.3.3 GenVertex * HepMC::GenVertex::vertex_iterator::follow_edge_ () [protected]

non-null if recursive iter. created

Definition at line 781 of file GenVertex.cc.

References HepMC::family, HepMC::GenVertex::edge_iterator::is_parent(), and vertex_iterator().

Referenced by operator++(), and vertex_iterator().

9.25.3.4 GenVertex * HepMC::GenVertex::vertex_iterator::operator * (void) const

return a pointer to a vertex

Definition at line 694 of file GenVertex.cc.

9.25.3.5 bool HepMC::GenVertex::vertex_iterator::operator!= (const vertex_iterator &) const [inline]

inequality

Definition at line 491 of file GenVertex.h.

9.25.3.6 `GenVertex::vertex_iterator` `HepMC::GenVertex::vertex_iterator::operator++ (int)`

Post-fix increment.

Definition at line 751 of file `GenVertex.cc`.

9.25.3.7 `GenVertex::vertex_iterator &` `HepMC::GenVertex::vertex_iterator::operator++ (void)`

Pre-fix increment.

Definition at line 709 of file `GenVertex.cc`.

References `HepMC::GenVertex::edges_end()`, and `follow_edge_()`.

9.25.3.8 `GenVertex::vertex_iterator &` `HepMC::GenVertex::vertex_iterator::operator= (const vertex_iterator &)`

make a copy

Definition at line 657 of file `GenVertex.cc`.

References `copy_recursive_iterator_()`, `m_edge`, `m_it_owns_set`, `m_range`, `m_recursive_iterator`, `m_vertex`, and `m_visited_vertices`.

9.25.3.9 `bool` `HepMC::GenVertex::vertex_iterator::operator== (const vertex_iterator &) const` `[inline]`

equality

Definition at line 486 of file `GenVertex.h`.

9.25.3.10 `IteratorRange` `HepMC::GenVertex::vertex_iterator::range () const` `[inline]`

iterator range

Definition at line 500 of file `GenVertex.h`.

Referenced by `HepMC::GenVertex::particle_iterator::advance_to_first_()`, `HepMC::GenVertex::particle_iterator::operator++()`, and `HepMC::GenVertex::particle_iterator::particle_iterator()`.

9.25.3.11 `GenVertex *` `HepMC::GenVertex::vertex_iterator::vertex_root () const` `[inline]`

vertex that this iterator begins from

Definition at line 496 of file `GenVertex.h`.

The documentation for this class was generated from the following files:

- `GenVertex.h`
- `GenVertex.cc`

9.26 HepMC::GenVertexParticleRange Class Reference

GenVertexParticleRange (p. 151) acts like a collection of particles.

```
#include <GenRanges.h>
```

Public Member Functions

- **GenVertexParticleRange** (**GenVertex** &*v*, **IteratorRange** *range*=*relatives*)
the constructor requires a GenVertex (p. 126)
- **GenVertex::particle_iterator** **begin** ()
- **GenVertex::particle_iterator** **end** ()

9.26.1 Detailed Description

GenVertexParticleRange (p. 151) acts like a collection of particles.

HepMC::GenVertexParticleRange (p. 151) is used to mimic a collection of particles for ease of use - especially with utilities such as the Boost foreach funtion

Definition at line 140 of file GenRanges.h.

9.26.2 Constructor & Destructor Documentation

9.26.2.1 HepMC::GenVertexParticleRange::GenVertexParticleRange (**GenVertex** & *v*, **IteratorRange** *range* = *relatives*) [inline]

the constructor requires a **GenVertex** (p. 126)

Definition at line 145 of file GenRanges.h.

9.26.3 Member Function Documentation

9.26.3.1 GenVertex::particle_iterator HepMC::GenVertexParticleRange::begin () [inline]

Definition at line 148 of file GenRanges.h.

References HepMC::GenVertex::particles_begin().

9.26.3.2 GenVertex::particle_iterator HepMC::GenVertexParticleRange::end () [inline]

Definition at line 149 of file GenRanges.h.

References HepMC::GenVertex::particles_end().

The documentation for this class was generated from the following file:

- **GenRanges.h**

9.27 HepMC::HeavyIon Class Reference

The **HeavyIon** (p. 152) class stores information about heavy ions.

```
#include <HeavyIon.h>
```

Public Member Functions

- **HeavyIon ()**
default constructor
- **HeavyIon (int nh, int np, int nt, int nc, int ns, int nsp, int nnw=0, int nwn=0, int nwnw=0, float im=0., float pl=0., float ec=0., float s=0.)**
The first 6 values must be provided.
- **~HeavyIon ()**
- **HeavyIon (HeavyIon const &orig)**
copy constructor
- **HeavyIon & operator= (HeavyIon const &rhs)**
make a copy
- **void swap (HeavyIon &other)**
swap two HeavyIon (p. 152) objects
- **bool operator== (const HeavyIon &) const**
check for equality
- **bool operator!= (const HeavyIon &) const**
check for inequality
- **int Ncoll_hard () const**
Number of hard scatterings.
- **int Npart_proj () const**
Number of projectile participants.
- **int Npart_targ () const**
Number of target participants.
- **int Ncoll () const**
Number of NN (nucleon-nucleon) collisions.
- **int spectator_neutrons () const**
Number of spectator neutrons.
- **int spectator_protons () const**
Number of spectator protons.
- **int N_Nwounded_collisions () const**

Number of N-Nwounded collisions.

- **int Nwounded_N_collisions () const**
Number of Nwounded-N collisions.
- **int Nwounded_Nwounded_collisions () const**
Number of Nwounded-Nwounded collisions.
- **float impact_parameter () const**
Impact Parameter(in fm) of collision.
- **float event_plane_angle () const**
Azimuthal angle of event plane.
- **float eccentricity () const**
- **float sigma_inel_NN () const**
nucleon-nucleon inelastic (including diffractive) cross-section
- **bool is_valid () const**
verify that the instance contains non-zero information
- **void set_Ncoll_hard (const int &i)**
set number of hard scatterings
- **void set_Npart_proj (const int &i)**
set number of projectile participants
- **void set_Npart_targ (const int &i)**
set number of target participants
- **void set_Ncoll (const int &i)**
set number of NN (nucleon-nucleon) collisions
- **void set_spectator_neutrons (const int &i)**
set number of spectator neutrons
- **void set_spectator_protons (const int &i)**
set number of spectator protons
- **void set_N_Nwounded_collisions (const int &i)**
set number of N-Nwounded collisions
- **void set_Nwounded_N_collisions (const int &i)**
set number of Nwounded-N collisions
- **void set_Nwounded_Nwounded_collisions (const int &i)**
set number of Nwounded-Nwounded collisions
- **void set_impact_parameter (const float &f)**
set Impact Parameter in fm

- **void set_event_plane_angle (const float &f)**
set azimuthal angle of event plane
- **void set_eccentricity (const float &f)**
set eccentricity of participating nucleons in the transverse plane
- **void set_sigma_inel_NN (const float &f)**
set nucleon-nucleon inelastic cross-section

9.27.1 Detailed Description

The **HeavyIon** (p. 152) class stores information about heavy ions.

HepMC::HeavyIon (p. 152) provides additional information storage for Heavy Ion generators in **Gen-Event** (p. 73). Creation and use of this information is optional.

Examples:

`testMass.cc.in.`

Definition at line 45 of file HeavyIon.h.

9.27.2 Constructor & Destructor Documentation

9.27.2.1 HepMC::HeavyIon::HeavyIon () [inline]

default constructor

Definition at line 51 of file HeavyIon.h.

9.27.2.2 HepMC::HeavyIon::HeavyIon (int nh, int np, int nt, int nc, int ns, int nsp, int nnw = 0, int nwn = 0, int nwnw = 0, float im = 0., float pl = 0., float ec = 0., float s = 0.) [inline]

The first 6 values must be provided.

Required members are the number of hard scatterings, the number of projectile participants. the number of target participants. the number of nucleon-nucleon collisions, the number of spectator neutrons, and the number of spectator protons.

Definition at line 178 of file HeavyIon.h.

9.27.2.3 HepMC::HeavyIon::~~HeavyIon () [inline]

Definition at line 72 of file HeavyIon.h.

9.27.2.4 HepMC::HeavyIon::HeavyIon (HeavyIon const & orig) [inline]

copy constructor

Definition at line 196 of file HeavyIon.h.

9.27.3 Member Function Documentation

9.27.3.1 float HepMC::HeavyIon::eccentricity () const [inline]

eccentricity of participating nucleons in the transverse plane (as in phobos nucl-ex/0510031)

Definition at line 110 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.2 float HepMC::HeavyIon::event_plane_angle () const [inline]

Azimuthal angle of event plane.

Definition at line 107 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.3 float HepMC::HeavyIon::impact_parameter () const [inline]

Impact Parameter(in fm) of collision.

Definition at line 105 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.4 bool HepMC::HeavyIon::is_valid () const [inline]

verify that the instance contains non-zero information

Definition at line 260 of file HeavyIon.h.

9.27.3.5 int HepMC::HeavyIon::N_Nwounded_collisions () const [inline]

Number of N-Nwounded collisions.

Definition at line 99 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.6 int HepMC::HeavyIon::Ncoll () const [inline]

Number of NN (nucleon-nucleon) collisions.

Definition at line 93 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.7 int HepMC::HeavyIon::Ncoll_hard () const [inline]

Number of hard scatterings.

Definition at line 87 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.8 int HepMC::HeavyIon::Npart_proj () const [inline]

Number of projectile participants.

Definition at line 89 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.9 int HepMC::HeavyIon::Npart_targ () const [inline]

Number of target participants.

Definition at line 91 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.10 int HepMC::HeavyIon::Nwounded_N_collisions () const [inline]

Number of Nwounded-N collisons.

Definition at line 101 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.11 int HepMC::HeavyIon::Nwounded_Nwounded_collisions () const [inline]

Number of Nwounded-Nwounded collisions.

Definition at line 103 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.12 bool HepMC::HeavyIon::operator!= (const HeavyIon &) const [inline]

check for inequality

any nonmatching member generates inequality

Definition at line 254 of file HeavyIon.h.

9.27.3.13 HeavyIon & HepMC::HeavyIon::operator= (HeavyIon const & rhs) [inline]

make a copy

Definition at line 212 of file HeavyIon.h.

References swap().

9.27.3.14 bool HepMC::HeavyIon::operator== (const HeavyIon &) const [inline]

check for equality

equality requires that each member match

Definition at line 236 of file HeavyIon.h.

References `eccentricity()`, `event_plane_angle()`, `impact_parameter()`, `N_Nwounded_collisions()`, `Ncoll()`, `Ncoll_hard()`, `Npart_proj()`, `Npart_targ()`, `Nwounded_N_collisions()`, `Nwounded_Nwounded_collisions()`, `sigma_inel_NN()`, `spectator_neutrons()`, and `spectator_protons()`.

9.27.3.15 void HepMC::HeavyIon::set_eccentricity (const float &f) [inline]

set eccentricity of participating nucleons in the transverse plane

Definition at line 142 of file `HeavyIon.h`.

Referenced by `HepMC::operator>>()`.

9.27.3.16 void HepMC::HeavyIon::set_event_plane_angle (const float &f) [inline]

set azimuthal angle of event plane

Definition at line 140 of file `HeavyIon.h`.

Referenced by `HepMC::operator>>()`.

9.27.3.17 void HepMC::HeavyIon::set_impact_parameter (const float &f) [inline]

set Impact Parameter in fm

Definition at line 138 of file `HeavyIon.h`.

Referenced by `HepMC::operator>>()`.

9.27.3.18 void HepMC::HeavyIon::set_N_Nwounded_collisions (const int &i) [inline]

set number of N-Nwounded collisions

Definition at line 131 of file `HeavyIon.h`.

Referenced by `HepMC::operator>>()`.

9.27.3.19 void HepMC::HeavyIon::set_Ncoll (const int &i) [inline]

set number of NN (nucleon-nucleon) collisions

Definition at line 125 of file `HeavyIon.h`.

Referenced by `HepMC::operator>>()`.

9.27.3.20 void HepMC::HeavyIon::set_Ncoll_hard (const int &i) [inline]

set number of hard scatterings

Definition at line 119 of file `HeavyIon.h`.

Referenced by `HepMC::operator>>()`.

9.27.3.21 void HepMC::HeavyIon::set_Npart_proj (const int &i) [inline]

set number of projectile participants

Definition at line 121 of file HeavyIon.h.

Referenced by HepMC::operator>>().

9.27.3.22 void HepMC::HeavyIon::set_Npart_targ (const int & i) [inline]

set number of target participants

Definition at line 123 of file HeavyIon.h.

Referenced by HepMC::operator>>().

9.27.3.23 void HepMC::HeavyIon::set_Nwounded_N_collisions (const int & i) [inline]

set number of Nwounded-N collisions

Definition at line 133 of file HeavyIon.h.

Referenced by HepMC::operator>>().

9.27.3.24 void HepMC::HeavyIon::set_Nwounded_Nwounded_collisions (const int & i) [inline]

set number of Nwounded-Nwounded collisions

Definition at line 135 of file HeavyIon.h.

Referenced by HepMC::operator>>().

9.27.3.25 void HepMC::HeavyIon::set_sigma_inel_NN (const float & f) [inline]

set nucleon-nucleon inelastic cross-section

Definition at line 144 of file HeavyIon.h.

Referenced by HepMC::operator>>().

9.27.3.26 void HepMC::HeavyIon::set_spectator_neutrons (const int & i) [inline]

set number of spectator neutrons

Definition at line 127 of file HeavyIon.h.

Referenced by HepMC::operator>>().

9.27.3.27 void HepMC::HeavyIon::set_spectator_protons (const int & i) [inline]

set number of spectator protons

Definition at line 129 of file HeavyIon.h.

Referenced by HepMC::operator>>().

9.27.3.28 float HepMC::HeavyIon::sigma_inel_NN () const [inline]

nucleon-nucleon inelastic (including diffractive) cross-section

Definition at line 112 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.29 int HepMC::HeavyIon::spectator_neutrons () const [inline]

Number of spectator neutrons.

Definition at line 95 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.30 int HepMC::HeavyIon::spectator_protons () const [inline]

Number of spectator protons.

Definition at line 97 of file HeavyIon.h.

Referenced by HepMC::operator<<(), and operator==().

9.27.3.31 void HepMC::HeavyIon::swap (HeavyIon & other) [inline]

swap two **HeavyIon** (p. 152) objects

Definition at line 219 of file HeavyIon.h.

References m_eccentricity, m_event_plane_angle, m_impact_parameter, m_N_Nwounded_collisions, m_Ncoll, m_Ncoll_hard, m_Npart_proj, m_Npart_targ, m_Nwounded_N_collisions, m_Nwounded_Nwounded_collisions, m_sigma_inel_NN, m_spectator_neutrons, and m_spectator_protons.

Referenced by operator=().

The documentation for this class was generated from the following file:

- **HeavyIon.h**

9.28 HepMC::HEPEVT_Wrapper Class Reference

Generic Wrapper for the fortran HEPEVT common block.

```
#include <HEPEVT_Wrapper.h>
```

Static Public Member Functions

- static void **print_hepevt** (std::ostream &ostr=std::cout)
write information from HEPEVT common block
- static void **print_hepevt_particle** (int index, std::ostream &ostr=std::cout)
write particle information to ostr
- static bool **is_double_precision** ()
True if common block uses double.
- static bool **check_hepevt_consistency** (std::ostream &ostr=std::cout)
check for problems with HEPEVT common block
- static void **zero_everything** ()
set all entries in HEPEVT to zero
- static int **event_number** ()
event number
- static int **number_entries** ()
num entries in current evt
- static int **status** (int index)
status code
- static int **id** (int index)
PDG particle id.
- static int **first_parent** (int index)
index of 1st mother
- static int **last_parent** (int index)
index of last mother
- static int **number_parents** (int index)
number of parents
- static int **first_child** (int index)
index of 1st daughter
- static int **last_child** (int index)
index of last daughter

- **static int number_children (int index)**
number of children
- **static double px (int index)**
X momentum.
- **static double py (int index)**
Y momentum.
- **static double pz (int index)**
Z momentum.
- **static double e (int index)**
Energy.
- **static double m (int index)**
generated mass
- **static double x (int index)**
X Production vertex.
- **static double y (int index)**
Y Production vertex.
- **static double z (int index)**
Z Production vertex.
- **static double t (int index)**
production time
- **static void set_event_number (int evtno)**
set event number
- **static void set_number_entries (int noentries)**
set number of entries in HEPEVT
- **static void set_status (int index, int status)**
set particle status
- **static void set_id (int index, int id)**
set particle ID
- **static void set_parents (int index, int firstparent, int lastparent)**
define parents of a particle
- **static void set_children (int index, int firstchild, int lastchild)**
define children of a particle
- **static void set_momentum (int index, double px, double py, double pz, double e)**
set particle momentum

- **static void set_mass (int index, double mass)**
set particle mass
- **static void set_position (int index, double x, double y, double z, double t)**
set particle production vertex
- **static unsigned int sizeof_int ()**
size of integer in bytes
- **static unsigned int sizeof_real ()**
size of real in bytes
- **static int max_number_entries ()**
size of common block
- **static void set_sizeof_int (unsigned int)**
define size of integer
- **static void set_sizeof_real (unsigned int)**
define size of real
- **static void set_max_number_entries (unsigned int)**
define size of common block

Static Protected Member Functions

- **static double byte_num_to_double (unsigned int)**
navigate a byte array
- **static int byte_num_to_int (unsigned int)**
navigate a byte array
- **static void write_byte_num (double, unsigned int)**
pretend common block is an array of bytes
- **static void write_byte_num (int, unsigned int)**
pretend common block is an array of bytes
- **static void print_legend (std::ostream &ostr=std::cout)**
print output legend

9.28.1 Detailed Description

Generic Wrapper for the fortran HEPEVT common block.

This class is intended for static use only - it makes no sense to instantiate it.

Definition at line 130 of file HEPEVT_Wrapper.h.

9.28.2 Member Function Documentation

9.28.2.1 `double HepMC::HEPEVT_Wrapper::byte_num_to_double (unsigned int)` `[inline, static, protected]`

navigate a byte array

Definition at line 255 of file HEPEVT_Wrapper.h.

References `hepevt`, and `hepevt_bytes_allocation`.

Referenced by `e()`, `m()`, `px()`, `py()`, `pz()`, `t()`, `x()`, `y()`, and `z()`.

9.28.2.2 `int HepMC::HEPEVT_Wrapper::byte_num_to_int (unsigned int)` `[inline, static, protected]`

navigate a byte array

Definition at line 273 of file HEPEVT_Wrapper.h.

References `hepevt`, and `hepevt_bytes_allocation`.

Referenced by `event_number()`, `first_child()`, `first_parent()`, `id()`, `last_child()`, `last_parent()`, `number_entries()`, and `status()`.

9.28.2.3 `bool HepMC::HEPEVT_Wrapper::check_hepevt_consistency (std::ostream & ostr = std::cout)` `[static]`

check for problems with HEPEVT common block

This method inspects the HEPEVT common block and looks for inconsistencies in the mother/daughter pointers

Definition at line 88 of file HEPEVT_Wrapper.cc.

References `event_number()`, `first_child()`, `first_parent()`, `last_child()`, `last_parent()`, `m()`, `number_entries()`, `print_hepevt_particle()`, and `print_legend()`.

9.28.2.4 `double HepMC::HEPEVT_Wrapper::e (int index)` `[inline, static]`

Energy.

Definition at line 446 of file HEPEVT_Wrapper.h.

References `byte_num_to_double()`, `max_number_entries()`, `sizeof_int()`, and `sizeof_real()`.

Referenced by `HepMC::IO_HERWIG::build_particle()`, `HepMC::IO_HEPEVT::build_particle()`, `print_hepevt_particle()`, and `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`.

9.28.2.5 `int HepMC::HEPEVT_Wrapper::event_number ()` `[inline, static]`

event number

Definition at line 343 of file HEPEVT_Wrapper.h.

References `byte_num_to_int()`.

Referenced by `HepMC::IO_HERWIG::build_end_vertex()`, `HepMC::IO_HEPEVT::build_end_vertex()`, `HepMC::IO_HERWIG::build_production_vertex()`, `HepMC::IO_HEPEVT::build_production_vertex()`,

check_hepevt_consistency(), HepMC::IO_HERWIG::fill_next_event(), HepMC::IO_HEPEVT::fill_next_event(), and print_hepevt().

9.28.2.6 int HepMC::HEPEVT_Wrapper::first_child (int *index*) [inline, static]

index of 1st daughter

Definition at line 394 of file HEPEVT_Wrapper.h.

References byte_num_to_int(), max_number_entries(), number_entries(), and sizeof_int().

Referenced by HepMC::IO_HERWIG::build_end_vertex(), HepMC::IO_HEPEVT::build_end_vertex(), check_hepevt_consistency(), last_child(), number_children(), print_hepevt_particle(), HepMC::IO_HERWIG::remove_gaps_in_hepevt(), and HepMC::IO_HERWIG::repair_hepevt().

9.28.2.7 int HepMC::HEPEVT_Wrapper::first_parent (int *index*) [inline, static]

index of 1st mother

Definition at line 362 of file HEPEVT_Wrapper.h.

References byte_num_to_int(), max_number_entries(), number_entries(), and sizeof_int().

Referenced by HepMC::IO_HERWIG::build_production_vertex(), HepMC::IO_HEPEVT::build_production_vertex(), check_hepevt_consistency(), HepMC::IO_HERWIG::fill_next_event(), last_parent(), number_parents(), print_hepevt_particle(), HepMC::IO_HERWIG::remove_gaps_in_hepevt(), and HepMC::IO_HERWIG::repair_hepevt().

9.28.2.8 int HepMC::HEPEVT_Wrapper::id (int *index*) [inline, static]

PDG particle id.

Definition at line 356 of file HEPEVT_Wrapper.h.

References byte_num_to_int(), max_number_entries(), and sizeof_int().

Referenced by HepMC::IO_HERWIG::build_particle(), HepMC::IO_HEPEVT::build_particle(), HepMC::IO_HERWIG::remove_gaps_in_hepevt(), and HepMC::IO_HERWIG::repair_hepevt().

9.28.2.9 bool HepMC::HEPEVT_Wrapper::is_double_precision () [inline, static]

True if common block uses double.

Definition at line 337 of file HEPEVT_Wrapper.h.

References sizeof_real().

Referenced by print_hepevt().

9.28.2.10 int HepMC::HEPEVT_Wrapper::last_child (int *index*) [inline, static]

index of last daughter

Definition at line 402 of file HEPEVT_Wrapper.h.

References byte_num_to_int(), first_child(), max_number_entries(), number_entries(), and sizeof_int().

Referenced by HepMC::IO_HERWIG::build_end_vertex(), HepMC::IO_HEPEVT::build_end_vertex(), check_hepevt_consistency(), number_children(), print_hepevt_particle(), HepMC::IO_HERWIG::remove_gaps_in_hepevt(), and HepMC::IO_HERWIG::repair_hepevt().

9.28.2.11 int HepMC::HEPEVT_Wrapper::last_parent (int *index*) [inline, static]

index of last mother

Definition at line 370 of file HEPEVT_Wrapper.h.

References byte_num_to_int(), first_parent(), max_number_entries(), number_entries(), and sizeof_int().

Referenced by HepMC::IO_HERWIG::build_production_vertex(), HepMC::IO_HEPEVT::build_production_vertex(), check_hepevt_consistency(), number_parents(), print_hepevt_particle(), HepMC::IO_HERWIG::remove_gaps_in_hepevt(), and HepMC::IO_HERWIG::repair_hepevt().

9.28.2.12 double HepMC::HEPEVT_Wrapper::m (int *index*) [inline, static]

generated mass

Definition at line 452 of file HEPEVT_Wrapper.h.

References byte_num_to_double(), max_number_entries(), sizeof_int(), and sizeof_real().

Referenced by HepMC::IO_HERWIG::build_particle(), HepMC::IO_HEPEVT::build_particle(), check_hepevt_consistency(), print_hepevt_particle(), and HepMC::IO_HERWIG::remove_gaps_in_hepevt().

9.28.2.13 int HepMC::HEPEVT_Wrapper::max_number_entries () [inline, static]

size of common block

Definition at line 229 of file HEPEVT_Wrapper.h.

Referenced by e(), first_child(), first_parent(), id(), last_child(), last_parent(), m(), number_entries(), print_hepevt(), px(), py(), pz(), set_children(), set_id(), set_mass(), set_momentum(), set_parents(), set_position(), set_status(), t(), HepMC::IO_HEPEVT::write_event(), x(), y(), z(), zero_everything(), and HepMC::IO_HERWIG::zero_hepevt_entry().

9.28.2.14 int HepMC::HEPEVT_Wrapper::number_children (int *index*) [inline, static]

number of children

Definition at line 420 of file HEPEVT_Wrapper.h.

References first_child(), and last_child().

Referenced by HepMC::IO_HERWIG::build_end_vertex(), and HepMC::IO_HEPEVT::build_end_vertex().

9.28.2.15 int HepMC::HEPEVT_Wrapper::number_entries () [inline, static]

num entries in current evt

Definition at line 346 of file HEPEVT_Wrapper.h.

References byte_num_to_int(), max_number_entries(), and sizeof_int().

Referenced by `check_hepevt_consistency()`, `HepMC::IO_HERWIG::fill_next_event()`, `HepMC::IO_HEPEVT::fill_next_event()`, `first_child()`, `first_parent()`, `last_child()`, `last_parent()`, `print_hepevt()`, `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`, and `HepMC::IO_HERWIG::repair_hepevt()`.

9.28.2.16 `int HepMC::HEPEVT_Wrapper::number_parents (int index)` `[inline, static]`

number of parents

Definition at line 388 of file `HEPEVT_Wrapper.h`.

References `first_parent()`, and `last_parent()`.

Referenced by `HepMC::IO_HERWIG::build_production_vertex()`, and `HepMC::IO_HEPEVT::build_production_vertex()`.

9.28.2.17 `void HepMC::HEPEVT_Wrapper::print_hepevt (std::ostream & ostr = std::cout)` `[static]`

write information from HEPEVT common block

dumps the content of this HEPEVT event to ostr (Width is 80)

Examples:

`example_MyHerwig.cc`.

Definition at line 27 of file `HEPEVT_Wrapper.cc`.

References `event_number()`, `is_double_precision()`, `max_number_entries()`, `number_entries()`, `print_hepevt_particle()`, `print_legend()`, `sizeof_int()`, and `sizeof_real()`.

Referenced by `main()`.

9.28.2.18 `void HepMC::HEPEVT_Wrapper::print_hepevt_particle (int index, std::ostream & ostr = std::cout)` `[static]`

write particle information to ostr

dumps the content HEPEVT particle entry i (Width is 120) here i is the C array index (i.e. it starts at 0 ... whereas the fortran array index starts at 1) So if there's 100 particles, the last valid index is 100-1=99

Definition at line 68 of file `HEPEVT_Wrapper.cc`.

References `e()`, `first_child()`, `first_parent()`, `last_child()`, `last_parent()`, `m()`, `px()`, `py()`, `pz()`, `status()`, `t()`, `x()`, `y()`, and `z()`.

Referenced by `check_hepevt_consistency()`, and `print_hepevt()`.

9.28.2.19 `void HepMC::HEPEVT_Wrapper::print_legend (std::ostream & ostr = std::cout)` `[static, protected]`

print output legend

Definition at line 55 of file `HEPEVT_Wrapper.cc`.

Referenced by `check_hepevt_consistency()`, and `print_hepevt()`.

9.28.2.20 double HepMC::HEPEVT_Wrapper::px (int *index*) [inline, static]

X momentum.

Definition at line 427 of file HEPEVT_Wrapper.h.

References `byte_num_to_double()`, `max_number_entries()`, `sizeof_int()`, and `sizeof_real()`.

Referenced by `HepMC::IO_HERWIG::build_particle()`, `HepMC::IO_HEPEVT::build_particle()`, `print_hepevt_particle()`, and `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`.

9.28.2.21 double HepMC::HEPEVT_Wrapper::py (int *index*) [inline, static]

Y momentum.

Definition at line 433 of file HEPEVT_Wrapper.h.

References `byte_num_to_double()`, `max_number_entries()`, `sizeof_int()`, and `sizeof_real()`.

Referenced by `HepMC::IO_HERWIG::build_particle()`, `HepMC::IO_HEPEVT::build_particle()`, `print_hepevt_particle()`, and `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`.

9.28.2.22 double HepMC::HEPEVT_Wrapper::pz (int *index*) [inline, static]

Z momentum.

Definition at line 440 of file HEPEVT_Wrapper.h.

References `byte_num_to_double()`, `max_number_entries()`, `sizeof_int()`, and `sizeof_real()`.

Referenced by `HepMC::IO_HERWIG::build_particle()`, `HepMC::IO_HEPEVT::build_particle()`, `print_hepevt_particle()`, and `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`.

9.28.2.23 void HepMC::HEPEVT_Wrapper::set_children (int *index*, int *firstchild*, int *lastchild*)
[inline, static]

define children of a particle

Definition at line 514 of file HEPEVT_Wrapper.h.

References `max_number_entries()`, `sizeof_int()`, and `write_byte_num()`.

Referenced by `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`, `HepMC::IO_HERWIG::repair_hepevt()`, `HepMC::IO_HEPEVT::write_event()`, `zero_everything()`, and `HepMC::IO_HERWIG::zero_hepevt_entry()`.

9.28.2.24 void HepMC::HEPEVT_Wrapper::set_event_number (int *evtno*) [inline, static]

set event number

Definition at line 486 of file HEPEVT_Wrapper.h.

References `write_byte_num()`.

Referenced by `HepMC::IO_HEPEVT::write_event()`, and `zero_everything()`.

9.28.2.25 void HepMC::HEPEVT_Wrapper::set_id (int *index*, int *id*) [inline, static]

set particle ID

Definition at line 498 of file HEPEVT_Wrapper.h.

References max_number_entries(), sizeof_int(), and write_byte_num().

Referenced by HepMC::IO_HERWIG::remove_gaps_in_hepevt(), HepMC::IO_HERWIG::repair_hepevt(), HepMC::IO_HEPEVT::write_event(), zero_everything(), and HepMC::IO_HERWIG::zero_hepevt_entry().

9.28.2.26 void HepMC::HEPEVT_Wrapper::set_mass (int *index*, double *mass*) [inline, static]

set particle mass

Definition at line 538 of file HEPEVT_Wrapper.h.

References max_number_entries(), sizeof_int(), sizeof_real(), and write_byte_num().

Referenced by HepMC::IO_HERWIG::remove_gaps_in_hepevt(), HepMC::IO_HEPEVT::write_event(), zero_everything(), and HepMC::IO_HERWIG::zero_hepevt_entry().

9.28.2.27 void HepMC::HEPEVT_Wrapper::set_max_number_entries (unsigned *int*) [inline, static]

define size of common block

Examples:

example_MyHerwig.cc, example_MyPythia.cc, example_MyPythiaOnlyToHepMC.cc, example_PythiaStreamIO.cc, testHerwigCopies.cc, and testPythiaCopies.cc.

Definition at line 251 of file HEPEVT_Wrapper.h.

Referenced by event_selection(), main(), pythia_in_out(), pythia_out(), pythia_particle_out(), and write_PythiaStreamIO().

9.28.2.28 void HepMC::HEPEVT_Wrapper::set_momentum (int *index*, double *px*, double *py*, double *pz*, double *e*) [inline, static]

set particle momentum

Definition at line 524 of file HEPEVT_Wrapper.h.

References max_number_entries(), sizeof_int(), sizeof_real(), and write_byte_num().

Referenced by HepMC::IO_HERWIG::remove_gaps_in_hepevt(), HepMC::IO_HEPEVT::write_event(), zero_everything(), and HepMC::IO_HERWIG::zero_hepevt_entry().

9.28.2.29 void HepMC::HEPEVT_Wrapper::set_number_entries (int *noentries*) [inline, static]

set number of entries in HEPEVT

Definition at line 489 of file HEPEVT_Wrapper.h.

References `sizeof_int()`, and `write_byte_num()`.

Referenced by `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`, `HepMC::IO_HEPEVT::write_event()`, and `zero_everything()`.

9.28.2.30 `void HepMC::HEPEVT_Wrapper::set_parents (int index, int firstparent, int lastparent)`
[inline, static]

define parents of a particle

Definition at line 504 of file `HEPEVT_Wrapper.h`.

References `max_number_entries()`, `sizeof_int()`, and `write_byte_num()`.

Referenced by `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`, `HepMC::IO_HERWIG::repair_hepevt()`, `HepMC::IO_HEPEVT::write_event()`, `zero_everything()`, and `HepMC::IO_HERWIG::zero_hepevt_entry()`.

9.28.2.31 `void HepMC::HEPEVT_Wrapper::set_position (int index, double x, double y, double z, double t)` [inline, static]

set particle production vertex

Definition at line 545 of file `HEPEVT_Wrapper.h`.

References `max_number_entries()`, `sizeof_int()`, `sizeof_real()`, and `write_byte_num()`.

Referenced by `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`, `HepMC::IO_HEPEVT::write_event()`, `zero_everything()`, and `HepMC::IO_HERWIG::zero_hepevt_entry()`.

9.28.2.32 `void HepMC::HEPEVT_Wrapper::set_sizeof_int (unsigned int)` [inline, static]

define size of integer

Definition at line 232 of file `HEPEVT_Wrapper.h`.

9.28.2.33 `void HepMC::HEPEVT_Wrapper::set_sizeof_real (unsigned int)` [inline, static]

define size of real

Examples:

`example_MyHerwig.cc`, `example_MyPythia.cc`, `example_MyPythiaOnlyToHepMC.cc`, `example_PythiaStreamIO.cc`, `testHerwigCopies.cc`, and `testPythiaCopies.cc`.

Definition at line 242 of file `HEPEVT_Wrapper.h`.

Referenced by `event_selection()`, `main()`, `pythia_in_out()`, `pythia_out()`, `pythia_particle_out()`, and `write_PythiaStreamIO()`.

9.28.2.34 `void HepMC::HEPEVT_Wrapper::set_status (int index, int status)` [inline, static]

set particle status

Definition at line 492 of file HEPEVT_Wrapper.h.

References `max_number_entries()`, `sizeof_int()`, and `write_byte_num()`.

Referenced by `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`, `HepMC::IO_HEPEVT::write_event()`, `zero_everything()`, and `HepMC::IO_HERWIG::zero_hepevt_entry()`.

9.28.2.35 `unsigned int HepMC::HEPEVT_Wrapper::sizeof_int ()` `[inline, static]`

size of integer in bytes

Definition at line 225 of file HEPEVT_Wrapper.h.

Referenced by `e()`, `first_child()`, `first_parent()`, `id()`, `last_child()`, `last_parent()`, `m()`, `number_entries()`, `print_hepevt()`, `px()`, `py()`, `pz()`, `set_children()`, `set_id()`, `set_mass()`, `set_momentum()`, `set_number_entries()`, `set_parents()`, `set_position()`, `set_status()`, `status()`, `t()`, `x()`, `y()`, and `z()`.

9.28.2.36 `unsigned int HepMC::HEPEVT_Wrapper::sizeof_real ()` `[inline, static]`

size of real in bytes

Definition at line 227 of file HEPEVT_Wrapper.h.

Referenced by `e()`, `is_double_precision()`, `m()`, `print_hepevt()`, `px()`, `py()`, `pz()`, `set_mass()`, `set_momentum()`, `set_position()`, `t()`, `x()`, `y()`, and `z()`.

9.28.2.37 `int HepMC::HEPEVT_Wrapper::status (int index)` `[inline, static]`

status code

Definition at line 353 of file HEPEVT_Wrapper.h.

References `byte_num_to_int()`, and `sizeof_int()`.

Referenced by `HepMC::IO_HERWIG::build_particle()`, `HepMC::IO_HEPEVT::build_particle()`, `HepMC::IO_HERWIG::fill_next_event()`, `print_hepevt_particle()`, `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`, and `HepMC::IO_HERWIG::repair_hepevt()`.

9.28.2.38 `double HepMC::HEPEVT_Wrapper::t (int index)` `[inline, static]`

production time

Definition at line 479 of file HEPEVT_Wrapper.h.

References `byte_num_to_double()`, `max_number_entries()`, `sizeof_int()`, and `sizeof_real()`.

Referenced by `HepMC::IO_HERWIG::build_end_vertex()`, `HepMC::IO_HEPEVT::build_end_vertex()`, `HepMC::IO_HERWIG::build_production_vertex()`, `HepMC::IO_HEPEVT::build_production_vertex()`, `print_hepevt_particle()`, and `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`.

9.28.2.39 `void HepMC::HEPEVT_Wrapper::write_byte_num (int, unsigned int)` `[inline, static, protected]`

pretend common block is an array of bytes

Definition at line 312 of file HEPEVT_Wrapper.h.

References `hepevt`, and `hepevt_bytes_allocation`.

9.28.2.40 `void HepMC::HEPEVT_Wrapper::write_byte_num (double, unsigned int)` [inline, static, protected]

pretend common block is an array of bytes

Definition at line 295 of file HEPEVT_Wrapper.h.

References `hepevt`, and `hepevt_bytes_allocation`.

Referenced by `set_children()`, `set_event_number()`, `set_id()`, `set_mass()`, `set_momentum()`, `set_number_entries()`, `set_parents()`, `set_position()`, and `set_status()`.

9.28.2.41 `double HepMC::HEPEVT_Wrapper::x (int index)` [inline, static]

X Production vertex.

Definition at line 458 of file HEPEVT_Wrapper.h.

References `byte_num_to_double()`, `max_number_entries()`, `sizeof_int()`, and `sizeof_real()`.

Referenced by `HepMC::IO_HERWIG::build_end_vertex()`, `HepMC::IO_HEPEVT::build_end_vertex()`, `HepMC::IO_HERWIG::build_production_vertex()`, `HepMC::IO_HEPEVT::build_production_vertex()`, `print_hepevt_particle()`, and `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`.

9.28.2.42 `double HepMC::HEPEVT_Wrapper::y (int index)` [inline, static]

Y Production vertex.

Definition at line 465 of file HEPEVT_Wrapper.h.

References `byte_num_to_double()`, `max_number_entries()`, `sizeof_int()`, and `sizeof_real()`.

Referenced by `HepMC::IO_HERWIG::build_end_vertex()`, `HepMC::IO_HEPEVT::build_end_vertex()`, `HepMC::IO_HERWIG::build_production_vertex()`, `HepMC::IO_HEPEVT::build_production_vertex()`, `print_hepevt_particle()`, and `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`.

9.28.2.43 `double HepMC::HEPEVT_Wrapper::z (int index)` [inline, static]

Z Production vertex.

Definition at line 472 of file HEPEVT_Wrapper.h.

References `byte_num_to_double()`, `max_number_entries()`, `sizeof_int()`, and `sizeof_real()`.

Referenced by `HepMC::IO_HERWIG::build_end_vertex()`, `HepMC::IO_HEPEVT::build_end_vertex()`, `HepMC::IO_HERWIG::build_production_vertex()`, `HepMC::IO_HEPEVT::build_production_vertex()`, `print_hepevt_particle()`, and `HepMC::IO_HERWIG::remove_gaps_in_hepevt()`.

9.28.2.44 `void HepMC::HEPEVT_Wrapper::zero_everything ()` [static]

set all entries in HEPEVT to zero

Definition at line 212 of file HEPEVT_Wrapper.cc.

References `max_number_entries()`, `set_children()`, `set_event_number()`, `set_id()`, `set_mass()`, `set_momentum()`, `set_number_entries()`, `set_parents()`, `set_position()`, and `set_status()`.

The documentation for this class was generated from the following files:

- **HEPEVT_Wrapper.h**
- **HEPEVT_Wrapper.cc**

9.29 hwgev Struct Reference

```
#include <HerwigWrapper.h>
```

Public Attributes

- double AVWGT
- double EVWGT
- double GAMWT
- double TLOUT
- double WBIGST
- double WGTMAX
- double WGTSUM
- double WSQSUM
- int IDHW [herwig_hepevt_size]
- int IERROR
- int ISTAT
- int LWEVT
- int MAXER
- int MAXPR
- int NOWGT
- int NRN [2]
- int NUMER
- int NUMERU
- int NWGTS
- int GENSOFF

9.29.1 Detailed Description

Definition at line 56 of file HerwigWrapper.h.

9.29.2 Member Data Documentation

9.29.2.1 double hwgev::AVWGT

Definition at line 57 of file HerwigWrapper.h.

9.29.2.2 double hwgev::EVWGT

Definition at line 57 of file HerwigWrapper.h.

9.29.2.3 double hwgev::GAMWT

Definition at line 57 of file HerwigWrapper.h.

9.29.2.4 int hwgev::GENSOFF

Definition at line 60 of file HerwigWrapper.h.

9.29.2.5 int hwgev::IDHW[herwig_hepevt_size]

Definition at line 58 of file HerwigWrapper.h.

9.29.2.6 int hwgev::IERROR

Definition at line 58 of file HerwigWrapper.h.

9.29.2.7 int hwgev::ISTAT

Definition at line 58 of file HerwigWrapper.h.

9.29.2.8 int hwgev::LWEVT

Definition at line 58 of file HerwigWrapper.h.

9.29.2.9 int hwgev::MAXER

Definition at line 58 of file HerwigWrapper.h.

9.29.2.10 int hwgev::MAXPR

Definition at line 58 of file HerwigWrapper.h.

9.29.2.11 int hwgev::NOWGT

Definition at line 59 of file HerwigWrapper.h.

9.29.2.12 int hwgev::NRN[2]

Definition at line 59 of file HerwigWrapper.h.

9.29.2.13 int hwgev::NUMER

Definition at line 59 of file HerwigWrapper.h.

9.29.2.14 int hwgev::NUMERU

Definition at line 59 of file HerwigWrapper.h.

9.29.2.15 int hwgev::NWGTS

Definition at line 59 of file HerwigWrapper.h.

9.29.2.16 double hwgev::TLOUT

Definition at line 57 of file HerwigWrapper.h.

9.29.2.17 double hwgev::WBGST

Definition at line 57 of file HerwigWrapper.h.

9.29.2.18 double hwgev::WGTMAX

Definition at line 57 of file HerwigWrapper.h.

9.29.2.19 double hwgev::WGTSUM

Definition at line 57 of file HerwigWrapper.h.

9.29.2.20 double hwgev::WSQSUM

Definition at line 57 of file HerwigWrapper.h.

The documentation for this struct was generated from the following file:


- **HerwigWrapper.h**

9.30 HepMC::IO_AsciiParticles Class Reference

event input/output in ascii format for eye and machine reading

```
#include <IO_AsciiParticles.h>
```

Inheritance diagram for HepMC::IO_AsciiParticles::



Public Member Functions

- **IO_AsciiParticles** (const char *filename="IO_AsciiParticles.dat", std::ios::openmode mode=std::ios::out)
constructor requiring a file name and std::ios mode
- **virtual ~IO_AsciiParticles** ()
- **void write_event** (const GenEvent *evt)
write this event
- **bool fill_next_event** (GenEvent *evt)
get the next event
- **void write_comment** (const std::string comment)
- **void setPrecision** (int iprec)
set output precision
- **int rdstate** () const
check the state of the IO stream
- **void clear** ()
clear the IO stream
- **void print** (std::ostream &ostr=std::cout) const
write to ostr

Protected Member Functions

- **bool write_end_listing** ()
write end tag

9.30.1 Detailed Description

event input/output in ascii format for eye and machine reading

Strategy for reading or writing events as machine readable ascii to a file. When instantiating, the mode of file to be created must be specified.

Examples:

example_MyPythia.cc, testHepMC.cc.in, and testStreamIO.cc.in.

Definition at line 54 of file IO_AsciiParticles.h.

9.30.2 Constructor & Destructor Documentation

9.30.2.1 HepMC::IO_AsciiParticles::IO_AsciiParticles (const char * *filename* = "IO_AsciiParticles.dat", std::ios::openmode *mode* = std::ios::out)

constructor requiring a file name and std::ios mode

Definition at line 17 of file IO_AsciiParticles.cc.

9.30.2.2 HepMC::IO_AsciiParticles::~~IO_AsciiParticles () [virtual]

Definition at line 46 of file IO_AsciiParticles.cc.

9.30.3 Member Function Documentation

9.30.3.1 void HepMC::IO_AsciiParticles::clear () [inline]

clear the IO stream

Definition at line 97 of file IO_AsciiParticles.h.

9.30.3.2 bool HepMC::IO_AsciiParticles::fill_next_event (GenEvent * *evt*) [virtual]

get the next event

Implements **HepMC::IO_BaseClass p.** (classHepMC₁₁*IO_BaseClass_f1dfb95a44d521af510f6431a30f942* ??)

Definition at line 179 of file IO_AsciiParticles.cc.

9.30.3.3 void HepMC::IO_AsciiParticles::print (std::ostream & *ostr* = std::cout) const
[virtual]

write to ostr

Reimplemented from **HepMC::IO_BaseClass p.** (classHepMC₁₁*IO_BaseClass_8a23f5de9c6bb10931dcacdeb7677413* ??)

Definition at line 53 of file IO_AsciiParticles.cc.

9.30.3.4 `int HepMC::IO_AsciiParticles::rdstate () const` `[inline]`

check the state of the IO stream

Definition at line 96 of file IO_AsciiParticles.h.

9.30.3.5 `void HepMC::IO_AsciiParticles::setPrecision (int iprec)` `[inline]`

set output precision

Definition at line 98 of file IO_AsciiParticles.h.

9.30.3.6 `void HepMC::IO_AsciiParticles::write_comment (const std::string comment)`

insert a comment directly into the output file — normally you only want to do this at the beginning or end of the file. All comments are preceded with "HepMC::IO_AsciiParticles-COMMENT\n"

Definition at line 202 of file IO_AsciiParticles.cc.

References `write_end_listing()`.

9.30.3.7 `bool HepMC::IO_AsciiParticles::write_end_listing ()` `[protected]`

write end tag

Definition at line 217 of file IO_AsciiParticles.cc.

Referenced by `write_comment()`.

9.30.3.8 `void HepMC::IO_AsciiParticles::write_event (const GenEvent * evt)` `[virtual]`

write this event

Implements **HepMC::IO_BaseClass** `p.` (`classHepMC11IO_BaseClass7929dfd8412207c7904f29652810c1f4 ??`)

Definition at line 63 of file IO_AsciiParticles.cc.

References `HepMC::GenEvent::alphaQCD()`, `HepMC::GenEvent::alphaQED()`, `HepMC::GenVertex::barcode()`, `HepMC::WeightContainer::begin()`, `HepMC::WeightContainer::end()`, `HepMC::GenEvent::event_number()`, `HepMC::GenEvent::event_scale()`, `HepMC::detail::output()`, `HepMC::GenEvent::particles_begin()`, `HepMC::GenEvent::particles_end()`, `HepMC::GenEvent::particles_size()`, `HepMC::GenEvent::random_states()`, `HepMC::GenEvent::signal_process_id()`, `HepMC::GenEvent::signal_process_vertex()`, `HepMC::WeightContainer::size()`, `HepMC::versionName()`, `HepMC::GenEvent::vertices_size()`, and `HepMC::GenEvent::weights()`.

The documentation for this class was generated from the following files:


- `IO_AsciiParticles.h`
- `IO_AsciiParticles.cc`

9.31 HepMC::IO_BaseClass Class Reference

all input/output classes inherit from **IO_BaseClass** (p. 179)

```
#include <IO_BaseClass.h>
```

Inheritance diagram for HepMC::IO_BaseClass::



Public Member Functions

- virtual `~IO_BaseClass ()`
- virtual `void write_event (const GenEvent *)=0`
write this GenEvent (p. 73)
- virtual `bool fill_next_event (GenEvent *)=0`
fill this GenEvent (p. 73)
- virtual `void print (std::ostream &ostr=std::cout) const`
write output to ostr
- `GenEvent * read_next_event ()`
do not over-ride
- virtual `GenEvent *& operator>> (GenEvent *&)`
the same as read_next_event
- virtual `const GenEvent *& operator<< (const GenEvent *&)`
the same as write_event
- virtual `GenEvent *& operator<< (GenEvent *&)`
the same as write_event

9.31.1 Detailed Description

all input/output classes inherit from **IO_BaseClass** (p. 179)

If you want to write a new IO class, then inherit from this class and re-define `read_event()` and **write_event()** (p. 181)

Definition at line 34 of file `IO_BaseClass.h`.

9.31.2 Constructor & Destructor Documentation

9.31.2.1 virtual HepMC::IO_BaseClass::~~IO_BaseClass () [inline, virtual]

Definition at line 36 of file IO_BaseClass.h.

9.31.3 Member Function Documentation

9.31.3.1 virtual bool HepMC::IO_BaseClass::fill_next_event (GenEvent *) [pure virtual]

fill this **GenEvent** (p. 73)

Implemented in **HepMC::IO_AsciiParticles p.** (classHepMC₁₁*IO_AsciiParticles*_{fd859891c2ac09f8758d081357c17ce} ??)HepMC

the same as write_event

Definition at line 105 of file IO_BaseClass.h.

References write_event().

9.31.3.3 const GenEvent *& HepMC::IO_BaseClass::operator<< (const GenEvent *&) [inline, virtual]

the same as write_event

Definition at line 99 of file IO_BaseClass.h.

References write_event().

9.31.3.4 GenEvent *& HepMC::IO_BaseClass::operator>> (GenEvent *&) [inline, virtual]

the same as read_next_event

Definition at line 94 of file IO_BaseClass.h.

References read_next_event().

9.31.3.5 void HepMC::IO_BaseClass::print (std::ostream & ostr = std::cout) const [inline, virtual]

write output to ostr

Reimplemented in **HepMC::IO_AsciiParticles p.** (classHepMC₁₁*IO_AsciiParticles*_{2c9bec0be07d8b946ff8c27bf2d0636} ??)HepM

do not over-ride

creates a new event and fills it by calling the sister method read_next_event(GenEvent*)

Examples:

example_MyHerwig.cc, example_MyPythia.cc, example_MyPythiaOnlyToHepMC.cc, example_PythiaStreamIO.cc, testHerwigCopies.cc, testMultipleCopies.cc.in, and testPythia-Copies.cc.

Definition at line 74 of file IO_BaseClass.h.

References `fill_next_event()`.

Referenced by `event_selection()`, `main()`, `operator>>()`, `pythia_in()`, `pythia_in_out()`, `pythia_out()`, `pythia_particle_out()`, and `writePythiaStreamIO()`.

9.31.3.7 `virtual void HepMC::IO_BaseClass::write_event (const GenEvent *)` [pure virtual]

write this **GenEvent** (p. 73)


Implemented in **HepMC::IO_AsciiParticles** p. (classHepMC₁₁*IO_AsciiParticles*_{2d45b9474967ec0cdeccece86d5d8c5e} ??)HepMC :

9.32 HepMC::IO_Exception Class Reference

IO exception handling.

```
#include <IO_Exception.h>
```

Inheritance diagram for HepMC::IO_Exception::



Public Types

- **OK**
- **NullEvent**
- **WrongFileType**
- **MissingStartKey**
- **EndOfStream**
- **EndKeyMismatch**
- **MissingEndKey**
- **InvalidData**
- **InputAndOutput**
- **BadOutputStream**
- **BadInputStream**
- **enum ErrorType {**
 OK, NullEvent, WrongFileType, MissingStartKey,
 EndOfStream, EndKeyMismatch, MissingEndKey, InvalidData,
 InputAndOutput, BadOutputStream, BadInputStream }
IO error types.

Public Member Functions

- **IO_Exception (const std::string &msg)**

9.32.1 Detailed Description

IO exception handling.

IO_GenEvent (p. 184), etc. catch the throw and set data members with the error type and message Some of the messages are constructed with transient information (e.g., contents of a bad **GenParticle** (p. 111))

Examples:

testStreamIO.cc.in.

Definition at line 28 of file `IO_Exception.h`.

9.32.2 Member Enumeration Documentation

9.32.2.1 enum HepMC::IO_Exception::ErrorType

IO error types.

Enumerator:

OK
NullEvent
WrongFileType
MissingStartKey
EndOfStream
EndKeyMismatch
MissingEndKey
InvalidData
InputAndOutput
BadOutputStream
BadInputStream

Definition at line 34 of file IO_Exception.h.

9.32.3 Constructor & Destructor Documentation

9.32.3.1 HepMC::IO_Exception::IO_Exception (const std::string & msg) [inline]

Definition at line 30 of file IO_Exception.h.

The documentation for this class was generated from the following file:


- **IO_Exception.h**

9.33 HepMC::IO_GenEvent Class Reference

IO_GenEvent (p. 184) also deals with **HeavyIon** (p. 152) and **PdfInfo** (p. 220).

```
#include <IO_GenEvent.h>
```

Inheritance diagram for HepMC::IO_GenEvent::



Public Member Functions

- **IO_GenEvent** (const std::string &filename="IO_GenEvent.dat", std::ios::openmode mode=std::ios::out)
constructor requiring a file name and std::ios mode
- **IO_GenEvent** (std::istream &)
constructor requiring an input stream
- **IO_GenEvent** (std::ostream &)
constructor requiring an output stream
- **virtual ~IO_GenEvent** ()
- **void write_event** (const GenEvent *evt)
write this event
- **bool fill_next_event** (GenEvent *evt)
get the next event
- **void write_comment** (const std::string comment)
- **int rdstate** () const
check the state of the IO stream
- **void clear** ()
clear the IO stream
- **void print** (std::ostream &ostr=std::cout) const
write to ostr
- **void use_input_units** (Units::MomentumUnit, Units::LengthUnit)
- **void precision** (int)
- **int error_type** () const
integer (enum) associated with read error
- **const std::string & error_message** () const
the read error message string

9.33.1 Detailed Description

IO_GenEvent (p. 184) also deals with **HeavyIon** (p. 152) and **PdfInfo** (p. 220).

event input/output in ascii format for machine reading extended format contains **HeavyIon** (p. 152) and **PdfInfo** (p. 220) classes

Strategy for reading or writing events using iostreams When instantiating with a file name, the mode of file to be created must be specified. Options are: `std::ios::in` open file for input `std::ios::out` open file for output `std::ios::trunc` erase old file when opening (i.e. `ios::out|iostrunc` removes oldfile, and creates a new one for output) `std::ios::app` append output to end of file for the purposes of this class, simultaneous input and output mode (`std::ios::in | std::ios::out`) is not allowed.

Event listings are preceded by the key: "HepMC::IO_GenEvent-START_EVENT_LISTING\n" and terminated by the key: "HepMC::IO_GenEvent-END_EVENT_LISTING\n" **GenParticle** (p. 111) Data tables are preceded by the key: "HepMC::IO_GenEvent-START_PARTICLE_DATA\n" and terminated by the key: "HepMC::IO_GenEvent-END_PARTICLE_DATA\n" Comments are allowed. They need not be preceded by anything, though if a comment is written using `write_comment(const string)` then it will be preceded by "HepMC::IO_GenEvent-COMMENT\n" Each event, vertex, particle, particle data, heavy ion, or pdf info line is preceded by "E ", "V ", "P ", "D ", "H ", "F " respectively. Comments may appear anywhere in the file – so long as they do not contain any of the start/stop keys.

Examples:

`example_EventSelection.cc`, `example_MyHerwig.cc`, `example_MyPythia.cc`, `example_Using-Iterators.cc`, `testFlow.cc`, `testHepMC.cc.in`, `testHepMCIteration.cc.in`, `testMass.cc.in`, `test-MultipleCopies.cc.in`, and `testStreamIO.cc.in`.

Definition at line 63 of file `IO_GenEvent.h`.

9.33.2 Constructor & Destructor Documentation

9.33.2.1 HepMC::IO_GenEvent::IO_GenEvent (const std::string & filename = "IO_GenEvent.dat", std::ios::openmode mode = std::ios::out)

constructor requiring a file name and `std::ios` mode

Definition at line 16 of file `IO_GenEvent.cc`.

References `HepMC::detail::establish_input_stream_info()`, `HepMC::detail::establish_output_stream_info()`, and `HepMC::IO_Exception::InputAndOutput`.

9.33.2.2 HepMC::IO_GenEvent::IO_GenEvent (std::istream &)

constructor requiring an input stream

Definition at line 50 of file `IO_GenEvent.cc`.

References `HepMC::detail::establish_input_stream_info()`.

9.33.2.3 HepMC::IO_GenEvent::IO_GenEvent (std::ostream &)

constructor requiring an output stream

Definition at line 61 of file `IO_GenEvent.cc`.

References `HepMC::detail::establish_output_stream_info()`.

9.33.2.4 HepMC::IO_GenEvent::~~IO_GenEvent () [virtual]

Definition at line 72 of file IO_GenEvent.cc.

References HepMC::write_HepMC_IO_block_end().

9.33.3 Member Function Documentation

9.33.3.1 void HepMC::IO_GenEvent::clear () [inline]

clear the IO stream

Definition at line 133 of file IO_GenEvent.h.

9.33.3.2 const std::string & HepMC::IO_GenEvent::error_message () const [inline]

the read error message string

Definition at line 145 of file IO_GenEvent.h.

9.33.3.3 int HepMC::IO_GenEvent::error_type () const [inline]

integer (enum) associated with read error

Definition at line 141 of file IO_GenEvent.h.

9.33.3.4 bool HepMC::IO_GenEvent::fill_next_event (GenEvent * evt) [virtual]

get the next event

Implements **HepMC::IO_BaseClass p.** (classHepMC₁₁*IO_BaseClass_f1df fb95a44d521af510f6431a30f942* ??)

Definition at line 109 of file IO_GenEvent.cc.

References HepMC::GenEvent::clear(), HepMC::IO_Exception::InvalidData, HepMC::GenEvent::is_valid(), HepMC::IO_Exception::NullEvent, HepMC::IO_Exception::OK, and HepMC::IO_Exception::WrongFileType.

9.33.3.5 void HepMC::IO_GenEvent::precision (int)

set output precision The default precision is 16.

Definition at line 96 of file IO_GenEvent.cc.

9.33.3.6 void HepMC::IO_GenEvent::print (std::ostream & ostr = std::cout) const [virtual]

write to ostr

Reimplemented from **HepMC::IO_BaseClass p.** (classHepMC₁₁*IO_BaseClass_a23f5de9c6bb10931dcacdeb7677413* ??)

Definition at line 86 of file IO_GenEvent.cc.

9.33.3.7 int HepMC::IO_GenEvent::rdstate () const [inline]

check the state of the IO stream

Definition at line 123 of file IO_GenEvent.h.

Referenced by main().

9.33.3.8 void HepMC::IO_GenEvent::use_input_units (Units::MomentumUnit, Units::LengthUnit)

needed when reading a file without units if those units are different than the declared default units (e.g., the default units are MeV, but the file was written with GeV) This method is not necessary if the units are written in the file

Definition at line 79 of file IO_GenEvent.cc.

References HepMC::set_input_units().

9.33.3.9 void HepMC::IO_GenEvent::write_comment (const std::string comment)

insert a comment directly into the output file — normally you only want to do this at the beginning or end of the file. All comments are preceded with "HepMC::IO_GenEvent-COMMENT\n"

Definition at line 162 of file IO_GenEvent.cc.

References HepMC::write_HepMC_IO_block_end(), and HepMC::IO_Exception::WrongFileType.

9.33.3.10 void HepMC::IO_GenEvent::write_event (const GenEvent * evt) [virtual]

write this event

Writes evt to output stream. It does NOT delete the event after writing.

Implements **HepMC::IO_BaseClass** **p.** (classHepMC₁₁ *IO_BaseClass*_{7929dfd8412207c7904f29652810c1f4} **??**)

Definition at line 143 of file IO_GenEvent.cc.

References HepMC::write_HepMC_IO_block_begin(), and HepMC::IO_Exception::WrongFileType.

The documentation for this class was generated from the following files:


- **IO_GenEvent.h**
- **IO_GenEvent.cc**

9.34 HepMC::IO_HEPEVT Class Reference

HEPEVT IO class.

```
#include <IO_HEPEVT.h>
```

Inheritance diagram for HepMC::IO_HEPEVT::



Public Member Functions

- **IO_HEPEVT ()**
- **virtual ~IO_HEPEVT ()**
- **bool fill_next_event (GenEvent *)**
fill this GenEvent (p. 73)
- **void write_event (const GenEvent *)**
write this GenEvent (p. 73)
- **void print (std::ostream &ostr=std::cout) const**
write output to ostr
- **bool trust_both_mothers_and_daughters () const**
default is false
- **bool trust_mothers_before_daughters () const**
default is true
- **bool print_inconsistency_errors () const**
default is true
- **bool trust_beam_particles () const**
default is true
- **void set_trust_mothers_before_daughters (bool b=true)**
define mother daughter trust rules
- **void set_trust_both_mothers_and_daughters (bool b=false)**
define mother daughter trust rules
- **void set_print_inconsistency_errors (bool b=true)**
- **void set_trust_beam_particles (bool b=true)**
declare whether or not beam particles exist

Protected Member Functions

- **GenParticle * build_particle (int index)**
create a GenParticle (p. 111)
- **void build_production_vertex (int i, std::vector< HepMC::GenParticle * > &hepevt_particle, GenEvent *evt)**
create a production vertex
- **void build_end_vertex (int i, std::vector< HepMC::GenParticle * > &hepevt_particle, GenEvent *evt)**
create an end vertex
- **int find_in_map (const std::map< HepMC::GenParticle *, int > &m, GenParticle *p) const**
find this particle in the particle map

9.34.1 Detailed Description

HEPEVT IO class.

IO class for reading the standard HEPEVT common block.

Examples:

example_MyPythia.cc, example_MyPythiaOnlyToHepMC.cc, example_PythiaStreamIO.cc, and testPythiaCopies.cc.

Definition at line 39 of file IO_HEPEVT.h.

9.34.2 Constructor & Destructor Documentation

9.34.2.1 HepMC::IO_HEPEVT::IO_HEPEVT ()

Definition at line 12 of file IO_HEPEVT.cc.

9.34.2.2 HepMC::IO_HEPEVT::~~IO_HEPEVT () [virtual]

Definition at line 18 of file IO_HEPEVT.cc.

9.34.3 Member Function Documentation

9.34.3.1 void HepMC::IO_HEPEVT::build_end_vertex (int i, std::vector< HepMC::GenParticle * > &hepevt_particle, GenEvent * evt) [protected]

create an end vertex

for particle in HEPEVT with index i, build an end vertex if appropriate, and add that vertex to the event

Definition at line 257 of file IO_HEPEVT.cc.

References HepMC::GenVertex::add_particle_in(), HepMC::GenVertex::add_particle_out(), HepMC::GenEvent::add_vertex(), HepMC::HEPEVT_Wrapper::event_number(), HepMC::HEPEVT_Wrapper::first_child(), HepMC::HEPEVT_Wrapper::last_child(), HepMC::HEPEVT_Wrapper::number_children(), p, HepMC::GenVertex::position(), HepMC::GenVertex::set_position(), HepMC::HEPEVT_Wrapper::t(), HepMC::HEPEVT_Wrapper::x(), HepMC::HEPEVT_Wrapper::y(), and HepMC::HEPEVT_Wrapper::z().

Referenced by fill_next_event().

9.34.3.2 GenParticle * HepMC::IO_HEPEVT::build_particle (int *index*) [protected]

create a **GenParticle** (p. 111)

Builds a particle object corresponding to index in HEPEVT

Definition at line 325 of file IO_HEPEVT.cc.

References HepMC::HEPEVT_Wrapper::e(), HepMC::HEPEVT_Wrapper::id(), HepMC::HEPEVT_Wrapper::m(), p, HepMC::HEPEVT_Wrapper::px(), HepMC::HEPEVT_Wrapper::py(), HepMC::HEPEVT_Wrapper::pz(), and HepMC::HEPEVT_Wrapper::status().

Referenced by fill_next_event().

9.34.3.3 void HepMC::IO_HEPEVT::build_production_vertex (int *i*, std::vector< HepMC::GenParticle * > & *hepevt_particle*, GenEvent * *evt*) [protected]

create a production vertex

for particle in HEPEVT with index i, build a production vertex if appropriate, and add that vertex to the event

Definition at line 191 of file IO_HEPEVT.cc.

References HepMC::GenVertex::add_particle_in(), HepMC::GenVertex::add_particle_out(), HepMC::GenEvent::add_vertex(), HepMC::HEPEVT_Wrapper::event_number(), HepMC::HEPEVT_Wrapper::first_parent(), HepMC::HEPEVT_Wrapper::last_parent(), HepMC::HEPEVT_Wrapper::number_parents(), p, HepMC::GenVertex::position(), HepMC::GenVertex::set_position(), HepMC::HEPEVT_Wrapper::t(), HepMC::HEPEVT_Wrapper::x(), HepMC::HEPEVT_Wrapper::y(), and HepMC::HEPEVT_Wrapper::z().

Referenced by fill_next_event().

9.34.3.4 bool HepMC::IO_HEPEVT::fill_next_event (GenEvent *) [virtual]

fill this **GenEvent** (p. 73)

Implements HepMC::IO_BaseClass p. (classHepMC₁₁IO_{BaseClass}1df fb95a44d521af510f6431a30f942 ??)

Definition at line 31 of file IO_HEPEVT.cc.

References HepMC::GenVertex::add_particle_out(), HepMC::GenEvent::add_vertex(), build_end_vertex(), build_particle(), build_production_vertex(), HepMC::HEPEVT_Wrapper::event_number(), HepMC::HEPEVT_Wrapper::number_entries(), HepMC::GenEvent::set_beam_particles(), HepMC::GenEvent::set_event_number(), and trust_beam_particles().

9.34.3.5 `int HepMC::IO_HEPEVT::find_in_map (const std::map< HepMC::GenParticle *, int > & m, GenParticle * p) const` [protected]

find this particle in the particle map

Definition at line 340 of file IO_HEPEVT.cc.

References p.

Referenced by write_event().

9.34.3.6 `void HepMC::IO_HEPEVT::print (std::ostream & ostr = std::cout) const` [virtual]

write output to ostr

Reimplemented from **HepMC::IO_BaseClass** p. (classHepMC₁₁IO_{BaseClass}_{8a23f5de9c6bb10931dcacdeb7677413} ??)

Definition at line 20 of file IO_HEPEVT.cc.

9.34.3.7 `bool HepMC::IO_HEPEVT::print_inconsistency_errors () const` [inline]

default is true

Definition at line 120 of file IO_HEPEVT.h.

9.34.3.8 `void HepMC::IO_HEPEVT::set_print_inconsistency_errors (bool b = true)` [inline]

Since HEPEVT has bi-directional pointers, it is possible that the mother/daughter pointers are inconsistent (though physically speaking this should never happen). In practise it happens often. When a conflict occurs (i.e. when mother/daughter pointers are in disagreement, where an empty (0) pointer is not considered a disagreement) an error is printed. These errors can be turned off with: `myio_hepevt.set_print_inconsistency_errors(0)`; but it is **STRONGLY** recommended that you print the HEPEVT common and understand the inconsistency **BEFORE** you turn off the errors. The messages are there for a reason [remember, there is no message printed when the information is missing, ... only when is it inconsistent. User beware.] You can inspect the HEPEVT common block for inconsistencies with **HEPEVT_Wrapper::check_hepevt_consistency()** (p. 163)

There is a switch controlling whether the mother pointers or the daughters are to be trusted. For example, in Pythia the mother information is always correctly included, but the daughter information is often left unfilled: in this case we want to trust the mother pointers and not necessarily the daughters. [THIS IS THE DEFAULT]. Unfortunately the reverse happens for the stdhep(2001) translation of Isajet, so we need an option to toggle the choices.

Definition at line 129 of file IO_HEPEVT.h.

9.34.3.9 `void HepMC::IO_HEPEVT::set_trust_beam_particles (bool b = true)` [inline]

declare whether or not beam particles exist

Definition at line 135 of file IO_HEPEVT.h.

9.34.3.10 `void HepMC::IO_HEPEVT::set_trust_both_mothers_and_daughters (bool b = false)`
`[inline]`

define mother daughter trust rules

Definition at line 123 of file IO_HEPEVT.h.

9.34.3.11 `void HepMC::IO_HEPEVT::set_trust_mothers_before_daughters (bool b = true)`
`[inline]`

define mother daughter trust rules

Definition at line 126 of file IO_HEPEVT.h.

9.34.3.12 `bool HepMC::IO_HEPEVT::trust_beam_particles () const` `[inline]`

default is true

Definition at line 132 of file IO_HEPEVT.h.

Referenced by `fill_next_event()`.

9.34.3.13 `bool HepMC::IO_HEPEVT::trust_both_mothers_and_daughters () const` `[inline]`

default is false

Definition at line 114 of file IO_HEPEVT.h.

9.34.3.14 `bool HepMC::IO_HEPEVT::trust_mothers_before_daughters () const` `[inline]`

default is true

Definition at line 117 of file IO_HEPEVT.h.

9.34.3.15 `void HepMC::IO_HEPEVT::write_event (const GenEvent *)` `[virtual]`

write this **GenEvent** (p. 73)

Implements **HepMC::IO_BaseClass** **p.** (classHepMC11IO_BaseClass7929dfd8412207c7904f29652810c1f4??)

Definition at line 110 of file IO_HEPEVT.cc.

References `HepMC::FourVector::e()`, `HepMC::GenEvent::event_number()`, `find_in_map()`, `HepMC::HEPEVT_Wrapper::max_number_entries()`, `p`, `HepMC::FourVector::px()`, `HepMC::FourVector::py()`, `HepMC::FourVector::pz()`, `HepMC::HEPEVT_Wrapper::set_children()`, `HepMC::HEPEVT_Wrapper::set_event_number()`, `HepMC::HEPEVT_Wrapper::set_id()`, `HepMC::HEPEVT_Wrapper::set_mass()`, `HepMC::HEPEVT_Wrapper::set_momentum()`, `HepMC::HEPEVT_Wrapper::set_number_entries()`, `HepMC::HEPEVT_Wrapper::set_parents()`, `HepMC::HEPEVT_Wrapper::set_position()`, `HepMC::HEPEVT_Wrapper::set_status()`, `v`, `HepMC::GenEvent::vertices_begin()`, and `HepMC::GenEvent::vertices_end()`.

The documentation for this class was generated from the following files:


- **IO_HEPEVT.h**
- **IO_HEPEVT.cc**

9.35 HepMC::IO_HERWIG Class Reference

IO_HERWIG (p. 193) is used to get Herwig information.

```
#include <IO_HERWIG.h>
```

Inheritance diagram for HepMC::IO_HERWIG::



Public Member Functions

- **IO_HERWIG ()**
- **virtual ~IO_HERWIG ()**
- **bool fill_next_event (GenEvent *)**
get the next event
- **void print (std::ostream &ostr=std::cout) const**
write to ostr
- **double interfaces_to_version_number () const**
this information is dubious
- **bool print_inconsistency_errors () const**
default is true
- **void set_print_inconsistency_errors (bool b=true)**
decide whether or not to print inconsistency errors
- **bool no_gaps_in_barcodes () const**
ask how to deal with extra non-physical pseudo particles
- **void set_no_gaps_in_barcodes (bool a)**

Protected Member Functions

- **bool trust_both_mothers_and_daughters () const**
default is true
- **bool trust_mothers_before_daughters () const**
default is false
- **void set_trust_mothers_before_daughters (bool b=true)**
define mother daughter trust rules
- **void set_trust_both_mothers_and_daughters (bool b=false)**

define mother daughter trust rules

- **GenParticle * build_particle (int index)**
make a particle
- **void build_production_vertex (int i, std::vector< GenParticle * > &hepevt_particle, GenEvent *evt)**
make a production vertex
- **void build_end_vertex (int i, std::vector< GenParticle * > &hepevt_particle, GenEvent *evt)**
make a decay vertex
- **int find_in_map (const std::map< GenParticle *, int > &m, GenParticle *p) const**
find this particle in the map
- **void repair_hepevt () const**
make the HERWIG HEPEVT common block look like the standard
- **void remove_gaps_in_hepevt () const**
deal with artifacts of repairing HEPEVT
- **void zero_hepevt_entry (int i) const**
zero out a HEPEVT pseudo particle
- **int translate_herwig_to_pdg_id (int i) const**
translate particle ID

9.35.1 Detailed Description

IO_HERWIG (p. 193) is used to get Herwig information.

IO class for reading the HEPEVT common block from the Herwig monte carlo program.

Examples:

example_MyHerwig.cc, and testHerwigCopies.cc.

Definition at line 56 of file IO_HERWIG.h.

9.35.2 Constructor & Destructor Documentation

9.35.2.1 HepMC::IO_HERWIG::IO_HERWIG ()

Definition at line 12 of file IO_HERWIG.cc.

9.35.2.2 HepMC::IO_HERWIG::~~IO_HERWIG () [virtual]

Definition at line 83 of file IO_HERWIG.cc.

9.35.3 Member Function Documentation

9.35.3.1 void HepMC::IO_HERWIG::build_end_vertex (int *i*, std::vector< GenParticle * > & *hepevt_particle*, GenEvent * *evt*) [protected]

make a decay vertex

for particle in HEPEVT with index *i*, build an end vertex if appropriate, and add that vertex to the event

Definition at line 304 of file IO_HERWIG.cc.

References HepMC::GenVertex::add_particle_in(), HepMC::GenVertex::add_particle_out(), HepMC::GenEvent::add_vertex(), HepMC::HEPEVT_Wrapper::event_number(), HepMC::HEPEVT_Wrapper::first_child(), HepMC::HEPEVT_Wrapper::last_child(), HepMC::HEPEVT_Wrapper::number_children(), *p*, HepMC::GenVertex::position(), HepMC::GenVertex::set_position(), HepMC::HEPEVT_Wrapper::t(), HepMC::HEPEVT_Wrapper::x(), HepMC::HEPEVT_Wrapper::y(), and HepMC::HEPEVT_Wrapper::z().

Referenced by fill_next_event().

9.35.3.2 GenParticle * HepMC::IO_HERWIG::build_particle (int *index*) [protected]

make a particle

Builds a particle object corresponding to index in HEPEVT

Definition at line 372 of file IO_HERWIG.cc.

References HepMC::HEPEVT_Wrapper::e(), HepMC::HEPEVT_Wrapper::id(), HepMC::HEPEVT_Wrapper::m(), *p*, HepMC::HEPEVT_Wrapper::px(), HepMC::HEPEVT_Wrapper::py(), HepMC::HEPEVT_Wrapper::pz(), and HepMC::HEPEVT_Wrapper::status().

Referenced by fill_next_event().

9.35.3.3 void HepMC::IO_HERWIG::build_production_vertex (int *i*, std::vector< GenParticle * > & *hepevt_particle*, GenEvent * *evt*) [protected]

make a production vertex

for particle in HEPEVT with index *i*, build a production vertex if appropriate, and add that vertex to the event

Definition at line 231 of file IO_HERWIG.cc.

References HepMC::GenVertex::add_particle_in(), HepMC::GenVertex::add_particle_out(), HepMC::GenEvent::add_vertex(), HepMC::HEPEVT_Wrapper::event_number(), HepMC::HEPEVT_Wrapper::first_parent(), HepMC::HEPEVT_Wrapper::last_parent(), HepMC::HEPEVT_Wrapper::number_parents(), *p*, HepMC::GenVertex::position(), HepMC::GenVertex::print(), HepMC::GenVertex::set_position(), HepMC::HEPEVT_Wrapper::t(), HepMC::HEPEVT_Wrapper::x(), HepMC::HEPEVT_Wrapper::y(), and HepMC::HEPEVT_Wrapper::z().

Referenced by fill_next_event().

9.35.3.4 bool HepMC::IO_HERWIG::fill_next_event (GenEvent *) [virtual]

get the next event

read one event from the Herwig HEPEVT common block and fill **GenEvent** (p.73) return T/F =success/failure

sufficient to do one or the other.

Implements **HepMC::IO_BaseClass** **p.** (classHepMC₁₁*IO_BaseClass*_{1dfbf95a44d521af510f6431a30f942} **??**)

Definition at line 96 of file IO_HERWIG.cc.

References HepMC::GenVertex::add_particle_in(), HepMC::GenVertex::add_particle_out(), HepMC::GenEvent::add_vertex(), build_end_vertex(), build_particle(), build_production_vertex(), HepMC::HEPEVT_Wrapper::event_number(), HepMC::HEPEVT_Wrapper::first_parent(), HepMC::HEPEVT_Wrapper::number_entries(), repair_hepevt(), HepMC::GenEvent::set_beam_particles(), HepMC::GenEvent::set_event_number(), HepMC::GenEvent::set_signal_process_vertex(), and HepMC::HEPEVT_Wrapper::status().

9.35.3.5 int HepMC::IO_HERWIG::find_in_map (const std::map< GenParticle *, int > & m, GenParticle * p) const [protected]

find this particle in the map

Definition at line 387 of file IO_HERWIG.cc.

References p.

9.35.3.6 double HepMC::IO_HERWIG::interfaces_to_version_number () const [inline]

this information is dubious

Definition at line 65 of file IO_HERWIG.h.

9.35.3.7 bool HepMC::IO_HERWIG::no_gaps_in_barcodes () const [inline]

ask how to deal with extra non-physical pseudo particles

Definition at line 74 of file IO_HERWIG.h.

9.35.3.8 void HepMC::IO_HERWIG::print (std::ostream & ostr = std::cout) const [virtual]

write to ostr

Reimplemented from **HepMC::IO_BaseClass** **p.** (classHepMC₁₁*IO_BaseClass*_{8a23f5de9c6bb10931dcacdeb7677413} **??**)

Definition at line 85 of file IO_HERWIG.cc.

9.35.3.9 bool HepMC::IO_HERWIG::print_inconsistency_errors () const [inline]

default is true

Definition at line 145 of file IO_HERWIG.h.

9.35.3.10 void HepMC::IO_HERWIG::remove_gaps_in_hepevt () const [protected]

deal with artifacts of repairing HEPEVT

in this scenario, we do not allow there to be zero-ed entries in the HEPEVT common block, and so be reshuffle the common block, removing the zero-ed entries as we go and making sure we keep the mother/daughter relationships appropriate

Definition at line 682 of file IO_HERWIG.cc.

References HepMC::HEPEVT_Wrapper::e(), HepMC::HEPEVT_Wrapper::first_child(), HepMC::HEPEVT_Wrapper::first_parent(), HepMC::HEPEVT_Wrapper::id(), HepMC::HEPEVT_Wrapper::last_child(), HepMC::HEPEVT_Wrapper::last_parent(), HepMC::HEPEVT_Wrapper::m(), HepMC::HEPEVT_Wrapper::number_entries(), HepMC::HEPEVT_Wrapper::px(), HepMC::HEPEVT_Wrapper::py(), HepMC::HEPEVT_Wrapper::pz(), HepMC::HEPEVT_Wrapper::set_children(), HepMC::HEPEVT_Wrapper::set_id(), HepMC::HEPEVT_Wrapper::set_mass(), HepMC::HEPEVT_Wrapper::set_momentum(), HepMC::HEPEVT_Wrapper::set_number_entries(), HepMC::HEPEVT_Wrapper::set_parents(), HepMC::HEPEVT_Wrapper::set_position(), HepMC::HEPEVT_Wrapper::set_status(), HepMC::HEPEVT_Wrapper::status(), HepMC::HEPEVT_Wrapper::t(), HepMC::HEPEVT_Wrapper::x(), HepMC::HEPEVT_Wrapper::y(), and HepMC::HEPEVT_Wrapper::z().

Referenced by repair_hepevt().

9.35.3.11 void HepMC::IO_HERWIG::repair_hepevt () const [protected]

make the HERWIG HEPEVT common block look like the standard

This routine takes the HEPEVT common block as used in HERWIG, and converts it into the HEPEVT common block in the standard format

This means it:

- removes the color structure, which herwig overloads into the mother/daughter fields
- zeros extra entries for hard subprocess, etc.

Special HERWIG status codes 101,102 colliding beam particles 103 beam-beam collision CMS vector 120 hard subprocess CMS vector 121,122 hard subprocess colliding partons 123-129 hard subprocess outgoing particles 141-149 (ID=94) mirror image of hard subprocess particles 100 (ID=0) cone)

Special HERWIG particle id's 91 clusters 94 jets 0 others with no pdg code

Definition at line 394 of file IO_HERWIG.cc.

References HepMC::HEPEVT_Wrapper::first_child(), HepMC::HEPEVT_Wrapper::first_parent(), HepMC::HEPEVT_Wrapper::id(), HepMC::HEPEVT_Wrapper::last_child(), HepMC::HEPEVT_Wrapper::last_parent(), HepMC::HEPEVT_Wrapper::number_entries(), remove_gaps_in_hepevt(), HepMC::HEPEVT_Wrapper::set_children(), HepMC::HEPEVT_Wrapper::set_id(), HepMC::HEPEVT_Wrapper::set_parents(), HepMC::HEPEVT_Wrapper::status(), translate_herwig_to_pdg_id(), and zero_hepevt_entry().

Referenced by fill_next_event().

9.35.3.12 void HepMC::IO_HERWIG::set_no_gaps_in_barcodes (bool a) [inline]

The HERWIG HEPEVT common block has some EXTRA non-physical ENTRIES (such as CMS frame, HARD subprocess, and CONE). These are removed by **IO_HERWIG** (p. 193). Thus the **HepMC** (p. 23) event will **APPEAR** to have fewer particles in it that herwig did. There is a switch `m_no_gaps_in_barcodes`. For true - then the extra particles are removed from HEPEVT, with the result that the **HepMC** (p. 23) barcodes will be sequential, with no gaps. false - the barcodes will correspond directly to the HEPEVT index, but there will be gaps ... ie some barcodes will be unassigned. this switch requested by I Hinchliffe, October 31, 2002

Definition at line 87 of file IO_HERWIG.h.

9.35.3.13 `void HepMC::IO_HERWIG::set_print_inconsistency_errors (bool b = true)`
`[inline]`

decide whether or not to print inconsistency errors

Definition at line 154 of file IO_HERWIG.h.

9.35.3.14 `void HepMC::IO_HERWIG::set_trust_both_mothers_and_daughters (bool b = false)`
`[inline, protected]`

define mother daughter trust rules

Definition at line 148 of file IO_HERWIG.h.

9.35.3.15 `void HepMC::IO_HERWIG::set_trust_mothers_before_daughters (bool b = true)`
`[inline, protected]`

define mother daughter trust rules

Definition at line 151 of file IO_HERWIG.h.

9.35.3.16 `int HepMC::IO_HERWIG::translate_herwig_to_pdg_id (int i) const` `[protected]`

translate particle ID

This routine is copied from Lynn Garren's stdhep 5.01. see
<http://cepa.fnal.gov/psm/stdhep/>

Definition at line 753 of file IO_HERWIG.cc.

Referenced by `repair_hepevt()`.

9.35.3.17 `bool HepMC::IO_HERWIG::trust_both_mothers_and_daughters () const` `[inline, protected]`

default is true

Definition at line 139 of file IO_HERWIG.h.

9.35.3.18 `bool HepMC::IO_HERWIG::trust_mothers_before_daughters () const` `[inline, protected]`

default is false

Definition at line 142 of file IO_HERWIG.h.

9.35.3.19 `void HepMC::IO_HERWIG::zero_hepevt_entry (int i) const` `[protected]`

zero out a HEPEVT pseudo particle

Definition at line 742 of file IO_HERWIG.cc.

References HepMC::HEPEVT_Wrapper::max_number_entries(), HepMC::HEPEVT_Wrapper::set_children(), HepMC::HEPEVT_Wrapper::set_id(), HepMC::HEPEVT_Wrapper::set_mass(), HepMC::HEPEVT_Wrapper::set_momentum(), HepMC::HEPEVT_Wrapper::set_parents(), HepMC::HEPEVT_Wrapper::set_position(), and HepMC::HEPEVT_Wrapper::set_status().

Referenced by repair_hepevt().

The documentation for this class was generated from the following files:

- **IO_HERWIG.h**
- **IO_HERWIG.cc**

9.36 HepMC::detail::is_arithmetic< T > Struct Template Reference

undefined and therefore non-arithmetic

```
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const value = false

9.36.1 Detailed Description

```
template<class T> struct HepMC::detail::is_arithmetic< T >
```

undefined and therefore non-arithmetic

Definition at line 22 of file is_arithmetic.h.

9.36.2 Member Data Documentation

9.36.2.1 template<class T> bool const HepMC::detail::is_arithmetic< T >::value = false
[static]

Definition at line 24 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- is_arithmetic.h

9.37 HepMC::detail::is_arithmetic< char > Struct Template Reference

```
character is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.37.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< char >

```
character is arithmetic
Definition at line 29 of file is_arithmetic.h.
```

9.37.2 Member Data Documentation

9.37.2.1 bool const HepMC::detail::is_arithmetic< char >::value = true [static]

Definition at line 30 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.38 HepMC::detail::is_arithmetic< double > Struct Template Reference

```
double is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.38.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< double >

```
double is arithmetic
```

Definition at line 79 of file is_arithmetic.h.

9.38.2 Member Data Documentation

9.38.2.1 bool const HepMC::detail::is_arithmetic< double >::value = true [static]

Definition at line 80 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.39 HepMC::detail::is_arithmetic< float > Struct Template Reference

```
float is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.39.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< float >

float is arithmetic

Definition at line 74 of file is_arithmetic.h.

9.39.2 Member Data Documentation

9.39.2.1 bool const HepMC::detail::is_arithmetic< float >::value = true [static]

Definition at line 75 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.40 HepMC::detail::is_arithmetic< int > Struct Template Reference

```
int is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.40.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< int >

```
int is arithmetic
```

Definition at line 54 of file is_arithmetic.h.

9.40.2 Member Data Documentation

9.40.2.1 bool const HepMC::detail::is_arithmetic< int >::value = true [static]

Definition at line 55 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.41 HepMC::detail::is_arithmetic< long > Struct Template Reference

```
long is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.41.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< long >

```
long is arithmetic
```

Definition at line 64 of file is_arithmetic.h.

9.41.2 Member Data Documentation

9.41.2.1 bool const HepMC::detail::is_arithmetic< long >::value = true [static]

Definition at line 65 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.42 HepMC::detail::is_arithmetic< long double > Struct Template Reference

```
long double is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.42.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< long double >

```
long double is arithmetic
Definition at line 84 of file is_arithmetic.h.
```

9.42.2 Member Data Documentation

9.42.2.1 bool const HepMC::detail::is_arithmetic< long double >::value = true [static]

Definition at line 85 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.43 HepMC::detail::is_arithmetic< short > Struct Template Reference

```
short is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.43.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< short >

short is arithmetic

Definition at line 44 of file is_arithmetic.h.

9.43.2 Member Data Documentation

9.43.2.1 bool const HepMC::detail::is_arithmetic< short >::value = true [static]

Definition at line 45 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.44 HepMC::detail::is_arithmetic< signed char > Struct Template Reference

```
signed character is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.44.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< signed char >

```
signed character is arithmetic
Definition at line 39 of file is_arithmetic.h.
```

9.44.2 Member Data Documentation

9.44.2.1 bool const HepMC::detail::is_arithmetic< signed char >::value = true [static]

Definition at line 40 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.45 HepMC::detail::is_arithmetic< unsigned char > Struct Template Reference

```
unsigned character is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.45.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< unsigned char >

```
unsigned character is arithmetic
Definition at line 34 of file is_arithmetic.h.
```

9.45.2 Member Data Documentation

9.45.2.1 bool const HepMC::detail::is_arithmetic< unsigned char >::value = true [static]

Definition at line 35 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.46 HepMC::detail::is_arithmetic< unsigned int > Struct Template Reference

```
unsigned int is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.46.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< unsigned int >

```
unsigned int is arithmetic
Definition at line 59 of file is_arithmetic.h.
```

9.46.2 Member Data Documentation

9.46.2.1 bool const HepMC::detail::is_arithmetic< unsigned int >::value = true [static]

Definition at line 60 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.47 HepMC::detail::is_arithmetic< unsigned long > Struct Template Reference

```
unsigned long is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.47.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< unsigned long >

```
unsigned long is arithmetic
```

Definition at line 69 of file is_arithmetic.h.

9.47.2 Member Data Documentation

9.47.2.1 bool const HepMC::detail::is_arithmetic< unsigned long >::value = true [static]

Definition at line 70 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.48 HepMC::detail::is_arithmetic< unsigned short > Struct Template Reference

```
unsigned short is arithmetic
#include <is_arithmetic.h>
```

Static Public Attributes

- static bool const **value = true**

9.48.1 Detailed Description

template<> struct HepMC::detail::is_arithmetic< unsigned short >

```
unsigned short is arithmetic
```

Definition at line 49 of file is_arithmetic.h.

9.48.2 Member Data Documentation

9.48.2.1 bool const HepMC::detail::is_arithmetic< unsigned short >::value = true [static]

Definition at line 50 of file is_arithmetic.h.

The documentation for this struct was generated from the following file:

- **is_arithmetic.h**

9.49 IsEventGood Class Reference

example class

Public Member Functions

- **bool operator() (const HepMC::GenEvent *evt)**
check this event for goodness

9.49.1 Detailed Description

example class

event selection predicate. returns true if the event contains a photon with $p_T > 50$ GeV

Examples:

example_EventSelection.cc.

Definition at line 20 of file example_EventSelection.cc.

9.49.2 Member Function Documentation

9.49.2.1 bool IsEventGood::operator() (const HepMC::GenEvent * evt) [inline]

check this event for goodness

Examples:

example_EventSelection.cc.

Definition at line 23 of file example_EventSelection.cc.

References `p`, `HepMC::GenEvent::particles_begin()`, and `HepMC::GenEvent::particles_end()`.

The documentation for this class was generated from the following file:

- **example_EventSelection.cc**

9.50 IsFinalState Class Reference

```
#include <testHepMCIteration.h>
```

Public Member Functions

- **bool operator() (const HepMC::GenParticle *p)**
returns true if the GenParticle does not decay

9.50.1 Detailed Description

this predicate returns true if the input has no decay vertex

Examples:

testHepMCIteration.cc.in.

Definition at line 24 of file testHepMCIteration.h.

9.50.2 Member Function Documentation

9.50.2.1 bool IsFinalState::operator() (const HepMC::GenParticle *p) [inline]

returns true if the GenParticle does not decay

Definition at line 27 of file testHepMCIteration.h.

References p.

The documentation for this class was generated from the following file:

- **testHepMCIteration.h**

9.51 IsGoodEvent Class Reference

used in the tests

```
#include <IsGoodEvent.h>
```

Public Member Functions

- `bool operator() (const HepMC::GenEvent *evt)`

9.51.1 Detailed Description

used in the tests

event selection predicate. returns true if the event contains a photon with $p_T > 50$ GeV

Examples:

`testHepMC.cc.in`, `testHepMCIteration.cc.in`, `testMass.cc.in`, `testMultipleCopies.cc.in`, and `test-StreamIO.cc.in`.

Definition at line 14 of file `IsGoodEvent.h`.

9.51.2 Member Function Documentation

9.51.2.1 `bool IsGoodEvent::operator() (const HepMC::GenEvent * evt)` [inline]

Definition at line 16 of file `IsGoodEvent.h`.

References `p`, `HepMC::GenEvent::particles_begin()`, and `HepMC::GenEvent::particles_end()`.

The documentation for this class was generated from the following file:

- `IsGoodEvent.h`

9.52 IsGoodEventMyPythia Class Reference

example class

Public Member Functions

- **bool operator() (const HepMC::GenEvent *evt)**
returns true if event is "good"

9.52.1 Detailed Description

example class

event selection predicate. returns true if the event contains a photon with $p_T > 25$ GeV

Examples:

example_MyPythia.cc.

Definition at line 61 of file example_MyPythia.cc.

9.52.2 Member Function Documentation

9.52.2.1 bool IsGoodEventMyPythia::operator() (const HepMC::GenEvent * evt) [inline]

returns true if event is "good"

Examples:

example_MyPythia.cc.

Definition at line 64 of file example_MyPythia.cc.

References `p`, `HepMC::GenEvent::particles_begin()`, and `HepMC::GenEvent::particles_end()`.

The documentation for this class was generated from the following file:

- **example_MyPythia.cc**

9.53 IsPhoton Class Reference

example class

Public Member Functions

- **bool operator() (const HepMC::GenParticle *p)**
returns true if the GenParticle is a photon with more than 10 GeV transverse momentum

9.53.1 Detailed Description

example class

this predicate returns true if the input particle is a photon in the central region ($\eta < 2.5$) with $p_T > 10$ GeV

Examples:

example_UsingIterators.cc.

Definition at line 20 of file example_UsingIterators.cc.

9.53.2 Member Function Documentation

9.53.2.1 bool IsPhoton::operator() (const HepMC::GenParticle *p) [inline]

returns true if the GenParticle is a photon with more than 10 GeV transverse momentum

Examples:

example_UsingIterators.cc.

Definition at line 23 of file example_UsingIterators.cc.

References p.

The documentation for this class was generated from the following file:

- **example_UsingIterators.cc**

9.54 IsStateFinal Class Reference

example class

Public Member Functions

- **bool operator() (const HepMC::GenParticle *p)**
returns true if the GenParticle does not decay

9.54.1 Detailed Description

example class

this predicate returns true if the input has no decay vertex

Examples:

example_UsingIterators.cc.

Definition at line 47 of file example_UsingIterators.cc.

9.54.2 Member Function Documentation

9.54.2.1 bool IsStateFinal::operator() (const HepMC::GenParticle *p) [inline]

returns true if the GenParticle does not decay

Examples:

example_UsingIterators.cc.

Definition at line 50 of file example_UsingIterators.cc.

References p.

The documentation for this class was generated from the following file:

- **example_UsingIterators.cc**

9.55 IsW_Boson Class Reference

example class

Public Member Functions

- **bool operator() (const HepMC::GenParticle *p)**
returns true if the GenParticle is a W

9.55.1 Detailed Description

example class

this predicate returns true if the input particle is a W+/W-

Examples:

example_UsingIterators.cc.

Definition at line 34 of file example_UsingIterators.cc.

9.55.2 Member Function Documentation

9.55.2.1 bool IsW_Boson::operator() (const HepMC::GenParticle *p) [inline]

returns true if the GenParticle is a W

Examples:

example_UsingIterators.cc.

Definition at line 37 of file example_UsingIterators.cc.

References p.

The documentation for this class was generated from the following file:

- **example_UsingIterators.cc**

9.56 HepMC::PdfInfo Class Reference

The **PdfInfo** (p.220) class stores PDF information.

```
#include <PdfInfo.h>
```

Public Member Functions

- **PdfInfo ()**
default constructor
- **PdfInfo (int i1, int i2, double x1, double x2, double q, double p1, double p2, int pdf_id1=0, int pdf_id2=0)**
all values EXCEPT pdf_id1 and pdf_id2 must be provided
- **~PdfInfo ()**
- **PdfInfo (PdfInfo const &orig)**
copy constructor
- **PdfInfo & operator= (PdfInfo const &rhs)**
make a copy
- **void swap (PdfInfo &other)**
swap two PdfInfo (p.220) objects
- **bool operator== (const PdfInfo &) const**
check for equality
- **bool operator!= (const PdfInfo &) const**
check for inequality
- **int id1 () const**
flavour code of first parton
- **int id2 () const**
flavour code of second parton
- **int pdf_id1 () const**
LHAPDF set id of first parton.
- **int pdf_id2 () const**
LHAPDF set id of second parton.
- **double x1 () const**
fraction of beam momentum carried by first parton ("beam side")
- **double x2 () const**
fraction of beam momentum carried by second parton ("target side")
- **double scalePDF () const**

Q-scale used in evaluation of PDF's (in GeV).

- **double pdf1 () const**
*PDF (id1, x1, Q) - x*f(x).*
- **double pdf2 () const**
*PDF (id2, x2, Q) - x*f(x).*
- **bool is_valid () const**
verify that the instance contains non-zero information
- **void set_id1 (const int &i)**
set flavour code of first parton
- **void set_id2 (const int &i)**
set flavour code of second parton
- **void set_pdf_id1 (const int &i)**
set LHAPDF set id of first parton
- **void set_pdf_id2 (const int &i)**
set LHAPDF set id of second parton
- **void set_x1 (const double &f)**
set fraction of beam momentum carried by first parton ("beam side")
- **void set_x2 (const double &f)**
set fraction of beam momentum carried by second parton ("target side")
- **void set_scalePDF (const double &f)**
set Q-scale used in evaluation of PDF's (in GeV)
- **void set_pdf1 (const double &f)**
*set x*f(x) of first parton*
- **void set_pdf2 (const double &f)**
*set x*f(x) of second parton*

9.56.1 Detailed Description

The **PdfInfo** (p.220) class stores PDF information.

HepMC::PdfInfo (p.220) stores additional PDF information for a **GenEvent** (p.73). Creation and use of this information is optional.

- `int id1; // flavour code of first parton`
- `int id2; // flavour code of second parton`
- `int pdf_id1; // LHAPDF set id of first parton (zero by default)`

- `int pdf_id2;` // LHAPDF set id of second parton (zero by default)
- `double x1;` // fraction of beam momentum carried by first parton ("beam side")
- `double x2;` // fraction of beam momentum carried by second parton ("target side")
- `double scalePDF;` // Q-scale used in evaluation of PDF's (in GeV)
- `double pdf1;` // PDF (id1, x1, Q)
- `double pdf2;` // PDF (id2, x2, Q)

Input parton flavour codes id1 & id2 are expected to obey the PDG code conventions, especially $g = 21$.

The contents of pdf1 and pdf2 are expected to be $x*f(x)$.
 The LHAPDF set ids are the entries in the first column of
<http://projects.hepforge.org/lhapdf/PDFsets.index>

Examples:

`testMass.cc.in.`

Definition at line 37 of file PdfInfo.h.

9.56.2 Constructor & Destructor Documentation

9.56.2.1 HepMC::PdfInfo::PdfInfo () [inline]

default constructor

Definition at line 43 of file PdfInfo.h.

9.56.2.2 HepMC::PdfInfo::PdfInfo (int i1, int i2, double x1, double x2, double q, double p1, double p2, int pdf_id1 = 0, int pdf_id2 = 0) [inline]

all values EXCEPT pdf_id1 and pdf_id2 must be provided

Definition at line 136 of file PdfInfo.h.

9.56.2.3 HepMC::PdfInfo::~~PdfInfo () [inline]

Definition at line 60 of file PdfInfo.h.

9.56.2.4 HepMC::PdfInfo::PdfInfo (PdfInfo const & orig) [inline]

copy constructor

Definition at line 150 of file PdfInfo.h.

9.56.3 Member Function Documentation

9.56.3.1 `int HepMC::PdfInfo::id1 () const` [inline]

flavour code of first parton

Definition at line 75 of file PdfInfo.h.

Referenced by `HepMC::operator<<()`, and `operator==()`.

9.56.3.2 `int HepMC::PdfInfo::id2 () const` [inline]

flavour code of second parton

Definition at line 77 of file PdfInfo.h.

Referenced by `HepMC::operator<<()`, and `operator==()`.

9.56.3.3 `bool HepMC::PdfInfo::is_valid () const` [inline]

verify that the instance contains non-zero information

Definition at line 202 of file PdfInfo.h.

9.56.3.4 `bool HepMC::PdfInfo::operator!=(const PdfInfo &) const` [inline]

check for inequality

any nonmatching member generates inequality

Definition at line 196 of file PdfInfo.h.

9.56.3.5 `PdfInfo & HepMC::PdfInfo::operator=(PdfInfo const & rhs)` [inline]

make a copy

Definition at line 162 of file PdfInfo.h.

References `swap()`.

9.56.3.6 `bool HepMC::PdfInfo::operator==(const PdfInfo &) const` [inline]

check for equality

equality requires that each member match

Definition at line 182 of file PdfInfo.h.

References `id1()`, `id2()`, `pdf1()`, `pdf2()`, `pdf_id1()`, `pdf_id2()`, `scalePDF()`, `x1()`, and `x2()`.

9.56.3.7 `double HepMC::PdfInfo::pdf1 () const` [inline]

PDF (`id1`, `x1`, `Q`) = `x*f(x)`.

Definition at line 89 of file PdfInfo.h.

Referenced by `HepMC::operator<<()`, and `operator==()`.

9.56.3.8 `double HepMC::PdfInfo::pdf2 () const` [inline]

PDF (id2, x2, Q) - $x \cdot f(x)$.

Definition at line 91 of file PdfInfo.h.

Referenced by `HepMC::operator<<()`, and `operator==()`.

9.56.3.9 `int HepMC::PdfInfo::pdf_id1 () const` [inline]

LHAPDF set id of first parton.

Definition at line 79 of file PdfInfo.h.

Referenced by `HepMC::operator<<()`, and `operator==()`.

9.56.3.10 `int HepMC::PdfInfo::pdf_id2 () const` [inline]

LHAPDF set id of second parton.

Definition at line 81 of file PdfInfo.h.

Referenced by `HepMC::operator<<()`, and `operator==()`.

9.56.3.11 `double HepMC::PdfInfo::scalePDF () const` [inline]

Q-scale used in evaluation of PDF's (in GeV).

Definition at line 87 of file PdfInfo.h.

Referenced by `HepMC::operator<<()`, and `operator==()`.

9.56.3.12 `void HepMC::PdfInfo::set_id1 (const int &i)` [inline]

set flavour code of first parton

Definition at line 98 of file PdfInfo.h.

Referenced by `HepMC::operator>>()`.

9.56.3.13 `void HepMC::PdfInfo::set_id2 (const int &i)` [inline]

set flavour code of second parton

Definition at line 100 of file PdfInfo.h.

Referenced by `HepMC::operator>>()`.

9.56.3.14 `void HepMC::PdfInfo::set_pdf1 (const double &f)` [inline]

set $x \cdot f(x)$ of first parton

Definition at line 112 of file PdfInfo.h.

Referenced by `HepMC::operator>>()`.

9.56.3.15 void HepMC::PdfInfo::set_pdf2 (const double &f) [inline]

set $x \cdot f(x)$ of second parton

Definition at line 114 of file PdfInfo.h.

Referenced by HepMC::operator>>().

9.56.3.16 void HepMC::PdfInfo::set_pdf_id1 (const int &i) [inline]

set LHAPDF set id of first parton

Definition at line 102 of file PdfInfo.h.

Referenced by HepMC::operator>>().

9.56.3.17 void HepMC::PdfInfo::set_pdf_id2 (const int &i) [inline]

set LHAPDF set id of second parton

Definition at line 104 of file PdfInfo.h.

Referenced by HepMC::operator>>().

9.56.3.18 void HepMC::PdfInfo::set_scalePDF (const double &f) [inline]

set Q-scale used in evaluation of PDF's (in GeV)

Definition at line 110 of file PdfInfo.h.

Referenced by HepMC::operator>>().

9.56.3.19 void HepMC::PdfInfo::set_x1 (const double &f) [inline]

set fraction of beam momentum carried by first parton ("beam side")

Definition at line 106 of file PdfInfo.h.

Referenced by HepMC::operator>>().

9.56.3.20 void HepMC::PdfInfo::set_x2 (const double &f) [inline]

set fraction of beam momentum carried by second parton ("target side")

Definition at line 108 of file PdfInfo.h.

Referenced by HepMC::operator>>().

9.56.3.21 void HepMC::PdfInfo::swap (PdfInfo &other) [inline]

swap two **PdfInfo** (p.220) objects

Definition at line 169 of file PdfInfo.h.

References m_id1, m_id2, m_pdf1, m_pdf2, m_pdf_id1, m_pdf_id2, m_scalePDF, m_x1, and m_x2.

Referenced by operator=().

9.56.3.22 double HepMC::PdfInfo::x1 () const [inline]

fraction of beam momentum carried by first parton ("beam side")

Definition at line 83 of file PdfInfo.h.

Referenced by `HepMC::operator<<()`, and `operator==()`.

9.56.3.23 double HepMC::PdfInfo::x2 () const [inline]

fraction of beam momentum carried by second parton ("target side")

Definition at line 85 of file PdfInfo.h.

Referenced by `HepMC::operator<<()`, and `operator==()`.

The documentation for this class was generated from the following file:

- PdfInfo.h

9.57 pin3 Struct Reference

```
#include <PythiaWrapper6_4.h>
```

Public Attributes

- double xsfx [81][2]
- int isig [3][1000]
- double sigh [1000]

9.57.1 Detailed Description

Definition at line 115 of file PythiaWrapper6_4.h.

9.57.2 Member Data Documentation

9.57.2.1 int pin3::isig[3][1000]

Definition at line 117 of file PythiaWrapper6_4.h.

9.57.2.2 double pin3::sigh[1000]

Definition at line 118 of file PythiaWrapper6_4.h.

9.57.2.3 double pin3::xsfx[81][2]

Definition at line 116 of file PythiaWrapper6_4.h.

The documentation for this struct was generated from the following file:

- PythiaWrapper6_4.h

9.58 pin5 Struct Reference

```
#include <PythiaWrapper6_4.h>
```

Public Attributes

- `int ngenpd`
- `int ngen [3][501]`
- `double xsec [3][501]`

9.58.1 Detailed Description

Definition at line 132 of file `PythiaWrapper6_4.h`.

9.58.2 Member Data Documentation

9.58.2.1 `int pin5::ngen[3][501]`

Definition at line 133 of file `PythiaWrapper6_4.h`.

9.58.2.2 `int pin5::ngenpd`

Definition at line 133 of file `PythiaWrapper6_4.h`.

9.58.2.3 `double pin5::xsec[3][501]`

Definition at line 134 of file `PythiaWrapper6_4.h`.

The documentation for this struct was generated from the following file:

- `PythiaWrapper6_4.h`

9.59 pin7 Struct Reference

```
#include <PythiaWrapper6_4.h>
```

Public Attributes

- double **sig**[6][7][7]

9.59.1 Detailed Description

Definition at line 140 of file PythiaWrapper6_4.h.

9.59.2 Member Data Documentation

9.59.2.1 double pin7::sig[6][7][7]

Definition at line 141 of file PythiaWrapper6_4.h.

The documentation for this struct was generated from the following file:

- **PythiaWrapper6_4.h**

9.60 pin8 Struct Reference

```
#include <PythiaWrapper6_4.h>
```

Public Attributes

- double **xpvm**d [13]
- double **xpan**l [13]
- double **xpan**h [13]
- double **xpbe**h [13]
- double **xpdi**r [13]

9.60.1 Detailed Description

Definition at line 147 of file PythiaWrapper6_4.h.

9.60.2 Member Data Documentation

9.60.2.1 double pin8::xpanh[13]

Definition at line 150 of file PythiaWrapper6_4.h.

9.60.2.2 double pin8::xpanl[13]

Definition at line 149 of file PythiaWrapper6_4.h.

9.60.2.3 double pin8::xpbeh[13]

Definition at line 151 of file PythiaWrapper6_4.h.

9.60.2.4 double pin8::xpdir[13]

Definition at line 152 of file PythiaWrapper6_4.h.

9.60.2.5 double pin8::xpvm[d][13]

Definition at line 148 of file PythiaWrapper6_4.h.

The documentation for this struct was generated from the following file:

- **PythiaWrapper6_4.h**

9.61 pin9 Struct Reference

```
#include <PythiaWrapper6_4.h>
```

Public Attributes

- double **vxpvm**d [13]
- double vxpanl [13]
- double vxpanh [13]
- double vxpdgm [13]

9.61.1 Detailed Description

Definition at line 158 of file PythiaWrapper6_4.h.

9.61.2 Member Data Documentation

9.61.2.1 double pin9::vxpanh[13]

Definition at line 161 of file PythiaWrapper6_4.h.

9.61.2.2 double pin9::vxpanl[13]

Definition at line 160 of file PythiaWrapper6_4.h.

9.61.2.3 double pin9::vxpdgm[13]

Definition at line 162 of file PythiaWrapper6_4.h.

9.61.2.4 double pin9::vxpvm[13]

Definition at line 159 of file PythiaWrapper6_4.h.

The documentation for this struct was generated from the following file:

- **PythiaWrapper6_4.h**

9.62 HepMC::Polarization Class Reference

The **Polarization** (p.232) class stores theta and phi for a **GenParticle** (p.111).

```
#include <Polarization.h>
```

Public Member Functions

- **Polarization ()**
default constructor
- **Polarization (double theta, double phi=0)**
constructor requiring at least one value
- **Polarization (const Polarization &inpolar)**
construct from another polarization object
- **Polarization (const ThreeVector &vec3in)**
construct using the polar and azimuthal angles from a ThreeVector (p.254)
- **virtual ~Polarization ()**
- **void swap (Polarization &other)**
swap
- **Polarization & operator= (const Polarization &inpolar)**
make a copy
- **bool operator== (const Polarization &) const**
equality requires that theta and phi are equal
- **bool operator!= (const Polarization &) const**
inequality results if either theta or phi differ
- **void print (std::ostream &ostr=std::cout) const**
print theta and phi
- **double theta () const**
returns polar angle in radians
- **double phi () const**
returns azimuthal angle in radians
- **ThreeVector normal3d () const**
unit 3 vector for easy manipulation
- **bool is_defined () const**
returns true if the Polarization (p.232) has been defined
- **double set_theta (double theta)**

set polar angle in radians

- **double set_phi (double phi)**
set azimuthal angle in radians
- **void set_theta_phi (double theta, double phi)**
set both polar and azimuthal angles in radians
- **ThreeVector set_normal3d (const ThreeVector &vec3in)**
sets polarization according to direction of 3 vec
- **void set_undefined ()**
declares the Polarization (p.232) as undefined and zeros the values

Friends

- **std::ostream & operator<< (std::ostream &, const Polarization &)**
print polarization information

9.62.1 Detailed Description

The **Polarization** (p.232) class stores theta and phi for a **GenParticle** (p.111).

HepMC::Polarization (p.232) stores a particle's theta and phi in radians. Use of this information is optional. By default, the polarization is set to zero.

Definition at line 29 of file Polarization.h.

9.62.2 Constructor & Destructor Documentation

9.62.2.1 HepMC::Polarization::Polarization ()

default constructor

Definition at line 11 of file Polarization.cc.

9.62.2.2 HepMC::Polarization::Polarization (double *theta*, double *phi* = 0)

constructor requiring at least one value

Definition at line 17 of file Polarization.cc.

9.62.2.3 HepMC::Polarization::Polarization (const Polarization & *inpolar*)

construct from another polarization object

Definition at line 23 of file Polarization.cc.

9.62.2.4 HepMC::Polarization::Polarization (const ThreeVector & vec3in)

construct using the polar and azimuthal angles from a **ThreeVector** (p.254)

Definition at line 29 of file Polarization.cc.

9.62.2.5 virtual HepMC::Polarization::~~Polarization () [inline, virtual]

Definition at line 43 of file Polarization.h.

9.62.3 Member Function Documentation

9.62.3.1 bool HepMC::Polarization::is_defined () const

returns true if the **Polarization** (p.232) has been defined

Definition at line 77 of file Polarization.cc.

Referenced by operator==().

9.62.3.2 ThreeVector HepMC::Polarization::normal3d () const

unit 3 vector for easy manipulation

Definition at line 57 of file Polarization.cc.

References phi(), HepMC::ThreeVector::setPhi(), HepMC::ThreeVector::setTheta(), and theta().

9.62.3.3 bool HepMC::Polarization::operator!=(const Polarization &) const [inline]

inequality results if either theta or phi differ

Definition at line 104 of file Polarization.h.

9.62.3.4 Polarization & HepMC::Polarization::operator= (const Polarization & inpolar)

make a copy

best practices implementation

Definition at line 42 of file Polarization.cc.

References swap().

9.62.3.5 bool HepMC::Polarization::operator==(const Polarization &) const [inline]

equality requires that theta and phi are equal

Definition at line 99 of file Polarization.h.

References is_defined(), phi(), and theta().

9.62.3.6 double HepMC::Polarization::phi () const [inline]

returns azimuthal angle in radians

Definition at line 93 of file Polarization.h.

Referenced by normal3d(), HepMC::operator<<(), and operator==().

9.62.3.7 void HepMC::Polarization::print (std::ostream & ostr = std::cout) const

print theta and phi

Definition at line 49 of file Polarization.cc.

9.62.3.8 ThreeVector HepMC::Polarization::set_normal3d (const ThreeVector & vec3in)

sets polarization according to direction of 3 vec

Definition at line 93 of file Polarization.cc.

References HepMC::ThreeVector::phi(), set_phi(), set_theta(), and HepMC::ThreeVector::theta().

9.62.3.9 double HepMC::Polarization::set_phi (double phi)

set azimuthal angle in radians

Phi is restricted to be between 0 -> 2pi if an out of range value is given, it is translated to this range.

Definition at line 71 of file Polarization.cc.

Referenced by set_normal3d(), and set_theta_phi().

9.62.3.10 double HepMC::Polarization::set_theta (double theta)

set polar angle in radians

Theta is restricted to be between 0 -> pi if an out of range value is given, it is translated to this range.

Definition at line 65 of file Polarization.cc.

Referenced by set_normal3d(), and set_theta_phi().

9.62.3.11 void HepMC::Polarization::set_theta_phi (double theta, double phi)

set both polar and azimuthal angles in radians

Definition at line 87 of file Polarization.cc.

References set_phi(), and set_theta().

9.62.3.12 void HepMC::Polarization::set_undefined ()

declares the **Polarization** (p.232) as undefined and zeros the values

Definition at line 81 of file Polarization.cc.

9.62.3.13 void HepMC::Polarization::swap (Polarization & *other*)

swap

Definition at line 35 of file Polarization.cc.

References `m_defined`, `m_phi`, and `m_theta`.

Referenced by `operator=()`, and `HepMC::GenParticle::swap()`.

9.62.3.14 double HepMC::Polarization::theta () const [inline]

returns polar angle in radians

Definition at line 92 of file Polarization.h.

Referenced by `normal3d()`, `HepMC::operator<<()`, and `operator==()`.

9.62.4 Friends And Related Function Documentation

9.62.4.1 std::ostream& operator<< (std::ostream & *ostr*, const Polarization & *polar*) [friend]

print polarization information

Definition at line 129 of file Polarization.cc.

The documentation for this class was generated from the following files:

- **Polarization.h**
- **Polarization.cc**

9.63 PrintChildren Class Reference

```
test class
#include <testHepMCIteration.h>
```

Public Member Functions

- **PrintChildren** (std::ostream &os)
- **void operator()** (HepMC::GenParticle *p)

9.63.1 Detailed Description

```
test class
prints the particle
```

Examples:

```
testHepMCIteration.cc.in.
```

Definition at line 62 of file testHepMCIteration.h.

9.63.2 Constructor & Destructor Documentation

9.63.2.1 PrintChildren::PrintChildren (std::ostream & os) [inline]

Definition at line 64 of file testHepMCIteration.h.

9.63.3 Member Function Documentation

9.63.3.1 void PrintChildren::operator() (HepMC::GenParticle *p) [inline]

Definition at line 65 of file testHepMCIteration.h.

References `p`, `HepMC::GenParticle::pdg_id()`, and `HepMC::GenParticle::status()`.

The documentation for this class was generated from the following file:

- **testHepMCIteration.h**

9.64 PrintDescendants Class Reference

```
test class
#include <testHepMCIteration.h>
```

Public Member Functions

- **PrintDescendants** (std::ostream &os)
- **void operator()** (const HepMC::GenParticle *p)

9.64.1 Detailed Description

```
test class
prints the particle
```

Examples:

```
testHepMCIteration.cc.in.
```

Definition at line 82 of file testHepMCIteration.h.

9.64.2 Constructor & Destructor Documentation

9.64.2.1 PrintDescendants::PrintDescendants (std::ostream & os) [inline]

Definition at line 84 of file testHepMCIteration.h.

9.64.3 Member Function Documentation

9.64.3.1 void PrintDescendants::operator() (const HepMC::GenParticle *p) [inline]

Definition at line 85 of file testHepMCIteration.h.

References p.

The documentation for this class was generated from the following file:

- testHepMCIteration.h

9.65 PrintParticle Class Reference

```
#include <testHepMCIteration.h>
```

Public Member Functions

- **PrintParticle** (std::ostream &os)
- **void operator()** (const HepMC::GenParticle *p)

9.65.1 Detailed Description

prints the particle

Examples:

testHepMCIteration.cc.in.

Definition at line 47 of file testHepMCIteration.h.

9.65.2 Constructor & Destructor Documentation

9.65.2.1 PrintParticle::PrintParticle (std::ostream & os) [inline]

Definition at line 49 of file testHepMCIteration.h.

9.65.3 Member Function Documentation

9.65.3.1 void PrintParticle::operator() (const HepMC::GenParticle * p) [inline]

Definition at line 50 of file testHepMCIteration.h.

References p.

The documentation for this class was generated from the following file:

- **testHepMCIteration.h**

9.66 PrintPhoton Class Reference

```
#include <testHepMCIteration.h>
```

Public Member Functions

- **PrintPhoton** (std::ostream &os)
- **void operator()** (const HepMC::GenParticle *p)

9.66.1 Detailed Description

prints the particle if it is a photon

Examples:

```
testHepMCIteration.cc.in.
```

Definition at line 35 of file testHepMCIteration.h.

9.66.2 Constructor & Destructor Documentation

9.66.2.1 PrintPhoton::PrintPhoton (std::ostream & os) [inline]

Definition at line 37 of file testHepMCIteration.h.

9.66.3 Member Function Documentation

9.66.3.1 void PrintPhoton::operator() (const HepMC::GenParticle *p) [inline]

Definition at line 38 of file testHepMCIteration.h.

References `IsPhoton()`, and `p`.

The documentation for this class was generated from the following file:

- **testHepMCIteration.h**

9.67 prvnv Struct Reference

```
#include <PythiaWrapper6_4.h>
```

Public Attributes

- double **ab** [2][16][2]
- double **rms** [4]
- double **res** [5][6]
- int **idr**
- int **idr2**
- double **dcmass**
- int **kfr** [3]

9.67.1 Detailed Description

Definition at line 200 of file PythiaWrapper6_4.h.

9.67.2 Member Data Documentation

9.67.2.1 double prvnv::ab[2][16][2]

Definition at line 201 of file PythiaWrapper6_4.h.

9.67.2.2 double prvnv::dcmass

Definition at line 206 of file PythiaWrapper6_4.h.

9.67.2.3 int prvnv::idr

Definition at line 204 of file PythiaWrapper6_4.h.

9.67.2.4 int prvnv::idr2

Definition at line 205 of file PythiaWrapper6_4.h.

9.67.2.5 int prvnv::kfr[3]

Definition at line 207 of file PythiaWrapper6_4.h.

9.67.2.6 double prvnv::res[5][6]

Definition at line 203 of file PythiaWrapper6_4.h.

9.67.2.7 double prvnv::rms[4]

Definition at line 202 of file PythiaWrapper6_4.h.

The documentation for this struct was generated from the following file:

- **PythiaWrapper6_4.h**

9.68 prvpkm Struct Reference

```
#include <PythiaWrapper6_4.h>
```

Public Attributes

- double **rm** [4]
- double **a** [2]
- double **b** [2]
- double **resm** [2]
- double **resw** [2]
- bool **mflag**

9.68.1 Detailed Description

Definition at line 213 of file PythiaWrapper6_4.h.

9.68.2 Member Data Documentation

9.68.2.1 double prvpkm::a[2]

Definition at line 215 of file PythiaWrapper6_4.h.

9.68.2.2 double prvpkm::b[2]

Definition at line 216 of file PythiaWrapper6_4.h.

9.68.2.3 bool prvpkm::mflag

Definition at line 219 of file PythiaWrapper6_4.h.

9.68.2.4 double prvpkm::resm[2]

Definition at line 217 of file PythiaWrapper6_4.h.

9.68.2.5 double prvpkm::resw[2]

Definition at line 218 of file PythiaWrapper6_4.h.

9.68.2.6 double prvpkm::rm[4]

Definition at line 214 of file PythiaWrapper6_4.h.

The documentation for this struct was generated from the following file:

- **PythiaWrapper6_4.h**

9.69 pssm Struct Reference

```
#include <PythiaWrapper6_4.h>
```

Public Attributes

- `int imss [100]`
- `double rmss [100]`

9.69.1 Detailed Description

Definition at line 168 of file `PythiaWrapper6_4.h`.

9.69.2 Member Data Documentation

9.69.2.1 `int pssm::imss[100]`

Definition at line 169 of file `PythiaWrapper6_4.h`.

9.69.2.2 `double pssm::rmss[100]`

Definition at line 170 of file `PythiaWrapper6_4.h`.

The documentation for this struct was generated from the following file:

- `PythiaWrapper6_4.h`

9.70 HepMC::StreamInfo Class Reference

StreamInfo (p.245) contains extra information needed when using streaming IO.

```
#include <StreamInfo.h>
```

Public Member Functions

- **StreamInfo ()**
default constructor
- **~StreamInfo ()**
destructor
- **std::string IO_GenEvent_Key () const**
IO_GenEvent (p.184) begin event block key.
- **std::string IO_GenEvent_End () const**
IO_GenEvent (p.184) end event block key.
- **std::string IO_Ascii_Key () const**
- **std::string IO_Ascii_End () const**
IO_Ascii end event block key.
- **std::string IO_Ascii_PDT_Key () const**
IO_Ascii begin particle data block key.
- **std::string IO_Ascii_PDT_End () const**
IO_Ascii end particle data block key.
- **std::string IO_ExtendedAscii_Key () const**
- **std::string IO_ExtendedAscii_End () const**
IO_ExtendedAscii end event block key.
- **std::string IO_ExtendedAscii_PDT_Key () const**
IO_ExtendedAscii begin particle data block key.
- **std::string IO_ExtendedAscii_PDT_End () const**
IO_ExtendedAscii end particle data block key.
- **int io_type () const**
get IO type
- **void set_io_type (int)**
set IO type
- **bool has_key () const**
- **void set_has_key (bool)**
set to false if the stream does not have a file type key

- **Units::MomentumUnit io_momentum_unit () const**
get the I/O momentum units
- **Units::LengthUnit io_position_unit () const**
get the I/O length units
- **int stream_id () const**
- **bool finished_first_event () const**
Special information is processed the first time we use the IO.
- **void set_finished_first_event (bool b)**
Special information is processed the first time we use the IO.
- **void use_input_units (Units::MomentumUnit, Units::LengthUnit)**
- **bool reading_event_header ()**
- **void set_reading_event_header (bool)**
set the reading_event_header flag

9.70.1 Detailed Description

StreamInfo (p.245) contains extra information needed when using streaming IO.

This class contains the extra information needed when using streaming IO to process **HepMC** (p.23) GenEvents

Definition at line 26 of file StreamInfo.h.

9.70.2 Constructor & Destructor Documentation

9.70.2.1 HepMC::StreamInfo::StreamInfo ()

default constructor

Definition at line 13 of file StreamInfo.cc.

9.70.2.2 HepMC::StreamInfo::~~StreamInfo () [inline]

destructor

Definition at line 31 of file StreamInfo.h.

9.70.3 Member Function Documentation

9.70.3.1 bool HepMC::StreamInfo::finished_first_event () const [inline]

Special information is processed the first time we use the IO.

Definition at line 81 of file StreamInfo.h.

Referenced by `HepMC::detail::establish_input_stream_info()`, `HepMC::establish_input_stream_info()`, `HepMC::detail::establish_output_stream_info()`, `HepMC::establish_output_stream_info()`, `HepMC::GenEvent::read()`, `HepMC::GenEvent::write()`, `HepMC::write_HepMC_IO_block_begin()`, and `HepMC::write_HepMC_IO_block_end()`.

9.70.3.2 `bool HepMC::StreamInfo::has_key() const` [inline]

true if the stream has a file type key `has_key` is true by default

Definition at line 67 of file `StreamInfo.h`.

Referenced by `HepMC::GenEvent::read()`.

9.70.3.3 `std::string HepMC::StreamInfo::IO_Ascii_End() const` [inline]

`IO_Ascii` end event block key.

Definition at line 43 of file `StreamInfo.h`.

9.70.3.4 `std::string HepMC::StreamInfo::IO_Ascii_Key() const` [inline]

`IO_Ascii` begin event block key `IO_Ascii` has been removed, but we want to be able to read existing files written by `IO_Ascii`

Definition at line 41 of file `StreamInfo.h`.

9.70.3.5 `std::string HepMC::StreamInfo::IO_Ascii_PDT_End() const` [inline]

`IO_Ascii` end particle data block key.

Definition at line 47 of file `StreamInfo.h`.

9.70.3.6 `std::string HepMC::StreamInfo::IO_Ascii_PDT_Key() const` [inline]

`IO_Ascii` begin particle data block key.

Definition at line 45 of file `StreamInfo.h`.

9.70.3.7 `std::string HepMC::StreamInfo::IO_ExtendedAscii_End() const` [inline]

`IO_ExtendedAscii` end event block key.

Definition at line 54 of file `StreamInfo.h`.

9.70.3.8 `std::string HepMC::StreamInfo::IO_ExtendedAscii_Key() const` [inline]

`IO_ExtendedAscii` begin event block key `IO_ExtendedAscii` has been removed, but we want to be able to read existing files written by `IO_ExtendedAscii`

Definition at line 52 of file `StreamInfo.h`.

9.70.3.9 `std::string HepMC::StreamInfo::IO_ExtendedAscii_PDT_End () const` [inline]

IO_ExtendedAscii end particle data block key.

Definition at line 58 of file StreamInfo.h.

9.70.3.10 `std::string HepMC::StreamInfo::IO_ExtendedAscii_PDT_Key () const` [inline]

IO_ExtendedAscii begin particle data block key.

Definition at line 56 of file StreamInfo.h.

9.70.3.11 `std::string HepMC::StreamInfo::IO_GenEvent_End () const` [inline]

IO_GenEvent (p.184) end event block key.

Definition at line 36 of file StreamInfo.h.

Referenced by `HepMC::write_HepMC_IO_block_end()`.

9.70.3.12 `std::string HepMC::StreamInfo::IO_GenEvent_Key () const` [inline]

IO_GenEvent (p.184) begin event block key.

Definition at line 34 of file StreamInfo.h.

Referenced by `HepMC::write_HepMC_IO_block_begin()`.

9.70.3.13 `Units::MomentumUnit HepMC::StreamInfo::io_momentum_unit () const` [inline]

get the I/O momentum units

Definition at line 72 of file StreamInfo.h.

Referenced by `HepMC::detail::read_units()`.

9.70.3.14 `Units::LengthUnit HepMC::StreamInfo::io_position_unit () const` [inline]

get the I/O length units

Definition at line 74 of file StreamInfo.h.

Referenced by `HepMC::detail::read_units()`.

9.70.3.15 `int HepMC::StreamInfo::io_type () const` [inline]

get IO type

Definition at line 61 of file StreamInfo.h.

Referenced by `HepMC::GenEvent::read()`, and `HepMC::detail::read_particle()`.

9.70.3.16 bool HepMC::StreamInfo::reading_event_header ()

reading_event_header will return true when streaming input is processing the **GenEvent** (p.73) header information

Definition at line 51 of file StreamInfo.cc.

Referenced by HepMC::GenEvent::read().

9.70.3.17 void HepMC::StreamInfo::set_finished_first_event (bool *b*) [inline]

Special information is processed the first time we use the IO.

Definition at line 83 of file StreamInfo.h.

Referenced by HepMC::GenEvent::read(), and HepMC::GenEvent::write().

9.70.3.18 void HepMC::StreamInfo::set_has_key (bool)

set to false if the stream does not have a file type key

Definition at line 47 of file StreamInfo.cc.

9.70.3.19 void HepMC::StreamInfo::set_io_type (int)

set IO type

Definition at line 43 of file StreamInfo.cc.

9.70.3.20 void HepMC::StreamInfo::set_reading_event_header (bool)

set the reading_event_header flag

Definition at line 55 of file StreamInfo.cc.

Referenced by HepMC::GenEvent::read().

9.70.3.21 int HepMC::StreamInfo::stream_id () const [inline]

get the I/O stream id This is used for sanity checking.

Definition at line 78 of file StreamInfo.h.

Referenced by HepMC::HepMCStreamCallback().

9.70.3.22 void HepMC::StreamInfo::use_input_units (Units::MomentumUnit, Units::LengthUnit)

needed when reading a file without units if those units are different than the declared default units (e.g., the default units are MeV, but the file was written with GeV) This method is not necessary if the units are written in the file

Definition at line 38 of file StreamInfo.cc.

Referenced by HepMC::set_input_units().

The documentation for this class was generated from the following files:

- **StreamInfo.h**
- **StreamInfo.cc**

9.71 HepMC::TempParticleMap Class Reference

TempParticleMap (p.251) is a temporary GenParticle* container used during input.

```
#include <TempParticleMap.h>
```

Public Types

- `typedef std::map< HepMC::GenParticle *, int > TempMap`
- `typedef std::map< int, HepMC::GenParticle * > TempOrderMap`
- `typedef TempMap::iterator TempMapIterator`
- `typedef TempOrderMap::iterator orderIterator`

Public Member Functions

- `TempParticleMap ()`
- `~TempParticleMap ()`
- `TempMapIterator begin ()`
- `TempMapIterator end ()`
- `orderIterator order_begin ()`
- `orderIterator order_end ()`
- `int end_vertex (GenParticle *)`
- `void addEndParticle (GenParticle *, int &)`

9.71.1 Detailed Description

TempParticleMap (p.251) is a temporary GenParticle* container used during input.

Used by IO classes for recoverable particle ordering. Map GenParticle* against both outgoing vertex and particle order.

Definition at line 24 of file TempParticleMap.h.

9.71.2 Member Typedef Documentation

9.71.2.1 `typedef TempOrderMap::iterator HepMC::TempParticleMap::orderIterator`

Definition at line 29 of file TempParticleMap.h.

9.71.2.2 `typedef std::map<HepMC::GenParticle*,int> HepMC::TempParticleMap::TempMap`

Definition at line 26 of file TempParticleMap.h.

9.71.2.3 `typedef TempMap::iterator HepMC::TempParticleMap::TempMapIterator`

Definition at line 28 of file TempParticleMap.h.

9.71.2.4 `typedef std::map<int,HepMC::GenParticle*> HepMC::TempParticleMap::TempOrder-Map`

Definition at line 27 of file TempParticleMap.h.

9.71.3 Constructor & Destructor Documentation

9.71.3.1 `HepMC::TempParticleMap::TempParticleMap ()` [inline]

Definition at line 31 of file TempParticleMap.h.

9.71.3.2 `HepMC::TempParticleMap::~~TempParticleMap ()` [inline]

Definition at line 34 of file TempParticleMap.h.

9.71.4 Member Function Documentation

9.71.4.1 `void HepMC::TempParticleMap::addEndParticle (GenParticle *, int &)` [inline]

Definition at line 58 of file TempParticleMap.h.

References `p`.

Referenced by `HepMC::detail::read_particle()`.

9.71.4.2 `TempMapIterator HepMC::TempParticleMap::begin ()` [inline]

Definition at line 36 of file TempParticleMap.h.

9.71.4.3 `TempMapIterator HepMC::TempParticleMap::end ()` [inline]

Definition at line 37 of file TempParticleMap.h.

Referenced by `end_vertex()`.

9.71.4.4 `int HepMC::TempParticleMap::end_vertex (GenParticle *)` [inline]

Definition at line 50 of file TempParticleMap.h.

References `end()`, and `p`.

Referenced by `HepMC::GenEvent::read()`.

9.71.4.5 `orderIterator HepMC::TempParticleMap::order_begin ()` [inline]

Definition at line 38 of file TempParticleMap.h.

Referenced by `HepMC::GenEvent::read()`.

9.71.4.6 orderIterator HepMC::TempParticleMap::order_end () [inline]

Definition at line 39 of file TempParticleMap.h.

Referenced by HepMC::GenEvent::read().

The documentation for this class was generated from the following file:

- TempParticleMap.h

9.72 HepMC::ThreeVector Class Reference

ThreeVector (p.254) is a simple representation of a position or displacement 3 vector.

```
#include <SimpleVector.h>
```

Public Member Functions

- **ThreeVector (double xin, double yin=0, double zin=0)**
construct using x, y, and z (only x is required)
- **ThreeVector ()**
- **template<class T> ThreeVector (const T &v, typename detail::disable_if< detail::is_arithmetic< T >::value, void >::type !=0)**
- **ThreeVector (const ThreeVector &v)**
copy constructor
- **void swap (ThreeVector &other)**
swap
- **double x () const**
return x
- **double y () const**
return y
- **double z () const**
return z
- **void setX (double x)**
set x
- **void setY (double y)**
set y
- **void setZ (double z)**
set z
- **void set (double x, double y, double z)**
set x, y, and z
- **double phi () const**
The azimuth angle.
- **double theta () const**
The polar angle.
- **double r () const**
The magnitude.

- **void setPhi (double)**
Set phi keeping magnitude and theta constant (BaBar).
- **void setTheta (double)**
Set theta keeping magnitude and phi constant (BaBar).
- **double perp2 () const**
The transverse component squared (ρ^2 in cylindrical coordinate system).
- **double perp () const**
The transverse component (ρ in cylindrical coordinate system).
- **ThreeVector & operator= (const ThreeVector &)**
make a copy
- **bool operator== (const ThreeVector &) const**
equality
- **bool operator!= (const ThreeVector &) const**
inequality

9.72.1 Detailed Description

ThreeVector (p.254) is a simple representation of a position or displacement 3 vector.

For compatibility with existing code, the basic expected geometrical access methods are provided. Also, there is a templated constructor that will take another vector (HepLorentzVector, GenVector, ...) which must have the following methods: **x()** (p.259), **y()** (p.259), **z()** (p.259).

Examples:

testSimpleVector.cc, and VectorConversion.h.

Definition at line 131 of file SimpleVector.h.

9.72.2 Constructor & Destructor Documentation

9.72.2.1 HepMC::ThreeVector::ThreeVector (double *xin*, double *yin* = 0, double *zin* = 0) [inline]

construct using x, y, and z (only x is required)

Definition at line 136 of file SimpleVector.h.

9.72.2.2 HepMC::ThreeVector::ThreeVector () [inline]

Definition at line 139 of file SimpleVector.h.

9.72.2.3 `template<class T> HepMC::ThreeVector::ThreeVector (const T & v, typename detail::disable_if< detail::is_arithmetic< T >::value, void >::type * = 0) [inline]`

templated constructor this is used ONLY if T is not arithmetic

Definition at line 145 of file SimpleVector.h.

9.72.2.4 `HepMC::ThreeVector::ThreeVector (const ThreeVector & v) [inline]`

copy constructor

Definition at line 150 of file SimpleVector.h.

9.72.3 Member Function Documentation

9.72.3.1 `bool HepMC::ThreeVector::operator!= (const ThreeVector &) const`

inequality

9.72.3.2 `ThreeVector& HepMC::ThreeVector::operator= (const ThreeVector &)`

make a copy

9.72.3.3 `bool HepMC::ThreeVector::operator== (const ThreeVector &) const`

equality

9.72.3.4 `double HepMC::ThreeVector::perp () const`

The transverse component (rho in cylindrical coordinate system).

Examples:

`testSimpleVector.cc.`

Referenced by `main()`.

9.72.3.5 `double HepMC::ThreeVector::perp2 () const`

The transverse component squared (rho^2 in cylindrical coordinate system).

Examples:

`testSimpleVector.cc.`

Referenced by `main()`.

9.72.3.6 double HepMC::ThreeVector::phi () const

The azimuth angle.

Examples:

`testSimpleVector.cc.`

Referenced by `main()`, and `HepMC::Polarization::set_normal3d()`.

9.72.3.7 double HepMC::ThreeVector::r () const

The magnitude.

Examples:

`testSimpleVector.cc.`

Referenced by `main()`.

9.72.3.8 void HepMC::ThreeVector::set (double x, double y, double z)

set x, y, and z

Examples:

`testSimpleVector.cc.`

Referenced by `main()`.

9.72.3.9 void HepMC::ThreeVector::setPhi (double)

Set phi keeping magnitude and theta constant (BaBar).

Examples:

`testSimpleVector.cc.`

Referenced by `main()`, and `HepMC::Polarization::normal3d()`.

9.72.3.10 void HepMC::ThreeVector::setTheta (double)

Set theta keeping magnitude and phi constant (BaBar).

Examples:

`testSimpleVector.cc.`

Referenced by `main()`, and `HepMC::Polarization::normal3d()`.

9.72.3.11 void HepMC::ThreeVector::setX (double *x*) [inline]

set *x*

Examples:

`testSimpleVector.cc.`

Definition at line 159 of file SimpleVector.h.

Referenced by `main()`.

9.72.3.12 void HepMC::ThreeVector::setY (double *y*) [inline]

set *y*

Examples:

`testSimpleVector.cc.`

Definition at line 160 of file SimpleVector.h.

Referenced by `main()`.

9.72.3.13 void HepMC::ThreeVector::setZ (double *z*) [inline]

set *z*

Examples:

`testSimpleVector.cc.`

Definition at line 161 of file SimpleVector.h.

Referenced by `main()`.

9.72.3.14 void HepMC::ThreeVector::swap (ThreeVector & *other*)

swap

9.72.3.15 double HepMC::ThreeVector::theta () const

The polar angle.

Examples:

`testSimpleVector.cc.`

Referenced by `main()`, and `HepMC::Polarization::set_normal3d()`.

9.72.3.16 double HepMC::ThreeVector::x () const [inline]

```
return x
```

Examples:

```
testSimpleVector.cc.
```

Definition at line 155 of file SimpleVector.h.

Referenced by main().

9.72.3.17 double HepMC::ThreeVector::y () const [inline]

```
return y
```

Examples:

```
testSimpleVector.cc.
```

Definition at line 156 of file SimpleVector.h.

Referenced by main().

9.72.3.18 double HepMC::ThreeVector::z () const [inline]

```
return z
```

Examples:

```
testSimpleVector.cc.
```

Definition at line 157 of file SimpleVector.h.

Referenced by main().

The documentation for this class was generated from the following file:

- SimpleVector.h

9.73 HepMC::WeightContainer Class Reference

Container for the Weights associated with an event or vertex.

```
#include <WeightContainer.h>
```

Public Types

- `typedef std::size_t size_type`
defining the size type used by vector and map
- `typedef std::vector< double >::iterator iterator`
iterator for the weight container
- `typedef std::vector< double >::const_iterator const_iterator`
const iterator for the weight container

Public Member Functions

- `WeightContainer (size_type n=0, double value=0.)`
default constructor
- `WeightContainer (const std::vector< double > &weights)`
construct from a vector of weights
- `WeightContainer (const WeightContainer &in)`
copy
- `~WeightContainer ()`
- `void swap (WeightContainer &other)`
swap
- `WeightContainer & operator= (const WeightContainer &)`
copy assignment
- `WeightContainer & operator= (const std::vector< double > &in)`
alternate assignment using a vector of doubles
- `void print (std::ostream &ostr=std::cout) const`
print weights
- `void write (std::ostream &ostr=std::cout) const`
write weights in a readable table
- `size_type size () const`
size of weight container
- `bool empty () const`
return true if weight container is empty

- **void push_back (const double &)**
push onto weight container
- **void pop_back ()**
pop from weight container
- **void clear ()**
clear the weight container
- **bool has_key (const std::string &s) const**
check to see if a name exists in the map
- **double & operator[] (size_type n)**
access the weight container
- **const double & operator[] (size_type n) const**
access the weight container
- **double & operator[] (const std::string &s)**
access the weight container
- **const double & operator[] (const std::string &s) const**
access the weight container
- **bool operator== (const WeightContainer &) const**
equality
- **bool operator!= (const WeightContainer &) const**
inequality
- **double & front ()**
returns the first element
- **const double & front () const**
returns the first element
- **double & back ()**
returns the last element
- **const double & back () const**
returns the last element
- **iterator begin ()**
beginning of the weight container
- **iterator end ()**
end of the weight container
- **const_iterator begin () const**

begining of the weight container

- `const_iterator end () const`
end of the weight container

Friends

- `class GenEvent`

9.73.1 Detailed Description

Container for the Weights associated with an event or vertex.

This class has both map-like and vector-like functionality. Named weights are now supported.

Definition at line 29 of file WeightContainer.h.

9.73.2 Member Typedef Documentation

9.73.2.1 `typedef std::vector<double>::const_iterator HepMC::WeightContainer::const_iterator`

`const iterator` for the weight container

Definition at line 38 of file WeightContainer.h.

9.73.2.2 `typedef std::vector<double>::iterator HepMC::WeightContainer::iterator`

`iterator` for the weight container

Definition at line 36 of file WeightContainer.h.

9.73.2.3 `typedef std::size_t HepMC::WeightContainer::size_type`

defining the size type used by vector and map

Definition at line 34 of file WeightContainer.h.

9.73.3 Constructor & Destructor Documentation

9.73.3.1 `HepMC::WeightContainer::WeightContainer (size_type n = 0, double value = 0.)` `[explicit]`

`default constructor`

Definition at line 22 of file WeightContainer.cc.

9.73.3.2 `HepMC::WeightContainer::WeightContainer (const std::vector< double > & weights)`

`construct from a vector of weights`

Definition at line 26 of file WeightContainer.cc.

References `size()`.

9.73.3.3 HepMC::WeightContainer::WeightContainer (const WeightContainer & *in*) [inline]

copy

Definition at line 141 of file WeightContainer.h.

9.73.3.4 HepMC::WeightContainer::~~WeightContainer () [inline]

Definition at line 145 of file WeightContainer.h.

9.73.4 Member Function Documentation

9.73.4.1 const double & HepMC::WeightContainer::back () const [inline]

returns the last element

Definition at line 192 of file WeightContainer.h.

9.73.4.2 double & HepMC::WeightContainer::back () [inline]

returns the last element

Definition at line 190 of file WeightContainer.h.

9.73.4.3 WeightContainer::const_iterator HepMC::WeightContainer::begin () const [inline]

beginning of the weight container

Definition at line 201 of file WeightContainer.h.

9.73.4.4 WeightContainer::iterator HepMC::WeightContainer::begin () [inline]

beginning of the weight container

Definition at line 195 of file WeightContainer.h.

Referenced by `write()`, and `HepMC::IO_AsciiParticles::write_event()`.

9.73.4.5 void HepMC::WeightContainer::clear () [inline]

clear the weight container

Definition at line 173 of file WeightContainer.h.

9.73.4.6 bool HepMC::WeightContainer::empty () const [inline]

return true if weight container is empty

Definition at line 171 of file WeightContainer.h.

Referenced by `main()`.

9.73.4.7 `WeightContainer::const_iterator HepMC::WeightContainer::end () const` [inline]

end of the weight container

Definition at line 204 of file `WeightContainer.h`.

9.73.4.8 `WeightContainer::iterator HepMC::WeightContainer::end ()` [inline]

end of the weight container

Definition at line 198 of file `WeightContainer.h`.

Referenced by `HepMC::GenVertex::print()`, `write()`, and `HepMC::IO_Ascii-Particles::write_event()`.

9.73.4.9 `const double & HepMC::WeightContainer::front () const` [inline]

returns the first element

Definition at line 187 of file `WeightContainer.h`.

9.73.4.10 `double & HepMC::WeightContainer::front ()` [inline]

returns the first element

Definition at line 185 of file `WeightContainer.h`.

9.73.4.11 `bool HepMC::WeightContainer::has_key (const std::string & s) const`

check to see if a name exists in the map

Definition at line 105 of file `WeightContainer.cc`.

Referenced by `main()`.

9.73.4.12 `bool HepMC::WeightContainer::operator!= (const WeightContainer &) const`

inequality

Definition at line 100 of file `WeightContainer.cc`.

9.73.4.13 `WeightContainer & HepMC::WeightContainer::operator= (const std::vector< double > & in)` [inline]

alternate assignment using a vector of doubles

best practices implementation

Definition at line 162 of file `WeightContainer.h`.

9.73.4.14 WeightContainer & HepMC::WeightContainer::operator= (const WeightContainer &)
[inline]

copy assignment

best practices implementation

Definition at line 154 of file WeightContainer.h.

9.73.4.15 bool HepMC::WeightContainer::operator== (const WeightContainer &) const

equality

Definition at line 92 of file WeightContainer.cc.

References `m_names`, `m_weights`, and `size()`.

9.73.4.16 const double & HepMC::WeightContainer::operator[] (const std::string & s) const

access the weight container

Definition at line 80 of file WeightContainer.cc.

9.73.4.17 double & HepMC::WeightContainer::operator[] (const std::string & s)

access the weight container

Definition at line 66 of file WeightContainer.cc.

9.73.4.18 const double & HepMC::WeightContainer::operator[] (size_type n) const [inline]

access the weight container

Definition at line 182 of file WeightContainer.h.

9.73.4.19 double & HepMC::WeightContainer::operator[] (size_type n) [inline]

access the weight container

Definition at line 179 of file WeightContainer.h.

9.73.4.20 void HepMC::WeightContainer::pop_back ()

pop from weight container

Definition at line 51 of file WeightContainer.cc.

References `size()`.

Referenced by `main()`.

9.73.4.21 void HepMC::WeightContainer::print (std::ostream & ostr = std::cout) const

print weights

Definition at line 111 of file WeightContainer.cc.

Referenced by `HepMC::GenEvent::print()`.

9.73.4.22 `void HepMC::WeightContainer::push_back (const double &)`

push onto weight container

Definition at line 42 of file `WeightContainer.cc`.

Referenced by `main()`.

9.73.4.23 `WeightContainer::size_type HepMC::WeightContainer::size () const` [inline]

size of weight container

Definition at line 169 of file `WeightContainer.h`.

Referenced by `main()`, `operator==()`, `pop_back()`, `HepMC::GenVertex::print()`, `HepMC::GenEvent::print()`, `WeightContainer()`, `HepMC::GenEvent::write()`, and `HepMC::IO_AsciiParticles::write_event()`.

9.73.4.24 `void HepMC::WeightContainer::swap (WeightContainer & other)` [inline]

swap

Definition at line 147 of file `WeightContainer.h`.

References `m_names`, and `m_weights`.

Referenced by `HepMC::GenVertex::swap()`, and `HepMC::GenEvent::swap()`.

9.73.4.25 `void HepMC::WeightContainer::write (std::ostream & ostr = std::cout) const`

write weights in a readable table

Definition at line 121 of file `WeightContainer.cc`.

References `begin()`, and `end()`.

Referenced by `main()`.

9.73.5 Friends And Related Function Documentation

9.73.5.1 `friend class GenEvent` [friend]

Definition at line 30 of file `WeightContainer.h`.

The documentation for this class was generated from the following files:

- `WeightContainer.h`
- `WeightContainer.cc`

Chapter 10

HepMC File Documentation

10.1 CompareGenEvent.cc File Reference

```
#include <iostream>
#include "HepMC/CompareGenEvent.h"
#include "HepMC/GenEvent.h"
```

Namespaces

- namespace **HepMC**

Functions

- `bool HepMC::compareGenEvent (GenEvent *, GenEvent *)`
- `bool HepMC::compareSignalProcessVertex (GenEvent *, GenEvent *)`
- `bool HepMC::compareBeamParticles (GenEvent *, GenEvent *)`
- `bool HepMC::compareWeights (GenEvent *, GenEvent *)`
- `bool HepMC::compareParticles (GenEvent *, GenEvent *)`
- `bool HepMC::compareVertices (GenEvent *, GenEvent *)`
- `bool HepMC::compareVertex (GenVertex *v1, GenVertex *v2)`

10.2 CompareGenEvent.h File Reference

```
#include <iostream>
#include "HepMC/GenEvent.h"
```

Namespaces

- namespace **HepMC**

Functions

- `bool HepMC::compareGenEvent (GenEvent *, GenEvent *)`
- `bool HepMC::compareSignalProcessVertex (GenEvent *, GenEvent *)`
- `bool HepMC::compareBeamParticles (GenEvent *, GenEvent *)`
- `bool HepMC::compareWeights (GenEvent *, GenEvent *)`
- `bool HepMC::compareVertices (GenEvent *, GenEvent *)`
- `bool HepMC::compareParticles (GenEvent *, GenEvent *)`
- `bool HepMC::compareVertex (GenVertex *v1, GenVertex *v2)`

10.3 enable_if.h File Reference

Namespaces

- namespace **HepMC**
- namespace **HepMC::detail**

Classes

- struct **HepMC::detail::enable_if**<, >
internal - used to decide if a class is arithmetic
- struct **HepMC::detail::enable_if**< true, T >
internal - use if class T is arithmetic
- struct **HepMC::detail::disable_if**<, >
internal - used by SimpleVector to decide if a class is arithmetic
- struct **HepMC::detail::disable_if**< false, T >
internal - used by SimpleVector to decide if a class is arithmetic

10.4 example_BuildEventFromScratch.cc File Reference

```
#include <iostream>
#include "VectorConversion.h"
#include "HepMC/GenEvent.h"
#include "CLHEP/Vector/LorentzVector.h"
```

Functions

- `int main()`

10.4.1 Function Documentation

10.4.1.1 `int main()`

Examples:

`example_BuildEventFromScratch.cc`, `example_EventSelection.cc`, `example_MyHerwig.cc`, `example_MyPythia.cc`, `example_MyPythiaOnlyToHepMC.cc`, `example_PythiaStreamIO.cc`, `example_UsingIterators.cc`, `testFlow.cc`, `testHepMC.cc.in`, `testHepMCIteration.cc.in`, `testHerwigCopies.cc`, `testMass.cc.in`, `testMultipleCopies.cc.in`, `testPrintBug.cc`, `testPythiaCopies.cc`, `testSimpleVector.cc`, `testStreamIO.cc.in`, and `testUnits.cc`.

Definition at line 25 of file `example_BuildEventFromScratch.cc`.

References `HepMC::GenVertex::add_particle_in()`, `HepMC::GenVertex::add_particle_out()`, `HepMC::GenEvent::add_vertex()`, `convertTo()`, `HepMC::Units::GEV`, `HepMC::Units::MM`, `p`, `HepMC::GenEvent::particles_begin()`, `HepMC::GenEvent::particles_end()`, `HepMC::GenEvent::print()`, `HepMC::GenEvent::set_signal_process_vertex()`, and `HepMC::GenEvent::use_units()`.

10.5 example_EventSelection.cc File Reference

```
#include "HepMC/IO_GenEvent.h"  
#include "HepMC/GenEvent.h"
```

Classes

- class **IsEventGood**
example class

Functions

- int **main()**

10.5.1 Function Documentation

10.5.1.1 int main()

Definition at line 37 of file example_EventSelection.cc.

References `HepMC::GenEvent::event_number()`, and `HepMC::IO_BaseClass::read_next_event()`.

10.6 example_MyHerwig.cc File Reference

```
#include <iostream>
#include "HepMC/HerwigWrapper.h"
#include "HepMC/IO_HERWIG.h"
#include "HepMC/IO_GenEvent.h"
#include "HepMC/GenEvent.h"
#include "HepMC/HEPEVT_Wrapper.h"
```

Functions

- `int main ()`

10.6.1 Function Documentation

10.6.1.1 `int main ()`

To Compile: go to the **HepMC** (p.23) directory and type: `gmake examples/example_MyHerwig.exe`

In this example the precision and number of entries for the HEPEVT fortran common block are explicitly defined to correspond to those used in the Herwig version of the HEPEVT common block. If you get funny output from HEPEVT in your own code, probably you have set these values incorrectly!

Definition at line 24 of file `example_MyHerwig.cc`.

References `HepMC::getHerwigCrossSection()`, `HepMC::Units::GEV`, `hwbgen`, `hwbmch`, `hwcdec`, `hwcfor`, `hwdhad`, `hwdhob`, `hwdhvy`, `hwefin`, `hweini`, `hwepro`, `hwevnt`, `hwigin`, `hwmevt`, `hwproc`, `hwufne`, `hwuinc`, `hwuine`, `HepMC::Units::MM`, `HepMC::GenEvent::print()`, `HepMC::HEPEVT_Wrapper::print_hepevt()`, `HepMC::IO_BaseClass::read_next_event()`, `HepMC::GenEvent::set_cross_section()`, `HepMC::GenEvent::set_event_number()`, `HepMC::HEPEVT_Wrapper::set_max_number_entries()`, `HepMC::GenEvent::set_signal_process_id()`, `HepMC::HEPEVT_Wrapper::set_sizeof_real()`, and `HepMC::GenEvent::use_units()`.

10.7 example_MyPythia.cc File Reference

```
#include <iostream>
#include "HepMC/PythiaWrapper.h"
#include "HepMC/IO_HEPEVT.h"
#include "HepMC/IO_GenEvent.h"
#include "HepMC/IO_AsciiParticles.h"
#include "HepMC/GenEvent.h"
#include "PythiaHelper.h"
```

Classes

- `class IsGoodEventMyPythia`
example class

Functions

- `void pythia_out ()`
- `void pythia_in ()`
- `void pythia_in_out ()`
- `void event_selection ()`
- `void pythia_particle_out ()`
- `int main ()`

10.7.1 Function Documentation

10.7.1.1 `void event_selection ()`

Examples:

example_MyPythia.cc.

Definition at line 152 of file example_MyPythia.cc.

References `HepMC::getPythiaCrossSection()`, `HepMC::Units::GEV`, `initPythia()`, `HepMC::Units::MM`, `pypars`, `HepMC::IO_BaseClass::read_next_event()`, `HepMC::GenEvent::set_cross_section()`, `HepMC::HEPEVT_Wrapper::set_max_number_entries()`, `HepMC::GenEvent::set_mpi()`, `HepMC::HEPEVT_Wrapper::set_sizeof_real()`, and `HepMC::GenEvent::use_units()`.

Referenced by `main()`.

10.7.1.2 `int main ()`

Definition at line 85 of file example_MyPythia.cc.

References `event_selection()`, `pythia_in()`, `pythia_in_out()`, and `pythia_out()`.

10.7.1.3 void pythia_in ()

Examples:

example_MyPythia.cc.

Definition at line 205 of file example_MyPythia.cc.

References HepMC::GenEvent::event_number(), and HepMC::IO_BaseClass::read_next_event().

Referenced by main().

10.7.1.4 void pythia_in_out ()

Examples:

example_MyPythia.cc.

Definition at line 239 of file example_MyPythia.cc.

References HepMC::GenEvent::event_number(), HepMC::getPythiaCrossSection(), HepMC::Units::GEV, initPythia(), HepMC::Units::MM, HepMC::IO_BaseClass::read_next_event(), HepMC::GenEvent::set_cross_section(), HepMC::GenEvent::set_event_number(), HepMC::HEPEVT_Wrapper::set_max_number_entries(), HepMC::GenEvent::set_signal_process_id(), HepMC::HEPEVT_Wrapper::set_sizeof_real(), and HepMC::GenEvent::use_units().

Referenced by main().

10.7.1.5 void pythia_out ()

Examples:

example_MyPythia.cc.

Definition at line 99 of file example_MyPythia.cc.

References HepMC::getPythiaCrossSection(), HepMC::Units::GEV, initPythia(), HepMC::Units::MM, pypars, HepMC::IO_BaseClass::read_next_event(), HepMC::GenEvent::set_cross_section(), HepMC::GenEvent::set_event_number(), HepMC::HEPEVT_Wrapper::set_max_number_entries(), HepMC::GenEvent::set_mpi(), HepMC::GenEvent::set_signal_process_id(), HepMC::HEPEVT_Wrapper::set_sizeof_real(), and HepMC::GenEvent::use_units().

Referenced by main().

10.7.1.6 void pythia_particle_out ()

Examples:

example_MyPythia.cc.

Definition at line 311 of file example_MyPythia.cc.

References HepMC::getPythiaCrossSection(), HepMC::Units::GEV, initPythia(), HepMC::Units::MM, HepMC::IO_BaseClass::read_next_event(), HepMC::GenEvent::set_cross_section(), HepMC::GenEvent::set_event_number(), HepMC::HEPEVT_Wrapper::set_max_number_entries(), HepMC::GenEvent::set_signal_process_id(), HepMC::HEPEVT_Wrapper::set_sizeof_real(), and HepMC::GenEvent::use_units().

10.8 example_MyPythiaOnlyToHepMC.cc File Reference

```
#include <iostream>
#include "HepMC/PythiaWrapper.h"
#include "HepMC/IO_HEPEVT.h"
#include "HepMC/GenEvent.h"
#include "PythiaHelper.h"
```

Functions

- `int main()`

10.8.1 Function Documentation

10.8.1.1 `int main()`

Definition at line 23 of file `example_MyPythiaOnlyToHepMC.cc`.

References `HepMC::getPythiaCrossSection()`, `HepMC::Units::GEV`, `initPythia()`, `HepMC::Units::MM`, `pypars`, `HepMC::IO_BaseClass::read_next_event()`, `HepMC::GenEvent::set_cross_section()`, `HepMC::HEPEVT_Wrapper::set_max_number_entries()`, `HepMC::GenEvent::set_mpi()`, `HepMC::HEPEVT_Wrapper::set_sizeof_real()`, and `HepMC::GenEvent::use_units()`.

10.9 example_PythiaStreamIO.cc File Reference

```
#include <fstream>
#include <iostream>
#include "HepMC/PythiaWrapper.h"
#include "HepMC/IO_HEPEVT.h"
#include "HepMC/GenEvent.h"
#include "PythiaHelper.h"
```

Functions

- void **writePythiaStreamIO** ()
- void **readPythiaStreamIO** ()
- int **main** ()

10.9.1 Function Documentation

10.9.1.1 int main ()

Definition at line 31 of file example_PythiaStreamIO.cc.

References **readPythiaStreamIO()**, and **writePythiaStreamIO()**.

10.9.1.2 void readPythiaStreamIO ()

Examples:

example_PythiaStreamIO.cc.

Definition at line 103 of file example_PythiaStreamIO.cc.

References **HepMC::GenEvent::cross_section()**, **HepMC::GenEvent::is_valid()**, **HepMC::GenEvent::read()**, **HepMC::GenEvent::write()**, **HepMC::write_HepMC_IO_block_begin()**, and **HepMC::write_HepMC_IO_block_end()**.

Referenced by **main()**.

10.9.1.3 void writePythiaStreamIO ()

example of generating events with Pythia using **HepMC/PythiaWrapper.h** (p.341) Events are read into the **HepMC** (p.23) event record from the FORTRAN HEPEVT common block using the **IO_HEPEVT** strategy

To Compile: go to the **HepMC** (p.23) example directory and type: make **example_PythiaStreamIO.exe**

This example uses streaming I/O **writePythiaStreamIO()** (p.277) sets the cross section in GenRun **readPythiaStreamIO()** (p.277) reads the file written by **writePythiaStreamIO()** (p.277)

Examples:**example_PythiaStreamIO.cc.**

Definition at line 40 of file example_PythiaStreamIO.cc.

References HepMC::getPythiaCrossSection(), HepMC::Units::GEV, initPythia(), HepMC::Units::MM, pypars, HepMC::IO_BaseClass::read_next_event(), HepMC::GenEvent::set_cross_section(), HepMC::GenEvent::set_event_number(), HepMC::HEPEVT_Wrapper::set_max_number_entries(), HepMC::GenEvent::set_mpi(), HepMC::GenEvent::set_signal_process_id(), HepMC::HEPEVT_Wrapper::set_sizeof_real(), HepMC::GenEvent::use_units(), HepMC::write_HepMC_IO_block_begin(), and HepMC::write_HepMC_IO_block_end().

Referenced by main().

10.10 example_UsingIterators.cc File Reference

```
#include "HepMC/IO_GenEvent.h"
#include "HepMC/GenEvent.h"
#include <math.h>
#include <algorithm>
#include <list>
```

Classes

- `class IsPhoton`
example class
- `class IsW_Boson`
example class
- `class IsStateFinal`
example class

Functions

- `int main()`

10.10.1 Function Documentation

10.10.1.1 `int main()`

Definition at line 56 of file `example_UsingIterators.cc`.

References `HepMC::copy_if()`, `HepMC::descendants`, `p`, `HepMC::parents`, `HepMC::GenEvent::particles_begin()`, `HepMC::GenEvent::particles_end()`, `HepMC::IO_GenEvent::rdstate()`, `HepMC::IO_BaseClass::read_next_event()`, `v`, `HepMC::GenEvent::vertices_begin()`, and `HepMC::GenEvent::vertices_end()`.

10.11 filterEvent.cc File Reference

```
#include "HepMC/GenEvent.h"
```

Functions

- `void filterEvent (HepMC::GenEvent *ge)`

10.11.1 Function Documentation

10.11.1.1 void filterEvent (HepMC::GenEvent *ge)

Definition at line 5 of file filterEvent.cc.

References `HepMC::GenEvent::beam_particles()`, `HepMC::GenEvent::particles_begin()`, `HepMC::GenEvent::particles_end()`, `HepMC::GenVertex::particles_out_const_begin()`, `HepMC::GenVertex::particles_out_const_end()`, `HepMC::GenVertex::particles_out_size()`, `HepMC::GenVertex::remove_particle()`, `HepMC::GenEvent::vertices_begin()`, and `HepMC::GenEvent::vertices_end()`.

10.12 Flow.cc File Reference

```
#include "HepMC/Flow.h"  
#include "HepMC/GenParticle.h"  
#include "HepMC/GenVertex.h"  
#include "HepMC/SearchVector.h"
```

Namespaces

- namespace **HepMC**

Functions

- `std::ostream & HepMC::operator<< (std::ostream &ostr, const Flow &f)`
for printing

10.13 Flow.h File Reference

```
#include <iostream>
#include <map>
#include <vector>
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::Flow**
The flow object.

10.14 GenCrossSection.cc File Reference

```
#include <iostream>
#include <sstream>
#include "HepMC/GenCrossSection.h"
#include "HepMC/IO_Exception.h"
```

Namespaces

- namespace **HepMC**

10.15 GenCrossSection.h File Reference

```
#include <iostream>
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::GenCrossSection**

*The **GenCrossSection** (p. 69) class stores the generated cross section.*

Functions

- `std::ostream & HepMC::operator<< (std::ostream &os, GenCrossSection &xs)`
- `std::istream & HepMC::operator>> (std::istream &is, GenCrossSection &xs)`

10.16 GenEvent.cc File Reference

```
#include <iomanip>
#include "HepMC/GenEvent.h"
#include "HepMC/GenCrossSection.h"
#include "HepMC/Version.h"
#include "HepMC/StreamHelpers.h"
```

Namespaces

- namespace **HepMC**

10.17 GenEvent.h File Reference

```
#include "HepMC/GenVertex.h"
#include "HepMC/GenParticle.h"
#include "HepMC/WeightContainer.h"
#include "HepMC/GenCrossSection.h"
#include "HepMC/HeavyIon.h"
#include "HepMC/PdfInfo.h"
#include "HepMC/Units.h"
#include "HepMC/HepMCDefs.h"
#include <map>
#include <string>
#include <vector>
#include <algorithm>
#include <iostream>
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::GenEvent**
The GenEvent (p. 73) class is the core of HepMC (p. 23).
- class **HepMC::GenEvent::vertex_const_iterator**
const vertex iterator
- class **HepMC::GenEvent::vertex_iterator**
non-const vertex iterator
- class **HepMC::GenEvent::particle_const_iterator**
const particle iterator
- class **HepMC::GenEvent::particle_iterator**
non-const particle iterator

Functions

- `template<class InputIterator, class OutputIterator, class Predicate> void HepMC::copy_if (InputIterator first, InputIterator last, OutputIterator out, Predicate pred)`
define the type of iterator to use

- **std::ostream & HepMC::operator<< (std::ostream &, GenEvent &)**
standard streaming IO output operator
- **std::istream & HepMC::operator>> (std::istream &, GenEvent &)**
standard streaming IO input operator
- **std::istream & HepMC::set_input_units (std::istream &, Units::MomentumUnit, Units::LengthUnit)**
set the units for this input stream
- **std::ostream & HepMC::write_HepMC_IO_block_begin (std::ostream &)**
Explicitly write the begin block lines that IO_GenEvent (p. 184) uses.
- **std::ostream & HepMC::write_HepMC_IO_block_end (std::ostream &)**
Explicitly write the end block line that IO_GenEvent (p. 184) uses.
- **GenEvent & HepMC::convert_units (GenEvent &evt, Units::MomentumUnit m, Units::LengthUnit l)**

10.18 GenEventStreamIO.cc File Reference

```
#include <iostream>
#include <ostream>
#include <istream>
#include <sstream>
#include "HepMC/GenEvent.h"
#include "HepMC/GenCrossSection.h"
#include "HepMC/StreamInfo.h"
#include "HepMC/StreamHelpers.h"
#include "HepMC/Version.h"
#include "HepMC/IO_Exception.h"
```

Namespaces

- namespace **HepMC**
- namespace **HepMC::detail**

Functions

- **void HepMC::HepMCStreamCallback (std::ios_base::event e, std::ios_base &b, int i)**
- **template<class IO> StreamInfo & HepMC::get_stream_info (IO &iost)**
- **std::ostream & HepMC::operator<< (std::ostream &, GenEvent &)**
standard streaming IO output operator
- **std::istream & HepMC::operator>> (std::istream &, GenEvent &)**
standard streaming IO input operator
- **std::istream & HepMC::set_input_units (std::istream &, Units::MomentumUnit, Units::LengthUnit)**
set the units for this input stream
- **std::ostream & HepMC::write_HepMC_IO_block_begin (std::ostream &)**
Explicitly write the begin block lines that IO_GenEvent (p. 184) uses.
- **std::ostream & HepMC::write_HepMC_IO_block_end (std::ostream &)**
Explicitly write the end block line that IO_GenEvent (p. 184) uses.
- **std::ostream & HepMC::establish_output_stream_info (std::ostream &os)**
used by IO_GenEvent (p. 184) constructor
- **std::istream & HepMC::establish_input_stream_info (std::istream &is)**
used by IO_GenEvent (p. 184) constructor
- **std::istream & HepMC::detail::read_particle (std::istream &, TempParticleMap &, GenParticle *)**

- `std::istream & HepMC::detail::read_units (std::istream &is, GenEvent &evt)`
- `std::ostream & HepMC::detail::establish_output_stream_info (std::ostream &)`
used by `IO_GenEvent` (p. 184) constructor
- `std::istream & HepMC::detail::establish_input_stream_info (std::istream &)`
used by `IO_GenEvent` (p. 184) constructor

10.19 GenParticle.cc File Reference

```
#include "HepMC/GenEvent.h"  
#include "HepMC/GenVertex.h"  
#include "HepMC/GenParticle.h"  
#include <iomanip>
```

Namespaces

- namespace **HepMC**

Functions

- `std::ostream & HepMC::operator<< (std::ostream &ostr, const GenParticle &part)`
print particle

10.20 GenParticle.h File Reference

```
#include "HepMC/Flow.h"
#include "HepMC/Polarization.h"
#include "HepMC/SimpleVector.h"
#include "HepMC/IteratorRange.h"
#include <iostream>
#include <stdint.h>
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::GenParticle**
The GenParticle (p. 111) class contains information about generated particles.

Defines

- #define **hepmc_uint64_t** uint64_t

10.20.1 Define Documentation

10.20.1.1 #define hepmc_uint64_t uint64_t

Definition at line 38 of file GenParticle.h.

10.21 GenRanges.cc File Reference

```
#include <iostream>
#include "HepMC/GenRanges.h"
#include "HepMC/GenEvent.h"
#include "HepMC/GenVertex.h"
```

Namespaces

- namespace **HepMC**

10.22 GenRanges.h File Reference

```
#include <stdexcept>
#include "HepMC/GenEvent.h"
#include "HepMC/GenVertex.h"
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::GenEventVertexRange**
GenEventVertexRange (p. 110) acts like a collection of vertices.
- class **HepMC::ConstGenEventVertexRange**
ConstGenEventVertexRange (p. 45) acts like a collection of vertices.
- class **HepMC::GenEventParticleRange**
GenEventParticleRange (p. 109) acts like a collection of particles.
- class **HepMC::ConstGenEventParticleRange**
ConstGenEventParticleRange (p. 43) acts like a collection of particles.
- class **HepMC::GenVertexParticleRange**
GenVertexParticleRange (p. 151) acts like a collection of particles.
- class **HepMC::GenParticleProductionRange**
GenParticleProductionRange (p. 124) acts like a collection of particles.
- class **HepMC::ConstGenParticleProductionRange**
- class **HepMC::GenParticleEndRange**
GenParticleEndRange (p. 122) acts like a collection of particles.
- class **HepMC::ConstGenParticleEndRange**

10.23 GenVertex.cc File Reference

```
#include "HepMC/GenParticle.h"
#include "HepMC/GenVertex.h"
#include "HepMC/GenEvent.h"
#include "HepMC/SearchVector.h"
#include <iomanip>
```

Namespaces

- namespace **HepMC**

Functions

- `std::ostream & HepMC::operator<< (std::ostream &ostr, const GenVertex &vtx)`
print vertex information

10.24 GenVertex.h File Reference

```
#include "HepMC/WeightContainer.h"
#include "HepMC/SimpleVector.h"
#include "HepMC/IteratorRange.h"
#include <iostream>
#include <iterator>
#include <vector>
#include <set>
#include <algorithm>
#include <cstdint>
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::GenVertex**
GenVertex (p. 126) contains information about decay vertices.
- class **HepMC::GenVertex::edge_iterator**
edge iterator
- class **HepMC::GenVertex::vertex_iterator**
vertex iterator
- class **HepMC::GenVertex::particle_iterator**
particle iterator

10.25 HeavyIon.cc File Reference

```
#include <iostream>
#include <ostream>
#include <istream>
#include <sstream>
#include "HepMC/HeavyIon.h"
#include "HepMC/StreamHelpers.h"
#include "HepMC/IO_Exception.h"
```

Namespaces

- namespace **HepMC**

Functions

- `std::ostream & HepMC::operator<< (std::ostream &, HeavyIon const *)`
Write the contents of HeavyIon (p. 152) to an output stream.
- `std::istream & HepMC::operator>> (std::istream &, HeavyIon *)`
Read the contents of HeavyIon (p. 152) from an input stream.

10.26 HeavyIon.h File Reference

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::HeavyIon**
The HeavyIon (p. 152) class stores information about heavy ions.

Functions

- **std::ostream & HepMC::operator<< (std::ostream &, HeavyIon const *)**
Write the contents of HeavyIon (p. 152) to an output stream.
- **std::istream & HepMC::operator>> (std::istream &, HeavyIon *)**
Read the contents of HeavyIon (p. 152) from an input stream.

10.27 HEPEVT_Wrapper.cc File Reference

```
#include "HepMC/HEPEVT_Wrapper.h"
```

Namespaces

- namespace **HepMC**

10.28 HEPEVT_Wrapper.h File Reference

```
#include <ctype.h>
#include <iostream>
#include <cstdio>
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::HEPEVT_Wrapper**
Generic Wrapper for the fortran HEPEVT common block.

Defines

- #define **HEPEVT_EntriesAllocation 10000**
- #define **hepevt hepevt_**

Variables

- const unsigned int **hepevt_bytes_allocation**
- struct {
 char data [hepevt_bytes_allocation]
} **hepevt_**

10.28.1 Define Documentation

10.28.1.1 #define hepevt hepevt_

Definition at line 84 of file HEPEVT_Wrapper.h.

Referenced by `HepMC::HEPEVT_Wrapper::byte_num_to_double()`, `HepMC::HEPEVT_Wrapper::byte_num_to_int()`, and `HepMC::HEPEVT_Wrapper::write_byte_num()`.

10.28.1.2 #define HEPEVT_EntriesAllocation 10000

Definition at line 4 of file HEPEVT_Wrapper.h.

10.28.2 Variable Documentation

10.28.2.1 char data[hepevt_bytes_allocation]

Definition at line 81 of file HEPEVT_Wrapper.h.

10.28.2.2 struct { ... } hepevt_**10.28.2.3 const unsigned int hepevt_bytes_allocation****Initial value:**

```
sizeof(long int) * ( 2 + 6 * HEPEVT_EntriesAllocation )  
+ sizeof(double) * ( 9 * HEPEVT_EntriesAllocation )
```

Definition at line 66 of file HEPEVT_Wrapper.h.

Referenced by `HepMC::HEPEVT_Wrapper::byte_num_to_double()`, `HepMC::HEPEVT_Wrapper::byte_num_to_int()`, and `HepMC::HEPEVT_Wrapper::write_byte_num()`.

10.29 HepMCDefs.h File Reference

Defines

- `#define HEPMC_VERSION "2.06.05"`

10.29.1 Define Documentation

10.29.1.1 `#define HEPMC_VERSION "2.06.05"`

Definition at line 65 of file HepMCDefs.h.

Referenced by `HepMC::versionName()`.

10.30 HerwigWrapper.cc File Reference

```
#include <cmath>
#include "HepMC/HerwigWrapper.h"
#include "HepMC/GenCrossSection.h"
```

Namespaces

- namespace **HepMC**

Functions

- GenCrossSection **HepMC::getHerwigCrossSection (int ngen)**

Variables

- hwgev hwevnt_

10.30.1 Variable Documentation

10.30.1.1 struct hwgev hwevnt_

Definition at line 20 of file HerwigWrapper.cc.

10.31 HerwigWrapper.h File Reference

```
#include <ctype.h>
#include "HepMC/GenCrossSection.h"
```

Classes

- struct **hwgev**

Defines

- #define **hwproc** **hwproc_**
- #define **hwbeam** **hwbeam_**
- #define **hwbmch** **hwbmch_**
- #define **hwevnt** **hwevnt_**
- #define **hwpram** **hwpram_**
- #define **hwigin** **hwigin_**
- #define **hwigup** **hwigup_**
- #define **hwuinc** **hwuinc_**
- #define **hwusta** **hwusta_**
- #define **hweini** **hweini_**
- #define **hwuine** **hwuine_**
- #define **hwepro** **hwepro_**
- #define **hwupro** **hwupro_**
- #define **hwbgen** **hwbgen_**
- #define **hwdhob** **hwdhob_**
- #define **hwcfor** **hwcfor_**
- #define **hwcdec** **hwcdec_**
- #define **hwdhad** **hwdhad_**
- #define **hwdhvy** **hwdhvy_**
- #define **hwmevt** **hwmevt_**
- #define **hwufne** **hwufne_**
- #define **hwefin** **hwefin_**
- #define **hwudpr** **hwudpr_**
- #define **hwuepr** **hwuepr_**
- #define **hwupup** **hwupup_**
- #define **hwegup** **hwegup_**
- #define **hwudat** **hwudat_**

Variables

- struct {
 double **EBEAM1**
 double **EBEAM2**
 double **PBEAM1**
 double **PBEAM2**
 int **IPROC**
 int **MAXEV**
} **hwproc_**

```

• struct {
    int  IPART1
    int  IPART2
} hwbeam_

• struct {
    char PART1 [8]
    char PART2 [8]
} hwbmch_

• const int herwig_hepevt_size = 4000
• hwgev hwevnt_
• struct {
    double AFCH [2][16]
    double ALPHEM
    double B1LIM
    double BETAF
    double BTCLM
    double CAFAC
    double CFFAC
    double CLMAX
    double CLPOW
    double CLSMR [2]
    double CSPEED
    double ENSOF
    double ETAMIX
    double F0MIX
    double F1MIX
    double F2MIX
    double GAMH
    double GAMW
    double GAMZ
    double GAMZP
    double GEV2NB
    double H1MIX
    double PDIQK
    double PGSMX
    double PGSPL [4]
    double PHIMIX
    double PIFAC
    double PRSOF
    double PSPLT [2]
    double PTRMS
    double PXRMS
    double QC DL3
    double QC DL5
    double QC DLAM
    double QDIQK
    double QFCH [16]
    double QG
    double QSPAC
    double QV
    double SCABI
    double SWEIN

```

```
double TMTOP
double VFCH [2][16]
double VCKM [3][3]
double VGCUT
double VQCUT
double VPCUT
double ZBINM
double EFFMIN
double OMHMIX
double ET2MIX
double PH3MIX
double GCUTME
int IOPREM
int IPRINT
int ISPAC
int LRSUD
int LWSUD
int MODPDF [2]
int NBTRY
int NCOLO
int NCTRY
int NDTRY
int NETRY
int NFLAV
int NGSPL
int NSTRU
int NSTRY
int NZBIN
int IOP4JT [2]
int NPRFMT
int AZSOFT
int AZSPIN
int CLDIR [2]
int HARDME
int NOSPAC
int PRNDEC
int PRVTX
int SOFTME
int ZPRIME
int PRNDEF
int PRNTEX
int PRNWEB
} hwpram_
```

10.31.1 Define Documentation

10.31.1.1 #define hwbeam hwbeam_

Definition at line 40 of file HerwigWrapper.h.

10.31.1.2 `#define hwbgen hwbgen_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 104 of file `HerwigWrapper.h`.

Referenced by `main()`.

10.31.1.3 `#define hwbmch hwbmch_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 49 of file `HerwigWrapper.h`.

Referenced by `main()`.

10.31.1.4 `#define hwcdec hwcdec_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 107 of file `HerwigWrapper.h`.

Referenced by `main()`.

10.31.1.5 `#define hwcfor hwcfor_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 106 of file `HerwigWrapper.h`.

Referenced by `main()`.

10.31.1.6 `#define hwdhad hwdhad_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 108 of file `HerwigWrapper.h`.

Referenced by `main()`.

10.31.1.7 `#define hwdhob hwdhob_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 105 of file HerwigWrapper.h.

Referenced by `main()`.

10.31.1.8 `#define hwdhvy hwdhvy_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 109 of file HerwigWrapper.h.

Referenced by `main()`.

10.31.1.9 `#define hwefin hwefin_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 112 of file HerwigWrapper.h.

Referenced by `main()`.

10.31.1.10 `#define hwegup hwegup_`

Definition at line 117 of file HerwigWrapper.h.

10.31.1.11 `#define hweini hweini_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 100 of file HerwigWrapper.h.

Referenced by `main()`.

10.31.1.12 `#define hwepro hwepro_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 102 of file HerwigWrapper.h.

Referenced by `main()`.

10.31.1.13 `#define hwevnt hwevnt_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 63 of file HerwigWrapper.h.

Referenced by `HepMC::getHerwigCrossSection()`, and `main()`.

10.31.1.14 #define hwigin hwigin_**Examples:**

example_MyHerwig.cc, and testHerwigCopies.cc.

Definition at line 96 of file HerwigWrapper.h.

Referenced by main().

10.31.1.15 #define hwigup hwigup_

Definition at line 97 of file HerwigWrapper.h.

10.31.1.16 #define hwmevt hwmevt_**Examples:**

example_MyHerwig.cc, and testHerwigCopies.cc.

Definition at line 110 of file HerwigWrapper.h.

Referenced by main().

10.31.1.17 #define hwpram hwpram_

Definition at line 91 of file HerwigWrapper.h.

10.31.1.18 #define hwproc hwproc_**Examples:**

example_MyHerwig.cc, and testHerwigCopies.cc.

Definition at line 32 of file HerwigWrapper.h.

Referenced by main().

10.31.1.19 #define hwudat hwudat_**10.31.1.20 #define hwudpr hwudpr_**

Definition at line 114 of file HerwigWrapper.h.

10.31.1.21 #define hwuepr hwuepr_

Definition at line 115 of file HerwigWrapper.h.

10.31.1.22 #define hwufne hwufne_**Examples:**

example_MyHerwig.cc, and testHerwigCopies.cc.

Definition at line 111 of file HerwigWrapper.h.
Referenced by `main()`.

10.31.1.23 `#define hwuinc hwuinc_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 98 of file HerwigWrapper.h.
Referenced by `main()`.

10.31.1.24 `#define hwuine hwuine_`

Examples:

`example_MyHerwig.cc`, and `testHerwigCopies.cc`.

Definition at line 101 of file HerwigWrapper.h.
Referenced by `main()`.

10.31.1.25 `#define hwupro hwupro_`

Definition at line 103 of file HerwigWrapper.h.

10.31.1.26 `#define hwupup hwupup_`

Definition at line 116 of file HerwigWrapper.h.

10.31.1.27 `#define hwusta hwusta_`

Definition at line 99 of file HerwigWrapper.h.

10.31.2 Variable Documentation

10.31.2.1 `double AFCH[2][16]`

Definition at line 79 of file HerwigWrapper.h.

10.31.2.2 `double ALPHEM`

Definition at line 79 of file HerwigWrapper.h.

10.31.2.3 `int AZSOFT`

Definition at line 87 of file HerwigWrapper.h.

10.31.2.4 int AZSPIN

Definition at line 87 of file HerwigWrapper.h.

10.31.2.5 double B1LIM

Definition at line 79 of file HerwigWrapper.h.

10.31.2.6 double BETAF

Definition at line 79 of file HerwigWrapper.h.

10.31.2.7 double BTCLM

Definition at line 79 of file HerwigWrapper.h.

10.31.2.8 double CAFAC

Definition at line 79 of file HerwigWrapper.h.

10.31.2.9 double CFFAC

Definition at line 79 of file HerwigWrapper.h.

10.31.2.10 int CLDIR[2]

Definition at line 87 of file HerwigWrapper.h.

10.31.2.11 double CLMAX

Definition at line 79 of file HerwigWrapper.h.

10.31.2.12 double CLPOW

Definition at line 79 of file HerwigWrapper.h.

10.31.2.13 double CLSMR[2]

Definition at line 79 of file HerwigWrapper.h.

10.31.2.14 double CSPEED

Definition at line 79 of file HerwigWrapper.h.

10.31.2.15 double EBEAM1

Definition at line 28 of file HerwigWrapper.h.

10.31.2.16 double EBEAM2

Definition at line 28 of file HerwigWrapper.h.

10.31.2.17 double EFFMIN

Definition at line 79 of file HerwigWrapper.h.

10.31.2.18 double ENSOF

Definition at line 79 of file HerwigWrapper.h.

10.31.2.19 double ET2MIX

Definition at line 79 of file HerwigWrapper.h.

10.31.2.20 double ETAMIX

Definition at line 79 of file HerwigWrapper.h.

10.31.2.21 double F0MIX

Definition at line 79 of file HerwigWrapper.h.

10.31.2.22 double F1MIX

Definition at line 79 of file HerwigWrapper.h.

10.31.2.23 double F2MIX

Definition at line 79 of file HerwigWrapper.h.

10.31.2.24 double GAMH

Definition at line 79 of file HerwigWrapper.h.

10.31.2.25 double GAMW

Definition at line 79 of file HerwigWrapper.h.

10.31.2.26 double GAMZ

Definition at line 79 of file HerwigWrapper.h.

10.31.2.27 double GAMZP

Definition at line 79 of file HerwigWrapper.h.

10.31.2.28 double GCUTME

Definition at line 79 of file HerwigWrapper.h.

10.31.2.29 double GEV2NB

Definition at line 79 of file HerwigWrapper.h.

10.31.2.30 double H1MIX

Definition at line 79 of file HerwigWrapper.h.

10.31.2.31 int HARDME

Definition at line 87 of file HerwigWrapper.h.

10.31.2.32 const int herwig_hepevt_size = 4000

Definition at line 54 of file HerwigWrapper.h.

10.31.2.33 struct { ... } hwbeam_**10.31.2.34 struct { ... } hwbmch_****10.31.2.35 struct hwgev hwevnt_****10.31.2.36 struct { ... } hwpram_****10.31.2.37 struct { ... } hwproc_****10.31.2.38 int IOP4JT[2]**

Definition at line 85 of file HerwigWrapper.h.

10.31.2.39 int IOPREM

Definition at line 85 of file HerwigWrapper.h.

10.31.2.40 int IPART1

Definition at line 37 of file HerwigWrapper.h.

10.31.2.41 int IPART2

Definition at line 37 of file HerwigWrapper.h.

10.31.2.42 int IPRINT

Definition at line 85 of file HerwigWrapper.h.

10.31.2.43 int IPROC

Definition at line 29 of file HerwigWrapper.h.

10.31.2.44 int ISPAC

Definition at line 85 of file HerwigWrapper.h.

10.31.2.45 int LRSUD

Definition at line 85 of file HerwigWrapper.h.

10.31.2.46 int LWSUD

Definition at line 85 of file HerwigWrapper.h.

10.31.2.47 int MAXEV

Definition at line 29 of file HerwigWrapper.h.

10.31.2.48 int MODPDF[2]

Definition at line 85 of file HerwigWrapper.h.

10.31.2.49 int NBTRY

Definition at line 85 of file HerwigWrapper.h.

10.31.2.50 int NCOLO

Definition at line 85 of file HerwigWrapper.h.

10.31.2.51 int NCTRY

Definition at line 85 of file HerwigWrapper.h.

10.31.2.52 int NDTRY

Definition at line 85 of file HerwigWrapper.h.

10.31.2.53 int NETRY

Definition at line 85 of file HerwigWrapper.h.

10.31.2.54 int NFLAV

Definition at line 85 of file HerwigWrapper.h.

10.31.2.55 int NGSPL

Definition at line 85 of file HerwigWrapper.h.

10.31.2.56 int NOSPAC

Definition at line 87 of file HerwigWrapper.h.

10.31.2.57 int NPRFMT

Definition at line 85 of file HerwigWrapper.h.

10.31.2.58 int NSTRU

Definition at line 85 of file HerwigWrapper.h.

10.31.2.59 int NSTRY

Definition at line 85 of file HerwigWrapper.h.

10.31.2.60 int NZBIN

Definition at line 85 of file HerwigWrapper.h.

10.31.2.61 double OMHMIX

Definition at line 79 of file HerwigWrapper.h.

10.31.2.62 char PART1[8]

Definition at line 46 of file HerwigWrapper.h.

10.31.2.63 char PART2[8]

Definition at line 46 of file HerwigWrapper.h.

10.31.2.64 double PBEAM1

Definition at line 28 of file HerwigWrapper.h.

10.31.2.65 double PBEAM2

Definition at line 28 of file HerwigWrapper.h.

10.31.2.66 double PDIQK

Definition at line 79 of file HerwigWrapper.h.

10.31.2.67 double PGSMX

Definition at line 79 of file HerwigWrapper.h.

10.31.2.68 double PGSPL[4]

Definition at line 79 of file HerwigWrapper.h.

10.31.2.69 double PH3MIX

Definition at line 79 of file HerwigWrapper.h.

10.31.2.70 double PHIMIX

Definition at line 79 of file HerwigWrapper.h.

10.31.2.71 double PIFAC

Definition at line 79 of file HerwigWrapper.h.

10.31.2.72 int PRNDEC

Definition at line 87 of file HerwigWrapper.h.

10.31.2.73 int PRNDEF

Definition at line 87 of file HerwigWrapper.h.

10.31.2.74 int PRNTEX

Definition at line 87 of file HerwigWrapper.h.

10.31.2.75 int PRNWEB

Definition at line 87 of file HerwigWrapper.h.

10.31.2.76 double PRSOF

Definition at line 79 of file HerwigWrapper.h.

10.31.2.77 int PRVTX

Definition at line 87 of file HerwigWrapper.h.

10.31.2.78 double PSPLT[2]

Definition at line 79 of file HerwigWrapper.h.

10.31.2.79 double PTRMS

Definition at line 79 of file HerwigWrapper.h.

10.31.2.80 double PXRMS

Definition at line 79 of file HerwigWrapper.h.

10.31.2.81 double QCDL3

Definition at line 79 of file HerwigWrapper.h.

10.31.2.82 double QCDL5

Definition at line 79 of file HerwigWrapper.h.

10.31.2.83 double QCDLAM

Definition at line 79 of file HerwigWrapper.h.

10.31.2.84 double QDIQK

Definition at line 79 of file HerwigWrapper.h.

10.31.2.85 double QFCH[16]

Definition at line 79 of file HerwigWrapper.h.

10.31.2.86 double QG

Definition at line 79 of file HerwigWrapper.h.

10.31.2.87 double QSPAC

Definition at line 79 of file HerwigWrapper.h.

10.31.2.88 double QV

Definition at line 79 of file HerwigWrapper.h.

10.31.2.89 double SCABI

Definition at line 79 of file HerwigWrapper.h.

10.31.2.90 int SOFTME

Definition at line 87 of file HerwigWrapper.h.

10.31.2.91 double SWEIN

Definition at line 79 of file HerwigWrapper.h.

10.31.2.92 double TMTOP

Definition at line 79 of file HerwigWrapper.h.

10.31.2.93 double VCKM[3][3]

Definition at line 79 of file HerwigWrapper.h.

10.31.2.94 double VFCH[2][16]

Definition at line 79 of file HerwigWrapper.h.

10.31.2.95 double VGCUT

Definition at line 79 of file HerwigWrapper.h.

10.31.2.96 double VPCUT

Definition at line 79 of file HerwigWrapper.h.

10.31.2.97 double VQCUT

Definition at line 79 of file HerwigWrapper.h.

10.31.2.98 double ZBINM

Definition at line 79 of file HerwigWrapper.h.

10.31.2.99 int ZPRIME

Definition at line 87 of file HerwigWrapper.h.

10.32 initPythia.cc File Reference

```
#include "HepMC/PythiaWrapper.h"
#include "PythiaHelper.h"
```

Functions

- `void initPythia ()`

10.32.1 Function Documentation

10.32.1.1 `void initPythia ()`

Examples:

`example_MyPythia.cc`, `example_MyPythiaOnlyToHepMC.cc`, `example_PythiaStreamIO.cc`,
and `testPythiaCopies.cc`.

Definition at line 12 of file `initPythia.cc`.

References `pydat2`, `pydatr`, `pypars`, and `pysubs`.

Referenced by `event_selection()`, `main()`, `pythia_in_out()`, `pythia_out()`, `pythia_particle_out()`, and `writePythiaStreamIO()`.

10.33 IO_AsciiParticles.cc File Reference

```
#include "HepMC/IO_AsciiParticles.h"  
#include "HepMC/GenEvent.h"  
#include "HepMC/Version.h"
```

Namespaces

- namespace **HepMC**

10.34 IO_AsciiParticles.h File Reference

```
#include <fstream>
#include <string>
#include <map>
#include <vector>
#include "HepMC/IO_BaseClass.h"
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::IO_AsciiParticles**
event input/output in ascii format for eye and machine reading

10.35 IO_BaseClass.h File Reference

```
#include <iostream>
#include "HepMC/GenEvent.h"
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::IO_BaseClass**
all input/output classes inherit from IO_BaseClass (p. 179)

10.36 IO_Exception.h File Reference

```
#include <stdexcept>
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::IO_Exception**
IO exception handling.

10.37 IO_GenEvent.cc File Reference

```
#include "HepMC/IO_GenEvent.h"  
#include "HepMC/IO_Exception.h"  
#include "HepMC/GenEvent.h"  
#include "HepMC/StreamHelpers.h"
```

Namespaces

- namespace **HepMC**

10.38 IO_GenEvent.h File Reference

```
#include <fstream>
#include <string>
#include <map>
#include <vector>
#include "HepMC/IO_BaseClass.h"
#include "HepMC/IO_Exception.h"
#include "HepMC/Units.h"
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::IO_GenEvent**
IO_GenEvent (p. 184) also deals with *HeavyIon* (p. 152) and *PdfInfo* (p. 220).

10.39 IO_HEPEVT.cc File Reference

```
#include "HepMC/IO_HEPEVT.h"  
#include "HepMC/GenEvent.h"  
#include <cstdio>
```

Namespaces

- namespace **HepMC**

10.40 IO_HEPEVT.h File Reference

```
#include <map>
#include <vector>
#include "HepMC/IO_BaseClass.h"
#include "HepMC/HEPEVT_Wrapper.h"
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::IO_HEPEVT**
HEPEVT IO class.

10.41 IO_HERWIG.cc File Reference

```
#include "HepMC/IO_HERWIG.h"  
#include "HepMC/GenEvent.h"  
#include <cstdio>
```

Namespaces

- namespace **HepMC**

10.42 IO_HERWIG.h File Reference

```
#include <set>
#include <vector>
#include "HepMC/IO_BaseClass.h"
#include "HepMC/HEPEVT_Wrapper.h"
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::IO_HERWIG**
IO_HERWIG (p. 193) is used to get Herwig information.

10.43 is_arithmetic.h File Reference

Namespaces

- namespace **HepMC**
- namespace **detail**
- namespace **HepMC::detail**

Classes

- struct **HepMC::detail::is_arithmetic**< T >
undefined and therefore non-arithmetic
- struct **HepMC::detail::is_arithmetic**< char >
character is arithmetic
- struct **HepMC::detail::is_arithmetic**< unsigned char >
unsigned character is arithmetic
- struct **HepMC::detail::is_arithmetic**< signed char >
signed character is arithmetic
- struct **HepMC::detail::is_arithmetic**< short >
short is arithmetic
- struct **HepMC::detail::is_arithmetic**< unsigned short >
unsigned short is arithmetic
- struct **HepMC::detail::is_arithmetic**< int >
int is arithmetic
- struct **HepMC::detail::is_arithmetic**< unsigned int >
unsigned int is arithmetic
- struct **HepMC::detail::is_arithmetic**< long >
long is arithmetic
- struct **HepMC::detail::is_arithmetic**< unsigned long >
unsigned long is arithmetic
- struct **HepMC::detail::is_arithmetic**< float >
float is arithmetic
- struct **HepMC::detail::is_arithmetic**< double >
double is arithmetic
- struct **HepMC::detail::is_arithmetic**< long double >
long double is arithmetic

10.44 IsGoodEvent.h File Reference

Classes

- `class` **IsGoodEvent**
used in the tests

10.45 IteratorRange.h File Reference

Namespaces

- namespace **HepMC**

Enumerations

- enum **HepMC::IteratorRange** {
 HepMC::parents, **HepMC::children**, **HepMC::family**, **HepMC::ancestors**,
 HepMC::descendants, **HepMC::relatives** }
 type of iteration

10.46 `list_of_examples.cc` File Reference

10.47 list_of_examples.cc File Reference

10.48 PdfInfo.cc File Reference

```
#include <iostream>
#include <ostream>
#include <istream>
#include <sstream>
#include "HepMC/PdfInfo.h"
#include "HepMC/StreamHelpers.h"
#include "HepMC/IO_Exception.h"
```

Namespaces

- namespace **HepMC**

Functions

- `std::ostream & HepMC::operator<< (std::ostream &, PdfInfo const *)`
- `std::istream & HepMC::operator>> (std::istream &, PdfInfo *)`

10.49 PdfInfo.h File Reference

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::PdfInfo**
The PdfInfo (p. 220) class stores PDF information.

Functions

- **std::ostream & HepMC::operator<< (std::ostream &, PdfInfo const *)**
- **std::istream & HepMC::operator>> (std::istream &, PdfInfo *)**

10.50 Polarization.cc File Reference

```
#include "HepMC/Polarization.h"
```

Namespaces

- namespace **HepMC**

Functions

- `std::ostream & HepMC::operator<< (std::ostream &ostr, const Polarization &polar)`
print polarization information

10.51 Polarization.h File Reference

```
#include "HepMC/SimpleVector.h"  
#include <iostream>  
#include <cmath>
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::Polarization**
The Polarization (p.232) class stores theta and phi for a GenParticle (p.111).

Variables

- static const double **HepMC::HepMC_pi = 3.14159265358979323846**

10.52 PythiaHelper.h File Reference

```
#include "HepMC/PythiaWrapper.h"
```

Functions

- `void initPythia ()`

10.52.1 Function Documentation

10.52.1.1 `void initPythia ()`

Definition at line 12 of file `initPythia.cc`.

References `pydat2`, `pydatr`, `pypars`, and `pysubs`.

Referenced by `event_selection()`, `main()`, `pythia_in_out()`, `pythia_out()`, `pythia_particle_out()`, and `writePythiaStreamIO()`.

10.53 PythiaWrapper.cc File Reference

```
#include <cmath>
#include "HepMC/PythiaWrapper.h"
#include "HepMC/GenCrossSection.h"
```

Namespaces

- namespace **HepMC**

Functions

- **HepMC::GenCrossSection HepMC::getPythiaCrossSection ()**
calculate the Pythia cross section and statistical error

Variables

- **pin3 pyint3_**
- **pin5 pyint5_**
- **pin7 pyint7_**
- **pin8 pyint8_**
- **pin9 pyint9_**
- **pssm pyssm_**
- **prvrv pyrvrv_**
- **prvpm pyrvpm_**

10.53.1 Variable Documentation

10.53.1.1 struct pin3 pyint3_

Definition at line 18 of file PythiaWrapper.cc.

10.53.1.2 struct pin5 pyint5_

Definition at line 19 of file PythiaWrapper.cc.

10.53.1.3 struct pin7 pyint7_

Definition at line 20 of file PythiaWrapper.cc.

10.53.1.4 struct pin8 pyint8_

Definition at line 21 of file PythiaWrapper.cc.

10.53.1.5 struct pin9 pyint9_

Definition at line 22 of file PythiaWrapper.cc.

10.53.1.6 struct prvrv pyrvrv_

Definition at line 24 of file PythiaWrapper.cc.

10.53.1.7 struct prvrv pyrvrv_

Definition at line 25 of file PythiaWrapper.cc.

10.53.1.8 struct pssm pyssm_

Definition at line 23 of file PythiaWrapper.cc.

10.54 PythiaWrapper.h File Reference

```
#include "HepMC/PythiaWrapper6_4.h"  
#include "HepMC/GenCrossSection.h"
```

Namespaces

- namespace **HepMC**

Functions

- **HepMC::GenCrossSection HepMC::getPythiaCrossSection ()**
calculate the Pythia cross section and statistical error

10.55 PythiaWrapper6_4.h File Reference

```
#include <ctype.h>
#include <cstring>
```

Classes

- struct **pin3**
- struct **pin5**
- struct **pin7**
- struct **pin8**
- struct **pin9**
- struct **pssm**
- struct **prvrv**
- struct **prvpm**

Defines

- #define **initpydata** **initpydata_**
- #define **pyjets** **pyjets_**
- #define **pydat1** **pydat1_**
- #define **pydat2** **pydat2_**
- #define **pydat3** **pydat3_**
- #define **pydatr** **pydatr_**
- #define **pysubs** **pysubs_**
- #define **pypars** **pypars_**
- #define **pyint1** **pyint1_**
- #define **pyint2** **pyint2_**
- #define **pyint3** **pyint3_**
- #define **pyint4** **pyint4_**
- #define **pyint5** **pyint5_**
- #define **pyint7** **pyint7_**
- #define **pyint8** **pyint8_**
- #define **pyint9** **pyint9_**
- #define **pyssm** **pyssm_**
- #define **pyssmt** **pyssmt_**
- #define **pymrv** **pymrv_**
- #define **pyrvrv** **pyrvrv_**
- #define **pyrvpm** **pyrvpm_**
- #define **pyints** **pyints_**
- #define **pyg2dx** **pyg2dx_**
- #define **pyhepc** **pyhepc_**
- #define **pyinit** **pyinit_**
- #define **pylist** **pylist_**
- #define **pystat** **pystat_**
- #define **pyevnt** **pyevnt_**
- #define **upinit** **upinit_**
- #define **upevnt** **upevnt_**
- #define **pydata** **pydata_**

Functions

- `void initpydata (void)`

Variables

- `const int pyjets_maxn = 4000`
- `struct {`
 - `int n`
 - `int npad`
 - `int k [5][pyjets_maxn]`
 - `double p [5][pyjets_maxn]`
 - `double v [5][pyjets_maxn]``} pyjets_`
- `struct {`
 - `int mstu [200]`
 - `double paru [200]`
 - `int mstj [200]`
 - `double parj [200]``} pydat1_`
- `struct {`
 - `int kchg [4][500]`
 - `double pmas [4][500]`
 - `double parf [2000]`
 - `double vckm [4][4]``} pydat2_`
- `struct {`
 - `int mdcy [3][500]`
 - `int mdme [2][8000]`
 - `double brat [8000]`
 - `int kfdp [5][8000]``} pydat3_`
- `struct {`
 - `int mrpy [6]`
 - `double rrp [100]``} pydatr_`
- `struct {`
 - `int msel`
 - `int mselpd`
 - `int msub [500]`
 - `int kfin [81][2]`
 - `double ckin [200]``} pysubs_`
- `struct {`
 - `int mstp [200]`
 - `double parp [200]`
 - `int msti [200]`

```

    double pari [200]
  } pypars_

• struct {
    int mint [400]
    double vint [400]
  } pyint1_

• struct {
    int iset [500]
    int kfpr [2][500]
    double coef [20][500]
    int icol [2][4][40]
  } pyint2_

• pin3 pyint3_
• struct {
    int mwid [500]
    double wids [5][500]
  } pyint4_

• pin5 pyint5_
• pin7 pyint7_
• pin8 pyint8_
• pin9 pyint9_
• pssm pyssm_
• struct {
    double zmix [4][4]
    double umix [2][2]
    double vmix [2][2]
    double smz [4]
    double smw [2]
    double sfmix [4][16]
    double zmixi [4][4]
    double umixi [2][2]
    double vmixi [2][2]
  } pyssmt_

• struct {
    double rvlam [3][3][3]
    double rvlamp [3][3][3]
    double rvlamb [3][3][3]
  } pymsrv_

• prvnv pyrvnv_
• prvpm pyrvpm_
• struct {
    double xxm [20]
  } pyints_

• struct {
    double x1
  } pyg2dx_

```

10.55.1 Define Documentation

10.55.1.1 `#define initpydata initpydata_`

Definition at line 30 of file PythiaWrapper6_4.h.

10.55.1.2 `#define pydat1 pydat1_`

Definition at line 52 of file PythiaWrapper6_4.h.

10.55.1.3 `#define pydat2 pydat2_`

Definition at line 60 of file PythiaWrapper6_4.h.

Referenced by `initPythia()`.

10.55.1.4 `#define pydat3 pydat3_`

Definition at line 69 of file PythiaWrapper6_4.h.

10.55.1.5 `#define pydata pydata_`

10.55.1.6 `#define pydatr pydatr_`

Definition at line 77 of file PythiaWrapper6_4.h.

Referenced by `initPythia()`.

10.55.1.7 `#define pyevnt pyevnt_`

Definition at line 245 of file PythiaWrapper6_4.h.

10.55.1.8 `#define pyg2dx pyg2dx_`

Definition at line 236 of file PythiaWrapper6_4.h.

10.55.1.9 `#define pyhepc pyhepc_`

Definition at line 241 of file PythiaWrapper6_4.h.

10.55.1.10 `#define pyinit pyinit_`

Definition at line 242 of file PythiaWrapper6_4.h.

10.55.1.11 `#define pyint1 pyint1_`

Definition at line 103 of file PythiaWrapper6_4.h.

10.55.1.12 #define pyint2 pyint2_

Definition at line 112 of file PythiaWrapper6_4.h.

10.55.1.13 #define pyint3 pyint3_

Definition at line 121 of file PythiaWrapper6_4.h.

10.55.1.14 #define pyint4 pyint4_

Definition at line 129 of file PythiaWrapper6_4.h.

10.55.1.15 #define pyint5 pyint5_

Definition at line 137 of file PythiaWrapper6_4.h.

Referenced by HepMC::getPythiaCrossSection().

10.55.1.16 #define pyint7 pyint7_

Definition at line 144 of file PythiaWrapper6_4.h.

10.55.1.17 #define pyint8 pyint8_

Definition at line 155 of file PythiaWrapper6_4.h.

10.55.1.18 #define pyint9 pyint9_

Definition at line 165 of file PythiaWrapper6_4.h.

10.55.1.19 #define pyints pyints_

Definition at line 229 of file PythiaWrapper6_4.h.

10.55.1.20 #define pyjets pyjets_

Definition at line 42 of file PythiaWrapper6_4.h.

10.55.1.21 #define pylist pylist_

Definition at line 243 of file PythiaWrapper6_4.h.

10.55.1.22 #define pmsrv pmsrv_

Definition at line 197 of file PythiaWrapper6_4.h.

10.55.1.23 #define pypars pypars_**Examples:**

**example_MyPythia.cc, example_MyPythiaOnlyToHepMC.cc, example_PythiaStreamIO.cc,
and testPythiaCopies.cc.**

Definition at line 95 of file PythiaWrapper6_4.h.

Referenced by `event_selection()`, `initPythia()`, `main()`, `pythia_out()`,
and `writePythiaStreamIO()`.

10.55.1.24 #define pyrvnv pyrvnv_

Definition at line 210 of file PythiaWrapper6_4.h.

10.55.1.25 #define pyrvpm pyrvpm_

Definition at line 222 of file PythiaWrapper6_4.h.

10.55.1.26 #define pyssm pyssm_

Definition at line 173 of file PythiaWrapper6_4.h.

10.55.1.27 #define pyssmt pyssmt_

Definition at line 188 of file PythiaWrapper6_4.h.

10.55.1.28 #define pystat pystat_

Definition at line 244 of file PythiaWrapper6_4.h.

10.55.1.29 #define pysubs pysubs_

Definition at line 85 of file PythiaWrapper6_4.h.

Referenced by `initPythia()`.

10.55.1.30 #define upevnt upevnt_

Definition at line 247 of file PythiaWrapper6_4.h.

10.55.1.31 #define upinit upinit_

Definition at line 246 of file PythiaWrapper6_4.h.

10.55.2 Function Documentation

10.55.2.1 void initpydata (void)

10.55.3 Variable Documentation

10.55.3.1 double brat[8000]

Definition at line 65 of file PythiaWrapper6_4.h.

10.55.3.2 double ckin[200]

Definition at line 82 of file PythiaWrapper6_4.h.

10.55.3.3 double coef[20][500]

Definition at line 108 of file PythiaWrapper6_4.h.

10.55.3.4 int icol[2][4][40]

Definition at line 109 of file PythiaWrapper6_4.h.

10.55.3.5 int iset[500]

Definition at line 107 of file PythiaWrapper6_4.h.

10.55.3.6 int k[5][pyjets_maxn]

Definition at line 38 of file PythiaWrapper6_4.h.

10.55.3.7 int kchg[4][500]

Definition at line 56 of file PythiaWrapper6_4.h.

10.55.3.8 int kfdp[5][8000]

Definition at line 66 of file PythiaWrapper6_4.h.

10.55.3.9 int kfin[81][2]

Definition at line 81 of file PythiaWrapper6_4.h.

10.55.3.10 int kfpr[2][500]

Definition at line 107 of file PythiaWrapper6_4.h.

10.55.3.11 int mdcy[3][500]

Definition at line 64 of file PythiaWrapper6_4.h.

10.55.3.12 int mdme[2][8000]

Definition at line 64 of file PythiaWrapper6_4.h.

10.55.3.13 int mint[400]

Definition at line 99 of file PythiaWrapper6_4.h.

10.55.3.14 int mrpy[6]

Definition at line 73 of file PythiaWrapper6_4.h.

10.55.3.15 int msel

Definition at line 81 of file PythiaWrapper6_4.h.

10.55.3.16 int mselpd

Definition at line 81 of file PythiaWrapper6_4.h.

10.55.3.17 int msti[200]

Definition at line 91 of file PythiaWrapper6_4.h.

10.55.3.18 int mstj[200]

Definition at line 48 of file PythiaWrapper6_4.h.

10.55.3.19 int mstp[200]

Definition at line 89 of file PythiaWrapper6_4.h.

10.55.3.20 int mstu[200]

Definition at line 46 of file PythiaWrapper6_4.h.

10.55.3.21 int msub[500]

Definition at line 81 of file PythiaWrapper6_4.h.

10.55.3.22 int mwid[500]

Definition at line 125 of file PythiaWrapper6_4.h.

10.55.3.23 int n

Definition at line 38 of file PythiaWrapper6_4.h.

10.55.3.24 int npad

Definition at line 38 of file PythiaWrapper6_4.h.

10.55.3.25 double p[5][pyjets_maxn]**Examples:**

example_BuildEventFromScratch.cc, example_EventSelection.cc, example_MyPythia.cc, example_UsingIterators.cc, and testHepMCIteration.cc.in.

Definition at line 39 of file PythiaWrapper6_4.h.

Referenced by HepMC::TempParticleMap::addEndParticle(), HepMC::already_in_vector(), HepMC::IO_HERWIG::build_end_vertex(), HepMC::IO_HEPEVT::build_end_vertex(), HepMC::IO_HERWIG::build_particle(), HepMC::IO_HEPEVT::build_particle(), HepMC::IO_HERWIG::build_production_vertex(), HepMC::IO_HEPEVT::build_production_vertex(), HepMC::Flow::connected_partners(), HepMC::Flow::dangling_connected_partners(), HepMC::GenVertex::edge_iterator::edge_iterator(), HepMC::TempParticleMap::end_vertex(), HepMC::IO_HERWIG::find_in_map(), HepMC::IO_HEPEVT::find_in_map(), findPiZero(), HepMC::GenEvent::GenEvent(), IsPhoton(), IsWBoson(), main(), HepMC::not_in_vector(), PrintDescendants::operator()(), PrintChildren::operator()(), PrintParticle::operator()(), PrintPhoton::operator()(), IsFinalState::operator()(), IsGoodEvent::operator()(), IsStateFinal::operator()(), IsW_Boson::operator()(), IsPhoton::operator()(), IsGoodEventMyPythia::operator()(), IsEventGood::operator()(), HepMC::GenVertex::edge_iterator::operator=(), HepMC::GenVertex::particles_in(), HepMC::GenVertex::particles_out(), particleTypes(), HepMC::GenEvent::read(), HepMC::detail::read_particle(), HepMC::GenEvent::remove_barcode(), repairUnits(), HepMC::GenEvent::set_barcode(), HepMC::GenEvent::set_pdf_info(), HepMC::GenEvent::valid_beam_particles(), and HepMC::IO_HEPEVT::write_event().

10.55.3.26 double parf[2000]

Definition at line 57 of file PythiaWrapper6_4.h.

10.55.3.27 double pari[200]

Definition at line 92 of file PythiaWrapper6_4.h.

10.55.3.28 double parj[200]

Definition at line 49 of file PythiaWrapper6_4.h.

10.55.3.29 double parp[200]

Definition at line 90 of file PythiaWrapper6_4.h.

10.55.3.30 double paru[200]

Definition at line 47 of file PythiaWrapper6_4.h.

10.55.3.31 double pmas[4][500]

Definition at line 57 of file PythiaWrapper6_4.h.

10.55.3.32 struct { ... } pydat1_**10.55.3.33 struct { ... } pydat2_****10.55.3.34 struct { ... } pydat3_****10.55.3.35 struct { ... } pydatr_****10.55.3.36 struct { ... } pyg2dx_****10.55.3.37 struct { ... } pyint1_****10.55.3.38 struct { ... } pyint2_****10.55.3.39 struct pin3 pyint3_****10.55.3.40 struct { ... } pyint4_****10.55.3.41 struct pin5 pyint5_****10.55.3.42 struct pin7 pyint7_****10.55.3.43 struct pin8 pyint8_****10.55.3.44 struct pin9 pyint9_****10.55.3.45 struct { ... } pyints_****10.55.3.46 struct { ... } pyjets_****10.55.3.47 const int pyjets_maxn = 4000**

Definition at line 35 of file PythiaWrapper6_4.h.

10.55.3.48 struct { ... } pymsrv_

10.55.3.49 struct { ... } pypars_

10.55.3.50 struct prvvnv pyrvnv_

10.55.3.51 struct prvpm pyrvpm_

10.55.3.52 struct pssm pyssm_

10.55.3.53 struct { ... } pyssmt_

10.55.3.54 struct { ... } pysubs_

10.55.3.55 double rrpv[100]

Definition at line 74 of file PythiaWrapper6_4.h.

10.55.3.56 double rvlam[3][3][3]

Definition at line 192 of file PythiaWrapper6_4.h.

10.55.3.57 double rvlamb[3][3][3]

Definition at line 194 of file PythiaWrapper6_4.h.

10.55.3.58 double rvlamp[3][3][3]

Definition at line 193 of file PythiaWrapper6_4.h.

10.55.3.59 double sfmix[4][16]

Definition at line 182 of file PythiaWrapper6_4.h.

10.55.3.60 double smw[2]

Definition at line 181 of file PythiaWrapper6_4.h.

10.55.3.61 double smz[4]

Definition at line 180 of file PythiaWrapper6_4.h.

10.55.3.62 double umix[2][2]

Definition at line 178 of file PythiaWrapper6_4.h.

10.55.3.63 double umixi[2][2]

Definition at line 184 of file PythiaWrapper6_4.h.

10.55.3.64 double v[5][pyjets_maxn]**Examples:**

example_UsingIterators.cc, testHepMCIteration.cc.in, and VectorConversion.h.

Definition at line 39 of file PythiaWrapper6_4.h.

Referenced by `HepMC::compareVertices()`, `convertTo()`, `HepMC::GenEvent::GenEvent()`, `main()`, `HepMC::GenEvent::read()`, `HepMC::detail::read_vertex()`, `HepMC::GenEvent::remove_barcode()`, `HepMC::GenEvent::set_barcode()`, `HepMC::GenEvent::write()`, and `HepMC::IO_HEPEVT::write_event()`.

10.55.3.65 double vckm[4][4]

Definition at line 57 of file PythiaWrapper6_4.h.

10.55.3.66 double vint[400]

Definition at line 100 of file PythiaWrapper6_4.h.

10.55.3.67 double vmix[2][2]

Definition at line 179 of file PythiaWrapper6_4.h.

10.55.3.68 double vmixi[2][2]

Definition at line 185 of file PythiaWrapper6_4.h.

10.55.3.69 double wids[5][500]

Definition at line 126 of file PythiaWrapper6_4.h.

10.55.3.70 double x1**Examples:**

testMass.cc.in.

Definition at line 233 of file PythiaWrapper6_4.h.

Referenced by `HepMC::operator>>()`.

10.55.3.71 double xxm[20]

Definition at line 226 of file PythiaWrapper6_4.h.

10.55.3.72 double zmix[4][4]

Definition at line 177 of file PythiaWrapper6_4.h.

10.55.3.73 double zmixi[4][4]

Definition at line 183 of file PythiaWrapper6_4.h.

10.56 PythiaWrapper6_4_WIN32.h File Reference

10.57 SearchVector.cc File Reference

```
#include "HepMC/SearchVector.h"
```

Namespaces

- namespace **HepMC**

Functions

- `bool HepMC::not_in_vector (std::vector< HepMC::GenParticle * > *, GenParticle *)`
returns true if it cannot find GenParticle in the vector*
- `std::vector< HepMC::GenParticle * >::iterator HepMC::already_in_vector (std::vector< GenParticle * > *v, GenParticle *p)`
returns true if GenParticle (p.111) is in the vector

10.58 SearchVector.h File Reference

```
#include "HepMC/GenVertex.h"
#include "HepMC/GenParticle.h"
```

Namespaces

- namespace **HepMC**

Functions

- **bool HepMC::not_in_vector** (std::vector< HepMC::GenParticle * > *, GenParticle *)
returns true if it cannot find GenParticle in the vector*
- **std::vector< HepMC::GenParticle * >::iterator HepMC::already_in_vector** (std::vector< GenParticle * > *v, GenParticle *p)
returns true if GenParticle (p.111) is in the vector

10.59 SimpleVector.h File Reference

```
#include "HepMC/enable_if.h"
#include "HepMC/is_arithmetic.h"
#include "HepMC/SimpleVector.icc"
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::FourVector**
FourVector (p. 59) is a simple representation of a physics 4 vector.
- class **HepMC::ThreeVector**
ThreeVector (p. 254) is a simple representation of a position or displacement 3 vector.

10.60 StreamHelpers.cc File Reference

```
#include <ostream>
#include <istream>
#include <sstream>
#include "HepMC/GenVertex.h"
#include "HepMC/GenParticle.h"
#include "HepMC/StreamHelpers.h"
#include "HepMC/IO_Exception.h"
```

Namespaces

- namespace **HepMC**
- namespace **HepMC::detail**

Functions

- `std::istream & HepMC::detail::read_vertex (std::istream &, TempParticleMap &, GenVertex *)`
- `std::istream & HepMC::detail::find_event_end (std::istream &)`
used to read to the end of a bad event

10.61 StreamHelpers.h File Reference

```
#include <ostream>
#include <istream>
#include "HepMC/GenEvent.h"
#include "HepMC/TempParticleMap.h"
```

Namespaces

- namespace **HepMC**
- namespace **HepMC::detail**

Functions

- **std::ostream & HepMC::detail::establish_output_stream_info (std::ostream &)**
used by IO_GenEvent (p. 184) constructor
- **std::istream & HepMC::detail::establish_input_stream_info (std::istream &)**
used by IO_GenEvent (p. 184) constructor
- **std::istream & HepMC::detail::read_vertex (std::istream &, TempParticleMap &, GenVertex *)**
- **std::istream & HepMC::detail::read_particle (std::istream &, TempParticleMap &, GenParticle *)**
- **std::ostream & HepMC::detail::output (std::ostream &os, const double &d)**
write a double - for internal use by streaming IO
- **std::ostream & HepMC::detail::output (std::ostream &os, const float &d)**
write a float - for internal use by streaming IO
- **std::ostream & HepMC::detail::output (std::ostream &os, const int &i)**
write an int - for internal use by streaming IO
- **std::ostream & HepMC::detail::output (std::ostream &os, const long &i)**
write a long - for internal use by streaming IO
- **std::ostream & HepMC::detail::output (std::ostream &os, const char &c)**
write a single char - for internal use by streaming IO
- **std::istream & HepMC::detail::find_event_end (std::istream &)**
used to read to the end of a bad event

10.62 StreamInfo.cc File Reference

```
#include <string>
#include "HepMC/StreamInfo.h"
```

Namespaces

- namespace **HepMC**

10.63 StreamInfo.h File Reference

```
#include <string>
#include "HepMC/Units.h"
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::StreamInfo**
StreamInfo (p.245) contains extra information needed when using streaming IO.

Enumerations

- enum **HepMC::known_io** {
 HepMC::gen = 1, HepMC::ascii, HepMC::extascii, HepMC::ascii_pdt,
 HepMC::extascii_pdt }
 The known_io enum is used to track which type of input is being read.

10.64 TempParticleMap.h File Reference

```
#include <map>
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::TempParticleMap**
TempParticleMap (p. 251) is a temporary *GenParticle** container used during input.

10.65 testFlow.cc File Reference

```
#include <iostream>
#include <fstream>
#include <vector>
#include "HepMC/GenEvent.h"
#include "HepMC/IO_GenEvent.h"
```

Typedefs

- typedef std::vector< **HepMC::GenParticle *** > **FlowVec**

Functions

- int **main()**

10.65.1 Typedef Documentation

10.65.1.1 typedef std::vector<HepMC::GenParticle*> FlowVec

Definition at line 15 of file testFlow.cc.

10.65.2 Function Documentation

10.65.2.1 int main()

Definition at line 17 of file testFlow.cc.

References `HepMC::GenVertex::add_particle_in()`, `HepMC::GenVertex::add_particle_out()`, `HepMC::GenEvent::add_vertex()`, `HepMC::GenParticle::barcode()`, `HepMC::Flow::erase()`, `HepMC::GenParticle::flow()`, `HepMC::Units::GEV`, `HepMC::Units::MM`, `HepMC::GenEvent::print()`, `HepMC::GenParticle::set_flow()`, `HepMC::GenEvent::set_signal_process_vertex()`, `HepMC::GenEvent::use_units()`, and `HepMC::GenEvent::write()`.

10.66 testHepMCIteration.h File Reference

Classes

- `class IsFinalState`
- `class PrintPhoton`
- `class PrintParticle`
- `class PrintChildren`
test class
- `class PrintDescendants`
test class

Functions

- `bool IsPhoton (const HepMC::GenParticle *p)`
returns true if the GenParticle particle is a photon with $p_T > 10$ GeV
- `bool IsWBoson (const HepMC::GenParticle *p)`
returns true if the GenParticle is a W^+/W^-

10.66.1 Function Documentation

10.66.1.1 `bool IsPhoton (const HepMC::GenParticle *p)`

returns true if the GenParticle particle is a photon with $p_T > 10$ GeV

Examples:

`testHepMCIteration.cc.in.`

Definition at line 10 of file testHepMCIteration.h.

References `p`.

Referenced by `PrintPhoton::operator()()`.

10.66.1.2 `bool IsWBoson (const HepMC::GenParticle *p)`

returns true if the GenParticle is a W^+/W^-

Examples:

`testHepMCIteration.cc.in.`

Definition at line 17 of file testHepMCIteration.h.

References `p`.

10.67 testHepMCMethods.cc File Reference

```
#include "testHepMCMethods.h"
```

Functions

- `double findPiZero (HepMC::GenEvent *evt)`
- `void particleTypes (HepMC::GenEvent *evt, std::ostream &os)`
- `void repairUnits (HepMC::GenEvent *evt, HepMC::Units::MomentumUnit from, HepMC::Units::MomentumUnit to)`

10.67.1 Function Documentation

10.67.1.1 `double findPiZero (HepMC::GenEvent * evt)`

Examples:

`testHepMC.cc.in`, and `testStreamIO.cc.in`.

Definition at line 11 of file `testHepMCMethods.cc`.

References `p`, `HepMC::GenEvent::particles_begin()`, and `HepMC::GenEvent::particles_end()`.

10.67.1.2 `void particleTypes (HepMC::GenEvent * evt, std::ostream & os)`

Examples:

`testHepMC.cc.in`, and `testStreamIO.cc.in`.

Definition at line 22 of file `testHepMCMethods.cc`.

References `HepMC::GenEvent::event_number()`, `p`, `HepMC::GenEvent::particles_begin()`, `HepMC::GenEvent::particles_end()`, and `HepMC::GenEvent::particles_size()`.

10.67.1.3 `void repairUnits (HepMC::GenEvent * evt, HepMC::Units::MomentumUnit from, HepMC::Units::MomentumUnit to)`

Examples:

`testHepMC.cc.in`.

Definition at line 78 of file `testHepMCMethods.cc`.

References `HepMC::Units::conversion_factor()`, `HepMC::FourVector::e()`, `p`, `HepMC::GenEvent::particles_begin()`, `HepMC::GenEvent::particles_end()`, `HepMC::FourVector::py()`, and `HepMC::FourVector::pz()`.

10.68 testHepMCMethods.h File Reference

```
#include "HepMC/GenEvent.h"
```

Functions

- `double findPiZero (HepMC::GenEvent *)`
- `void particleTypes (HepMC::GenEvent *, std::ostream &os=std::cout)`
- `void repairUnits (HepMC::GenEvent *, HepMC::Units::MomentumUnit, HepMC::Units::MomentumUnit)`

10.68.1 Function Documentation

10.68.1.1 `double findPiZero (HepMC::GenEvent *)`

Definition at line 11 of file testHepMCMethods.cc.

References `p`, `HepMC::GenEvent::particles_begin()`, and `HepMC::GenEvent::particles_end()`.

10.68.1.2 `void particleTypes (HepMC::GenEvent *, std::ostream &os = std::cout)`

Definition at line 22 of file testHepMCMethods.cc.

References `HepMC::GenEvent::event_number()`, `p`, `HepMC::GenEvent::particles_begin()`, `HepMC::GenEvent::particles_end()`, and `HepMC::GenEvent::particles_size()`.

10.68.1.3 `void repairUnits (HepMC::GenEvent *, HepMC::Units::MomentumUnit, HepMC::Units::MomentumUnit)`

Definition at line 78 of file testHepMCMethods.cc.

References `HepMC::Units::conversion_factor()`, `HepMC::FourVector::e()`, `p`, `HepMC::GenEvent::particles_begin()`, `HepMC::GenEvent::particles_end()`, `HepMC::FourVector::py()`, and `HepMC::FourVector::pz()`.

10.69 testHerwigCopies.cc File Reference

```
#include <fstream>
#include <iostream>
#include "HepMC/HerwigWrapper.h"
#include "HepMC/IO_HERWIG.h"
#include "HepMC/GenEvent.h"
#include "HepMC/CompareGenEvent.h"
#include "HepMC/HEPEVT_Wrapper.h"
```

Functions

- `int main()`

10.69.1 Function Documentation

10.69.1.1 `int main()`

Definition at line 16 of file testHerwigCopies.cc.

References `HepMC::compareGenEvent()`, `HepMC::GenEvent::event_number()`, `HepMC::getHerwigCrossSection()`, `HepMC::Units::GEV`, `hwbgen`, `hwbmch`, `hwcdec`, `hwcfor`, `hwdhad`, `hwdhob`, `hwdhvy`, `hwefin`, `hweini`, `hwepro`, `hwevnt`, `hwigin`, `hwmevt`, `hwproc`, `hwufne`, `hwuinc`, `hwuine`, `HepMC::Units::MM`, `HepMC::GenEvent::print()`, `HepMC::IO_BaseClass::read_next_event()`, `HepMC::GenEvent::set_cross_section()`, `HepMC::GenEvent::set_event_number()`, `HepMC::HEPEVT_Wrapper::set_max_number_entries()`, `HepMC::GenEvent::set_signal_process_id()`, `HepMC::HEPEVT_Wrapper::set_sizeof_real()`, and `HepMC::GenEvent::use_units()`.

10.70 testPolarization.cc File Reference

```
#include <iostream>
#include <fstream>
#include <vector>
#include "HepMC/GenEvent.h"
#include "HepMC/IO_GenEvent.h"
```

Functions

- `int main()`

10.70.1 Function Documentation

10.70.1.1 `int main()`

Definition at line 14 of file testPolarization.cc.

References `HepMC::GenVertex::add_particle_in()`, `HepMC::GenVertex::add_particle_out()`, `HepMC::GenEvent::add_vertex()`, `HepMC::GenEvent::particles_begin()`, `HepMC::GenEvent::particles_end()`, `HepMC::GenEvent::print()`, `HepMC::GenParticle::set_flow()`, `HepMC::GenParticle::set_polarization()`, `HepMC::GenEvent::set_signal_process_vertex()`, and `HepMC::GenEvent::write()`.

10.71 testPrintBug.cc File Reference

```
#include <fstream>
#include "HepMC/GenEvent.h"
#include "HepMC/SimpleVector.h"
```

Functions

- `int main()`

10.71.1 Function Documentation

10.71.1.1 `int main()`

Definition at line 10 of file testPrintBug.cc.

References `HepMC::GenVertex::add_particle_in()`, `HepMC::GenVertex::add_particle_out()`, `HepMC::GenEvent::add_vertex()`, `HepMC::Units::GEV`, `HepMC::Units::MM`, `HepMC::GenEvent::print()`, and `HepMC::GenEvent::use_units()`.

10.72 testPythiaCopies.cc File Reference

```
#include <fstream>
#include <iostream>
#include "HepMC/PythiaWrapper.h"
#include "HepMC/IO_HEPEVT.h"
#include "HepMC/GenEvent.h"
#include "HepMC/CompareGenEvent.h"
#include "PythiaHelper.h"
```

Functions

- `int main()`

10.72.1 Function Documentation

10.72.1.1 `int main()`

Definition at line 16 of file testPythiaCopies.cc.

References `HepMC::compareGenEvent()`, `HepMC::GenEvent::event_number()`, `HepMC::getPythiaCrossSection()`, `HepMC::Units::GEV`, `initPythia()`, `HepMC::Units::MM`, `HepMC::GenEvent::print()`, `pypars`, `HepMC::IO_BaseClass::read_next_event()`, `HepMC::GenEvent::set_cross_section()`, `HepMC::HEPEVT_Wrapper::set_max_number_entries()`, `HepMC::GenEvent::set_mpi()`, `HepMC::HEPEVT_Wrapper::set_sizeof_real()`, `HepMC::GenEvent::use_units()`, and `HepMC::GenEvent::weights()`.

10.73 testSimpleVector.cc File Reference

```
#include <iostream>
#include "HepMC/SimpleVector.h"
```

Functions

- `int main()`

10.73.1 Function Documentation

10.73.1.1 `int main()`

Definition at line 8 of file testSimpleVector.cc.

References `HepMC::FourVector::e()`, `HepMC::FourVector::eta()`, `HepMC::FourVector::m()`, `HepMC::FourVector::m2()`, `HepMC::FourVector::perp()`, `HepMC::ThreeVector::perp()`, `HepMC::FourVector::perp2()`, `HepMC::ThreeVector::perp2()`, `HepMC::FourVector::phi()`, `HepMC::ThreeVector::phi()`, `HepMC::FourVector::pseudoRapidity()`, `HepMC::FourVector::px()`, `HepMC::FourVector::py()`, `HepMC::FourVector::pz()`, `HepMC::ThreeVector::r()`, `HepMC::FourVector::rho()`, `HepMC::FourVector::set()`, `HepMC::ThreeVector::set()`, `HepMC::FourVector::setE()`, `HepMC::ThreeVector::setPhi()`, `HepMC::FourVector::setPx()`, `HepMC::FourVector::setPy()`, `HepMC::FourVector::setPz()`, `HepMC::FourVector::setT()`, `HepMC::ThreeVector::setTheta()`, `HepMC::FourVector::setX()`, `HepMC::ThreeVector::setX()`, `HepMC::FourVector::setY()`, `HepMC::ThreeVector::setY()`, `HepMC::FourVector::setZ()`, `HepMC::ThreeVector::setZ()`, `HepMC::FourVector::t()`, `HepMC::FourVector::theta()`, `HepMC::ThreeVector::theta()`, `HepMC::FourVector::x()`, `HepMC::ThreeVector::x()`, `HepMC::FourVector::y()`, `HepMC::ThreeVector::y()`, `HepMC::FourVector::z()`, and `HepMC::ThreeVector::z()`.

10.74 testUnits.cc File Reference

```
#include <iostream>
#include "HepMC/Units.h"
```

Functions

- `int main()`

10.74.1 Function Documentation

10.74.1.1 `int main()`

Definition at line 8 of file testUnits.cc.

References `HepMC::Units::CM`, `HepMC::Units::conversion_factor()`, `HepMC::Units::default_length_unit()`, `HepMC::Units::default_momentum_unit()`, `HepMC::Units::GEV`, `HepMC::Units::MEV`, `HepMC::Units::MM`, and `HepMC::Units::name()`.

10.75 testWeights.cc File Reference

```
#include <assert.h>
#include <iostream>
#include <string>
#include <vector>
#include "HepMC/WeightContainer.h"
#include <stdexcept>
```

Functions

- `int main ()`

10.75.1 Function Documentation

10.75.1.1 `int main ()`

Definition at line 16 of file testWeights.cc.

References `HepMC::WeightContainer::empty()`, `HepMC::WeightContainer::has_key()`, `HepMC::WeightContainer::pop_back()`, `HepMC::WeightContainer::push_back()`, `HepMC::WeightContainer::size()`, and `HepMC::WeightContainer::write()`.

10.76 Units.h File Reference

```
#include <iostream>
#include <string>
```

Namespaces

- namespace **HepMC**
- namespace **Units**
- namespace **HepMC::Units**

Enumerations

- enum **HepMC::Units::MomentumUnit** { **HepMC::Units::MEV**, **HepMC::Units::GEV** }
- enum **HepMC::Units::LengthUnit** { **HepMC::Units::MM**, **HepMC::Units::CM** }

Functions

- **LengthUnit HepMC::Units::default_length_unit ()**
default unit is defined by configure
- **MomentumUnit HepMC::Units::default_momentum_unit ()**
default unit is defined by configure
- **std::string HepMC::Units::name (MomentumUnit)**
convert enum to string
- **std::string HepMC::Units::name (LengthUnit)**
convert enum to string
- **double HepMC::Units::conversion_factor (MomentumUnit from, MomentumUnit to)**
scaling factor relative to MeV
- **double HepMC::Units::conversion_factor (LengthUnit from, LengthUnit to)**

10.77 VectorConversion.h File Reference

```
#include "HepMC/SimpleVector.h"
#include "CLHEP/Vector/LorentzVector.h"
```

Namespaces

- namespace **CLHEP**

Functions

- **CLHEP::Hep3Vector convertTo (const HepMC::ThreeVector &v)**
Convert from HepMC::ThreeVector (p.254) to CLHEP::Hep3Vector.
- **CLHEP::HepLorentzVector convertTo (const HepMC::FourVector &v)**
Convert from HepMC::FourVector (p.59) to CLHEP::HepLorentzVector.

10.77.1 Function Documentation

10.77.1.1 CLHEP::HepLorentzVector convertTo (const HepMC::FourVector &v) [inline]

Convert from **HepMC::FourVector** (p.59) to **CLHEP::HepLorentzVector**.
Definition at line 25 of file `VectorConversion.h`.
References `v`.

10.77.1.2 CLHEP::Hep3Vector convertTo (const HepMC::ThreeVector &v) [inline]

Convert from **HepMC::ThreeVector** (p.254) to **CLHEP::Hep3Vector**.

Examples:

example_BuildEventFromScratch.cc, and **VectorConversion.h**.

Definition at line 21 of file `VectorConversion.h`.
References `v`.
Referenced by `main()`.

10.78 Version.h File Reference

```
#include <string>
#include <iostream>
#include "HepMC/HepMCDefs.h"
```

Namespaces

- namespace **HepMC**

Functions

- **void HepMC::version (std::ostream &os=std::cout)**
print HepMC (p. 23) version
- **void HepMC::writeVersion (std::ostream &os)**
write HepMC (p. 23) version to os
- **std::string HepMC::versionName ()**
return HepMC (p. 23) version

10.79 WeightContainer.cc File Reference

```
#include <iostream>
#include <iomanip>
#include <sstream>
#include <vector>
#include <string>
#include <map>
#include <stdexcept>
#include "HepMC/WeightContainer.h"
```

Namespaces

- namespace **HepMC**

10.80 WeightContainer.h File Reference

```
#include <iostream>
#include <vector>
#include <string>
#include <map>
```

Namespaces

- namespace **HepMC**

Classes

- class **HepMC::WeightContainer**
Container for the Weights associated with an event or vertex.

Chapter 11

HepMC Example Documentation

11.1 example_BuildEventFromScratch.cc

Example of building an event and a particle data table from scratch
This is meant to be of use for persons implementing **HepMC** (p.23) inside
a MC event generator

```
1
2 // Matt.Dobbs@Cern.CH, Feb 2000
3 // Example of building an event and a particle data table from scratch
4 // This is meant to be of use for persons implementing HepMC inside a MC
5 // event generator
6 // To Compile: go to the HepMC directory and type:
7 // gmake examples/example_BuildEventFromScratch.exe
8 //
9
10
11 #include <iostream>
12
13 #include "VectorConversion.h"
14 #include "HepMC/GenEvent.h"
15 #include "CLHEP/Vector/LorentzVector.h"
16
17 // in this example we use the HepMC namespace, so that we do not have to
18 // precede all HepMC classes with HepMC::
19
20 // This example also shows how to use the CLHEP Lorentz vector with HepMC2
21
22 using namespace HepMC;
23 using namespace CLHEP;
24
25 int main() {
26     //
27     // In this example we will place the following event into HepMC "by hand"
28     //
29     //      name status pdg_id  parent Px      Py      Pz      Energy      Mass
30     //  1  !p+!      3    2212    0,0    0.000    0.000 7000.000 7000.000    0.938
31     //  2  !p+!      3    2212    0,0    0.000    0.000-7000.000 7000.000    0.938
32     //=====
33     //  3  !d!       3      1    1,1    0.750   -1.569   32.191   32.238    0.000
34     //  4  !u~!      3     -2    2,2   -3.047  -19.000  -54.629   57.920    0.000
35     //  5  !W-!      3    -24    1,2    1.517   -20.68   -20.605   85.925    80.799
36     //  6  !gamma!   1     22    1,2   -3.813    0.113   -1.833    4.233    0.000
37     //  7  !d!       1      1    5,5   -2.445   28.816    6.082   29.552    0.010
38     //  8  !u~!      1     -2    5,5    3.962  -49.498  -26.687   56.373    0.006
39
40     // now we build the graph, which will look like
```

```

41      //                                     p7          #
42      // p1                                     /          #
43      // \v1__p3      p5---v4                #
44      //      \_v3_/      \                #
45      //      /      \      p8                #
46      //      v2__p4      \                #
47      //      /      p6                #
48      // p2                                #
49      //                                #
50
51      // First create the event container, with Signal Process 20, event number 1
52      //
53      // Note that the HepLorentzVectors will be automatically converted to
54      // HepMC::FourVector within GenParticle and GenVertex
55      GenEvent* evt = new GenEvent( 20, 1 );
56      // define the units
57      evt->use_units(HepMC::Units::GEV, HepMC::Units::MM);
58      //
59      // create vertex 1 and vertex 2, together with their inparticles
60      GenVertex* v1 = new GenVertex();
61      evt->add_vertex( v1 );
62      v1->add_particle_in( new GenParticle( HepLorentzVector(0,0,7000,7000),
63                                     2212, 3 ) );
64      GenVertex* v2 = new GenVertex();
65      evt->add_vertex( v2 );
66      v2->add_particle_in( new GenParticle( HepLorentzVector(0,0,-7000,7000),
67                                     2212, 3 ) );
68      //
69      // create the outgoing particles of v1 and v2
70      GenParticle* p3 =
71          new GenParticle( HepLorentzVector(.750,-1.569,32.191,32.238), 1, 3 );
72      v1->add_particle_out( p3 );
73      GenParticle* p4 =
74          new GenParticle( HepLorentzVector(-3.047,-19.,-54.629,57.920), -2, 3 );
75      v2->add_particle_out( p4 );
76      //
77      // create v3
78      GenVertex* v3 = new GenVertex();
79      evt->add_vertex( v3 );
80      v3->add_particle_in( p3 );
81      v3->add_particle_in( p4 );
82      v3->add_particle_out(
83          new GenParticle( HepLorentzVector(-3.813,0.113,-1.833,4.233 ), 22, 1 )
84      );
85      GenParticle* p5 =
86          new GenParticle( HepLorentzVector(1.517,-20.68,-20.605,85.925), -24,3);
87      v3->add_particle_out( p5 );
88      //
89      // create v4
90      GenVertex* v4 = new GenVertex(HepLorentzVector(0.12,-0.3,0.05,0.004));
91      evt->add_vertex( v4 );
92      v4->add_particle_in( p5 );
93      v4->add_particle_out(
94          new GenParticle( HepLorentzVector(-2.445,28.816,6.082,29.552), 1,1 )
95      );
96      v4->add_particle_out(
97          new GenParticle( HepLorentzVector(3.962,-49.498,-26.687,56.373), -2,1 )
98      );
99      //
100     // tell the event which vertex is the signal process vertex
101     evt->set_signal_process_vertex( v3 );
102     // the event is complete, we now print it out to the screen
103     evt->print();
104
105     // example conversion back to Lorentz vector
106     // add all outgoing momenta
107     std::cout << std::endl;

```

```
108     std::cout << " Add output momenta " << std::endl;
109     HepLorentzVector sum;
110     for ( GenEvent::particle_const_iterator p = evt->particles_begin();
111          p != evt->particles_end(); ++p ){
112         if( (*p)->status() == 1 ) {
113             sum += convertTo( (*p)->momentum() );
114             (*p)->print();
115         }
116     }
117     std::cout << "Vector Sum: " << sum << std::endl;
118
119     // now clean-up by deleteing all objects from memory
120     //
121     // deleting the event deletes all contained vertices, and all particles
122     // contained in those vertices
123     delete evt;
124
125     return 0;
126 }
```

11.2 example_EventSelection.cc

Example of applying an event selection to the events written to file using example_MyPythia.cxx Events containing a photon of $p_T > 25$ GeV pass the selection and are written to "example_EventSelection.dat"

```

1
2 // Matt.Dobbs@Cern.CH, Feb 2000
3 // Example of applying an event selection to the events written to file
4 // using example_MyPythia.cxx
5 // Events containing a photon of  $p_T > 25$  GeV pass the selection and are
6 // written to "example_EventSelection.dat"
7 // To Compile: go to the HepMC directory and type:
8 // gmake examples/example_EventSelection.exe
9 //
10 //
11
12 #include "HepMC/IO_GenEvent.h"
13 #include "HepMC/GenEvent.h"
14
15
16
17 class IsEventGood {
18 public:
19     bool operator()( const HepMC::GenEvent* evt ) {
20         for ( HepMC::GenEvent::particle_const_iterator p
21              = evt->particles_begin(); p != evt->particles_end(); ++p ){
22             if ( (*p)->pdg_id() == 22 && (*p)->momentum().perp() > 25. ) {
23                 //std::cout << "Event " << evt->event_number()
24                 //      << " is a good event." << std::endl;
25                 //(*p)->print();
26                 return 1;
27             }
28         }
29         return 0;
30     }
31 };
32
33 int main() {
34     // declare an input strategy to read the data produced with the
35     // example_MyPythia
36     { // begin scope of ascii_in and ascii_out
37         HepMC::IO_GenEvent ascii_in("example_MyPythia.dat",std::ios::in);
38         // declare another IO_GenEvent for writing out the good events
39         HepMC::IO_GenEvent ascii_out("example_EventSelection.dat",std::ios::out);
40         // declare an instance of the event selection predicate
41         IsEventGood is_good_event;
42         //.....EVENT LOOP
43         int icount=0;
44         int num_good_events=0;
45         HepMC::GenEvent* evt = ascii_in.read_next_event();
46         while ( evt ) {
47             icount++;
48             if ( icount%50==1 ) std::cout << "Processing Event Number " << icount
49                                     << " its # " << evt->event_number()
50                                     << std::endl;
51
52             if ( is_good_event(evt) ) {
53                 ascii_out << evt;
54                 ++num_good_events;
55             }
56             delete evt;
57             ascii_in >> evt;
58         }
59         //.....PRINT RESULT
60         std::cout << num_good_events << " out of " << icount
61                 << " processed events passed the cuts. Finished." << std::endl;
62     } // end scope of ascii_in and ascii_out
63     return 0;
64 }

```

```
67 }  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77
```

11.3 example_MyHerwig.cc

```

1
2 // Matt.Dobbs@Cern.CH, October 2002
3 // example of generating events with Herwig using HepMC/HerwigWrapper.h
4 // Events are read into the HepMC event record from the FORTRAN HEPEVT
5 // common block using the IO_HERWIG strategy.
6
7 #include <iostream>
8 #include "HepMC/HerwigWrapper.h"
9 #include "HepMC/IO_HERWIG.h"
10 #include "HepMC/IO_GenEvent.h"
11 #include "HepMC/GenEvent.h"
12 #include "HepMC/HEPEVT_Wrapper.h"
13
14 int main() {
15     //
16     //.....HEPEVT
17     // Herwig 6.4 uses HEPEVT with 4000 entries and 8-byte floating point
18     // numbers. We need to explicitly pass this information to the
19     // HEPEVT_Wrapper.
20     //
21     HepMC::HEPEVT_Wrapper::set_max_number_entries(4000);
22     HepMC::HEPEVT_Wrapper::set_sizeof_real(8);
23     //
24     //.....INITIALIZATIONS
25
26     hwproc.PBEAM1 = 7000.; // energy of beam1
27     hwproc.PBEAM2 = 7000.; // energy of beam2
28     // 1610 = gg->H-> WW, 1706 = qq->ttbar, 2510 = ttH -> ttWW
29     hwproc.IPROC = 1706; // qq -> ttbar production
30     hwproc.MAXEV = 100; // number of events
31     // tell it what the beam particles are:
32     for ( unsigned int i = 0; i < 8; ++i ) {
33         hwbmch.PART1[i] = (i < 1) ? 'P' : ' ';
34         hwbmch.PART2[i] = (i < 1) ? 'P' : ' ';
35     }
36     hwigin(); // INITIALISE OTHER COMMON BLOCKS
37     hwevnt.MAXPR = 1; // number of events to print
38     hwiinc(); // compute parameter-dependent constants
39     hweini(); // initialise elementary process
40
41     //.....HepMC INITIALIZATIONS
42     //
43     // Instantiate an IO strategy for reading from HEPEVT.
44     HepMC::IO_HERWIG hepevtio;
45     // Instantiate an IO strategy to write the data to file
46     HepMC::IO_GenEvent ascii_io("example_MyHerwig.dat",std::ios::out);
47     //
48     //.....EVENT LOOP
49     for ( int i = 1; i <= hwproc.MAXEV; i++ ) {
50         if ( i%50==1 ) std::cout << "Processing Event Number "
51             << i << std::endl;
52
53         // initialise event
54         hwiue();
55         // generate hard subprocess
56         hwepro();
57         // generate parton cascades
58         hwbgen();
59         // do heavy object decays
60         hwdhob();
61         // do cluster formation
62         hwcfor();
63         // do cluster decays
64         hwcdec();
65         // do unstable particle decays
66         hwdhad();
67     }
68 }

```

```
76         // do heavy flavour hadron decays
77         hwdhvy();
78         // add soft underlying event if needed
79         hwmevt();
80         // finish event
81         hwufne();
82         HepMC::GenEvent* evt = hepevtio.read_next_event();
83         // define the units (Herwig uses GeV and mm)
84         evt->use_units(HepMC::Units::GEV, HepMC::Units::MM);
85         // set cross section information
86         evt->set_cross_section( HepMC::getHerwigCrossSection(i) );
87         // add some information to the event
88         evt->set_event_number(i);
89         evt->set_signal_process_id(20);
90         if (i<=hwevnt.MAXPR) {
91             std::cout << "\n\n This is the FIXED version of HEPEVT as "
92                 << "coded in IO_HERWIG " << std::endl;
93             HepMC::HEPEVT_Wrapper::print_hepevt();
94             evt->print();
95         }
96         // write the event to the ascii file
97         ascii_io << evt;
98
99         // we also need to delete the created event from memory
100        delete evt;
101    }
102    //.....TERMINATION
103    hwefin();
104
105    return 0;
106 }
```

11.4 example_MyPythia.cc

example to generate events and write output example to generate events
and perform simple event selection example to read the file written by
pythia_out example to generate events, write them, and read them back

```

1
2 // Matt.Dobbs@Cern.CH, December 1999
3 // November 2000, updated to use Pythia 6.1
4 //
46
47
48 #include <iostream>
49 #include "HepMC/PythiaWrapper.h"
50 #include "HepMC/IO_HEPEVT.h"
51 #include "HepMC/IO_GenEvent.h"
52 #include "HepMC/IO_AsciiParticles.h"
53 #include "HepMC/GenEvent.h"
54 #include "PythiaHelper.h"
55
56
57
61 class IsGoodEventMyPythia {
62 public:
63     bool operator()( const HepMC::GenEvent* evt ) {
64         for ( HepMC::GenEvent::particle_const_iterator p
65              = evt->particles_begin(); p != evt->particles_end(); ++p ){
66             if ( (*p)->pdg_id() == 22 && (*p)->momentum().perp() > 25. ) {
67                 //std::cout << "Event " << evt->event_number()
68                 //      << " is a good event." << std::endl;
69                 //(*p)->print();
70                 return 1;
71             }
72         }
73         return 0;
74     }
75 };
76
77
78
79 void pythia_out();
80 void pythia_in();
81 void pythia_in_out();
82 void event_selection();
83 void pythia_particle_out();
84
85 int main() {
86     // example to generate events and write output
87     pythia_out();
88     // example to generate events and perform simple event selection
89     event_selection();
90     // example to read the file written by pythia_out
91     pythia_in();
92     // example to generate events, write them, and read them back
93     pythia_in_out();
94
95     return 0;
96 }
97
98
99 void pythia_out()
100 {
101     std::cout << std::endl;
102     std::cout << "Begin pythia_out()" << std::endl;
103     //.....HEPEVT
104     // Pythia 6.1 uses HEPEVT with 4000 entries and 8-byte floating point
105     // numbers. We need to explicitly pass this information to the
106     // HEPEVT_Wrapper.

```

```

107  //
108  HepMC::HEPEVT_Wrapper::set_max_number_entries(4000);
109  HepMC::HEPEVT_Wrapper::set_sizeof_real(8);
110  //
111  //.....PYTHIA INITIALIZATIONS
112  initPythia();
113
114  //.....HepMC INITIALIZATIONS
115  //
116  // Instantiate an IO strategy for reading from HEPEVT.
117  HepMC::IO_HEPEVT hepevtio;
118  //
119  { // begin scope of ascii_io
120      // Instantiate an IO strategy to write the data to file
121      HepMC::IO_GenEvent ascii_io("example_MyPythia.dat",std::ios::out);
122      //
123      //.....EVENT LOOP
124      for ( int i = 1; i <= 100; i++ ) {
125          if ( i%50==1 ) std::cout << "Processing Event Number "
126                                << i << std::endl;
127          call_pyevnt(); // generate one event with Pythia
128          // pythia pyhepc routine converts common PYJETS in common HEPEVT
129          call_pyhepc( 1 );
130          HepMC::GenEvent* evt = hepevtio.read_next_event();
131          // define the units (Pythia uses GeV and mm)
132          evt->use_units(HepMC::Units::GEV, HepMC::Units::MM);
133          // add some information to the event
134          evt->set_event_number(i);
135          evt->set_signal_process_id(20);
136          // set number of multi parton interactions
137          evt->set_mpi( pypars.msti[31-1] );
138          // set cross section information
139          evt->set_cross_section( HepMC::getPythiaCrossSection() );
140          // write the event out to the ascii files
141          ascii_io << evt;
142          // we also need to delete the created event from memory
143          delete evt;
144      }
145      //.....TERMINATION
146      // write out some information from Pythia to the screen
147      call_pystat( 1 );
148  } // end scope of ascii_io
149 }
150
151
152 void event_selection()
153 {
154     std::cout << std::endl;
155     std::cout << "Begin event_selection()" << std::endl;
156     //.....HEPEVT
157     // Pythia 6.1 uses HEPEVT with 4000 entries and 8-byte floating point
158     // numbers. We need to explicitly pass this information to the
159     // HEPEVT_Wrapper.
160     //
161     HepMC::HEPEVT_Wrapper::set_max_number_entries(4000);
162     HepMC::HEPEVT_Wrapper::set_sizeof_real(8);
163     //
164     //.....PYTHIA INITIALIZATIONS
165     initPythia();
166     //
167     //.....HepMC INITIALIZATIONS
168     // Instantiate an IO strategy for reading from HEPEVT.
169     HepMC::IO_HEPEVT hepevtio;
170     // declare an instance of the event selection predicate
171     IsGoodEventMyPythia is_good_event;
172     //.....EVENT LOOP
173     int icount=0;

```

```

174     int num_good_events=0;
175     for ( int i = 1; i <= 100; i++ ) {
176         icount++;
177         if ( i%50==1 ) std::cout << "Processing Event Number "
178             << i << std::endl;
179         call_pyevnt(); // generate one event with Pythia
180         // pythia pyhepc routine convert common PYJETS in common HEPEVT
181         call_pyhepc( 1 );
182         HepMC::GenEvent* evt = hepevtio.read_next_event();
183         // define the units (Pythia uses GeV and mm)
184         evt->use_units(HepMC::Units::GEV, HepMC::Units::MM);
185         // set number of multi parton interactions
186         evt->set_mpi( pypars.msti[31-1] );
187         // set cross section information
188         evt->set_cross_section( HepMC::getPythiaCrossSection() );
189         // do event selection
190         if ( is_good_event(evt) ) {
191             std::cout << "Good Event Number " << i << std::endl;
192             ++num_good_events;
193         }
194         // we also need to delete the created event from memory
195         delete evt;
196     }
197     //.....TERMINATION
198     // write out some information from Pythia to the screen
199     call_pystat( 1 );
200     //.....PRINT RESULTS
201     std::cout << num_good_events << " out of " << icount
202         << " processed events passed the cuts. Finished." << std::endl;
203 }
204
205 void pythia_in()
206 {
207     std::cout << std::endl;
208     std::cout << "Begin pythia_in()" << std::endl;
209     std::cout << "reading example_MyPythia.dat" << std::endl;
210     //.....define an input scope
211     {
212         // open input stream
213         std::ifstream istr( "example_MyPythia.dat" );
214         if( !istr ) {
215             std::cerr << "example_ReadMyPythia: cannot open example_MyPythia.dat" << std::endl;
216             exit(-1);
217         }
218         HepMC::IO_GenEvent ascii_in(istr);
219         // open output stream (alternate method)
220         HepMC::IO_GenEvent ascii_out("example_MyPythia2.dat",std::ios::out);
221         // now read the file
222         int icount=0;
223         HepMC::GenEvent* evt = ascii_in.read_next_event();
224         while ( evt ) {
225             icount++;
226             if ( icount%50==1 ) std::cout << "Processing Event Number " << icount
227                 << " its # " << evt->event_number()
228                 << std::endl;
229             // write the event out to the ascii file
230             ascii_out << evt;
231             delete evt;
232             ascii_in >> evt;
233         }
234         //.....PRINT RESULT
235         std::cout << icount << " events found. Finished." << std::endl;
236     } // ascii_out and istr destructors are called here
237 }
238
239 void pythia_in_out()
240 {

```

```

241     std::cout << std::endl;
242     std::cout << "Begin pythia_in_out()" << std::endl;
243     //.....HEPEVT
244     // Pythia 6.3 uses HEPEVT with 4000 entries and 8-byte floating point
245     // numbers. We need to explicitly pass this information to the
246     // HEPEVT_Wrapper.
247     //
248     HepMC::HEPEVT_Wrapper::set_max_number_entries(4000);
249     HepMC::HEPEVT_Wrapper::set_sizeof_real(8);
250     //
251     //.....PYTHIA INITIALIZATIONS
252     initPythia();
253
254     //.....HepMC INITIALIZATIONS
255     //
256     // Instantiate an IO strategy for reading from HEPEVT.
257     HepMC::IO_HEPEVT hepevtio;
258     //
259     //.....define the output scope
260     {
261         // Instantial an IO strategy to write the data to file
262         HepMC::IO_GenEvent ascii_io("example_MyPythiaRead.dat",std::ios::out);
263         //
264         //.....EVENT LOOP
265         for ( int i = 1; i <= 100; i++ ) {
266             if ( i%50==1 ) std::cout << "Processing Event Number "
267                 << i << std::endl;
268             call_pyevnt(); // generate one event with Pythia
269             // pythia pyhepc routine converts common PYJETS in common HEPEVT
270             call_pyhepc( 1 );
271             HepMC::GenEvent* evt = hepevtio.read_next_event();
272             // define the units (Pythia uses GeV and mm)
273             evt->use_units(HepMC::Units::GEV, HepMC::Units::MM);
274             // set cross section information
275             evt->set_cross_section( HepMC::getPythiaCrossSection() );
276             // add some information to the event
277             evt->set_event_number(i);
278             evt->set_signal_process_id(20);
279             // write the event out to the ascii file
280             ascii_io << evt;
281             // we also need to delete the created event from memory
282             delete evt;
283         }
284         //.....TERMINATION
285         // write out some information from Pythia to the screen
286         call_pystat( 1 );
287     } // ascii_io destructor is called here
288     //
289     //.....define an input scope
290     {
291         // now read the file we wrote
292         HepMC::IO_GenEvent ascii_in("example_MyPythiaRead.dat",std::ios::in);
293         HepMC::IO_GenEvent ascii_io2("example_MyPythiaRead2.dat",std::ios::out);
294         int icount=0;
295         HepMC::GenEvent* evt = ascii_in.read_next_event();
296         while ( evt ) {
297             icount++;
298             if ( icount%50==1 ) std::cout << "Processing Event Number " << icount
299                 << " its # " << evt->event_number()
300                 << std::endl;
301             // write the event out to the ascii file
302             ascii_io2 << evt;
303             delete evt;
304             ascii_in >> evt;
305         }
306         //.....PRINT RESULT
307         std::cout << icount << " events found. Finished." << std::endl;

```

```

308     } // ascii_io2 and ascii_in destructors are called here
309 }
310
311 void pythia_particle_out()
312 {
313     std::cout << std::endl;
314     std::cout << "Begin pythia_particle_out()" << std::endl;
315     //.....HEPEVT
316     // Pythia 6.1 uses HEPEVT with 4000 entries and 8-byte floating point
317     // numbers. We need to explicitly pass this information to the
318     // HEPEVT_Wrapper.
319     //
320     HepMC::HEPEVT_Wrapper::set_max_number_entries(4000);
321     HepMC::HEPEVT_Wrapper::set_sizeof_real(8);
322     //
323     //.....PYTHIA INITIALIZATIONS
324     initPythia();
325
326     //.....HepMC INITIALIZATIONS
327     //
328     // Instantiate an IO strategy for reading from HEPEVT.
329     HepMC::IO_HEPEVT hepevtio;
330     //
331     { // begin scope of ascii_io
332         // Instantiate an IO strategy to write the data to file
333         HepMC::IO_AsciiParticles ascii_io("example_PythiaParticle.dat",std::ios::out);
334         //
335         //.....EVENT LOOP
336         for ( int i = 1; i <= 100; i++ ) {
337             if ( i%50==1 ) std::cout << "Processing Event Number "
338                                     << i << std::endl;
339             call_pyevnt(); // generate one event with Pythia
340             // pythia pyhepc routine converts common PYJETS in common HEPEVT
341             call_pyhepc( 1 );
342             HepMC::GenEvent* evt = hepevtio.read_next_event();
343             // define the units (Pythia uses GeV and mm)
344             evt->use_units(HepMC::Units::GEV, HepMC::Units::MM);
345             // set cross section information
346             evt->set_cross_section( HepMC::getPythiaCrossSection() );
347             // add some information to the event
348             evt->set_event_number(i);
349             evt->set_signal_process_id(20);
350             // write the event out to the ascii file
351             ascii_io << evt;
352             // we also need to delete the created event from memory
353             delete evt;
354         }
355         //.....TERMINATION
356         // write out some information from Pythia to the screen
357         call_pystat( 1 );
358     } // end scope of ascii_io
359 }
360

```

11.5 example_MyPythiaOnlyToHepMC.cc

Example of generating events with Pythia using **HepMC/PythiaWrapper.h** (p.341) Events are read into the **HepMC** (p.23) event record from the FORTRAN HEPEVT common block using the IO_HEPEVT strategy - nothing is done with them. This program is just used to find the total time required to transfer from HEPEVT into the **HepMC** (p.23) event record.

```

1
2 // Matt.Dobbs@Cern.CH, December 1999
3 // November 2000, updated to use Pythia 6.1
4 // example of generating events with Pythia
5 // using HepMC/PythiaWrapper.h
6 // Events are read into the HepMC event record from the FORTRAN HEPEVT
7 // common block using the IO_HEPEVT strategy -- nothing is done with them.
8 // This program is just used to find the total time required to transfer
9 // from HEPEVT into the HepMC event record.
11 // To Compile: go to the HepMC directory and type:
12 // gmake examples/example_MyPythiaOnlyTo HepMC.exe
13 //
14 // See comments in examples/example_MyPythia.cxx regarding the HEPEVT wrapper.
15 //
16
17 #include <iostream>
18 #include "HepMC/PythiaWrapper.h"
19 #include "HepMC/IO_HEPEVT.h"
20 #include "HepMC/GenEvent.h"
21 #include "PythiaHelper.h"
22
23 int main() {
24     //
25     //.....HEPEVT
26     // Pythia 6.1 uses HEPEVT with 4000 entries and 8-byte floating point
27     // numbers. We need to explicitly pass this information to the
28     // HEPEVT_Wrapper.
29     //
30     HepMC::HEPEVT_Wrapper::set_max_number_entries(4000);
31     HepMC::HEPEVT_Wrapper::set_sizeof_real(8);
32     //
33     //.....PYTHIA INITIALIZATIONS
34     initPythia();
35     //
36     //.....HepMC INITIALIZATIONS
37     //
38     // Instantiate an IO strategy for reading from HEPEVT.
39     HepMC::IO_HEPEVT hepevtio;
40     //
41     //.....EVENT LOOP
42     for ( int i = 1; i <= 100; i++ ) {
43         if ( i%50==1 ) std::cout << "Processing Event Number "
44             << i << std::endl;
45         call_pyevnt(); // generate one event with Pythia
46         // pythia pyhepc routine convert common PYJETS in common HEPEVT
47         call_pyhepc( 1 );
48         HepMC::GenEvent* evt = hepevtio.read_next_event();
49         // define the units (Pythia uses GeV and mm)
50         evt->use_units(HepMC::Units::GEV, HepMC::Units::MM);
51         // set number of multi parton interactions
52         evt->set_mpi( pypars.msti[31-1] );
53         // set cross section information
54         evt->set_cross_section( HepMC::getPythiaCrossSection() );
55         //
56         //.....USER WOULD PROCESS EVENT HERE
57         //
58         // we also need to delete the created event from memory

```

```
59         delete evt;
60     }
61     //.....TERMINATION
62     // write out some information from Pythia to the screen
63     call_pystat( 1 );
64
65     return 0;
66 }
67
68
69
```

11.6 example_PythiaStreamIO.cc

This example generates Pythia events and fills cross section information from pyint5. The example uses streaming I/O to write a file and then read it.

```

1
2 // example_PythiaStreamIO.cc
3 //
4 // garren@fnal.gov, May 2009
5 //
19
20
21 #include <fstream>
22 #include <iostream>
23 #include "HepMC/PythiaWrapper.h"
24 #include "HepMC/IO_HEPEVT.h"
25 #include "HepMC/GenEvent.h"
26 #include "PythiaHelper.h"
27
28 void writePythiaStreamIO();
29 void readPythiaStreamIO();
30
31 int main() {
32
33     writePythiaStreamIO();
34     readPythiaStreamIO();
35
36     return 0;
37 }
38
39
40 void writePythiaStreamIO() {
41     // example to generate events and write output
42     std::cout << std::endl;
43     std::cout << "Begin pythia_out()" << std::endl;
44     //.....HEPEVT
45     // Pythia 6.1 uses HEPEVT with 4000 entries and 8-byte floating point
46     // numbers. We need to explicitly pass this information to the
47     // HEPEVT_Wrapper.
48     //
49     HepMC::HEPEVT_Wrapper::set_max_number_entries(4000);
50     HepMC::HEPEVT_Wrapper::set_sizeof_real(8);
51     //
52     //.....PYTHIA INITIALIZATIONS
53     initPythia();
54
55     //.....HepMC INITIALIZATIONS
56     //
57     // Instantiate an IO strategy for reading from HEPEVT.
58     HepMC::IO_HEPEVT hepevtio;
59     //
60     { // begin scope of ascii_io
61         // declare an output stream
62         const char outfile[] = "example_PythiaStreamIO_write.dat";
63         std::ofstream ascii_io( outfile );
64         if( !ascii_io ) {
65             std::cerr << "cannot open " << outfile << std::endl;
66             exit(-1);
67         }
68         // use the default IO_GenEvent precision
69         ascii_io.precision(16);
70         // write the line that defines the beginning of a GenEvent block
71         HepMC::write_HepMC_IO_block_begin( ascii_io );
72         //
73         //.....EVENT LOOP

```

```

74     for ( int i = 1; i <= 100; i++ ) {
75         if ( i%50==1 ) std::cout << "Processing Event Number "
76                               << i << std::endl;
77         call_pyevnt();          // generate one event with Pythia
78         // pythia pyhepc routine converts common PYJETS in common HEPEVT
79         call_pyhepc( 1 );
80         HepMC::GenEvent* evt = hepevtio.read_next_event();
81         // define the units (Pythia uses GeV and mm)
82         evt->use_units(HepMC::Units::GEV, HepMC::Units::MM);
83         // add some information to the event
84         evt->set_event_number(i);
85         evt->set_signal_process_id(20);
86         // set number of multi parton interactions
87         evt->set_mpi( pypars.msti[31-1] );
88         // set cross section information
89         evt->set_cross_section( HepMC::getPythiaCrossSection() );
90         // write the event out to the ascii files
91         ascii_io << (*evt);;
92         // we also need to delete the created event from memory
93         delete evt;
94     }
95     // write the line that defines the end of a GenEvent block
96     HepMC::write_HepMC_IO_block_end( ascii_io );
97     //.....TERMINATION
98     // write out some information from Pythia to the screen
99     call_pystat( 1 );
100 } // end scope of ascii_io
101 }
102
103 void readPythiaStreamIO() {
104     // example to read events written by writePythiaStreamIO
105     // and write them back out
106     std::cout << std::endl;
107     // input units are GeV and mm
108     const char infile[] = "example_PythiaStreamIO_write.dat";
109     std::ifstream is( infile );
110     if( !is ) {
111         std::cerr << "cannot open " << infile << std::endl;
112         exit(-1);
113     }
114     //
115     { // begin scope of ascii_io
116         // declare an output stream
117         const char outfile[] = "example_PythiaStreamIO_read.dat";
118         std::ofstream ascii_io( outfile );
119         if( !ascii_io ) {
120             std::cerr << "cannot open " << outfile << std::endl;
121             exit(-1);
122         }
123         ascii_io.precision(16);
124         HepMC::write_HepMC_IO_block_begin( ascii_io );
125         //
126         //.....EVENT LOOP
127         HepMC::GenEvent evt;
128         int i = 0;
129         while ( is ) {
130             evt.read( is );
131             // make sure we have a valid event
132             if( evt.is_valid() ) {
133                 ++i;
134                 if ( i%50==1 ) std::cout << "Processing Event Number "
135                                           << i << std::endl;
136                 if ( i%25==2 ) {
137                     // write the cross section if it exists
138                     if( evt.cross_section() ) {
139                         std::cout << "cross section at event " << i << " is "
140                                   << evt.cross_section()->cross_section()

```

```
141                                     << std::endl;
142                                     }
143                                     }
144                                     // write the event out to the ascii files
145                                     evt.write( ascii_io );
146                                     }
147                                     }
148                                     //.....TERMINATION
149                                     HepMC::write_HepMC_IO_block_end( ascii_io );
150     } // end scope of ascii_io
151 }
```

11.7 example_UsingIterators.cc

This example shows how to use the particle and vertex iterators

```

1
2 // Matt.Dobbs@Cern.CH, Feb 2000
3 // This example shows how to use the particle and vertex iterators
5 // To Compile: go to the HepMC directory and type:
6 // gmake examples/example_UsingIterators.exe
7 //
8
9 #include "HepMC/IO_GenEvent.h"
10 #include "HepMC/GenEvent.h"
11 #include <math.h>
12 #include <algorithm>
13 #include <list>
14
15
16
17 class IsPhoton {
18 public:
19     bool operator()( const HepMC::GenParticle* p ) {
20         if ( p->pdg_id() == 22
21             && p->momentum().perp() > 10. ) return 1;
22         return 0;
23     }
24 };
25
26
27 class IsW_Boson {
28 public:
29     bool operator()( const HepMC::GenParticle* p ) {
30         if ( abs(p->pdg_id()) == 24 ) return 1;
31         return 0;
32     }
33 };
34
35
36 class IsStateFinal {
37 public:
38     bool operator()( const HepMC::GenParticle* p ) {
39         if ( !p->end_vertex() && p->status()==1 ) return 1;
40         return 0;
41     }
42 };
43
44
45 int main() {
46     { // begin scope of ascii_in
47         // an event has been prepared in advance for this example, read it
48         // into memory using the IO_GenEvent input strategy
49         HepMC::IO_GenEvent ascii_in("example_UsingIterators.txt",std::ios::in);
50         if ( ascii_in.rdstate() == std::ios::failbit ) {
51             std::cerr << "ERROR input file example_UsingIterators.txt is needed "
52                 << "and does not exist. "
53                 << "\n Look for it in HepMC/examples, Exit." << std::endl;
54             return 1;
55         }
56
57         HepMC::GenEvent* evt = ascii_in.read_next_event();
58
59         // if you wish to have a look at the event, then use evt->print();
60
61         // use GenEvent::vertex_iterator to fill a list of all
62         // vertices in the event
63         std::list<HepMC::GenVertex*> allvertices;
64         for ( HepMC::GenEvent::vertex_iterator v = evt->vertices_begin();
65              v != evt->vertices_end(); ++v ) {

```

```

77         allvertices.push_back(*v);
78     }
79
80     // we could do the same thing with the STL algorithm copy
81     std::list<HepMC::GenVertex*> allvertices2;
82     copy( evt->vertices_begin(), evt->vertices_end(),
83           back_inserter(allvertices2) );
84
85     // fill a list of all final state particles in the event, by requiring
86     // that each particle satisfies the IsStateFinal predicate
87     IsStateFinal isfinal;
88     std::list<HepMC::GenParticle*> finalstateparticles;
89     for ( HepMC::GenEvent::particle_iterator p = evt->particles_begin();
90           p != evt->particles_end(); ++p ) {
91         if ( isfinal(*p) ) finalstateparticles.push_back(*p);
92     }
93
94     // an STL-like algorithm called HepMC::copy_if is provided in the
95     // GenEvent.h header to do this sort of operation more easily,
96     // you could get the identical results as above by using:
97     std::list<HepMC::GenParticle*> finalstateparticles2;
98     HepMC::copy_if( evt->particles_begin(), evt->particles_end(),
99                     back_inserter(finalstateparticles2), IsStateFinal() );
100
101     // lets print all photons in the event that satisfy the IsPhoton criteria
102     IsPhoton isphoton;
103     for ( HepMC::GenEvent::particle_iterator p = evt->particles_begin();
104           p != evt->particles_end(); ++p ) {
105         if ( isphoton(*p) ) (*p)->print();
106     }
107
108     // the GenVertex::particle_iterator and GenVertex::vertex_iterator
109     // are slightly different from the GenEvent:: versions, in that
110     // the iterator starts at the given vertex, and walks through the attached
111     // vertex returning particles/vertices.
112     // Thus only particles/vertices which are in the same graph as the given
113     // vertex will be returned. A range is specified with these iterators,
114     // the choices are:
115     //   parents, children, family, ancestors, descendants, relatives
116     // here are some examples.
117
118     // use GenEvent::particle_iterator to find all W's in the event,
119     // then
120     // (1) for each W user the GenVertex::particle_iterator with a range of
121     //     parents to return and print the immediate mothers of these W's.
122     // (2) for each W user the GenVertex::particle_iterator with a range of
123     //     descendants to return and print all descendants of these W's.
124     IsW_Boson isw;
125     for ( HepMC::GenEvent::particle_iterator p = evt->particles_begin();
126           p != evt->particles_end(); ++p ) {
127         if ( isw(*p) ) {
128             std::cout << "A W boson has been found: " << std::endl;
129             (*p)->print();
130             // return all parents
131             // we do this by pointing to the production vertex of the W
132             // particle and asking for all particle parents of that vertex
133             std::cout << "\t Its parents are: " << std::endl;
134             if ( (*p)->production_vertex() ) {
135                 for ( HepMC::GenVertex::particle_iterator mother
136                       = (*p)->production_vertex()->
137                         particles_begin(HepMC::parents);
138                       mother != (*p)->production_vertex()->
139                         particles_end(HepMC::parents);
140                       ++mother ) {
141                 std::cout << "\t";
142                 (*mother)->print();
143             }

```

```
144         }
145         // return all descendants
146         // we do this by pointing to the end vertex of the W
147         // particle and asking for all particle descendants of that vertex
148         std::cout << "\t\t Its descendants are: " << std::endl;
149         if ( (*p)->end_vertex() ) {
150             for ( HepMC::GenVertex::particle_iterator des
151                  = (*p)->end_vertex()->
152                    particles_begin(HepMC::descendants);
153                  des != (*p)->end_vertex()->
154                    particles_end(HepMC::descendants);
155                  ++des ) {
156                 std::cout << "\t\t";
157                 (*des)->print();
158             }
159         }
160     }
161 }
162 // cleanup
163 delete evt;
164 // in analogy to the above, similar use can be made of the
165 // HepMC::GenVertex::vertex_iterator, which also accepts a range.
166 } // end scope of ascii_in
167
168 return 0;
169 }
```

11.8 testFlow.cc

Use a modified example_BuildEventFromScratch to test Flow

```

1
2 // testFlow.cc
3 //
4 // garren@fnal.gov, June 2009
5 // based on example_BuildEventFromScratch.cc
6
7
8 #include <iostream>
9 #include <fstream>
10 #include <vector>
11
12 #include "HepMC/GenEvent.h"
13 #include "HepMC/IO_GenEvent.h"
14
15 typedef std::vector<HepMC::GenParticle*> FlowVec;
16
17 int main() {
18     //
19     // In this example we will place the following event into HepMC "by hand"
20     //
21     //      name status pdg_id  parent Px      Py      Pz      Energy      Mass
22     //  1  !p+!      3    2212    0,0    0.000    0.000 7000.000 7000.000    0.938
23     //  2  !p+!      3    2212    0,0    0.000    0.000-7000.000 7000.000    0.938
24     //=====
25     //  3  !d!        3        1    1,1    0.750   -1.569   32.191   32.238    0.000
26     //  4  !u~!       3       -2    2,2   -3.047  -19.000  -54.629   57.920    0.000
27     //  5  !W-!       3      -24    1,2    1.517   -20.68   -20.605   85.925   80.799
28     //  6  !gamma!    1        22    1,2   -3.813    0.113   -1.833    4.233    0.000
29     //  7  !d!        1         1    5,5   -2.445   28.816    6.082   29.552    0.010
30     //  8  !u~!       1       -2    5,5    3.962  -49.498  -26.687   56.373    0.006
31
32     // open an output file
33     const char outfile[] = "testFlow.out";
34     std::ofstream os( outfile );
35     if( !os ) {
36         std::cerr << "cannot open " << outfile << std::endl;
37         exit(-1);
38     }
39     // declare several IO_GenEvent instances for comparison
40     HepMC::IO_GenEvent xout1("testFlow.out1",std::ios::out);
41     HepMC::IO_GenEvent xout2("testFlow.out2",std::ios::out);
42     HepMC::IO_GenEvent xout3("testFlow.out3",std::ios::out);
43     // output streams for copy test
44     std::ofstream xout4( "testFlow.out4" );
45     std::ofstream xout5( "testFlow.out5" );
46
47     int numbad = 0;
48
49
50     // build the graph, which will look like
51     //
52     //      p1
53     //      /
54     //  \v1__p3      p5---v4
55     //      \_v3_/
56     //      /      \
57     //  v2__p4      \
58     //      /      \
59     //      /      \
60     //      /      \
61     //      /      \
62     //      /      \
63     //      /      \
64     //      /      \
65     //      /      \
66     //      /      \
67     //      /      \
68     //      /      \
69     //      /      \
70     //      /      \
71     //      /      \
72     //      /      \
73     //      /      \
74     //      /      \
75     //      /      \
76     //      /      \
77     //      /      \
78     //      /      \
79     //      /      \
80     //      /      \
81     //      /      \
82     //      /      \
83     //      /      \
84     //      /      \
85     //      /      \
86     //      /      \
87     //      /      \
88     //      /      \
89     //      /      \
90     //      /      \
91     //      /      \
92     //      /      \
93     //      /      \
94     //      /      \
95     //      /      \
96     //      /      \
97     //      /      \
98     //      /      \
99     //      /      \
100    //      /      \
101    //      /      \
102    //      /      \
103    //      /      \
104    //      /      \
105    //      /      \
106    //      /      \
107    //      /      \
108    //      /      \
109    //      /      \
110    //      /      \
111    //      /      \
112    //      /      \
113    //      /      \
114    //      /      \
115    //      /      \
116    //      /      \
117    //      /      \
118    //      /      \
119    //      /      \
120    //      /      \
121    //      /      \
122    //      /      \
123    //      /      \
124    //      /      \
125    //      /      \
126    //      /      \
127    //      /      \
128    //      /      \
129    //      /      \
130    //      /      \
131    //      /      \
132    //      /      \
133    //      /      \
134    //      /      \
135    //      /      \
136    //      /      \
137    //      /      \
138    //      /      \
139    //      /      \
140    //      /      \
141    //      /      \
142    //      /      \
143    //      /      \
144    //      /      \
145    //      /      \
146    //      /      \
147    //      /      \
148    //      /      \
149    //      /      \
150    //      /      \
151    //      /      \
152    //      /      \
153    //      /      \
154    //      /      \
155    //      /      \
156    //      /      \
157    //      /      \
158    //      /      \
159    //      /      \
160    //      /      \
161    //      /      \
162    //      /      \
163    //      /      \
164    //      /      \
165    //      /      \
166    //      /      \
167    //      /      \
168    //      /      \
169    //      /      \
170    //      /      \
171    //      /      \
172    //      /      \
173    //      /      \
174    //      /      \
175    //      /      \
176    //      /      \
177    //      /      \
178    //      /      \
179    //      /      \
180    //      /      \
181    //      /      \
182    //      /      \
183    //      /      \
184    //      /      \
185    //      /      \
186    //      /      \
187    //      /      \
188    //      /      \
189    //      /      \
190    //      /      \
191    //      /      \
192    //      /      \
193    //      /      \
194    //      /      \
195    //      /      \
196    //      /      \
197    //      /      \
198    //      /      \
199    //      /      \
200    //      /      \
201    //      /      \
202    //      /      \
203    //      /      \
204    //      /      \
205    //      /      \
206    //      /      \
207    //      /      \
208    //      /      \
209    //      /      \
210    //      /      \
211    //      /      \
212    //      /      \
213    //      /      \
214    //      /      \
215    //      /      \
216    //      /      \
217    //      /      \
218    //      /      \
219    //      /      \
220    //      /      \
221    //      /      \
222    //      /      \
223    //      /      \
224    //      /      \
225    //      /      \
226    //      /      \
227    //      /      \
228    //      /      \
229    //      /      \
230    //      /      \
231    //      /      \
232    //      /      \
233    //      /      \
234    //      /      \
235    //      /      \
236    //      /      \
237    //      /      \
238    //      /      \
239    //      /      \
240    //      /      \
241    //      /      \
242    //      /      \
243    //      /      \
244    //      /      \
245    //      /      \
246    //      /      \
247    //      /      \
248    //      /      \
249    //      /      \
250    //      /      \
251    //      /      \
252    //      /      \
253    //      /      \
254    //      /      \
255    //      /      \
256    //      /      \
257    //      /      \
258    //      /      \
259    //      /      \
260    //      /      \
261    //      /      \
262    //      /      \
263    //      /      \
264    //      /      \
265    //      /      \
266    //      /      \
267    //      /      \
268    //      /      \
269    //      /      \
270    //      /      \
271    //      /      \
272    //      /      \
273    //      /      \
274    //      /      \
275    //      /      \
276    //      /      \
277    //      /      \
278    //      /      \
279    //      /      \
280    //      /      \
281    //      /      \
282    //      /      \
283    //      /      \
284    //      /      \
285    //      /      \
286    //      /      \
287    //      /      \
288    //      /      \
289    //      /      \
290    //      /      \
291    //      /      \
292    //      /      \
293    //      /      \
294    //      /      \
295    //      /      \
296    //      /      \
297    //      /      \
298    //      /      \
299    //      /      \
300    //      /      \
301    //      /      \
302    //      /      \
303    //      /      \
304    //      /      \
305    //      /      \
306    //      /      \
307    //      /      \
308    //      /      \
309    //      /      \
310    //      /      \
311    //      /      \
312    //      /      \
313    //      /      \
314    //      /      \
315    //      /      \
316    //      /      \
317    //      /      \
318    //      /      \
319    //      /      \
320    //      /      \
321    //      /      \
322    //      /      \
323    //      /      \
324    //      /      \
325    //      /      \
326    //      /      \
327    //      /      \
328    //      /      \
329    //      /      \
330    //      /      \
331    //      /      \
332    //      /      \
333    //      /      \
334    //      /      \
335    //      /      \
336    //      /      \
337    //      /      \
338    //      /      \
339    //      /      \
340    //      /      \
341    //      /      \
342    //      /      \
343    //      /      \
344    //      /      \
345    //      /      \
346    //      /      \
347    //      /      \
348    //      /      \
349    //      /      \
350    //      /      \
351    //      /      \
352    //      /      \
353    //      /      \
354    //      /      \
355    //      /      \
356    //      /      \
357    //      /      \
358    //      /      \
359    //      /      \
360    //      /      \
361    //      /      \
362    //      /      \
363    //      /      \
364    //      /      \
365    //      /      \
366    //      /      \
367    //      /      \
368    //      /      \
369    //      /      \
370    //      /      \
371    //      /      \
372    //      /      \
373    //      /      \
374    //      /      \
375    //      /      \
376    //      /      \
377    //      /      \
378    //      /      \
379    //      /      \
380    //      /      \
381    //      /      \
382    //      /      \
383    //      /      \
384    //      /      \
385    //      /      \
386    //      /      \
387    //      /      \
388    //      /      \
389    //      /      \
390    //      /      \
391    //      /      \
392    //      /      \
393    //      /      \
394    //      /      \
395    //      /      \
396    //      /      \
397    //      /      \
398    //      /      \
399    //      /      \
400    //      /      \
401    //      /      \
402    //      /      \
403    //      /      \
404    //      /      \
405    //      /      \
406    //      /      \
407    //      /      \
408    //      /      \
409    //      /      \
410    //      /      \
411    //      /      \
412    //      /      \
413    //      /      \
414    //      /      \
415    //      /      \
416    //      /      \
417    //      /      \
418    //      /      \
419    //      /      \
420    //      /      \
421    //      /      \
422    //      /      \
423    //      /      \
424    //      /      \
425    //      /      \
426    //      /      \
427    //      /      \
428    //      /      \
429    //      /      \
430    //      /      \
431    //      /      \
432    //      /      \
433    //      /      \
434    //      /      \
435    //      /      \
436    //      /      \
437    //      /      \
438    //      /      \
439    //      /      \
440    //      /      \
441    //      /      \
442    //      /      \
443    //      /      \
444    //      /      \
445    //      /      \
446    //      /      \
447    //      /      \
448    //      /      \
449    //      /      \
450    //      /      \
451    //      /      \
452    //      /      \
453    //      /      \
454    //      /      \
455    //      /      \
456    //      /      \
457    //      /      \
458    //      /      \
459    //      /      \
460    //      /      \
461    //      /      \
462    //      /      \
463    //      /      \
464    //      /      \
465    //      /      \
466    //      /      \
467    //      /      \
468    //      /      \
469    //      /      \
470    //      /      \
471    //      /      \
472    //      /      \
473    //      /      \
474    //      /      \
475    //      /      \
476    //      /      \
477    //      /      \
478    //      /      \
479    //      /      \
480    //      /      \
481    //      /      \
482    //      /      \
483    //      /      \
484    //      /      \
485    //      /      \
486    //      /      \
487    //      /      \
488    //      /      \
489    //      /      \
490    //      /      \
491    //      /      \
492    //      /      \
493    //      /      \
494    //      /      \
495    //      /      \
496    //      /      \
497    //      /      \
498    //      /      \
499    //      /      \
500    //      /      \
501    //      /      \
502    //      /      \
503    //      /      \
504    //      /      \
505    //      /      \
506    //      /      \
507    //      /      \
508    //      /      \
509    //      /      \
510    //      /      \
511    //      /      \
512    //      /      \
513    //      /      \
514    //      /      \
515    //      /      \
516    //      /      \
517    //      /      \
518    //      /      \
519    //      /      \
520    //      /      \
521    //      /      \
522    //      /      \
523    //      /      \
524    //      /      \
525    //      /      \
526    //      /      \
527    //      /      \
528    //      /      \
529    //      /      \
530    //      /      \
531    //      /      \
532    //      /      \
533    //      /      \
534    //      /      \
535    //      /      \
536    //      /      \
537    //      /      \
538    //      /      \
539    //      /      \
540    //      /      \
541    //      /      \
542    //      /      \
543    //      /      \
544    //      /      \
545    //      /      \
546    //      /      \
547    //      /      \
548    //      /      \
549    //      /      \
550    //      /      \
551    //      /      \
552    //      /      \
553    //      /      \
554    //      /      \
555    //      /      \
556    //      /      \
557    //      /      \
558    //      /      \
559    //      /      \
560    //      /      \
561    //      /      \
562    //      /      \
563    //      /      \
564    //      /      \
565    //      /      \
566    //      /      \
567    //      /      \
568    //      /      \
569    //      /      \
570    //      /      \
571    //      /      \
572    //      /      \
573    //      /      \
574    //      /      \
575    //      /      \
576    //      /      \
577    //      /      \
578    //      /      \
579    //      /      \
580    //      /      \
581    //      /      \
582    //      /      \
583    //      /      \
584    //      /      \
585    //      /      \
586    //      /      \
587    //      /      \
588    //      /      \
589    //      /      \
590    //      /      \
591    //      /      \
592    //      /      \
593    //      /      \
594    //      /      \
595    //      /      \
596    //      /      \
597    //      /      \
598    //      /      \
599    //      /      \
600    //      /      \
601    //      /      \
602    //      /      \
603    //      /      \
604    //      /      \
605    //      /      \
606    //      /      \
607    //      /      \
608    //      /      \
609    //      /      \
610    //      /      \
611    //      /      \
612    //      /      \
613    //      /      \
614    //      /      \
615    //      /      \
616    //      /      \
617    //      /      \
618    //      /      \
619    //      /      \
620    //      /      \
621    //      /      \
622    //      /      \
623    //      /      \
624    //      /      \
625    //      /      \
626    //      /      \
627    //      /      \
628    //      /      \
629    //      /      \
630    //      /      \
631    //      /      \
632    //      /      \
633    //      /      \
634    //      /      \
635    //      /      \
636    //      /      \
637    //      /      \
638    //      /      \
639    //      /      \
640    //      /      \
641    //      /      \
642    //      /      \
643    //      /      \
644    //      /      \
645    //      /      \
646    //      /      \
647    //      /      \
648    //      /      \
649    //      /      \
650    //      /      \
651    //      /      \
652    //      /      \
653    //      /      \
654    //      /      \
655    //      /      \
656    //      /      \
657    //      /      \
658    //      /      \
659    //      /      \
660    //      /      \
661    //      /      \
662    //      /      \
663    //      /      \
664    //      /      \
665    //      /      \
666    //      /      \
667    //      /      \
668    //      /      \
669    //      /      \
670    //      /      \
671    //      /      \
672    //      /      \
673    //      /      \
674    //      /      \
675    //      /      \
676    //      /      \
677    //      /      \
678    //      /      \
679    //      /      \
680    //      /      \
681    //      /      \
682    //      /      \
683    //      /      \
684    //      /      \
685    //      /      \
686    //      /      \
687    //      /      \
688    //      /      \
689    //      /      \
690    //      /      \
691    //      /      \
692    //      /      \
693    //      /      \
694    //      /      \
695    //      /      \
696    //      /      \
697    //      /      \
698    //      /      \
699    //      /      \
700    //      /      \
701    //      /      \
702    //      /      \
703    //      /      \
704    //      /      \
705    //      /      \
706    //      /      \
707    //      /      \
708    //      /      \
709    //      /      \
710    //      /      \
711    //      /      \
712    //      /      \
713    //      /      \
714    //      /      \
715    //      /      \
716    //      /      \
717    //      /      \
718    //      /      \
719    //      /      \
720    //      /      \
721    //      /      \
722    //      /      \
723    //      /      \
724    //      /      \
725    //      /      \
726    //      /      \
727    //      /      \
728    //      /      \
729    //      /      \
730    //      /      \
731    //      /      \
732    //      /      \
733    //      /      \
734    //      /      \
735    //      /      \
736    //      /      \
737    //      /      \
738    //      /      \
739    //      /      \
740    //      /      \
741    //      /      \
742    //      /      \
743    //      /      \
744    //      /      \
745    //      /      \
746    //      /      \
747    //      /      \
748    //      /      \
749    //      /      \
750    //      /      \
751    //      /      \
752    //      /      \
753    //      /      \
754    //      /      \
755    //      /      \
756    //      /      \
757    //      /      \
758    //      /      \
759    //      /      \
760    //      /      \
761    //      /      \
762    //      /      \
763    //      /      \
764    //      /      \
765    //      /      \
766    //      /      \
767    //      /      \
768    //      /      \
769    //      /      \
770    //      /      \
771    //      /      \
772    //      /      \
773    //      /      \
774    //      /      \
775    //      /      \
776    //      /      \
777    //      /      \
778    //      /      \
779    //      /      \
780    //      /      \
781    //      /      \
782    //      /      \
783    //      /      \
784    //      /      \
785    //      /      \
786    //      /      \
787    //      /      \
788    //      /      \
789    //      /      \
790    //      /      \
791    //      /      \
792    //      /      \
793    //      /      \
794    //      /      \
795    //      /      \
796    //      /      \
797    //      /      \
798    //      /      \
799    //      /      \
800    //      /      \
801    //      /      \
802    //      /      \
803    //      /      \
804    //      /      \
805    //      /      \
806    //      /      \
807    //      /      \
808    //      /      \
809    //      /      \
810    //      /      \
811    //      /      \
812    //      /      \
813    //      /      \
814    //      /      \
815    //      /      \
816    //      /      \
817    //      /      \
818    //      /      \
819    //      /      \
820    //      /      \
821    //      /      \
822    //      /      \
823    //      /      \
824    //      /      \
825    //      /      \
826    //      /      \
827    //      /      \
828    //      /      \
829    //      /      \
830    //      /      \
831    //      /      \
832    //      /      \
833    //      /      \
834    //      /      \
835    //      /      \
836    //      /      \
837    //      /      \
838    //      /      \
839    //      /      \
840    //      /      \
841    //      /      \
842    //      /      \
843    //      /      \
844    //      /      \
845    //      /      \
846    //      /      \
847    //      /      \
848    //      /      \
849    //      /      \
850    //      /      \
851    //      /      \
852    //      /      \
853    //      /      \
854    //      /      \
855    //      /      \
856    //      /      \
857    //      /      \
858    //      /      \
859    //      /      \
860    //      /      \
861    //      /      \
862    //      /      \
863    //      /      \
864    //      /      \
865    //      /      \
866    //      /      \
867    //      /      \
868    //      /      \
869    //      /      \
870    //      /      \
871    //      /      \
872    //      /      \
873    //      /      \
874    //      /      \
875    //      /      \
876    //      /      \
877    //      /      \
878    //      /      \
879    //      /      \
880    //      /      \
881    //      /      \
882    //      /      \
883    //      /      \
884    //      /      \
885    //      /      \
886    //      /      \
887    //      /      \
888    //      /      \
889    //      /      \
890    //      /      \
891    //      /      \
892    //      /      \
893    //      /      \
894    //      /      \
895    //      /      \
896    //      /      \
897    //      /      \
898    //      /      \
899    //      /      \
900    //      /      \
901    //      /      \
902    //      /      \
903    //      /      \
904    //      /      \
905    //      /      \
906    //      /      \
907    //      /      \
908    //      /      \
909    //      /      \
910    //      /      \
911    //      /      \
912    //      /      \
913    //      /      \
914    //      /      \
915    //      /      \
916    //      /      \
917    //      /      \
918    //      /      \
919    //      /      \
920    //      /      \
921    //      /      \
922    //      /      \
923    //      /      \
924    //      /      \
925    //      /      \
926    //      /      \
927    //      /      \
928    //      /      \
929    //      /      \
930    //      /      \
931    //      /      \
932    //      /      \
933    //      /      \
934    //      /      \
935    //      /      \
936    //      /      \
937    //      /      \
938    //      /      \
939    //      /      \
940    //      /      \
941    //      /      \
942    //      /      \
943    //      /      \
944    //      /      \
945    //      /      \
946    //      /      \
947    //      /      \
948    //      /      \
949    //      /      \
950    //      /      \
951    //      /      \
952    //      /      \
953    //      /      \
954    //      /      \
955    //      /      \
956    //      /      \
957    //      /      \
958    //      /      \
959    //      /      \
960    //      /      \
961    //      /      \
962    //      /      \
963    //      /      \
964    //      /      \
965    //      /      \
966    //      /      \
967    //      /      \
968    //      /      \
969    //      /      \
970    //      /      \
971    //      /      \
972    //      /      \
973    //      /      \
974    //      /      \
975    //      /      \
976    //      /      \
977    //      /      \
978    //      /      \
979    //      /      \
980    //      /      \
981    //      /      \
982    //      /      \
983    //      /      \
984    //      /      \
985    //      /      \
986    //      /      \
987    //      /      \
988    //      /      \
989    //      /      \
990    //      /      \
991    //      /      \
992    //      /      \
993    //      /      \
994    //      /      \
995    //      /      \
996    //      /      \
997    //      /      \
998    //      /      \
999    //      /      \
1000   //      /      \

```

```

64 // First create the event container, with Signal Process 20, event number 1
65 //
66 HepMC::GenEvent* evt = new HepMC::GenEvent( 20, 1 );
67 evt->use_units(HepMC::Units::GEV, HepMC::Units::MM);
68 //
69 // create vertex 1 and vertex 2, together with their inparticles
70 HepMC::GenVertex* v1 = new HepMC::GenVertex();
71 evt->add_vertex( v1 );
72 HepMC::GenParticle* p1 = new HepMC::GenParticle( HepMC::FourVector(0,0,7000,7000),
73                                                    2212, 3 );
74 p1->set_flow(1,231);
75 v1->add_particle_in( p1 );
76 HepMC::GenVertex* v2 = new HepMC::GenVertex();
77 evt->add_vertex( v2 );
78 HepMC::GenParticle* p2 = new HepMC::GenParticle( HepMC::FourVector(0,0,-7000,7000),
79                                                    2212, 3 );
80 p2->set_flow(1,243);
81 v2->add_particle_in( p2 );
82 //
83 // create the outgoing particles of v1 and v2
84 HepMC::GenParticle* p3 =
85     new HepMC::GenParticle( HepMC::FourVector(.750,-1.569,32.191,32.238),
86                             1, 3 );
87 p3->set_flow(1,231);
88 v1->add_particle_out( p3 );
89 HepMC::GenParticle* p4 =
90     new HepMC::GenParticle( HepMC::FourVector(-3.047,-19.,-54.629,57.920),
91                             -2, 3 );
92 p4->set_flow(1,243);
93 v2->add_particle_out( p4 );
94 //
95 // create v3
96 HepMC::GenVertex* v3 = new HepMC::GenVertex();
97 evt->add_vertex( v3 );
98 v3->add_particle_in( p3 );
99 v3->add_particle_in( p4 );
100 HepMC::GenParticle* p6 =
101     new HepMC::GenParticle( HepMC::FourVector(-3.813,0.113,-1.833,4.233 ),
102                             22, 1 );
103 p6->set_flow(1,231);
104 v3->add_particle_out( p6 );
105 HepMC::GenParticle* p5 =
106     new HepMC::GenParticle( HepMC::FourVector(1.517,-20.68,-20.605,85.925),
107                             -24, 3 );
108 p5->set_flow(1,243);
109 v3->add_particle_out( p5 );
110 //
111 // create v4
112 HepMC::GenVertex* v4 = new HepMC::GenVertex( HepMC::FourVector(0.12,-0.3,0.05,0.004) );
113 evt->add_vertex( v4 );
114 v4->add_particle_in( p5 );
115 HepMC::GenParticle* p7 = new HepMC::GenParticle( HepMC::FourVector(-2.445,28.816,6.082,29.552), 1,
116 v4->add_particle_out( p7 );
117 HepMC::GenParticle* p8 = new HepMC::GenParticle( HepMC::FourVector(3.962,-49.498,-26.687,56.373),
118 v4->add_particle_out( p8 );
119 //
120 // tell the event which vertex is the signal process vertex
121 evt->set_signal_process_vertex( v3 );
122 // the event is complete, we now print it out
123 evt->print( os );
124
125 // look at the flow we created
126 os << std::endl;
127 FlowVec result1 = p1->flow().dangling_connected_partners( p1->flow().icode(1) );
128 FlowVec result2 = p1->flow().connected_partners( p1->flow().icode(1) );
129 FlowVec::iterator it;
130 os << "dangling partners of particle " << p1->barcode() << std::endl;

```

```

131     for( it = result1.begin(); it != result1.end(); ++it ) {
132         os << (*it)->barcode() << " " ;
133         os.width(8);
134         os << (*it)->pdg_id() << " " << (*it)->flow(1) << std::endl;
135     }
136     os << "all partners of particle " << p1->barcode() << std::endl;
137     for( it = result2.begin(); it != result2.end(); ++it ) {
138         os << (*it)->barcode() << " " ;
139         os.width(8);
140         os << (*it)->pdg_id() << " " << (*it)->flow(1) << std::endl;
141     }
142     FlowVec result3 = p2->flow().dangling_connected_partners( p2->flow().icode(1) );
143     FlowVec result4 = p2->flow().connected_partners( p2->flow().icode(1) );
144     os << "dangling partners of particle " << p2->barcode() << std::endl;
145     for( it = result3.begin(); it != result3.end(); ++it ) {
146         os << (*it)->barcode() << " " ;
147         os.width(8);
148         os << (*it)->pdg_id() << " " << (*it)->flow(1) << std::endl;
149     }
150     os << "all partners of particle " << p2->barcode() << std::endl;
151     for( it = result4.begin(); it != result4.end(); ++it ) {
152         os << (*it)->barcode() << " " ;
153         os.width(8);
154         os << (*it)->pdg_id() << " " << (*it)->flow(1) << std::endl;
155     }
156     // write event
157     xout1 << evt;
158     // testing bug #73987 - flow not copied
159     // call the write method directly
160     evt->write(xout4);
161     // make a copy and write it
162     HepMC::GenEvent(*evt).write(xout5);
163
164     // try changing and erasing flow
165     p2->set_flow(2,345);
166     xout2 << evt;
167     FlowVec result5 = p2->flow().connected_partners( p2->flow().icode(1) );
168     if ( result4 != result5 ) {
169         std::cerr << "ERROR: list of partners has changed after adding flow" << std::endl;
170         ++numbad;
171     }
172     // the flow method returns a copy,
173     // so we must set the flow again to change it
174     HepMC::Flow f2 = p2->flow();
175     if( f2.erase(2) ) {
176         p2->set_flow( f2 );
177     } else {
178         std::cerr << "ERROR: first erase was NOT successful" << std::endl;
179         ++numbad;
180     }
181     f2 = p2->flow();
182     if( f2.erase(2) ) {
183         std::cerr << "ERROR: second erase was successful" << std::endl;
184     }
185     xout3 << evt;
186     FlowVec result6 = p2->flow().connected_partners( p2->flow().icode(1) );
187     if ( result4 != result6 ) {
188         std::cerr << "ERROR: list of partners has changed after removing flow" << std::endl;
189         ++numbad;
190     }
191
192     // now clean-up by deleting all objects from memory
193     //
194     // deleting the event deletes all contained vertices, and all particles
195     // contained in those vertices
196     delete evt;
197

```

```
198     if( numbad > 0 ) std::cerr << numbad << " errors in testFlow" << std::endl;
199
200     return numbad;
201 }
```

11.9 testHepMC.cc.in

The **HepMC** (p.23) tests can also serve as useful examples based on `example_EventSelection`. Apply an event selection to the events in `testHepMC.input`. Events containing a photon of $p_T > 25$ GeV pass the selection and are written to `"testHepMC.out"`. Add arbitrary PDF information to the good events. Also write events using `IO_AsciiParticles`. Test the new `GenCrossSection` class.

```

1 //-----
2 // testHepMC.cc.in
3 //
4 // garren@fnal.gov, March 2006
5 // based on example_EventSelection
6 // Apply an event selection to the events in testHepMC.input
7 // Events containing a photon of pT > 25 GeV pass the selection
8 // and are written to "testHepMC.out"
9 // Also write events using IO_AsciiParticles
10 //-----
11 //
12
13 #include "HepMC/GenEvent.h"
14 #include "HepMC/GenCrossSection.h"
15 #ifndef HEPMC_IO_ASCII_REMOVED
16 #include "HepMC/IO_Ascii.h"
17 #endif
18 #ifdef HEPMC_HAS_IO_GENEVENT
19 #include "HepMC/IO_GenEvent.h"
20 #endif
21 #include "HepMC/IO_AsciiParticles.h"
22
23 // define methods and classes used by this test
24 #include "IsGoodEvent.h"
25 #include "testHepMCMethods.h"
26
27 void read_testIOGenEvent(std::ostream & os);
28 void read_variousFormats(std::ostream & os);
29 void writeWithCrossSection(std::ostream & os);
30 void readWithCrossSection(std::ostream & os);
31 void writeWithWeight(std::ostream & os);
32 void readWithWeight(std::ostream & os);
33 void read_nan(std::ostream & os);
34
35 int main() {
36     std::ofstream os( "testHepMC.cout" );
37     std::ofstream osv( "testHepMCVarious.cout" );
38     read_testIOGenEvent( os );
39     read_variousFormats( osv );
40     read_nan( os );
41     writeWithCrossSection( os );
42     readWithCrossSection( os );
43     writeWithWeight( os );
44     readWithWeight( os );
45     return 0;
46 }
47
48 void read_testIOGenEvent(std::ostream & os)
49 {
50     os << std::endl;
51     os << "basic IO_GenEvent input and output" << std::endl;
52     // declare an input strategy to read the data produced with the
53     // example_MyPythia - units are GeV and mm
54     HepMC::IO_GenEvent ascii_in("@srcdir/testIOGenEvent.input",std::ios::in);
55     ascii_in.use_input_units( HepMC::Units::GEV, HepMC::Units::MM );
56     // declare another IO_GenEvent for writing out the good events

```

```

57 HepMC::IO_GenEvent ascii_out("testHepMC.out",std::ios::out);
58 // declare an output IO_GenEvent for testing precision
59 HepMC::IO_GenEvent prec_out("testHepMCprecision.out",std::ios::out);
60 prec_out.precision(10);
61 // declare an IO_AsciiParticle for output
62 HepMC::IO_AsciiParticles particle_out("testHepMCParticle.out",std::ios::out);
63 // declare an instance of the event selection predicate
64 IsGoodEvent is_good_event;
65 //.....EVENT LOOP
66 int icount=0;
67 int num_good_events=0;
68 HepMC::GenEvent* evt = ascii_in.read_next_event();
69 while ( evt ) {
70     ++icount;
71     if ( icount%50==1 ) os << "Processing Event Number " << icount
72                             << " its # " << evt->event_number()
73                             << std::endl;
74     if ( is_good_event(evt) ) {
75         particleTypes(evt,os);
76         ascii_out << evt;
77         particle_out << evt;
78         prec_out << evt;
79         ++num_good_events;
80     }
81
82     // clean up and get next event
83     delete evt;
84     ascii_in >> evt;
85 }
86 //.....PRINT RESULT
87 os << num_good_events << " out of " << icount
88     << " processed events passed the cuts. Finished." << std::endl;
89 }
90
91 void read_variousFormats(std::ostream & os)
92 {
93     os << std::endl;
94     os << "process varied input" << std::endl;
95     // declare an input strategy
96     HepMC::IO_GenEvent ascii_in("@srcdir/testHepMCVarious.input",std::ios::in);
97     ascii_in.use_input_units( HepMC::Units::GEV, HepMC::Units::MM );
98     // declare another IO_GenEvent for writing out the good events
99     HepMC::IO_GenEvent ascii_out("testHepMCVarious.out",std::ios::out);
100    //.....EVENT LOOP
101    int icount=0;
102    HepMC::GenEvent* evt = ascii_in.read_next_event();
103    while ( evt ) {
104        icount++;
105        double pim;
106        os << "Processing Event Number " << icount
107            << " its # " << evt->event_number()
108            << std::endl;
109        ascii_out << evt;
110        // units should be unknown
111        evt->write_units(os);
112        pim = findPiZero(evt);
113        os << " pizero mass: " << pim << std::endl;
114        if( HepMC::Units::name( evt->momentum_unit() ) == "GEV" ) {
115            os << " GenEvent units are GeV" << std::endl;
116            if( pim > 1.0 ) {
117                // presume units are MEV and out of sync
118                os << " pizero units are MeV" << std::endl;
119                repairUnits(evt,HepMC::Units::MEV,HepMC::Units::GEV);
120                // set units to MeV and mm
121                evt->use_units(HepMC::Units::MEV, HepMC::Units::MM);
122                evt->write_units(os);
123                pim = findPiZero(evt);

```

```

124         os << " pizero mass: " << pim
125             << " " << HepMC::Units::name( evt->momentum_unit() ) << std::endl;
126         // convert units to MeV
127         evt->use_units(HepMC::Units::MEV, HepMC::Units::MM);
128         evt->write_units(os);
129         pim = findPiZero(evt);
130         os << " pizero mass: " << pim
131             << " " << HepMC::Units::name( evt->momentum_unit() ) << std::endl;
132     } else if( pim > 0.1 ) {
133         // presume units are GEV
134         os << " pizero units are GeV" << std::endl;
135         // set units to GeV and mm
136         evt->use_units(HepMC::Units::GEV, HepMC::Units::MM);
137         evt->write_units(os);
138         pim = findPiZero(evt);
139         os << " pizero mass: " << pim
140             << " " << HepMC::Units::name( evt->momentum_unit() ) << std::endl;
141         // convert units to MeV
142         evt->use_units(HepMC::Units::MEV, HepMC::Units::MM);
143         evt->write_units(os);
144         pim = findPiZero(evt);
145         os << " pizero mass: " << pim
146             << " " << HepMC::Units::name( evt->momentum_unit() ) << std::endl;
147     } else {
148         os << " pizero mass: " << pim
149             << " is inconsistent with allowed units " << std::endl;
150     }
151 } else if( HepMC::Units::name( evt->momentum_unit() ) == "MEV" ) {
152     os << " GenEvent units are MeV" << std::endl;
153     if( pim > 1.0 ) {
154         // presume units are MEV
155         os << " pizero units are MeV" << std::endl;
156         // set units to MeV and mm
157         evt->use_units(HepMC::Units::MEV, HepMC::Units::MM);
158         evt->write_units(os);
159         pim = findPiZero(evt);
160         os << " pizero mass: " << pim
161             << " " << HepMC::Units::name( evt->momentum_unit() ) << std::endl;
162         // convert units to MeV
163         evt->use_units(HepMC::Units::MEV, HepMC::Units::MM);
164         evt->write_units(os);
165         pim = findPiZero(evt);
166         os << " pizero mass: " << pim
167             << " " << HepMC::Units::name( evt->momentum_unit() ) << std::endl;
168     } else if( pim > 0.1 ) {
169         // presume units are GEV and out of sync
170         os << " pizero units are GeV" << std::endl;
171         repairUnits(evt, HepMC::Units::GEV, HepMC::Units::MEV);
172         evt->write_units(os);
173         pim = findPiZero(evt);
174         os << " pizero mass: " << pim
175             << " " << HepMC::Units::name( evt->momentum_unit() ) << std::endl;
176         // convert units to MeV
177         evt->use_units(HepMC::Units::MEV, HepMC::Units::MM);
178         evt->write_units(os);
179         pim = findPiZero(evt);
180         os << " pizero mass: " << pim
181             << " " << HepMC::Units::name( evt->momentum_unit() ) << std::endl;
182     } else {
183         os << " pizero mass: " << pim
184             << " is inconsistent with allowed units " << std::endl;
185     }
186 }
187 // clean up and get next event
188 delete evt;
189 ascii_in >> evt;
190 }

```

```

191     std::cout << "testHepMC: the HeavyIon and PdfInfo input stream errors are intentional" << std::endl;
192     //.....PRINT RESULT
193     os << icount << " events processed. Finished." << std::endl;
194 }
195
196 void writeWithCrossSection(std::ostream & os)
197 {
198     // declare an input strategy to read input data
199     // units are GeV and mm
200     HepMC::IO_GenEvent ascii_in("@srcdir@/testIOGenEvent.input",std::ios::in);
201     ascii_in.use_input_units( HepMC::Units::GEV, HepMC::Units::MM );
202     // declare another IO_GenEvent for writing out some events
203     HepMC::IO_GenEvent ascii_out("testCrossSection.out",std::ios::out);
204     // declare an output stream for printing events
205     std::ofstream xout( "testCrossSection.cout" );
206     // create an empty GenCrossSection object
207     HepMC::GenCrossSection cross;
208     //.....EVENT LOOP
209     int icount=0;
210     const double xs0 = 0.00346;
211     const double xs1 = 0.12;
212     const double xs2 = 33.234;
213     const double xs3 = 459.345;
214     double xserr = 0.0001;
215     double wgt1, wgt2;
216     HepMC::GenEvent* evt = ascii_in.read_next_event();
217     while ( evt ) {
218         icount++;
219         // use a variety of arbitrary cross section values
220         if( icount < 10 ) {
221             const double xs = xs0 - 1.34 * xserr;
222             cross.set_cross_section( xs, xserr );
223         } else if( icount < 20 ) {
224             const double xs = xs1 - 1.34 * xserr;
225             cross.set_cross_section( xs, xserr );
226         } else if( icount < 30 ) {
227             const double xs = xs2 - 1.34 * xserr;
228             cross.set_cross_section( xs, xserr );
229         } else {
230             const double xs = xs3 - 1.34 * xserr;
231             cross.set_cross_section( xs, xserr );
232         }
233         xserr *= 0.99;
234         if ( icount == 10 ) xserr += 0.01;
235         if ( icount == 20 ) xserr += 0.4;
236         if ( icount == 30 ) xserr += 1.0;
237         // attach this cross section to the event
238         evt->set_cross_section( cross );
239         evt->write_cross_section(os);
240         // add weights
241         wgt1 = 0.9853 + (double)icount * 0.00033;
242         wgt2 = 0.9853 + (double)(icount+1) * 0.00033;
243         evt->weights().push_back(0.3456);
244         evt->weights()["weightName"] = wgt1;
245         evt->weights()["second weight name"] = wgt2;
246         if ( icount%20==1 ) {
247             os << "writeWithCrossSection: Processing Event Number " << icount
248                 << " its # " << evt->event_number()
249                 << std::endl;
250             ascii_out << evt;
251             evt->print(xout);
252         }
253
254         // clean up and get next event
255         delete evt;
256         ascii_in >> evt;
257     }

```

```

258 //.....PRINT RESULT
259 os << "writeWithCrossSection processed " << icount << " events. Finished." << std::endl;
260 }
261
262 void readWithCrossSection(std::ostream & os)
263 {
264     // read the file we just wrote
265     HepMC::IO_GenEvent ascii_in("testCrossSection.out",std::ios::in);
266     // declare another IO_GenEvent for writing out some events
267     HepMC::IO_GenEvent ascii_out("testCrossSection2.out",std::ios::out);
268     //.....EVENT LOOP
269     int icount=0;
270     HepMC::GenEvent* evt = ascii_in.read_next_event();
271     while ( evt ) {
272         ++icount;
273         os << "readWithCrossSection: Processing Event Number " << icount
274             << " its # " << evt->event_number()
275             << std::endl;
276         if (evt->cross_section()->cross_section() <= 0) {
277             os << "testReadCrossSection: invalid cross-section!" << std::endl;
278         }
279         ascii_out << evt;
280
281         // clean up and get next event
282         delete evt;
283         ascii_in >> evt;
284     }
285     //.....PRINT RESULT
286     os << "readWithCrossSection processed " << icount << " events. Finished." << std::endl;
287 }
288
289 void read_nan(std::ostream & os)
290 {
291     // Read an input file that has corrupt information (nan's)
292     //
293     HepMC::IO_GenEvent xin("@srcdir@/testHepMCVarious.input",std::ios::in);
294     HepMC::IO_GenEvent xout("testNaN.out",std::ios::out);
295     //.....EVENT LOOP
296     int icount=0;
297     int invaliddata=0;
298     bool ok = true;
299     os << "----- " << std::endl;
300     os << "Begin NaN test " << std::endl;
301     HepMC::GenEvent* evt = xin.read_next_event();
302     //
303     // To recover from corrupt input, replace "while(evt) {...}"
304     // with "while(ok) { if(evt) {... xin >> evt;} else {...} }"
305     //
306     while ( ok ) {
307         if( evt ) {
308             ++icount;
309             os << "read_nan: Processing Event Number " << icount
310                 << " its # " << evt->event_number()
311                 << std::endl;
312             xout << evt;
313             // clean up and get next event
314             delete evt;
315             xin >> evt;
316         } else if (xin.error_type() == HepMC::IO_Exception::InvalidData ) {
317             ++invaliddata;
318             os << "INPUT ERROR: " << xin.error_message() << std::endl;
319             // clean up and get next event
320             delete evt;
321             xin >> evt;
322         } else if (invaliddata > 50 ) {
323             os << "INPUT ERROR: " << xin.error_message() << std::endl;
324             ok = false;

```

```

325         } else {
326             ok = false;
327         }
328     }
329     // print status of input stream
330     if ( xin.error_type() != 0 ) {
331         os << "processing of @srcdir@/testHepMCVarious.input ended with error "
332             << xin.error_type() << std::endl;
333         os << " --- " << xin.error_message() << std::endl;
334     }
335     os << icount << " events processed and "
336         << invaliddata << " events ignored. Finished."
337         << std::endl;
338     os << "End NaN test " << std::endl;
339     os << "----- " << std::endl;
340 }
341
342 void writeWithWeight(std::ostream & os)
343 {
344     // declare an input strategy to read input data
345     // units are GeV and mm
346     HepMC::IO_GenEvent ascii_in("@srcdir@/testIOGenEvent.input",std::ios::in);
347     ascii_in.use_input_units( HepMC::Units::GEV, HepMC::Units::MM );
348     // declare another IO_GenEvent for writing out some events
349     HepMC::IO_GenEvent ascii_out("testWithWeight.out",std::ios::out);
350     // declare an output stream for printing events
351     std::ofstream xout( "testWithWeight.cout" );
352     //.....EVENT LOOP
353     int icount=0;
354     double wgt1, wgt2;
355     HepMC::GenEvent* evt = ascii_in.read_next_event();
356     while ( evt ) {
357         icount++;
358         // add weights
359         wgt1 = 0.9853 + (double)icount * 0.00033;
360         wgt2 = 0.9853 + (double)(icount+1) * 0.00033;
361         evt->weights().push_back(0.3456);
362         evt->weights().push_back(wgt1);
363         evt->weights().push_back(wgt2);
364         if ( icount%20==1 ) {
365             os << "writeWithWeight: Processing Event Number " << icount
366                 << " its # " << evt->event_number()
367                 << std::endl;
368             ascii_out << evt;
369             evt->print(xout);
370         }
371
372         // clean up and get next event
373         delete evt;
374         ascii_in >> evt;
375     }
376     //.....PRINT RESULT
377     os << "writeWithWeight processed " << icount << " events. Finished." << std::endl;
378 }
379
380 void readWithWeight(std::ostream & os)
381 {
382     // read the file we just wrote
383     HepMC::IO_GenEvent ascii_in("testWithWeight.out",std::ios::in);
384     // declare another IO_GenEvent for writing out some events
385     HepMC::IO_GenEvent ascii_out("testWithWeight2.out",std::ios::out);
386     //.....EVENT LOOP
387     int icount=0;
388     HepMC::GenEvent* evt = ascii_in.read_next_event();
389     while ( evt ) {
390         ++icount;
391         os << "readWithWeight: Processing Event Number " << icount

```

```
392             << " its # " << evt->event_number()
393             << std::endl;
394         if ( !evt->cross_section() ) {
395             os << "testReadCrossSection: invalid cross-section!" << std::endl;
396         }
397         ascii_out << evt;
398
399         // clean up and get next event
400         delete evt;
401         ascii_in >> evt;
402     }
403     //.....PRINT RESULT
404     os << "readWithWeight processed " << icount << " events. Finished." << std::endl;
405 }
```

11.10 testHepMCIteration.cc.in

Use Matt's example_EventSelection along with example_UsingIterators to check **HepMC** (p.23) iteration. Apply an event selection to the events in testHepMC.input Events containing a photon of $p_T > 25$ GeV pass the selection. Use iterators on these events.

```

1
2 // testHepMCIteration.cc.in
3 //
4 // garren@fnal.gov, May 2007
5 // Use Matt's example_EventSelection along with example_UsingIterators
6 // to check HepMC iteration.
7 // Apply an event selection to the events in testHepMC.input
8 // Events containing a photon of  $p_T > 25$  GeV pass the selection.
9 // Use iterators on these events.
10
11
12 #include <list>
13
14 #include "HepMC/IO_GenEvent.h"
15 #include "HepMC/IO_AsciiParticles.h"
16 #include "HepMC/GenEvent.h"
17 #include "HepMC/GenRanges.h"
18
19 // define methods and classes used by this test
20 #include "IsGoodEvent.h"
21 #include "testHepMCIteration.h"
22
23 bool findW( HepMC::GenEvent* evt, std::ostream& os);
24 bool simpleIter ( HepMC::GenEvent* evt, std::ostream& os = std::cout );
25 bool simpleIter2( HepMC::GenEvent* evt, std::ostream& os = std::cout );
26 bool simpleIter3( HepMC::GenEvent* evt, std::ostream& os = std::cout );
27 bool simpleIter4( HepMC::GenEvent* evt, std::ostream& os = std::cout );
28
29 class PrintW {
30 public:
31     PrintW( std::ostream & os, int num ) : m_out( os ),m_event_num( num ) {}
32     void operator()( HepMC::GenParticle* p ) {
33         if ( IsWBoson(p) ) {
34             m_out << std::endl;
35             m_out << "A W boson has been found in event: " << m_event_num << std::endl;
36             p->print( m_out );
37             // return all parents
38             // we do this by pointing to the production vertex of the W
39             // particle and asking for all particle parents of that vertex
40             m_out << "\t Its parents are: " << std::endl;
41             if ( p->production_vertex() ) {
42                 std::for_each( p->particles_in(HepMC::parents).begin(),
43                               p->particles_in(HepMC::parents).end(),
44                               PrintParticle(m_out));
45             }
46
47             // return immediate children
48             m_out << "\t\t" << "Its children are: " << std::endl;
49             if ( p->end_vertex() ) {
50                 std::for_each( p->particles_out(HepMC::children).begin(),
51                               p->particles_out(HepMC::children).end(),
52                               PrintChildren(m_out));
53             }
54
55             // return all descendants
56             // we do this by pointing to the end vertex of the W
57             // particle and asking for all particle descendants of that vertex
58             m_out << "\t\t Its descendants are: " << std::endl;
59             if ( p->end_vertex() ) {
60                 std::for_each( p->particles_out(HepMC::descendants).begin(),

```

```

65                                     p->particles_out(HepMC::descendants).end(),
66                                     PrintDescendants(m_out));
67     }
68 } // if IsWBoson
69 }
70 private:
71     std::ostream & m_out;
72     int m_event_num;
73 };
74
75 class PrintConstW {
76 public:
77     PrintConstW( std::ostream & os, int num ) : m_out( os ),m_event_num( num ) {}
78     void operator()( HepMC::GenParticle* p ) {
79         if ( IsWBoson(p) ) {
80             m_out << std::endl;
81             m_out << "A W boson has been found in event: " << m_event_num << std::endl;
82             p->print( m_out );
83             // return all parents
84             // we do this by pointing to the production vertex of the W
85             // particle and asking for all particle parents of that vertex
86             m_out << "\t Its parents are: " << std::endl;
87             if ( p->production_vertex() ) {
88                 std::for_each( p->particles_in(HepMC::parents).begin(),
89                               p->particles_in(HepMC::parents).end(),
90                               PrintParticle(m_out));
91             }
92
93             // return immediate children
94             m_out << "\t\t" << "Its children are: " << std::endl;
95             if ( p->end_vertex() ) {
96                 std::for_each( p->particles_out(HepMC::children).begin(),
97                               p->particles_out(HepMC::children).end(),
98                               PrintChildren(m_out));
99             }
100
101             // return all descendants
102             // we do this by pointing to the end vertex of the W
103             // particle and asking for all particle descendants of that vertex
104             m_out << "\t\t Its descendants are: " << std::endl;
105             if ( p->end_vertex() ) {
106                 std::for_each( p->particles_out(HepMC::descendants).begin(),
107                               p->particles_out(HepMC::descendants).end(),
108                               PrintDescendants(m_out));
109             }
110         } // if IsWBoson
111     }
112 private:
113     std::ostream & m_out;
114     int m_event_num;
115 };
116
117 int main() {
118     // declare an input strategy to read the data produced with the
119     // example_MyPythia
120     HepMC::IO_GenEvent ascii_in("@srcdir@/testIOGenEvent.input",std::ios::in);
121     // declare an instance of the event selection predicate
122     IsGoodEvent is_good_event;
123     // define some output streams
124     std::ofstream os( "testHepMCIteration.out" );
125     std::ofstream os2( "testHepMCIteration2.out" );
126     std::ofstream os3( "testHepMCIteration3.out" );
127     //.....EVENT LOOP
128     int icount=0;
129     int num_good_events=0;
130     HepMC::GenEvent* evt = ascii_in.read_next_event();
131     HepMC::GenEvent* evcopy;

```

```

136 while ( evt ) {
137     icount++;
138     if ( icount%50==1 ) std::cout << "Processing Event Number " << icount
139                                     << " its # " << evt->event_number()
140                                     << std::endl;
141     // icount of 100 should be the last event
142     if ( icount==100 ) std::cout << "Processing Event Number " << icount
143                                     << " its # " << evt->event_number()
144                                     << std::endl;
145     evcopy = evt;
146     if ( is_good_event(evcopy) ) {
147         ++num_good_events;
148         // simple iteration several different ways
149         os << "Event " << evcopy->event_number() << " is good " << std::endl;
150         simpleIter( evcopy, os );
151         os2 << "Event " << evcopy->event_number() << " is good " << std::endl;
152         simpleIter2( evcopy, os2 );
153         os3 << "Event " << evcopy->event_number() << " is good " << std::endl;
154         simpleIter2( evcopy, os3 );
155         std::cout << "Event " << evcopy->event_number() << " is good " << std::endl;
156         simpleIter3( evcopy );
157         simpleIter4( evcopy );
158         // test iterators
159         findW( evcopy, os );
160         // this is the same as findW except that we use the STL for_each algorithm
161         std::for_each( evt->particles_begin(), evt->particles_end(),
162                       PrintW(os2,evcopy->event_number()));
163         // repeat, using the const iterator
164         std::for_each( evt->particles_begin(), evt->particles_end(),
165                       PrintConstW(os3,evcopy->event_number()));
166     }
167     evcopy->clear();
168
169     // clean up and get next event
170     delete evt;
171     evt = ascii_in.read_next_event();
172 }
173 //.....PRINT RESULT
174 std::cout << num_good_events << " out of " << icount
175           << " processed events passed the cuts. Finished." << std::endl;
176 }
177
178 bool simpleIter( HepMC::GenEvent* evt, std::ostream& os )
179 {
180     // use GenEvent::vertex_iterator to fill a list of all
181     // vertices in the event
182     std::list<HepMC::GenVertex*> allvertices;
183     for ( HepMC::GenEvent::vertex_iterator v = evt->vertices_begin();
184           v != evt->vertices_end(); ++v ) {
185         allvertices.push_back(*v);
186     }
187
188     // fill a list of all final state particles in the event, by requiring
189     // that each particle satisfyies the IsFinalState predicate
190     IsFinalState isfinal;
191     std::list<HepMC::GenParticle*> finalstateparticles;
192     for ( HepMC::GenEvent::particle_iterator p = evt->particles_begin();
193           p != evt->particles_end(); ++p ) {
194         if ( isfinal(*p) ) finalstateparticles.push_back(*p);
195     }
196
197     // print all photons in the event that satisfy the IsPhoton criteria
198     os << "photons in event " << evt->event_number() << ":" << std::endl;
199     for ( HepMC::GenEvent::particle_iterator p = evt->particles_begin();
200           p != evt->particles_end(); ++p ) {
201         if ( IsPhoton(*p) ) (*p)->print( os );
202     }

```

```

203
204     return true;
205 }
206
207 bool simpleIter2( HepMC::GenEvent* evt, std::ostream& os )
208 {
209     // illustrates the use various helpful algorithms
210
211     // use the STL copy algorithm to fill a list of all
212     // vertices in the event
213     std::list<HepMC::GenVertex*> allvertices2;
214     copy( evt->vertices_begin(), evt->vertices_end(),
215          back_inserter(allvertices2) );
216
217     // fill a list of all final state particles in the event, by requiring
218     // that each particle satisfies the IsFinalState predicate
219     // an STL-like algorithm called HepMC::copy_if is provided in the
220     // GenEvent.h header to do this sort of operation more easily
221     std::list<HepMC::GenParticle*> finalstateparticles2;
222     HepMC::copy_if( evt->particles_begin(), evt->particles_end(),
223                    back_inserter(finalstateparticles2), IsFinalState() );
224
225     // use the STL for_each algorithm to
226     // print all photons in the event that satisfy the IsPhoton criteria
227     os << "photons in event " << evt->event_number() << ":" << std::endl;
228     std::for_each(evt->particles_begin(), evt->particles_end(),
229                  PrintPhoton(os));
230
231     return true;
232 }
233
234 bool simpleIter3( HepMC::GenEvent* evt, std::ostream& os )
235 {
236     // very simple illustration of using GenEventVertexRange
237     // and GenEventParticleRange
238     // NOTE that instead of creating this list,
239     // you can just use GenEventVertexRange as if it were the list
240     std::list<HepMC::GenVertex*> allvertices;
241     HepMC::GenEventVertexRange vc(*evt);
242     for ( HepMC::GenEvent::vertex_iterator v = vc.begin(); v != vc.end(); ++v ) {
243         allvertices.push_back(*v);
244     }
245
246     // fill a list of all final state particles in the event, by requiring
247     // that each particle satisfies the IsFinalState predicate
248     IsFinalState isfinal;
249     std::list<HepMC::GenParticle*> finalstateparticles;
250     HepMC::GenEventParticleRange pc(*evt);
251     for ( HepMC::GenEvent::particle_iterator p = pc.begin(); p != pc.end(); ++p ) {
252         if ( isfinal(*p) ) finalstateparticles.push_back(*p);
253     }
254
255     // print all photons in the event that satisfy the IsPhoton criteria
256     os << "photons in event " << evt->event_number() << ":" << std::endl;
257     std::for_each(pc.begin(), pc.end(), PrintPhoton(os));
258
259     return true;
260 }
261
262 bool simpleIter4( HepMC::GenEvent* evt, std::ostream& os )
263 {
264     // very simple illustration of using
265     // GenEvent::vertex_range(), which returns GenEventVertexRange,
266     // and GenEvent::particle_range(), which returns GenEventParticleRange
267     // NOTE that instead of creating these lists,
268     // you can just use GenEvent::vertex_range() and GenEvent::particle_range()
269     // as if they were a list

```

```

270
271     std::list<HepMC::GenVertex*> allvertices;
272     for ( HepMC::GenEvent::vertex_iterator v = evt->vertex_range().begin();
273           v != evt->vertex_range().end(); ++v ) {
274         allvertices.push_back(*v);
275     }
276
277     // fill a list of all final state particles in the event, by requiring
278     // that each particle satisfyies the IsFinalState predicate
279     IsFinalState isfinal;
280     std::list<HepMC::GenParticle*> finalstateparticles;
281     for ( HepMC::GenEvent::particle_iterator p = evt->particle_range().begin();
282           p != evt->particle_range().end(); ++p ) {
283         if ( isfinal(*p) ) finalstateparticles.push_back(*p);
284     }
285
286     // print all photons in the event that satisfy the IsPhoton criteria
287     os << "photons in event " << evt->event_number() << ":" << std::endl;
288     std::for_each(evt->particle_range().begin(),
289                   evt->particle_range().end(),
290                   PrintPhoton(os));
291
292     return true;
293 }
294
295 bool findW( HepMC::GenEvent* evt, std::ofstream& os )
296 {
297     int num_W = 0;
298     // use GenEvent::particle_iterator to find all W's in the event,
299     // then
300     // (1) for each W user the GenVertex::particle_iterator with a range of
301     //     parents to return and print the immediate mothers of these W's.
302     // (2) for each W user the GenVertex::particle_iterator with a range of
303     //     descendants to return and print all descendants of these W's.
304     for ( HepMC::GenEvent::particle_iterator p = evt->particles_begin();
305           p != evt->particles_end(); ++p ) {
306         if ( IsWBoson(*p) ) {
307             ++num_W;
308             os << std::endl;
309             os << "A W boson has been found in event: " << evt->event_number() << std::endl;
310             (*p)->print( os );
311             // return all parents
312             // we do this by pointing to the production vertex of the W
313             // particle and asking for all particle parents of that vertex
314             os << "\t Its parents are: " << std::endl;
315             if ( (*p)->production_vertex() ) {
316                 for ( HepMC::GenVertex::particle_iterator mother
317                       = (*p)->production_vertex()->
318                         particles_begin(HepMC::parents);
319                       mother != (*p)->production_vertex()->
320                         particles_end(HepMC::parents);
321                       ++mother ) {
322                 os << "\t";
323                 (*mother)->print( os );
324             }
325         }
326
327         // return immediate children
328         os << "\t\t" << "Its children are: " << std::endl;
329         if ( (*p)->end_vertex() ) {
330             for ( HepMC::GenVertex::particle_iterator child =
331                   (*p)->end_vertex()->particles_begin(HepMC::children);
332                   child != (*p)->end_vertex()->particles_end(HepMC::children);
333                   ++child ) {
334                 // make a copy
335                 HepMC::GenVertex::particle_iterator cp = child;
336                 // use the copy and the original

```

```
337             os << "\t\t\t (id,barcode,status) "
338             << (*cp)->pdg_id() << " "
339             << (*child)->barcode() << " "
340             << (*cp)->status() << std::endl;
341         }
342     }
343
344     // return all descendants
345     // we do this by pointing to the end vertex of the W
346     // particle and asking for all particle descendants of that vertex
347     os << "\t\t Its descendants are: " << std::endl;
348     if ( (*p)->end_vertex() ) {
349         for ( HepMC::GenVertex::particle_iterator des
350              = (*p)->end_vertex()->
351                particles_begin(HepMC::descendants);
352              des != (*p)->end_vertex()->
353                particles_end(HepMC::descendants);
354              ++des ) {
355             os << "\t\t";
356             (*des)->print( os );
357         }
358     }
359     } // if IsWBoson
360 } // end particle loop
361 return true;
362 }
```

11.11 testHerwigCopies.cc

Multiple events in memory at the same time

```

1
2 // testHerwigCopies.cc
3 //
4 // garren@fnal.gov, January 2008
5 // Multiple events in memory at the same time
6
7
8 #include <fstream>
9 #include <iostream>
10 #include "HepMC/HerwigWrapper.h"
11 #include "HepMC/IO_HERWIG.h"
12 #include "HepMC/GenEvent.h"
13 #include "HepMC/CompareGenEvent.h"
14 #include "HepMC/HEPEVT_Wrapper.h"
15
16 int main() {
17     //
18     //.....HEPEVT
19     // Herwig 6.4 uses HEPEVT with 4000 entries and 8-byte floating point
20     // numbers. We need to explicitly pass this information to the
21     // HEPEVT_Wrapper.
22     //
23     HepMC::HEPEVT_Wrapper::set_max_number_entries(4000);
24     HepMC::HEPEVT_Wrapper::set_sizeof_real(8);
25     //
26     //.....INITIALIZATIONS
27
28     hwproc.PBEAM1 = 7000.; // energy of beam1
29     hwproc.PBEAM2 = 7000.; // energy of beam2
30     // 1610 = gg->H--> WW, 1706 = qq->ttbar, 2510 = ttH -> ttWW
31     hwproc.IPROC = 1706; // qq -> ttbar production
32     hwproc.MAXEV = 50; // number of events
33     // tell it what the beam particles are:
34     for ( unsigned int i = 0; i < 8; ++i ) {
35         hwbmch.PART1[i] = (i < 1) ? 'P' : ' ';
36         hwbmch.PART2[i] = (i < 1) ? 'P' : ' ';
37     }
38     hwigin(); // INITIALISE OTHER COMMON BLOCKS
39     hwevnt.MAXPR = 0; // number of events to print
40     hwuinc(); // compute parameter-dependent constants
41     hweini(); // initialise elementary process
42
43     //.....HepMC INITIALIZATIONS
44     //
45     // Instantiate an IO strategy for reading from HEPEVT.
46     HepMC::IO_HERWIG hepevtio;
47     //
48     // open some output files
49     std::ofstream out1( "testHerwigOriginals.dat" );
50     std::ofstream out2( "testHerwigCopies1.dat" );
51     std::ofstream out3( "testHerwigCopies2.dat" );
52     //
53     //.....EVENT LOOP
54     for ( int i = 1; i <= hwproc.MAXEV; i++ ) {
55         if ( i%50==1 ) std::cout << "Processing Event Number "
56             << i << std::endl;
57         // initialise event
58         hwuine();
59         // generate hard subprocess
60         hwepro();
61         // generate parton cascades
62         hwbgen();
63         // do heavy object decays

```

```

64         hwdhob();
65         // do cluster formation
66         hwcfor();
67         // do cluster decays
68         hwcdec();
69         // do unstable particle decays
70         hwdhad();
71         // do heavy flavour hadron decays
72         hwdhvy();
73         // add soft underlying event if needed
74         hwmevt();
75         // finish event
76         hwufne();
77         HepMC::GenEvent* evt = hepevtio.read_next_event();
78         // herwig uses GeV and mm
79         evt->use_units( HepMC::Units::GEV, HepMC::Units::MM);
80         // set cross section information
81         evt->set_cross_section( HepMC::getHerwigCrossSection(i) );
82         // add some information to the event
83         evt->set_event_number(i);
84         evt->set_signal_process_id(20);
85         //
86         //.....make some copies
87         evt->print(out1);
88         HepMC::GenEvent ec = (*evt);
89         ec.print(out2);
90         HepMC::GenEvent* evt4 = new HepMC::GenEvent(*evt);
91         evt4->print(out3);
92         if( !compareGenEvent(evt,evt4) ) {
93             std::cerr << "testHerwigCopies: GenEvent comparison fails at event "
94                 << evt->event_number() << std::endl;
95             return -1;
96         }
97
98         // we also need to delete the created event from memory
99         delete evt;
100        delete evt4;
101    }
102    //.....TERMINATION
103    hwefin();
104    std::cout << "testHerwigCopies: event comparison is successful" << std::endl;
105
106    return 0;
107 }

```

11.12 testMass.cc.in

Read events from testIOGenEvent.input Select events containing a photon of $p_T > 25$ GeV Add arbitrary PDF information to one of the good events Write the selected events and read them back in using an istream

```

1 //-----
2 // testMass.cc.in
3 //
4 // garren@fnal.gov, March 2006
5 // Read events written by example_MyPythia.cc
6 // Select events containing a photon of  $p_T > 25$  GeV
7 // Add arbitrary PDF information to one of the good events
8 // Add arbitrary HeavyIon information to one of the good events
9 // Write the selected events and read them back in using an istream
10 //-----
11
12 #include <cmath>           // for min()
13 #include <ostream>
14
15 #include "HepMC/IO_GenEvent.h"
16 #include "HepMC/GenEvent.h"
17 #include "HepMC/Version.h"
18
19 // define methods and classes used by this test
20 #include "IsGoodEvent.h"
21
22 void massInfo( const HepMC::GenEvent*, std::ostream& os );
23
24 int main() {
25     // output file
26     std::ofstream os( "testMass.cout" );
27     // read and process the input file
28     {
29         // declare an input strategy to read the data produced with the
30         // example_MyPythia
31         HepMC::IO_GenEvent ascii_in("@srcdir@/testIOGenEvent.input",std::ios::in);
32         ascii_in.use_input_units( HepMC::Units::GEV, HepMC::Units::MM );
33         // declare another IO_GenEvent for output
34         HepMC::IO_GenEvent ascii_out("testMass1.out",std::ios::out);
35         // declare an instance of the event selection predicate
36         IsGoodEvent is_good_event;
37         // send version to output
38         HepMC::version(os);
39         //.....EVENT LOOP
40         int icount=0;
41         int num_good_events=0;
42         double x1=0., x2=0., q=0., xf1=0., xf2=0.;
43         HepMC::GenEvent* evt = ascii_in.read_next_event();
44         while ( evt ) {
45             icount++;
46             if ( icount%50==1 ) os << "Processing Event Number " << icount
47                                 << " its # " << evt->event_number()
48                                 << std::endl;
49             if ( is_good_event(evt) ) {
50                 if ( num_good_events == 0 ) {
51                     // add some arbitrary PDF information
52                     x1 = std::min(0.8, 0.07 * icount);
53                     x2 = 1-x1;
54                     q = 1.69 * icount;
55                     // use beam momentum
56                     if( evt->valid_beam_particles() ) {
57                         HepMC::GenParticle* bp1 = evt->beam_particles().first;
58                         xf1 = x1*bp1->momentum().rho();
59                         xf2 = x2*bp1->momentum().rho();

```

```

60         } else {
61             xf1 = x1*0.34;
62             xf2 = x2*0.34;
63         }
64         // provide optional pdf set id numbers
65         // (two ints at the end of the constructor)
66         HepMC::PdfInfo pdf( 2, 3, x1, x2, q, xf1, xf2, 230, 230);
67         evt->set_pdf_info(pdf);
68         // add some arbitrary HeavyIon information
69         HepMC::HeavyIon ion(23,11,12,15,3,5,0,0,0,0.0145);
70         evt->set_heavy_ion( ion );
71     }
72     os << "saving Event " << evt->event_number() << std::endl;
73     if( evt->weights().size() > 0 ) {
74         os << "Weights: ";
75         evt->weights().print(os);
76     }
77     ascii_out << evt;
78     ++num_good_events;
79 }
80
81 // clean up and get next event
82 delete evt;
83 ascii_in >> evt;
84 }
85 //.....PRINT RESULT
86 os << num_good_events << " out of " << icount
87 << " processed events passed the cuts. Finished." << std::endl;
88 }
89 // now read the file we just created
90 {
91     // declare an input strategy
92     const char infile[] = "testMass1.out";
93     std::ifstream istr( infile );
94     if( !istr ) {
95         std::cerr << "testMass: cannot open " << infile << std::endl;
96         exit(-1);
97     }
98     HepMC::IO_GenEvent xin(istr);
99     // declare another IO_GenEvent for output
100    HepMC::IO_GenEvent xout("testMass2.out",std::ios::out);
101    //.....EVENT LOOP
102    int ixin=0;
103    HepMC::GenEvent* evt = xin.read_next_event();
104    while ( evt ) {
105        ixin++;
106        os << "reading Event " << evt->event_number() << std::endl;
107        if( evt->weights().size() > 0 ) {
108            os << "Weights: ";
109            evt->weights().print(os);
110        }
111        xout << evt;
112        // look at mass info
113        massInfo(evt,os);
114
115        // clean up and get next event
116        delete evt;
117        xin >> evt;
118    }
119    //.....PRINT RESULT
120    os << ixin << " events in the second pass. Finished." << std::endl;
121 }
122 }
123
124 void massInfo( const HepMC::GenEvent* e, std::ostream& os )
125 {
126     double gm, m, d;

```

```
127     for ( HepMC::GenEvent::particle_const_iterator p = e->particles_begin(); p != e->particles_end();
128           ++p ) {
129
130         gm = (*p)->generated_mass();
131         m = (*p)->momentum().m();
132         d = fabs(m-gm);
133         if( d > 1.0e-5 ) {
134             os << "Event " << e->event_number()
135                 << " Particle " << (*p)->barcode()
136                 << " " << (*p)->pdg_id()
137                 << " generated mass " << gm
138                 << " mass from momentum " << m
139                 << " difference " << d << std::endl;
140         }
141     }
142 }
```

11.13 testMultipleCopies.cc.in

Multiple events in memory at the same time run with valgrind or some other leak checker

```

1
2 // testMultipleCopies.cc.in
3 //
4 // garren@fnal.gov, January 2008
5 // Multiple events in memory at the same time
6 // run with valgrind or some other leak checker
7 //
8 //
9
10 #include <fstream>
11
12 #include "HepMC/IO_GenEvent.h"
13 #include "HepMC/GenEvent.h"
14 #include "HepMC/CompareGenEvent.h"
15
16 // define methods and classes used by this test
17 #include "IsGoodEvent.h"
18
19 int main() {
20     // use output file
21     std::ofstream os( "testMultipleCopies.out" );
22     {
23         // declare an input strategy
24         HepMC::IO_GenEvent ascii_in("@srcdir@/testIOGenEvent.input",std::ios::in);
25         // declare another input strategy
26         HepMC::IO_GenEvent ascii_in2("@srcdir@/testHepMCVarious.input",std::ios::in);
27         std::ofstream out1( "testMultipleOriginals.out" );
28         std::ofstream out2( "testMultipleCopies1.out" );
29         std::ofstream out3( "testMultipleCopies2.out" );
30         // declare an instance of the event selection predicate
31         IsGoodEvent is_good_event;
32
33         //.....EVENT LOOP
34         int icount=0;
35         int num_good_events=0;
36         int icnt;
37         HepMC::GenEvent* evt1 = ascii_in.read_next_event();
38         HepMC::GenEvent* evt2 = ascii_in2.read_next_event();
39         HepMC::GenEvent* evt3 = ascii_in.read_next_event();
40
41         while ( evt1 && evt2 ) {
42             icount++;
43             if ( icount%50==1 ) os << "Processing Event Number " << icount
44                                 << " stream 1 # " << evt1->event_number()
45                                 << " stream 2 # " << evt2->event_number()
46                                 << std::endl;
47
48             if ( is_good_event(evt1) ) {
49
50                 os << "good event in stream 1 # "
51                     << evt1->event_number() << std::endl;
52                 evt1->print(out1);
53                 ++num_good_events;
54                 HepMC::GenEvent ec = (*evt1);
55                 ec.print(out3);
56                 icnt=0;
57                 for ( HepMC::GenEvent::particle_const_iterator p1 = ec.particles_begin();
58                     p1 != ec.particles_end(); ++p1 ) {
59                     ++icnt;
60                     os << "particle " << icnt << " barcode " << (*p1)->barcode() << std::endl;
61                 }
62                 HepMC::GenEvent* evt4 = new HepMC::GenEvent(*evt1);

```

```

63         evt4->print(out2);
64         if( !compareGenEvent(evt1,evt4) ) { return -1; }
65         delete evt4;
66     }
67
68     // clean up and get next events
69     delete evt1;
70     delete evt2;
71     ascii_in >> evt1;
72     ascii_in2 >> evt2;
73 }
74 // might have either evt1 or evt2 still in memory, cleanup here
75 delete evt1;
76 delete evt2;
77 delete evt3;
78
79 //.....PRINT RESULT
80 os << std::endl;
81 os << num_good_events << " out of " << icount
82    << " processed events passed the cuts." << std::endl;
83 os << std::endl;
84 os << " GenEvent copy constructor passes the test" << std::endl;
85 os << std::endl;
86 }
87
88 // test operator= and swap
89 {
90     // declare an input strategy
91     HepMC::IO_GenEvent ascii_in("@srcdir@/testIOGenEvent.input",std::ios::in);
92     //
93     HepMC::GenEvent* evt5 = ascii_in.read_next_event();
94     HepMC::GenEvent* evt6 = new HepMC::GenEvent();
95     os << "event number for evt5: " << evt5->event_number() << std::endl;
96     os << "event number for evt6: " << evt6->event_number() << std::endl;
97     // copy GenEvent object
98     (*evt6) = (*evt5);
99     if( !compareGenEvent(evt5,evt6) ) { return -4; }
100    delete evt5;
101    os << "event number for evt6 after copy: " << evt6->event_number() << std::endl;
102    os << std::endl;
103    delete evt6;
104    os << " GenEvent operator= passes the test" << std::endl;
105    os << std::endl;
106
107    evt5 = ascii_in.read_next_event();
108    evt6 = ascii_in.read_next_event();
109    HepMC::GenEvent* evt7 = new HepMC::GenEvent(*evt5);
110    HepMC::GenEvent* evt8 = new HepMC::GenEvent(*evt6);
111    os << "event number for evt5: " << evt5->event_number() << std::endl;
112    os << "event number for evt6: " << evt6->event_number() << std::endl;
113    os << "before swap, evt5 has: " << evt5->vertices_size() << " vertices and "
114       << evt5->particles_size() << " particles" << std::endl;
115    os << "before swap, evt6 has: " << evt6->vertices_size() << " vertices and "
116       << evt6->particles_size() << " particles" << std::endl;
117    os << "before swap, evt7 has: " << evt7->vertices_size() << " vertices and "
118       << evt7->particles_size() << " particles" << std::endl;
119    os << "before swap, evt8 has: " << evt8->vertices_size() << " vertices and "
120       << evt8->particles_size() << " particles" << std::endl;
121    (*evt6).swap(*evt5);
122    os << "event number for evt5 after swap: " << evt5->event_number() << std::endl;
123    os << "event number for evt6 after swap: " << evt6->event_number() << std::endl;
124    // evt6 should now match evt7
125    os << "after swap, evt6 has: " << evt6->vertices_size() << " vertices and "
126       << evt6->particles_size() << " particles" << std::endl;
127    os << "after swap, evt7 has: " << evt7->vertices_size() << " vertices and "
128       << evt7->particles_size() << " particles" << std::endl;
129    if( !compareGenEvent(evt6,evt7) ) { return -6; }

```

```
130         // evt5 should now match evt8
131         os << "after swap, evt5 has: " << evt5->vertices_size() << " vertices and "
132           << evt5->particles_size() << " particles" << std::endl;
133         os << "after swap, evt8 has: " << evt8->vertices_size() << " vertices and "
134           << evt8->particles_size() << " particles" << std::endl;
135         if( !compareGenEvent(evt5,evt8) ) { return -5; }
136         // cleanup
137         delete evt5;
138         delete evt6;
139         delete evt7;
140         delete evt8;
141         os << std::endl;
142         os << " GenEvent swap passes the test" << std::endl;
143         os << std::endl;
144     }
145     return 0;
146 }
```

11.14 testPrintBug.cc

Thanks to Bob McElrath and Frank Siegert for this test

```
1 //
2 // Thanks to Bob McElrath and Frank Siegert for this test
3 //
4
5 #include <fstream>
6
7 #include "HepMC/GenEvent.h"
8 #include "HepMC/SimpleVector.h"
9
10 int main()
11 {
12     HepMC::GenEvent* p_event;
13
14     p_event = new HepMC::GenEvent();
15     p_event->use_units(HepMC::Units::GEV, HepMC::Units::MM);
16
17     // define an output stream
18     std::ofstream os( "testPrintBug.out" );
19
20     for(int i=0; i<10; i++) {
21         HepMC::FourVector vector(1.0,1.0,1.0,1.0);
22         HepMC::GenVertex* vertex = new HepMC::GenVertex(vector,i);
23         for(int j=0; j<3; j++) {
24             HepMC::GenParticle* particle = new HepMC::GenParticle(vector,1,2);
25             vertex->add_particle_in(particle);
26         }
27         for(int j=0; j<3; j++) {
28             HepMC::GenParticle* particle = new HepMC::GenParticle(vector,1,2);
29             vertex->add_particle_out(particle);
30         }
31         p_event->add_vertex(vertex);
32     }
33     p_event->print(os);
34     // cleanup
35     delete p_event;
36     return 0;
37 }
```

11.15 testPythiaCopies.cc

Multiple events in memory at the same time

```

1
2 // testPythiaCopies.cc
3 //
4 // garren@fnal.gov, January 2008
5 // Multiple events in memory at the same time
6
7
8 #include <fstream>
9 #include <iostream>
10 #include "HepMC/PythiaWrapper.h"
11 #include "HepMC/IO_HEPEVT.h"
12 #include "HepMC/GenEvent.h"
13 #include "HepMC/CompareGenEvent.h"
14 #include "PythiaHelper.h"
15
16 int main() {
17     //
18     //.....HEPEVT
19     // Pythia 6.1 uses HEPEVT with 4000 entries and 8-byte floating point
20     // numbers. We need to explicitly pass this information to the
21     // HEPEVT_Wrapper.
22     //
23     HepMC::HEPEVT_Wrapper::set_max_number_entries(4000);
24     HepMC::HEPEVT_Wrapper::set_sizeof_real(8);
25     //
26     //.....PYTHIA INITIALIZATIONS
27     initPythia();
28     //
29     //.....HepMC INITIALIZATIONS
30     //
31     // Instantiate an IO strategy for reading from HEPEVT.
32     HepMC::IO_HEPEVT hepevtio;
33     //
34     // open some output files
35     std::ofstream out1( "testPythiaOriginals.dat" );
36     std::ofstream out2( "testPythiaCopies1.dat" );
37     std::ofstream out3( "testPythiaCopies2.dat" );
38     //
39     //.....EVENT LOOP
40     for ( int i = 1; i <= 50; i++ ) {
41         if ( i%50==1 ) std::cout << "Processing Event Number "
42             << i << std::endl;
43         call_pyevnt(); // generate one event with Pythia
44         // pythia pyhepc routine convert common PYJETS in common HEPEVT
45         call_pyhepc( 1 );
46         HepMC::GenEvent* evt = hepevtio.read_next_event();
47         // pythia uses GeV and mm
48         evt->use_units( HepMC::Units::GEV, HepMC::Units::MM);
49         // set a couple of arbitrary weights
50         evt->weights().push_back(0.456);
51         evt->weights()["test2"] = 0.8956;
52         // set number of multi parton interactions
53         evt->set_mpi( pypars.msti[31-1] );
54         // set cross section information
55         evt->set_cross_section( HepMC::getPythiaCrossSection() );
56         //
57         //.....make some copies
58         evt->print(out1);
59         HepMC::GenEvent ec = (*evt);
60         ec.print(out2);
61         HepMC::GenEvent* evt4 = new HepMC::GenEvent(*evt);
62         evt4->print(out3);
63         if( !compareGenEvent(evt,evt4) ) {

```

```
64         std::cerr << "testPythiaCopies: GenEvent comparison fails at event "
65         << evt->event_number() << std::endl;
66         return -1;
67     }
68     //
69     // now delete the created events from memory
70     delete evt;
71     delete evt4;
72 }
73 //.....TERMINATION
74 // write out some information from Pythia to the screen
75 call_pystat( 1 );
76 std::cout << "testPythiaCopies: event comparison is successful" << std::endl;
77
78 return 0;
79 }
80
81
82
```

11.16 testSimpleVector.cc

Exercise all the vector methods

```

1 //
2 // First pass - simply exercise all the vector methods
3 //
4 #include <iostream>
5
6 #include "HepMC/SimpleVector.h"
7
8 int main()
9 {
10     // ThreeVector
11     HepMC::ThreeVector vector3;
12     HepMC::ThreeVector v3(1.1,2.2,3.3);
13     HepMC::ThreeVector vx(1.34);
14
15     HepMC::ThreeVector v3copy( v3 );
16
17     double eps = 1.e-15; // allowed differnce between doubles
18     int numbad = 0;
19
20     double x = v3.x();
21     double y = v3.y();
22     double z = v3.z();
23     double p2 = v3.perp2();
24     double pt = v3.perp();
25     double r = v3.r();
26     double th = v3.theta();
27     double ph = v3.phi();
28     double mag = std::sqrt(x*x + y*y + z*z);
29     double pperp = std::sqrt(x*x + y*y);
30
31     vx.set(1., 2., 3.);
32     vx.setX(1.1);
33     vx.setY(2.3);
34     vx.setZ(4.4);
35     vx.setPhi(0.12);
36     vx.setTheta(0.54);
37
38     vector3 = v3;
39
40     if( fabs( mag - r ) > eps ) {
41         std::cout << "different ThreeVector magnitude: " << mag << " " << r << std::endl;
42         std::cout << "difference is : " << ( mag - r ) << std::endl;
43         ++numbad;
44     }
45     if( fabs( pperp - pt ) > eps ) {
46         std::cout << "different ThreeVector Pt: " << pperp << " " << pt << std::endl;
47         std::cout << "difference is : " << ( pperp - pt ) << std::endl;
48         ++numbad;
49     }
50
51     if( v3 == vector3 ) {
52     } else {
53         ++numbad;
54         std::cout << "vectors v3 and vector3 are different" << std::endl;
55     }
56     if( v3 != v3copy ) {
57         ++numbad;
58         std::cout << "vectors v3 and v3copy are different" << std::endl;
59     }
60
61     // FourVector
62     HepMC::FourVector vector;

```

```

63  HepMC::FourVector v4(1.1,2.2,3.3,4.4);
64  HepMC::FourVector vt(1.34);
65
66  HepMC::FourVector vectorcopy( v4 );
67  vector = v4;
68
69  double px = v4.px();
70  double py = v4.py();
71  double pz = v4.pz();
72  double e  = v4.e();
73  x = vectorcopy.x();
74  y = vectorcopy.y();
75  z = vectorcopy.z();
76  double t = vectorcopy.t();
77
78  p2 = v4.perp2();
79  pt = v4.perp();
80  th = v4.theta();
81  ph = v4.phi();
82  r = v4.rho();
83  double masssq1 = v4.m2();
84  double mass1 = v4.m();
85  double pr1 = v4.pseudoRapidity();
86  double eta1 = v4.eta();
87  double masssq2 = vector.m2();
88  double mass2 = vector.m();
89  double pr2 = vector.pseudoRapidity();
90  double eta2 = vector.eta();
91
92  vt.set(1., 2., 3., 5.5);
93  vt.setX(1.1);
94  vt.setY(2.3);
95  vt.setZ(4.4);
96  vt.setT(6.5);
97  vt.setPx(3.1);
98  vt.setPy(2.2);
99  vt.setPz(-1.1);
100 vt.setE(5.4);
101
102 mag = std::sqrt(x*x + y*y + z*z);
103 pperp = std::sqrt(x*x + y*y);
104 if( fabs( mag - r ) > eps ) {
105     std::cout << "different FourVector magnitude: " << mag << " " << r << std::endl;
106     std::cout << "difference is : " << ( mag - r ) << std::endl;
107     ++numbad;
108 }
109 if( fabs( pperp - pt ) > eps ) {
110     std::cout << "different FourVector Pt: " << pperp << " " << pt << std::endl;
111     std::cout << "difference is : " << ( pperp - pt ) << std::endl;
112     ++numbad;
113 }
114
115 if( px != x ) {
116     std::cout << "different X values: " << px << " " << x << std::endl;
117     ++numbad;
118 }
119 if( py != y ) {
120     std::cout << "different Y values: " << py << " " << y << std::endl;
121     ++numbad;
122 }
123 if( pz != z ) {
124     std::cout << "different Z values: " << pz << " " << z << std::endl;
125     ++numbad;
126 }
127 if( e != t ) {
128     std::cout << "different E values: " << e << " " << t << std::endl;
129     ++numbad;

```

```
130     }
131     if( fabs( masssq1 - masssq2 ) > eps ) {
132         std::cout << "different mass sq values: " << masssq1 << " " << masssq2 << std::endl;
133         std::cout << "difference is : " << ( masssq1 - masssq2 ) << std::endl;
134         ++numbad;
135     }
136     if( fabs( mass1 - mass2 ) > eps ) {
137         std::cout << "different mass values: " << mass1 << " " << mass2 << std::endl;
138         std::cout << "difference is : " << ( mass1 - mass2 ) << std::endl;
139         ++numbad;
140     }
141     if( fabs( pr1 - pr2 ) > eps ) {
142         std::cout << "different pseudorapidity values: " << pr1 << " " << pr2 << std::endl;
143         std::cout << "difference is : " << ( pr1 - pr2 ) << std::endl;
144         ++numbad;
145     }
146     if( fabs( eta1 - eta2 ) > eps ) {
147         std::cout << "different eta values: " << eta1 << " " << eta2 << std::endl;
148         std::cout << "difference is : " << ( eta1 - eta2 ) << std::endl;
149         ++numbad;
150     }
151     if( v4 == vector ) {
152     } else {
153         std::cout << "vectors v and vector are different" << std::endl;
154         ++numbad;
155     }
156     if( v4 != vectorcopy ) {
157         std::cout << "vectors v and vectorcopy are different" << std::endl;
158         ++numbad;
159     }
160
161     return numbad;
162 }
```

11.17 testStreamIO.cc.in

Use streaming IO to read and write a file

```

1
2 // testStreamIO.cc.in
3 //
4 // garren@fnal.gov, March 2006
5 //
6 // The same as testHepMC, but using the IO stream directly
7 //
8 //
9
10 #include <fstream>
11
12 #include "HepMC/GenEvent.h"
13 #include "HepMC/IO_AsciiParticles.h"
14 #ifdef HEPMC_HAS_IO_GENEVENT
15 #include "HepMC/IO_GenEvent.h"
16 #endif
17 #include "HepMC/Version.h"
18 #include "HepMC/IO_Exception.h"
19
20 // define methods and classes used by this test
21 #include "IsGoodEvent.h"
22 #include "testHepMCMethods.h"
23
24 void read_testIOGenEvent(std::ostream & os);
25 void read_variousFormats(std::ostream & os);
26 void write_to_stream(std::ostream & os);
27 void write_to_stream3(std::ostream & os);
28 void read_from_stream4(std::ostream & os);
29
30 int main() {
31     std::ofstream os( "testStreamIO.cout" );
32     std::ofstream osv( "testStreamIOVarious.cout" );
33     write_to_stream(os);
34     read_testIOGenEvent(os);
35     read_variousFormats(osv);
36     write_to_stream3(os);
37     read_from_stream4(os);
38     return 0;
39 }
40
41 void write_to_stream(std::ostream & os)
42 {
43     os << std::endl;
44     os << "basic IO_GenEvent input with streaming output" << std::endl;
45     // declare an input strategy to read the data produced with the
46     // example_MyPythia - units are GeV and mm
47     HepMC::IO_GenEvent_ascii_in("@srcdir/testIOGenEvent.input",std::ios::in);
48     ascii_in.use_input_units( HepMC::Units::GEV, HepMC::Units::MM );
49     // declare an output stream
50     const char outfile[] = "testStreamIO.out";
51     std::ofstream ascii_out( outfile );
52     if( !ascii_out ) {
53         std::cerr << "cannot open " << outfile << std::endl;
54         exit(-1);
55     }
56     ascii_out.precision(16);
57     HepMC::write_HepMC_IO_block_begin( ascii_out );
58     // declare an instance of the event selection predicate
59     IsGoodEvent is_good_event;
60     //.....EVENT LOOP
61     int icount=0;
62     int num_good_events=0;
63     HepMC::GenEvent* evt = ascii_in.read_next_event();

```

```

64     while ( evt ) {
65         icount++;
66         if ( icount%50==1 ) os << "Processing Event Number " << icount
67                                 << " its # " << evt->event_number()
68                                 << std::endl;
69         if ( is_good_event(evt) ) {
70             ++num_good_events;
71             particleTypes( evt, os );
72             ascii_out << (*evt);
73         }
74
75         // clean up and get next event
76         delete evt;
77         ascii_in >> evt;
78     }
79     HepMC::write_HepMC_IO_block_end( ascii_out );
80     //.....PRINT RESULT
81     os << num_good_events << " out of " << icount
82         << " processed events passed the cuts. Finished." << std::endl;
83 }
84
85 void read_testIOGenEvent(std::ostream & os)
86 {
87     os << std::endl;
88     os << "streaming input and output" << std::endl;
89     // input units are GeV and mm
90     const char infile[] = "@srcdir@/testIOGenEvent.input";
91     std::ifstream is( infile );
92     if( !is ) {
93         std::cerr << "cannot open " << infile << std::endl;
94         exit(-1);
95     }
96     // declare an output stream
97     const char outfile[] = "testStreamIO2.out";
98     std::ofstream ascii_out( outfile );
99     if( !ascii_out ) {
100         std::cerr << "cannot open " << outfile << std::endl;
101         exit(-1);
102     }
103     ascii_out.precision(16);
104     HepMC::write_HepMC_IO_block_begin( ascii_out );
105     // declare another output stream to test precision
106     const char poutfile[] = "testStreamIOPrecision.out";
107     std::ofstream pout( poutfile );
108     if( !pout ) {
109         std::cerr << "cannot open " << poutfile << std::endl;
110         exit(-1);
111     }
112     pout.precision(10);
113     // declare an IO_AsciiParticle for output
114     HepMC::IO_AsciiParticles particle_out("testStreamIOParticle.out",std::ios::out);
115     // declare an instance of the event selection predicate
116     IsGoodEvent is_good_event;
117     //.....EVENT LOOP
118     int icount=0;
119     int num_good_events=0;
120     HepMC::GenEvent evt;
121     while ( is ) {
122         // WARNING - we are not using pointers, so this could be an empty event
123         is >> evt;
124         // make sure this is a valid event
125         if( evt.is_valid() ) {
126             ++icount;
127             if ( icount%50==1 ) os << "Processing Event Number " << icount
128                                     << " its # " << evt.event_number()
129                                     << std::endl;
130             if ( is_good_event( &evt ) ) {

```

```

131         ++num_good_events;
132         particleTypes(&evt,os);
133         ascii_out << evt;
134         pout << evt;
135         // We must explicitly create the pointer if we want to use this event
136         // with any IO strategy (e.g., IO_AsciiParticles)
137         HepMC::GenEvent* pevt= &evt;
138         particle_out << pevt;
139     }
140 }
141 }
142 HepMC::write_HepMC_IO_block_end( ascii_out );
143 //.....PRINT RESULT
144 os << num_good_events << " out of " << icount
145     << " processed events passed the cuts. Finished." << std::endl;
146 }
147
148 void read_variousFormats(std::ostream & os)
149 {
150     os << std::endl;
151     os << "process varied input" << std::endl;
152     // declare an input stream
153     const char infile[] = "@srcdir@/testHepMCVarious.input";
154     std::ifstream is( infile );
155     if( !is ) {
156         std::cerr << "cannot open " << infile << std::endl;
157         exit(-1);
158     }
159     // set input units
160     HepMC::set_input_units( is, HepMC::Units::GEV, HepMC::Units::MM );
161     // declare an output stream
162     const char outfile[] = "testStreamIOVarious.out";
163     std::ofstream ascii_out( outfile );
164     if( !ascii_out ) {
165         std::cerr << "cannot open " << outfile << std::endl;
166         exit(-1);
167     }
168     ascii_out.precision(16);
169     HepMC::write_HepMC_IO_block_begin( ascii_out );
170     //.....EVENT LOOP
171     int icount=0, ibad=0;
172     HepMC::GenEvent evt;
173     while ( is ) {
174         // we have to do our own try/catch blocks
175         try {
176             is >> evt;
177         }
178         catch (HepMC::IO_Exception& e) {
179             evt.clear();
180             ++ibad;
181         }
182         // WARNING - we are not using pointers, so this could be an empty event
183         // make sure this is a valid event
184         if( evt.is_valid() ) {
185             icount++;
186             double pim;
187             os << "Processing Event Number " << icount
188                 << " its # " << evt.event_number()
189                 << std::endl;
190             ascii_out << evt;
191             // units should be unknown
192             evt.write_units(os);
193             pim = findPiZero(&evt);
194             os << " pizero mass: " << pim << std::endl;
195             // set units to GeV and mm
196             evt.use_units(HepMC::Units::GEV, HepMC::Units::MM);
197             evt.write_units(os);

```

```

198         pim = findPiZero(&evt);
199         os << " pizero mass: " << pim
200         << " " << HepMC::Units::name( evt.momentum_unit() ) << std::endl;
201         // convert units to MeV
202         evt.use_units(HepMC::Units::MEV, HepMC::Units::MM);
203         evt.write_units(os);
204         pim = findPiZero(&evt);
205         os << " pizero mass: " << pim
206         << " " << HepMC::Units::name( evt.momentum_unit() ) << std::endl;
207     }
208 }
209 std::cout << "testSteamIO: the HeavyIon and PdfInfo input stream errors are intentional" << std::endl;
210 HepMC::write_HepMC_IO_block_end( ascii_out );
211 //.....PRINT RESULT
212 os << icount << " valid events processed. " ;
213 os << ibad << " invalid events processed. Finished." << std::endl;
214 }
215
216 void write_to_stream3(std::ostream & os)
217 {
218     os << std::endl;
219     os << "basic IO_GenEvent input with streaming output using member function" << std::endl;
220     // declare an input strategy to read the data produced with the
221     // example_MyPythia - units are GeV and mm
222     HepMC::IO_GenEvent ascii_in("@srcdir@/testIOGenEvent.input",std::ios::in);
223     ascii_in.use_input_units( HepMC::Units::GEV, HepMC::Units::MM );
224     // declare an output stream
225     const char outfile[] = "testStreamIO3.out";
226     std::ofstream ascii_out( outfile );
227     if( !ascii_out ) {
228         std::cerr << "cannot open " << outfile << std::endl;
229         exit(-1);
230     }
231     ascii_out.precision(16);
232     HepMC::write_HepMC_IO_block_begin( ascii_out );
233     // declare an instance of the event selection predicate
234     IsGoodEvent is_good_event;
235     //.....EVENT LOOP
236     int icount=0;
237     int num_good_events=0;
238     HepMC::GenEvent* evt = ascii_in.read_next_event();
239     while ( evt ) {
240         icount++;
241         if ( icount%50==1 ) os << "Processing Event Number " << icount
242                             << " its # " << evt->event_number()
243                             << std::endl;
244         if ( is_good_event(evt) ) {
245             ++num_good_events;
246             particleTypes( evt, os );
247             evt->write(ascii_out);
248         }
249
250         // clean up and get next event
251         delete evt;
252         ascii_in >> evt;
253     }
254     HepMC::write_HepMC_IO_block_end( ascii_out );
255     //.....PRINT RESULT
256     os << num_good_events << " out of " << icount
257         << " processed events passed the cuts. Finished." << std::endl;
258 }
259
260 void read_from_stream4(std::ostream & os)
261 {
262     os << std::endl;
263     os << "streaming input and output using member functions" << std::endl;
264     // input units are GeV and mm

```

```

265     const char infile[] = "@srcdir@/testIOGenEvent.input";
266     std::ifstream is( infile );
267     if( !is ) {
268         std::cerr << "cannot open " << infile << std::endl;
269         exit(-1);
270     }
271     // declare an output stream
272     const char outfile[] = "testStreamIO4.out";
273     std::ofstream ascii_out( outfile );
274     if( !ascii_out ) {
275         std::cerr << "cannot open " << outfile << std::endl;
276         exit(-1);
277     }
278     ascii_out.precision(16);
279     HepMC::write_HepMC_IO_block_begin( ascii_out );
280     // declare an instance of the event selection predicate
281     IsGoodEvent is_good_event;
282     //.....EVENT LOOP
283     int icount=0;
284     int num_good_events=0;
285     HepMC::GenEvent evt;
286     while ( is ) {
287         // WARNING - we are not using pointers, so this could be an empty event
288         evt.read(is);
289         // make sure this is a valid event
290         if( evt.is_valid() ) {
291             ++icount;
292             if ( icount%50==1 ) os << "Processing Event Number " << icount
293                                     << " its # " << evt.event_number()
294                                     << std::endl;
295             if ( is_good_event( &evt ) ) {
296                 ++num_good_events;
297                 particleTypes(&evt,os);
298                 evt.write(ascii_out);
299             }
300         }
301     }
302     HepMC::write_HepMC_IO_block_end( ascii_out );
303     //.....PRINT RESULT
304     os << num_good_events << " out of " << icount
305         << " processed events passed the cuts. Finished." << std::endl;
306 }

```

11.18 testUnits.cc

Test MomentumUnits and PositionUnits Make sure set and change methods work as expected.

```

1 //
2 // Test Units
3 //
4 #include <iostream>
5
6 #include "HepMC/Units.h"
7
8 int main()
9 {
10
11     int err = 0;
12     double cf;
13
14     std::cout << "Default units: " << HepMC::Units::name(HepMC::Units::default_momentum_unit())
15         << " " << HepMC::Units::name(HepMC::Units::default_length_unit()) << std::endl;
16
17     // check momentum conversion factors
18     cf = conversion_factor( HepMC::Units::GEV, HepMC::Units::GEV );
19     if( cf != 1 ) {
20         ++err;
21         std::cerr << "wrong conversion factor " << cf
22             << " for GEV to GEV - should be 1 \n";
23     }
24     cf = conversion_factor( HepMC::Units::MEV, HepMC::Units::MEV );
25     if( cf != 1 ) {
26         ++err;
27         std::cerr << "wrong conversion factor " << cf
28             << " for MEV to MEV - should be 1 \n";
29     }
30     cf = conversion_factor( HepMC::Units::MEV, HepMC::Units::GEV );
31     if( cf != 0.001 ) {
32         ++err;
33         std::cerr << "wrong conversion factor " << cf
34             << " for MEV to GEV - should be 0.001 \n";
35     }
36     cf = conversion_factor( HepMC::Units::GEV, HepMC::Units::MEV );
37     if( cf != 1000.0 ) {
38         ++err;
39         std::cerr << "wrong conversion factor " << cf
40             << " for GEV to MEV - should be 1000 \n";
41     }
42
43     // check length conversion factors
44     cf = conversion_factor( HepMC::Units::MM, HepMC::Units::MM );
45     if( cf != 1 ) {
46         ++err;
47         std::cerr << "wrong conversion factor " << cf
48             << " for MM to MM - should be 1 \n";
49     }
50     cf = conversion_factor( HepMC::Units::CM, HepMC::Units::CM );
51     if( cf != 1 ) {
52         ++err;
53         std::cerr << "wrong conversion factor " << cf
54             << " for CM to CM - should be 1 \n";
55     }
56     cf = conversion_factor( HepMC::Units::CM, HepMC::Units::MM );
57     if( cf != 10.0 ) {
58         ++err;
59         std::cerr << "wrong conversion factor " << cf
60             << " for CM to MM - should be 10 \n";
61     }

```

```
62  cf = conversion_factor( HepMC::Units::MM, HepMC::Units::CM );
63  if( cf != 0.1 ) {
64      ++err;
65      std::cerr << "wrong conversion factor " << cf
66                << " for MM to CM - should be 0.1 \n";
67  }
68
69  return err;
70 }
```

11.19 VectorConversion.h

This example converts from ThreeVector and FourVector to CLHEP::Hep3Vector and CLHEP::HepLorentzVector. Similar (or perhaps templated) conversion methods could be added to any vector class.

```
1 #ifndef VECTOR_CONVERSION_H
2 #define VECTOR_CONVERSION_H
3 // garren@fnal.gov, January 2007
4 //
5 //
6 // This example converts from ThreeVector and FourVector to
7 // CLHEP::Hep3Vector and CLHEP::HepLorentzVector
8 // Similar (or perhaps templated) conversion methods could be added to
9 // any vector class.
10 //
11
12
13 #include "HepMC/SimpleVector.h"
14 #include "CLHEP/Vector/LorentzVector.h"
15
16
17 inline CLHEP::Hep3Vector convertTo( const HepMC::ThreeVector& v )
18     { return CLHEP::Hep3Vector( v.x(), v.y(), v.z() ); }
19
20
21 inline CLHEP::HepLorentzVector convertTo( const HepMC::FourVector& v )
22     { return CLHEP::HepLorentzVector( v.x(), v.y(), v.z(), v.t() ); }
23
24
25
26 #endif // VECTOR_CONVERSION_H
```


Chapter 12

HepMC Page Documentation

12.1 Todo List

Member filterEvent (p. 280) Have to build a list, since the `GV::add_particle_out` method modifies the end vertex!

Member filterEvent (p. 280) Why does this cause an error?

Index

- /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/HepMC/
 - Directory Reference, 17
- /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/examples/
 - Directory Reference, 15
- /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/HepMC/
 - ~particle_iterator
- /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/HepMC/
 - HepMC::GenEvent::particle_
- /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/HepMC/
 - iterator, 100
- /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/HepMC/
 - HepMC::GenVertex::particle_
- /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/HepMC/
 - iterator, 145
- /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/tests/
 - ~particle_iterator
- /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/tests/
 - HepMC::GenEvent::vertex_const_
- /home/cepa01/garren/lcg/hepmc/HepMC-2.06.05/tests/
 - iterator, 103
- ~Flow
 - HepMC::Flow, 54
- ~GenCrossSection
 - HepMC::GenCrossSection, 70
- ~GenEvent
 - HepMC::GenEvent, 79
- ~GenParticle
 - HepMC::GenParticle, 114
- ~GenVertex
 - HepMC::GenVertex, 130
- ~HeavyIon
 - HepMC::HeavyIon, 154
- ~IO_AsciiParticles
 - HepMC::IO_AsciiParticles, 177
- ~IO_BaseClass
 - HepMC::IO_BaseClass, 180
- ~IO_GenEvent
 - HepMC::IO_GenEvent, 185
- ~IO_HEPEVT
 - HepMC::IO_HEPEVT, 189
- ~IO_HERWIG
 - HepMC::IO_HERWIG, 194
- ~PdfInfo
 - HepMC::PdfInfo, 222
- ~Polarization
 - HepMC::Polarization, 234
- ~StreamInfo
 - HepMC::StreamInfo, 246
- ~TempParticleMap
 - HepMC::TempParticleMap, 252
- ~WeightContainer
 - HepMC::WeightContainer, 263
- ~edge_iterator
 - HepMC::GenVertex::edge_
- ~edge_iterator
 - iterator, 142
- ~vertex_iterator
 - HepMC::GenEvent::vertex_
- ~vertex_iterator
 - iterator, 106
- ~vertex_iterator
 - HepMC::GenVertex::vertex_
- ~vertex_iterator
 - iterator, 148
- a
 - prvpm, 243
- ab
 - prvnv, 241
- add_particle_in
 - HepMC::GenVertex, 130
- add_particle_out
 - HepMC::GenVertex, 131
- add_vertex
 - HepMC::GenEvent, 80
- addEndParticle
 - HepMC::TempParticleMap, 252
- advance_to_first_
 - HepMC::GenVertex::particle_
- advance_to_first_
 - iterator, 145
- AFCH
 - HerwigWrapper.h, 309
- alphaQCD
 - HepMC::GenEvent, 80
- alphaQED
 - HepMC::GenEvent, 80
- ALPHEM
 - HerwigWrapper.h, 309
- already_in_vector
 - HepMC, 32
- ancestors
 - HepMC, 27
- ascii

- HepMC, 27
- ascii_pdt
 - HepMC, 27
- AVWGT
 - hwgev, 173
- AZSOFT
 - HerwigWrapper.h, 309
- AZSPIN
 - HerwigWrapper.h, 309
- b
 - prvpm, 243
- B1LIM
 - HerwigWrapper.h, 310
- back
 - HepMC::WeightContainer, 263
- BadInputStream
 - HepMC::IO_Exception, 183
- BadOutputStream
 - HepMC::IO_Exception, 183
- barcode
 - HepMC::GenParticle, 114
 - HepMC::GenVertex, 131
- barcode_to_particle
 - HepMC::GenEvent, 80
- barcode_to_vertex
 - HepMC::GenEvent, 81
- beam_particles
 - HepMC::GenEvent, 81
- begin
 - HepMC::ConstGenEventParticleRange, 44
 - HepMC::ConstGenEventVertexRange, 45
 - HepMC::ConstGenParticleEndRange, 46
 - HepMC::ConstGenParticleProductionRange, 47
 - HepMC::Flow, 54, 55
 - HepMC::GenEventParticleRange, 109
 - HepMC::GenEventVertexRange, 110
 - HepMC::GenParticleEndRange, 122
 - HepMC::GenParticleProductionRange, 124
 - HepMC::GenVertexParticleRange, 151
 - HepMC::TempParticleMap, 252
 - HepMC::WeightContainer, 263
- BETAF
 - HerwigWrapper.h, 310
- brat
 - PythiaWrapper6_4.h, 348
- BTCLM
 - HerwigWrapper.h, 310
- build_end_vertex
 - HepMC::IO_HEPEVT, 189
 - HepMC::IO_HERWIG, 195
- build_particle
 - HepMC::IO_HEPEVT, 190
 - HepMC::IO_HERWIG, 195
- build_production_vertex
 - HepMC::IO_HEPEVT, 190
 - HepMC::IO_HERWIG, 195
- byte_num_to_double
 - HepMC::HEPEVT_Wrapper, 163
- byte_num_to_int
 - HepMC::HEPEVT_Wrapper, 163
- CAFAC
 - HerwigWrapper.h, 310
- CFFAC
 - HerwigWrapper.h, 310
- change_parent_event
 - HepMC::GenVertex, 131
- check_hepevt_consistency
 - HepMC::HEPEVT_Wrapper, 163
- check_momentum_conservation
 - HepMC::GenVertex, 131
- children
 - HepMC, 27
- ckin
 - PythiaWrapper6_4.h, 348
- CLDIR
 - HerwigWrapper.h, 310
- clear
 - HepMC::Flow, 55
 - HepMC::GenCrossSection, 70
 - HepMC::GenEvent, 81
 - HepMC::IO_AsciiParticles, 177
 - HepMC::IO_GenEvent, 186
 - HepMC::WeightContainer, 263
- CLHEP, 21
- CLMAX
 - HerwigWrapper.h, 310
- CLPOW
 - HerwigWrapper.h, 310
- CLSMR
 - HerwigWrapper.h, 310
- CM
 - HepMC::Units, 39
- coef
 - PythiaWrapper6_4.h, 348
- compareBeamParticles
 - HepMC, 28
- compareGenEvent
 - HepMC, 28
- CompareGenEvent.cc, 267

- CompareGenEvent.h, 268
- compareParticles
 - HepMC, 29
- compareSignalProcessVertex
 - HepMC, 28
- compareVertex
 - HepMC, 29
- compareVertices
 - HepMC, 28
- compareWeights
 - HepMC, 28
- connected_partners
 - HepMC::Flow, 55
- const_iterator
 - HepMC::Flow, 54
 - HepMC::WeightContainer, 262
- ConstGenEventParticleRange
 - HepMC::ConstGenEventParticle-
Range, 43
- ConstGenEventVertexRange
 - HepMC::ConstGenEventVertex-
Range, 45
- ConstGenParticleEndRange
 - HepMC::ConstGenParticleEnd-
Range, 46
- ConstGenParticleProductionRange
 - HepMC::ConstGenParticle-
ProductionRange, 47
- conversion_factor
 - HepMC::Units, 40
- convert_momentum
 - HepMC::GenParticle, 114
- convert_position
 - HepMC::GenVertex, 132
- convert_units
 - HepMC, 31
- convertTo
 - VectorConversion.h, 376
- copy_if
 - HepMC, 29
- copy_recursive_iterator_
 - HepMC::GenVertex::vertex_
iterator, 149
- copy_with_own_set
 - HepMC::GenVertex::vertex_
iterator, 149
- cross_section
 - HepMC::GenCrossSection, 70
 - HepMC::GenEvent, 81, 82
- cross_section_error
 - HepMC::GenCrossSection, 70
- CSPEED
 - HerwigWrapper.h, 310
- dangling_connected_partners
 - HepMC::Flow, 55
- data
 - HEPEVT_Wrapper.h, 299
- dcmass
 - prvrv, 241
- default_length_unit
 - HepMC::Units, 40
- default_momentum_unit
 - HepMC::Units, 40
- delete_adopted_particles
 - HepMC::GenVertex, 132
- delete_all_vertices
 - HepMC::GenEvent, 82
- descendants
 - HepMC, 27
- detail, 22
- e
 - HepMC::FourVector, 62
 - HepMC::HEPEVT_Wrapper, 163
- EBEAM1
 - HerwigWrapper.h, 310
- EBEAM2
 - HerwigWrapper.h, 310
- eccentricity
 - HepMC::HeavyIon, 155
- edge_iterator
 - HepMC::GenVertex, 139
 - HepMC::GenVertex::edge_
iterator, 142
- edges_begin
 - HepMC::GenVertex, 132
- edges_end
 - HepMC::GenVertex, 132
- edges_size
 - HepMC::GenVertex, 132
- EFFMIN
 - HerwigWrapper.h, 311
- empty
 - HepMC::Flow, 56
 - HepMC::WeightContainer, 263
- enable_if.h, 269
- end
 - HepMC::ConstGenEventParticle-
Range, 44
 - HepMC::ConstGenEventVertex-
Range, 45
 - HepMC::ConstGenParticleEnd-
Range, 46
 - HepMC::ConstGenParticle-
ProductionRange, 47
 - HepMC::Flow, 56

- HepMC::GenEventParticleRange, 109
- HepMC::GenEventVertexRange, 110
- HepMC::GenParticleEndRange, 122
- HepMC::GenParticleProduction-Range, 124
- HepMC::GenVertexParticleRange, 151
- HepMC::TempParticleMap, 252
- HepMC::WeightContainer, 264
- end_vertex
 - HepMC::GenParticle, 115
 - HepMC::TempParticleMap, 252
- EndKeyMismatch
 - HepMC::IO_Exception, 183
- EndOfStream
 - HepMC::IO_Exception, 183
- ENSOF
 - HerwigWrapper.h, 311
- erase
 - HepMC::Flow, 56
- error_message
 - HepMC::IO_GenEvent, 186
- error_type
 - HepMC::IO_GenEvent, 186
- ErrorType
 - HepMC::IO_Exception, 183
- establish_input_stream_info
 - HepMC, 33
 - HepMC::detail, 36
- establish_output_stream_info
 - HepMC, 33
 - HepMC::detail, 36
- ET2MIX
 - HerwigWrapper.h, 311
- eta
 - HepMC::FourVector, 62
- ETAMIX
 - HerwigWrapper.h, 311
- event_number
 - HepMC::GenEvent, 82
 - HepMC::HEPEVT_Wrapper, 163
- event_plane_angle
 - HepMC::HeavyIon, 155
- event_scale
 - HepMC::GenEvent, 82
- event_selection
 - example_MyPythia.cc, 273
- EVWGT
 - hwgev, 173
- example_BuildEventFromScratch.cc, 270
- example_BuildEventFromScratch.cc
 - main, 270
- example_EventSelection.cc, 271
- example_EventSelection.cc
 - main, 271
- example_MyHerwig.cc, 272
- example_MyHerwig.cc
 - main, 272
- example_MyPythia.cc, 273
- example_MyPythia.cc
 - event_selection, 273
 - main, 273
 - pythia_in, 273
 - pythia_in_out, 274
 - pythia_out, 274
 - pythia_particle_out, 274
- example_MyPythiaOnlyToHepMC.cc, 276
- example_MyPythiaOnlyToHepMC.cc
 - main, 276
- example_PythiaStreamIO.cc, 277
- example_PythiaStreamIO.cc
 - main, 277
 - readPythiaStreamIO, 277
 - writePythiaStreamIO, 277
- example_UsingIterators.cc, 279
- example_UsingIterators.cc
 - main, 279
- extascii
 - HepMC, 27
- extascii_pdt
 - HepMC, 27
- F0MIX
 - HerwigWrapper.h, 311
- F1MIX
 - HerwigWrapper.h, 311
- F2MIX
 - HerwigWrapper.h, 311
- family
 - HepMC, 27
- fill_next_event
 - HepMC::IO_AsciiParticles, 177
 - HepMC::IO_BaseClass, 180
 - HepMC::IO_GenEvent, 186
 - HepMC::IO_HEPEVT, 190
 - HepMC::IO_HERWIG, 195
- filterEvent
 - filterEvent.cc, 280
- filterEvent.cc, 280
- filterEvent.cc
 - filterEvent, 280
- find_event_end
 - HepMC::detail, 38
- find_in_map
 - HepMC::IO_HEPEVT, 190

- HepMC::IO_HERWIG, 196
- findPiZero
 - testHepMCMethods.cc, 366
 - testHepMCMethods.h, 367
- finished_first_event
 - HepMC::StreamInfo, 246
- first_child
 - HepMC::HEPEVT_Wrapper, 164
- first_parent
 - HepMC::HEPEVT_Wrapper, 164
- Flow
 - HepMC::Flow, 54
- flow
 - HepMC::GenParticle, 115
- Flow.cc, 281
- Flow.h, 282
- FlowVec
 - testFlow.cc, 364
- follow_edge_
 - HepMC::GenVertex::vertex_
 - iterator, 149
- FourVector
 - HepMC::FourVector, 61
- front
 - HepMC::WeightContainer, 264
- GAMH
 - HerwigWrapper.h, 311
- GAMW
 - HerwigWrapper.h, 311
- GAMWT
 - hwgev, 173
- GAMZ
 - HerwigWrapper.h, 311
- GAMZP
 - HerwigWrapper.h, 311
- GCUTME
 - HerwigWrapper.h, 311
- gen
 - HepMC, 27
- GenCrossSection
 - HepMC::GenCrossSection, 70
- GenCrossSection.cc, 283
- GenCrossSection.h, 284
- generated_mass
 - HepMC::GenParticle, 115
- generatedMass
 - HepMC::GenParticle, 115
- GenEvent
 - HepMC::GenEvent, 78, 79
 - HepMC::GenParticle, 121
 - HepMC::GenVertex, 139
 - HepMC::WeightContainer, 266
- GenEvent.cc, 285
- GenEvent.h, 286
- GenEventParticleRange
 - HepMC::GenEventParticleRange,
 - 109
- GenEventStreamIO.cc, 288
- GenEventVertexRange
 - HepMC::GenEventVertexRange, 110
- GenParticle
 - HepMC::GenEvent, 94
 - HepMC::GenParticle, 114
- GenParticle.cc, 290
- GenParticle.h, 291
- GenParticle.h
 - hepmc_uint64_t, 291
- GenParticleEndRange
 - HepMC::GenParticleEndRange, 122
- GenParticleProductionRange
 - HepMC::GenParticleProduction-
 - Range, 124
- GenRanges.cc, 292
- GenRanges.h, 293
- GENSOF
 - hwgev, 173
- GenVertex
 - HepMC::GenEvent, 94
 - HepMC::GenParticle, 121
 - HepMC::GenVertex, 130
- GenVertex.cc, 294
- GenVertex.h, 295
- GenVertexParticleRange
 - HepMC::GenVertexParticleRange,
 - 151
- get_stream_info
 - HepMC, 33
- getHerwigCrossSection
 - HepMC, 27
- getPythiaCrossSection
 - HepMC, 27
- GEV
 - HepMC::Units, 39
- GEV2NB
 - HerwigWrapper.h, 312
- H1MIX
 - HerwigWrapper.h, 312
- HARDME
 - HerwigWrapper.h, 312
- has_decayed
 - HepMC::GenParticle, 116
- has_key
 - HepMC::StreamInfo, 247
 - HepMC::WeightContainer, 264
- heavy_ion
 - HepMC::GenEvent, 82, 83

- HeavyIon
 - HepMC::HeavyIon, 154
- HeavyIon.cc, 296
- HeavyIon.h, 297
- hepevt
 - HEPEVT_Wrapper.h, 299
- hepevt_
 - HEPEVT_Wrapper.h, 299
- hepevt_bytes_allocation
 - HEPEVT_Wrapper.h, 300
- HEPEVT_EntriesAllocation
 - HEPEVT_Wrapper.h, 299
- HEPEVT_Wrapper.cc, 298
- HEPEVT_Wrapper.h, 299
 - data, 299
 - hepevt, 299
 - hepevt_, 299
 - hepevt_bytes_allocation, 300
 - HEPEVT_EntriesAllocation, 299
- HepMC, 23
 - ancestors, 27
 - ascii, 27
 - ascii_pdt, 27
 - children, 27
 - descendants, 27
 - extascii, 27
 - extascii_pdt, 27
 - family, 27
 - gen, 27
 - parents, 27
 - relatives, 27
- HepMC
 - already_in_vector, 32
 - compareBeamParticles, 28
 - compareGenEvent, 28
 - compareParticles, 29
 - compareSignalProcessVertex, 28
 - compareVertex, 29
 - compareVertices, 28
 - compareWeights, 28
 - convert_units, 31
 - copy_if, 29
 - establish_input_stream_info, 33
 - establish_output_stream_info, 33
 - get_stream_info, 33
 - getHerwigCrossSection, 27
 - getPythiaCrossSection, 27
 - HepMC_pi, 34
 - HepMCStreamCallback, 33
 - IteratorRange, 27
 - known_io, 27
 - not_in_vector, 32
 - operator<<, 29, 31, 33, 34
 - operator>>, 29-31
 - set_input_units, 30
 - version, 32
 - versionName, 32
 - write_HepMC_IO_block_begin, 30
 - write_HepMC_IO_block_end, 30
 - writeVersion, 32
- HepMC::ConstGenEventParticleRange, 43
- HepMC::ConstGenEventParticleRange
 - begin, 44
 - ConstGenEventParticleRange, 43
 - end, 44
- HepMC::ConstGenEventVertexRange, 45
- HepMC::ConstGenEventVertexRange
 - begin, 45
 - ConstGenEventVertexRange, 45
 - end, 45
- HepMC::ConstGenParticleEndRange, 46
- HepMC::ConstGenParticleEndRange
 - begin, 46
 - ConstGenParticleEndRange, 46
 - end, 46
- HepMC::ConstGenParticleProductionRange, 47
- HepMC::ConstGenParticleProduction-Range
 - begin, 47
 - ConstGenParticleProductionRange, 47
 - end, 47
- HepMC::detail, 35
- HepMC::detail
 - establish_input_stream_info, 36
 - establish_output_stream_info, 36
 - find_event_end, 38
 - output, 37, 38
 - read_particle, 37
 - read_units, 38
 - read_vertex, 37
- HepMC::detail::disable_if, 48
- HepMC::detail::disable_if< false, T >, 49
- HepMC::detail::disable_if< false, T >
 - type, 49
- HepMC::detail::enable_if, 50
- HepMC::detail::enable_if< true, T >, 51
- HepMC::detail::enable_if< true, T >

- type, 51
- HepMC::detail::is_arithmetic, 200
- HepMC::detail::is_arithmetic
 - value, 200
- HepMC::detail::is_arithmetic< char
 - >, 201
- HepMC::detail::is_arithmetic< char
 - >
 - value, 201
- HepMC::detail::is_arithmetic<
 - double >, 202
- HepMC::detail::is_arithmetic<
 - double >
 - value, 202
- HepMC::detail::is_arithmetic<
 - float >, 203
- HepMC::detail::is_arithmetic<
 - float >
 - value, 203
- HepMC::detail::is_arithmetic< int
 - >, 204
- HepMC::detail::is_arithmetic< int
 - >
 - value, 204
- HepMC::detail::is_arithmetic< long
 - >, 205
- HepMC::detail::is_arithmetic< long
 - >
 - value, 205
- HepMC::detail::is_arithmetic< long
 - double >, 206
- HepMC::detail::is_arithmetic< long
 - double >
 - value, 206
- HepMC::detail::is_arithmetic<
 - short >, 207
- HepMC::detail::is_arithmetic<
 - short >
 - value, 207
- HepMC::detail::is_arithmetic<
 - signed char >, 208
- HepMC::detail::is_arithmetic<
 - signed char >
 - value, 208
- HepMC::detail::is_arithmetic<
 - unsigned char >, 209
- HepMC::detail::is_arithmetic<
 - unsigned char >
 - value, 209
- HepMC::detail::is_arithmetic<
 - unsigned int >, 210
- HepMC::detail::is_arithmetic<
 - unsigned int >
 - value, 210
- HepMC::detail::is_arithmetic<
 - unsigned long >, 211
- HepMC::detail::is_arithmetic<
 - unsigned long >
 - value, 211
- HepMC::detail::is_arithmetic<
 - unsigned short >, 212
- HepMC::detail::is_arithmetic<
 - unsigned short >
 - value, 212
- HepMC::Flow, 52
- HepMC::Flow
 - ~Flow, 54
 - begin, 54, 55
 - clear, 55
 - connected_partners, 55
 - const_iterator, 54
 - dangling_connected_partners, 55
 - empty, 56
 - end, 56
 - erase, 56
 - Flow, 54
 - icode, 56
 - iterator, 54
 - operator!=, 56
 - operator<<, 58
 - operator=, 56
 - operator==, 57
 - particle_owner, 57
 - print, 57
 - set_icode, 57
 - set_unique_icode, 57
 - size, 57
 - swap, 57
- HepMC::FourVector, 59
- HepMC::FourVector
 - e, 62
 - eta, 62
 - FourVector, 61
 - m, 62
 - m2, 62
 - operator!=, 62
 - operator=, 63
 - operator==, 63
 - perp, 63
 - perp2, 63
 - phi, 63
 - pseudoRapidity, 63
 - px, 63
 - py, 64
 - pz, 64
 - rho, 64
 - set, 64
 - setE, 65

- setPx, 65
- setPy, 65
- setPz, 65
- setT, 65
- setX, 66
- setY, 66
- setZ, 66
- swap, 66
- t, 66
- theta, 67
- x, 67
- y, 67
- z, 67
- HepMC::GenCrossSection, 69
- HepMC::GenCrossSection
 - ~GenCrossSection, 70
 - clear, 70
 - cross_section, 70
 - cross_section_error, 70
 - GenCrossSection, 70
 - is_set, 71
 - operator!=, 71
 - operator=, 71
 - operator==, 71
 - read, 71
 - set_cross_section, 71
 - set_cross_section_error, 72
 - swap, 72
 - write, 72
- HepMC::GenEvent, 73
- HepMC::GenEvent
 - ~GenEvent, 79
 - add_vertex, 80
 - alphaQCD, 80
 - alphaQED, 80
 - barcode_to_particle, 80
 - barcode_to_vertex, 81
 - beam_particles, 81
 - clear, 81
 - cross_section, 81, 82
 - delete_all_vertices, 82
 - event_number, 82
 - event_scale, 82
 - GenEvent, 78, 79
 - GenParticle, 94
 - GenVertex, 94
 - heavy_ion, 82, 83
 - is_valid, 83
 - length_unit, 83
 - momentum_unit, 83
 - mpi, 83
 - operator=, 83
 - particle_const_iterator, 94
 - particle_iterator, 94
 - particle_range, 84
 - particles_begin, 84
 - particles_empty, 84
 - particles_end, 84, 85
 - particles_size, 85
 - pdf_info, 85
 - print, 85
 - print_version, 86
 - random_states, 86
 - read, 86
 - remove_barcode, 86, 87
 - remove_vertex, 87
 - set_alphaQCD, 87
 - set_alphaQED, 87
 - set_barcode, 87
 - set_beam_particles, 88
 - set_cross_section, 88
 - set_event_number, 88
 - set_event_scale, 89
 - set_heavy_ion, 89
 - set_mpi, 89
 - set_pdf_info, 89
 - set_random_states, 89
 - set_signal_process_id, 90
 - set_signal_process_vertex, 90
 - signal_process_id, 90
 - signal_process_vertex, 90
 - swap, 90
 - use_units, 91
 - valid_beam_particles, 91
 - vertex_const_iterator, 94
 - vertex_iterator, 95
 - vertex_range, 91
 - vertices_begin, 92
 - vertices_empty, 92
 - vertices_end, 92
 - vertices_size, 93
 - weights, 93
 - write, 93
 - write_cross_section, 94
 - write_units, 94
- HepMC::GenEvent::particle_const_iterator, 96
- HepMC::GenEvent::particle_const_iterator
 - ~particle_const_iterator, 97
 - m_map_iterator, 98
 - operator *, 97
 - operator!=, 97
 - operator++, 97, 98
 - operator=, 98
 - operator==, 98
 - particle_const_iterator, 97

```

HepMC::GenEvent::particle_-
    iterator, 99
HepMC::GenEvent::particle_iterator
    ~particle_iterator, 100
    m_map_iterator, 101
    operator *, 100
    operator particle_const_-
        iterator, 100
    operator !=, 100
    operator ++, 101
    operator =, 101
    operator ==, 101
    particle_iterator, 100
HepMC::GenEvent::vertex_const_-
    iterator, 102
HepMC::GenEvent::vertex_const_-
    iterator
    ~vertex_const_iterator, 103
    m_map_iterator, 104
    operator *, 103
    operator !=, 103
    operator ++, 103
    operator =, 104
    operator ==, 104
    vertex_const_iterator, 103
HepMC::GenEvent::vertex_iterator,
    105
HepMC::GenEvent::vertex_iterator
    ~vertex_iterator, 106
    m_map_iterator, 107
    operator *, 106
    operator vertex_const_iterator,
        106
    operator !=, 107
    operator ++, 107
    operator =, 107
    operator ==, 107
    vertex_iterator, 106
HepMC::GenEventParticleRange, 109
HepMC::GenEventParticleRange
    begin, 109
    end, 109
    GenEventParticleRange, 109
HepMC::GenEventVertexRange, 110
HepMC::GenEventVertexRange
    begin, 110
    end, 110
    GenEventVertexRange, 110
HepMC::GenParticle, 111
HepMC::GenParticle
    ~GenParticle, 114
    barcode, 114
    convert_momentum, 114
    end_vertex, 115
    flow, 115
    generated_mass, 115
    generatedMass, 115
    GenEvent, 121
    GenParticle, 114
    GenVertex, 121
    has_decayed, 116
    is_beam, 116
    is_undecayed, 116
    momentum, 116
    operator HepMC::FourVector, 116
    operator !=, 116
    operator <<, 121
    operator =, 116
    operator ==, 117
    parent_event, 117
    particles_in, 117
    particles_out, 117
    pdg_id, 117
    polarization, 118
    print, 118
    production_vertex, 118
    set_barcode_, 118
    set_end_vertex_, 118
    set_flow, 119
    set_generated_mass, 119
    set_momentum, 119
    set_pdg_id, 119
    set_polarization, 119
    set_production_vertex_, 119
    set_status, 120
    setGeneratedMass, 120
    status, 120
    suggest_barcode, 120
    swap, 120
HepMC::GenParticleEndRange, 122
HepMC::GenParticleEndRange
    begin, 122
    end, 122
    GenParticleEndRange, 122
HepMC::GenParticleProductionRange,
    124
HepMC::GenParticleProductionRange
    begin, 124
    end, 124
    GenParticleProductionRange, 124
HepMC::GenVertex, 126
HepMC::GenVertex
    ~GenVertex, 130
    add_particle_in, 130
    add_particle_out, 131
    barcode, 131
    change_parent_event_, 131

```

```

    check_momentum_conservation,
        131
    convert_position, 132
    delete_adopted_particles, 132
    edge_iterator, 139
    edges_begin, 132
    edges_end, 132
    edges_size, 132
    GenEvent, 139
    GenVertex, 130
    id, 132
    operator HepMC::FourVector, 133
    operator HepMC::ThreeVector,
        133
    operator!=, 133
    operator<<, 139
    operator=, 133
    operator==, 133
    parent_event, 134
    particle_iterator, 140
    particles, 134
    particles_begin, 134
    particles_end, 134
    particles_in, 134, 135
    particles_in_const_begin, 135
    particles_in_const_end, 135
    particles_in_const_iterator,
        130
    particles_in_size, 135
    particles_out, 135
    particles_out_const_begin, 136
    particles_out_const_end, 136
    particles_out_const_iterator,
        130
    particles_out_size, 136
    point3d, 136
    position, 136
    print, 136
    remove_particle, 137
    remove_particle_in, 137
    remove_particle_out, 137
    set_barcode_, 137
    set_id, 138
    set_parent_event_, 138
    set_position, 138
    suggest_barcode, 138
    swap, 138
    vertex_iterator, 140
    vertices_begin, 139
    vertices_end, 139
    weights, 139
HepMC::GenVertex::edge_iterator,
    141
HepMC::GenVertex::edge_iterator
    ~edge_iterator, 142
    edge_iterator, 142
    is_child, 142
    is_parent, 142
    operator *, 142
    operator!=, 142
    operator++, 143
    operator=, 143
    operator==, 143
    vertex_root, 143
HepMC::GenVertex::particle_
    iterator, 144
HepMC::GenVertex::particle_
    iterator
    ~particle_iterator, 145
    advance_to_first_, 145
    operator *, 145
    operator!=, 145
    operator++, 146
    operator=, 146
    operator==, 146
    particle_iterator, 145
HepMC::GenVertex::vertex_iterator,
    147
HepMC::GenVertex::vertex_iterator
    ~vertex_iterator, 148
    copy_recursive_iterator_, 149
    copy_with_own_set, 149
    follow_edge_, 149
    operator *, 149
    operator!=, 149
    operator++, 149, 150
    operator=, 150
    operator==, 150
    range, 150
    vertex_iterator, 148
    vertex_root, 150
HepMC::GenVertexParticleRange, 151
HepMC::GenVertexParticleRange
    begin, 151
    end, 151
    GenVertexParticleRange, 151
HepMC::HeavyIon, 152
HepMC::HeavyIon
    ~HeavyIon, 154
    eccentricity, 155
    event_plane_angle, 155
    HeavyIon, 154
    impact_parameter, 155
    is_valid, 155
    N_Nwounded_collisions, 155
    Ncoll, 155
    Ncoll_hard, 155
    Npart_proj, 155

```

- Npart_targ, 156
- Nwounded_N_collisions, 156
- Nwounded_Nwounded_collisions, 156
- operator!=, 156
- operator=, 156
- operator==, 156
- set_eccentricity, 157
- set_event_plane_angle, 157
- set_impact_parameter, 157
- set_N_Nwounded_collisions, 157
- set_Ncoll, 157
- set_Ncoll_hard, 157
- set_Npart_proj, 157
- set_Npart_targ, 158
- set_Nwounded_N_collisions, 158
- set_Nwounded_Nwounded_collisions, 158
- set_sigma_inel_NN, 158
- set_spectator_neutrons, 158
- set_spectator_protons, 158
- sigma_inel_NN, 158
- spectator_neutrons, 159
- spectator_protons, 159
- swap, 159
- HepMC::HEPEVT_Wrapper, 160
- HepMC::HEPEVT_Wrapper
 - byte_num_to_double, 163
 - byte_num_to_int, 163
 - check_hepevt_consistency, 163
 - e, 163
 - event_number, 163
 - first_child, 164
 - first_parent, 164
 - id, 164
 - is_double_precision, 164
 - last_child, 164
 - last_parent, 165
 - m, 165
 - max_number_entries, 165
 - number_children, 165
 - number_entries, 165
 - number_parents, 166
 - print_hepevt, 166
 - print_hepevt_particle, 166
 - print_legend, 166
 - px, 166
 - py, 167
 - pz, 167
 - set_children, 167
 - set_event_number, 167
 - set_id, 167
 - set_mass, 168
 - set_max_number_entries, 168
 - set_momentum, 168
 - set_number_entries, 168
 - set_parents, 169
 - set_position, 169
 - set_sizeof_int, 169
 - set_sizeof_real, 169
 - set_status, 169
 - sizeof_int, 170
 - sizeof_real, 170
 - status, 170
 - t, 170
 - write_byte_num, 170
 - x, 171
 - y, 171
 - z, 171
 - zero_everything, 171
- HepMC::IO_AsciiParticles, 176
- HepMC::IO_AsciiParticles
 - ~IO_AsciiParticles, 177
 - clear, 177
 - fill_next_event, 177
 - IO_AsciiParticles, 177
 - print, 177
 - rdstate, 177
 - setPrecision, 178
 - write_comment, 178
 - write_end_listing, 178
 - write_event, 178
- HepMC::IO_BaseClass, 179
- HepMC::IO_BaseClass
 - ~IO_BaseClass, 180
 - fill_next_event, 180
 - operator<<, 180
 - operator>>, 180
 - print, 180
 - read_next_event, 180
 - write_event, 181
- HepMC::IO_Exception, 182
 - BadInputStream, 183
 - BadOutputStream, 183
 - EndKeyMismatch, 183
 - EndOfStream, 183
 - InputAndOutput, 183
 - InvalidData, 183
 - MissingEndKey, 183
 - MissingStartKey, 183
 - NullEvent, 183
 - OK, 183
 - WrongFileType, 183
- HepMC::IO_Exception
 - ErrorType, 183
 - IO_Exception, 183
- HepMC::IO_GenEvent, 184
- HepMC::IO_GenEvent

- ~IO_GenEvent, 185
- clear, 186
- error_message, 186
- error_type, 186
- fill_next_event, 186
- IO_GenEvent, 185
- precision, 186
- print, 186
- rdstate, 186
- use_input_units, 187
- write_comment, 187
- write_event, 187
- HepMC::IO_HEPEVT, 188
- HepMC::IO_HEPEVT
 - ~IO_HEPEVT, 189
 - build_end_vertex, 189
 - build_particle, 190
 - build_production_vertex, 190
 - fill_next_event, 190
 - find_in_map, 190
 - IO_HEPEVT, 189
 - print, 191
 - print_inconsistency_errors, 191
 - set_print_inconsistency_errors, 191
 - set_trust_beam_particles, 191
 - set_trust_both_mothers_and_daughters, 191
 - set_trust_mothers_before_daughters, 192
 - trust_beam_particles, 192
 - trust_both_mothers_and_daughters, 192
 - trust_mothers_before_daughters, 192
 - write_event, 192
- HepMC::IO_HERWIG, 193
- HepMC::IO_HERWIG
 - ~IO_HERWIG, 194
 - build_end_vertex, 195
 - build_particle, 195
 - build_production_vertex, 195
 - fill_next_event, 195
 - find_in_map, 196
 - interfaces_to_version_number, 196
 - IO_HERWIG, 194
 - no_gaps_in_barcodes, 196
 - print, 196
 - print_inconsistency_errors, 196
 - remove_gaps_in_hepevt, 196
 - repair_hepevt, 197
 - set_no_gaps_in_barcodes, 197
 - set_print_inconsistency_errors, 198
 - set_trust_both_mothers_and_daughters, 198
 - set_trust_mothers_before_daughters, 198
 - translate_herwig_to_pdg_id, 198
 - trust_both_mothers_and_daughters, 198
 - trust_mothers_before_daughters, 198
 - zero_hepevt_entry, 198
- HepMC::PdfInfo, 220
- HepMC::PdfInfo
 - ~PdfInfo, 222
 - id1, 223
 - id2, 223
 - is_valid, 223
 - operator!=, 223
 - operator=, 223
 - operator==, 223
 - pdf1, 223
 - pdf2, 224
 - pdf_id1, 224
 - pdf_id2, 224
 - PdfInfo, 222
 - scalePDF, 224
 - set_id1, 224
 - set_id2, 224
 - set_pdf1, 224
 - set_pdf2, 224
 - set_pdf_id1, 225
 - set_pdf_id2, 225
 - set_scalePDF, 225
 - set_x1, 225
 - set_x2, 225
 - swap, 225
 - x1, 225
 - x2, 226
- HepMC::Polarization, 232
- HepMC::Polarization
 - ~Polarization, 234
 - is_defined, 234
 - normal3d, 234
 - operator!=, 234
 - operator<<, 236
 - operator=, 234
 - operator==, 234
 - phi, 234
 - Polarization, 233
 - print, 235
 - set_normal3d, 235
 - set_phi, 235
 - set_theta, 235

- set_theta_phi, 235
- set_undefined, 235
- swap, 236
- theta, 236
- HepMC::StreamInfo, 245
- HepMC::StreamInfo
 - ~StreamInfo, 246
 - finished_first_event, 246
 - has_key, 247
 - IO_Ascii_End, 247
 - IO_Ascii_Key, 247
 - IO_Ascii_PDT_End, 247
 - IO_Ascii_PDT_Key, 247
 - IO_ExtendedAscii_End, 247
 - IO_ExtendedAscii_Key, 247
 - IO_ExtendedAscii_PDT_End, 247
 - IO_ExtendedAscii_PDT_Key, 248
 - IO_GenEvent_End, 248
 - IO_GenEvent_Key, 248
 - io_momentum_unit, 248
 - io_position_unit, 248
 - io_type, 248
 - reading_event_header, 248
 - set_finished_first_event, 249
 - set_has_key, 249
 - set_io_type, 249
 - set_reading_event_header, 249
 - stream_id, 249
 - StreamInfo, 246
 - use_input_units, 249
- HepMC::TempParticleMap, 251
- HepMC::TempParticleMap
 - ~TempParticleMap, 252
 - addEndParticle, 252
 - begin, 252
 - end, 252
 - end_vertex, 252
 - order_begin, 252
 - order_end, 252
 - orderIterator, 251
 - TempMap, 251
 - TempMapIterator, 251
 - TempOrderMap, 251
 - TempParticleMap, 252
- HepMC::ThreeVector, 254
- HepMC::ThreeVector
 - operator!=, 256
 - operator=, 256
 - operator==, 256
 - perp, 256
 - perp2, 256
 - phi, 256
 - r, 257
 - set, 257
 - setPhi, 257
 - setTheta, 257
 - setX, 257
 - setY, 258
 - setZ, 258
 - swap, 258
 - theta, 258
 - ThreeVector, 255, 256
 - x, 258
 - y, 259
 - z, 259
- HepMC::Units, 39
 - CM, 39
 - GEV, 39
 - MEV, 39
 - MM, 39
- HepMC::Units
 - conversion_factor, 40
 - default_length_unit, 40
 - default_momentum_unit, 40
 - LengthUnit, 39
 - MomentumUnit, 39
 - name, 40
- HepMC::WeightContainer, 260
- HepMC::WeightContainer
 - ~WeightContainer, 263
 - back, 263
 - begin, 263
 - clear, 263
 - const_iterator, 262
 - empty, 263
 - end, 264
 - front, 264
 - GenEvent, 266
 - has_key, 264
 - iterator, 262
 - operator!=, 264
 - operator=, 264
 - operator==, 265
 - operator[], 265
 - pop_back, 265
 - print, 265
 - push_back, 266
 - size, 266
 - size_type, 262
 - swap, 266
 - WeightContainer, 262, 263
 - write, 266
- HepMC_pi
 - HepMC, 34
- hepmc_uint64_t
 - GenParticle.h, 291
- HEPMC_VERSION
 - HepMCDefs.h, 301

HepMCDefs.h, 301
HepMCDefs.h
 HEPMC_VERSION, 301
HepMCStreamCallback
 HepMC, 33
herwig_hepevt_size
 HerwigWrapper.h, 312
HerwigWrapper.cc, 302
HerwigWrapper.cc
 hwevnt_, 302
HerwigWrapper.h, 303
HerwigWrapper.h
 AFCH, 309
 ALPHEM, 309
 AZSOFT, 309
 AZSPIN, 309
 B1LIM, 310
 BETAF, 310
 BTCLM, 310
 CAFAC, 310
 CFFAC, 310
 CLDIR, 310
 CLMAX, 310
 CLPOW, 310
 CLSMR, 310
 CSPEED, 310
 EBEAM1, 310
 EBEAM2, 310
 EFFMIN, 311
 ENSOF, 311
 ET2MIX, 311
 ETAMIX, 311
 F0MIX, 311
 F1MIX, 311
 F2MIX, 311
 GAMH, 311
 GAMW, 311
 GAMZ, 311
 GAMZP, 311
 GCUTME, 311
 GEV2NB, 312
 H1MIX, 312
 HARDME, 312
 herwig_hepevt_size, 312
 hwbeam, 305
 hwbeam_, 312
 hwbgen, 305
 hwbmch, 306
 hwbmch_, 312
 hwcdec, 306
 hwcfor, 306
 hwdhad, 306
 hwdhob, 306
 hwdhvy, 307
 hwefin, 307
 hwegup, 307
 hweini, 307
 hwepro, 307
 hwevnt, 307
 hwevnt_, 312
 hwigin, 307
 hwigup, 308
 hwmevt, 308
 hwpram, 308
 hwpram_, 312
 hwproc, 308
 hwproc_, 312
 hwudat, 308
 hwudpr, 308
 hwuepr, 308
 hwufne, 308
 hwuinc, 309
 hwuine, 309
 hwupro, 309
 hwupup, 309
 hwusta, 309
 IOP4JT, 312
 IOPREM, 312
 IPART1, 312
 IPART2, 312
 IPRINT, 312
 IPROC, 313
 ISPAC, 313
 LRSUD, 313
 LWSUD, 313
 MAXEV, 313
 MODPDF, 313
 NBTRY, 313
 NCOLO, 313
 NCTRY, 313
 NDTRY, 313
 NETRY, 313
 NFLAV, 313
 NGSPL, 314
 NOSPAC, 314
 NPRFMT, 314
 NSTRU, 314
 NSTRY, 314
 NZBIN, 314
 OMHMIX, 314
 PART1, 314
 PART2, 314
 PBEAM1, 314
 PBEAM2, 314
 PDIQK, 314
 PGSMX, 315
 PGSPL, 315
 PH3MIX, 315

- PHIMIX, 315
- PIFAC, 315
- PRNDEC, 315
- PRNDEF, 315
- PRNTEX, 315
- PRNWEB, 315
- PRSOF, 315
- PRVTX, 315
- PSPLT, 315
- PTRMS, 316
- PXRMS, 316
- QCDL3, 316
- QCDL5, 316
- QCDLAM, 316
- QDIQK, 316
- QFCH, 316
- QG, 316
- QSPAC, 316
- QV, 316
- SCABI, 316
- SOFTME, 316
- SWEIN, 317
- TMTOP, 317
- VCKM, 317
- VFCH, 317
- VGCUT, 317
- VPCUT, 317
- VQCUT, 317
- ZBINM, 317
- ZPRIME, 317
- hwbeam
 - HerwigWrapper.h, 305
- hwbeam_
 - HerwigWrapper.h, 312
- hwbgen
 - HerwigWrapper.h, 305
- hwbmch
 - HerwigWrapper.h, 306
- hwbmch_
 - HerwigWrapper.h, 312
- hwcdec
 - HerwigWrapper.h, 306
- hwcfor
 - HerwigWrapper.h, 306
- hwdhad
 - HerwigWrapper.h, 306
- hwdhob
 - HerwigWrapper.h, 306
- hwdhvy
 - HerwigWrapper.h, 307
- hwefin
 - HerwigWrapper.h, 307
- hwegup
 - HerwigWrapper.h, 307
- hweini
 - HerwigWrapper.h, 307
- hwepro
 - HerwigWrapper.h, 307
- hwevnt
 - HerwigWrapper.h, 307
- hwevnt_
 - HerwigWrapper.cc, 302
 - HerwigWrapper.h, 312
- hwgev, 173
 - AVWGT, 173
 - EVWGT, 173
 - GAMWT, 173
 - GENSOF, 173
 - IDHW, 173
 - IERROR, 174
 - ISTAT, 174
 - LWEVT, 174
 - MAXER, 174
 - MAXPR, 174
 - NOWGT, 174
 - NRN, 174
 - NUMER, 174
 - NUMERU, 174
 - NWGTIS, 174
 - TLOUT, 174
 - WBGST, 175
 - WGTMAX, 175
 - WGTSUM, 175
 - WSQSUM, 175
- hwigin
 - HerwigWrapper.h, 307
- hwigup
 - HerwigWrapper.h, 308
- hwmevt
 - HerwigWrapper.h, 308
- hwpram
 - HerwigWrapper.h, 308
- hwpram_
 - HerwigWrapper.h, 312
- hwproc
 - HerwigWrapper.h, 308
- hwproc_
 - HerwigWrapper.h, 312
- hwudat
 - HerwigWrapper.h, 308
- hwudpr
 - HerwigWrapper.h, 308
- hwuepr
 - HerwigWrapper.h, 308
- hwufne
 - HerwigWrapper.h, 308
- hwuinc
 - HerwigWrapper.h, 309

- hwuine
 - HerwigWrapper.h, 309
- hwupro
 - HerwigWrapper.h, 309
- hwupup
 - HerwigWrapper.h, 309
- hwusta
 - HerwigWrapper.h, 309
- icode
 - HepMC::Flow, 56
- icol
 - PythiaWrapper6_4.h, 348
- id
 - HepMC::GenVertex, 132
 - HepMC::HEPEVT_Wrapper, 164
- id1
 - HepMC::PdfInfo, 223
- id2
 - HepMC::PdfInfo, 223
- IDHW
 - hwgev, 173
- idr
 - prvnv, 241
- idr2
 - prvnv, 241
- IERROR
 - hwgev, 174
- impact_parameter
 - HepMC::HeavyIon, 155
- imss
 - pssm, 244
- initpydata
 - PythiaWrapper6_4.h, 345, 348
- initPythia
 - initPythia.cc, 318
 - PythiaHelper.h, 338
- initPythia.cc, 318
- initPythia.cc
 - initPythia, 318
- InputAndOutput
 - HepMC::IO_Exception, 183
- interfaces_to_version_number
 - HepMC::IO_HERWIG, 196
- InvalidData
 - HepMC::IO_Exception, 183
- IO_Ascii_End
 - HepMC::StreamInfo, 247
- IO_Ascii_Key
 - HepMC::StreamInfo, 247
- IO_Ascii_PDT_End
 - HepMC::StreamInfo, 247
- IO_Ascii_PDT_Key
 - HepMC::StreamInfo, 247
- IO_AsciiParticles
 - HepMC::IO_AsciiParticles, 177
- IO_AsciiParticles.cc, 319
- IO_AsciiParticles.h, 320
- IO_BaseClass.h, 321
- IO_Exception
 - HepMC::IO_Exception, 183
- IO_Exception.h, 322
- IO_ExtendedAscii_End
 - HepMC::StreamInfo, 247
- IO_ExtendedAscii_Key
 - HepMC::StreamInfo, 247
- IO_ExtendedAscii_PDT_End
 - HepMC::StreamInfo, 247
- IO_ExtendedAscii_PDT_Key
 - HepMC::StreamInfo, 248
- IO_GenEvent
 - HepMC::IO_GenEvent, 185
- IO_GenEvent.cc, 323
- IO_GenEvent.h, 324
- IO_GenEvent_End
 - HepMC::StreamInfo, 248
- IO_GenEvent_Key
 - HepMC::StreamInfo, 248
- IO_HEPEVT
 - HepMC::IO_HEPEVT, 189
- IO_HEPEVT.cc, 325
- IO_HEPEVT.h, 326
- IO_HERWIG
 - HepMC::IO_HERWIG, 194
- IO_HERWIG.cc, 327
- IO_HERWIG.h, 328
- io_momentum_unit
 - HepMC::StreamInfo, 248
- io_position_unit
 - HepMC::StreamInfo, 248
- io_type
 - HepMC::StreamInfo, 248
- IOP4JT
 - HerwigWrapper.h, 312
- IOPREM
 - HerwigWrapper.h, 312
- IPART1
 - HerwigWrapper.h, 312
- IPART2
 - HerwigWrapper.h, 312
- IPRINT
 - HerwigWrapper.h, 312
- IPROC
 - HerwigWrapper.h, 313
- is_arithmetic.h, 329
- is_beam
 - HepMC::GenParticle, 116
- is_child

- HepMC::GenVertex::edge_iterator, 142
- is_defined
 - HepMC::Polarization, 234
- is_double_precision
 - HepMC::HEPEVT_Wrapper, 164
- is_parent
 - HepMC::GenVertex::edge_iterator, 142
- is_set
 - HepMC::GenCrossSection, 71
- is_undecayed
 - HepMC::GenParticle, 116
- is_valid
 - HepMC::GenEvent, 83
 - HepMC::HeavyIon, 155
 - HepMC::PdfInfo, 223
- iset
 - PythiaWrapper6_4.h, 348
- IsEventGood, 213
- IsEventGood
 - operator(), 213
- IsFinalState, 214
- IsFinalState
 - operator(), 214
- IsGoodEvent, 215
- IsGoodEvent
 - operator(), 215
- IsGoodEvent.h, 330
- IsGoodEventMyPythia, 216
- IsGoodEventMyPythia
 - operator(), 216
- isig
 - pin3, 227
- ISPAC
 - HerwigWrapper.h, 313
- IsPhoton, 217
 - testHepMCIteration.h, 365
- IsPhoton
 - operator(), 217
- IsStateFinal, 218
- IsStateFinal
 - operator(), 218
- ISTAT
 - hwgev, 174
- IsW_Boson, 219
- IsW_Boson
 - operator(), 219
- IsWBoson
 - testHepMCIteration.h, 365
- iterator
 - HepMC::Flow, 54
 - HepMC::WeightContainer, 262
- IteratorRange
 - HepMC, 27
- IteratorRange.h, 331
- k
 - PythiaWrapper6_4.h, 348
- kchg
 - PythiaWrapper6_4.h, 348
- kfdp
 - PythiaWrapper6_4.h, 348
- kfin
 - PythiaWrapper6_4.h, 348
- kfpr
 - PythiaWrapper6_4.h, 348
- kfr
 - prvvnv, 241
- known_io
 - HepMC, 27
- last_child
 - HepMC::HEPEVT_Wrapper, 164
- last_parent
 - HepMC::HEPEVT_Wrapper, 165
- length_unit
 - HepMC::GenEvent, 83
- LengthUnit
 - HepMC::Units, 39
- list_of_examples.cc, 332, 333
- LRSUD
 - HerwigWrapper.h, 313
- LWEVT
 - hwgev, 174
- LWSUD
 - HerwigWrapper.h, 313
- m
 - HepMC::FourVector, 62
 - HepMC::HEPEVT_Wrapper, 165
- m2
 - HepMC::FourVector, 62
- m_map_iterator
 - HepMC::GenEvent::particle_const_iterator, 98
 - HepMC::GenEvent::particle_iterator, 101
 - HepMC::GenEvent::vertex_const_iterator, 104
 - HepMC::GenEvent::vertex_iterator, 107
- main
 - example_BuildEventFromScratch.cc, 270
 - example_EventSelection.cc, 271
 - example_MyHerwig.cc, 272
 - example_MyPythia.cc, 273

- example_MyPythiaOnlyToHepMC.cc, 276
- example_PythiaStreamIO.cc, 277
- example_UsingIterators.cc, 279
- testFlow.cc, 364
- testHerwigCopies.cc, 368
- testPolarization.cc, 369
- testPrintBug.cc, 370
- testPythiaCopies.cc, 371
- testSimpleVector.cc, 372
- testUnits.cc, 373
- testWeights.cc, 374
- max_number_entries
 - HepMC::HEPEVT_Wrapper, 165
- MAXER
 - hwgev, 174
- MAXEV
 - HerwigWrapper.h, 313
- MAXPR
 - hwgev, 174
- mdcy
 - PythiaWrapper6_4.h, 348
- mdme
 - PythiaWrapper6_4.h, 349
- MEV
 - HepMC::Units, 39
- mflag
 - prvpm, 243
- mint
 - PythiaWrapper6_4.h, 349
- MissingEndKey
 - HepMC::IO_Exception, 183
- MissingStartKey
 - HepMC::IO_Exception, 183
- MM
 - HepMC::Units, 39
- MODPDF
 - HerwigWrapper.h, 313
- momentum
 - HepMC::GenParticle, 116
- momentum_unit
 - HepMC::GenEvent, 83
- MomentumUnit
 - HepMC::Units, 39
- mpi
 - HepMC::GenEvent, 83
- mrpy
 - PythiaWrapper6_4.h, 349
- msel
 - PythiaWrapper6_4.h, 349
- mselpd
 - PythiaWrapper6_4.h, 349
- msti
 - PythiaWrapper6_4.h, 349
- mstj
 - PythiaWrapper6_4.h, 349
- mstp
 - PythiaWrapper6_4.h, 349
- mstu
 - PythiaWrapper6_4.h, 349
- msub
 - PythiaWrapper6_4.h, 349
- mwid
 - PythiaWrapper6_4.h, 349
- n
 - PythiaWrapper6_4.h, 349
- N_Nwounded_collisions
 - HepMC::HeavyIon, 155
- name
 - HepMC::Units, 40
- NBTRY
 - HerwigWrapper.h, 313
- Ncoll
 - HepMC::HeavyIon, 155
- Ncoll_hard
 - HepMC::HeavyIon, 155
- NCOLO
 - HerwigWrapper.h, 313
- NCTRY
 - HerwigWrapper.h, 313
- NDTRY
 - HerwigWrapper.h, 313
- NETRY
 - HerwigWrapper.h, 313
- NFLAV
 - HerwigWrapper.h, 313
- ngen
 - pin5, 228
- ngenpd
 - pin5, 228
- NGSPL
 - HerwigWrapper.h, 314
- no_gaps_in_barcodes
 - HepMC::IO_HERWIG, 196
- normal3d
 - HepMC::Polarization, 234
- NOSPAC
 - HerwigWrapper.h, 314
- not_in_vector
 - HepMC, 32
- NOWGT
 - hwgev, 174
- npad
 - PythiaWrapper6_4.h, 350
- Npart_proj
 - HepMC::HeavyIon, 155
- Npart_targ

- HepMC::HeavyIon, 156
- NPRFMT
 - HerwigWrapper.h, 314
- NRN
 - hwgev, 174
- NSTRU
 - HerwigWrapper.h, 314
- NSTRY
 - HerwigWrapper.h, 314
- NullEvent
 - HepMC::IO_Exception, 183
- number_children
 - HepMC::HEPEVT_Wrapper, 165
- number_entries
 - HepMC::HEPEVT_Wrapper, 165
- number_parents
 - HepMC::HEPEVT_Wrapper, 166
- NUMER
 - hwgev, 174
- NUMERU
 - hwgev, 174
- NWGTS
 - hwgev, 174
- Nwounded_N_collisions
 - HepMC::HeavyIon, 156
- Nwounded_Nwounded_collisions
 - HepMC::HeavyIon, 156
- NZBIN
 - HerwigWrapper.h, 314
- OK
 - HepMC::IO_Exception, 183
- OMHMX
 - HerwigWrapper.h, 314
- operator *
 - HepMC::GenEvent::particle_
const_iterator, 97
 - HepMC::GenEvent::particle_
iterator, 100
 - HepMC::GenEvent::vertex_const_
iterator, 103
 - HepMC::GenEvent::vertex_
iterator, 106
 - HepMC::GenVertex::edge_
iterator, 142
 - HepMC::GenVertex::particle_
iterator, 145
 - HepMC::GenVertex::vertex_
iterator, 149
- operator HepMC::FourVector
 - HepMC::GenParticle, 116
 - HepMC::GenVertex, 133
- operator HepMC::ThreeVector
 - HepMC::GenVertex, 133
- operator particle_const_iterator
 - HepMC::GenEvent::particle_
iterator, 100
- operator vertex_const_iterator
 - HepMC::GenEvent::vertex_
iterator, 106
- operator!=
 - HepMC::Flow, 56
 - HepMC::FourVector, 62
 - HepMC::GenCrossSection, 71
 - HepMC::GenEvent::particle_
const_iterator, 97
 - HepMC::GenEvent::particle_
iterator, 100
 - HepMC::GenEvent::vertex_const_
iterator, 103
 - HepMC::GenEvent::vertex_
iterator, 107
 - HepMC::GenParticle, 116
 - HepMC::GenVertex, 133
 - HepMC::GenVertex::edge_
iterator, 142
 - HepMC::GenVertex::particle_
iterator, 145
 - HepMC::GenVertex::vertex_
iterator, 149
 - HepMC::HeavyIon, 156
 - HepMC::PdfInfo, 223
 - HepMC::Polarization, 234
 - HepMC::ThreeVector, 256
 - HepMC::WeightContainer, 264
- operator()
 - IsEventGood, 213
 - IsFinalState, 214
 - IsGoodEvent, 215
 - IsGoodEventMyPythia, 216
 - IsPhoton, 217
 - IsStateFinal, 218
 - IsW_Boson, 219
 - PrintChildren, 237
 - PrintDescendants, 238
 - PrintParticle, 239
 - PrintPhoton, 240
- operator++
 - HepMC::GenEvent::particle_
const_iterator, 97, 98
 - HepMC::GenEvent::particle_
iterator, 101
 - HepMC::GenEvent::vertex_const_
iterator, 103
 - HepMC::GenEvent::vertex_
iterator, 107
 - HepMC::GenVertex::edge_
iterator, 143

```

HepMC::GenVertex::particle_
    iterator, 146
HepMC::GenVertex::vertex_
    iterator, 149, 150
operator<<
    HepMC, 29, 31, 33, 34
    HepMC::Flow, 58
    HepMC::GenParticle, 121
    HepMC::GenVertex, 139
    HepMC::IO_BaseClass, 180
    HepMC::Polarization, 236
operator=
    HepMC::Flow, 56
    HepMC::FourVector, 63
    HepMC::GenCrossSection, 71
    HepMC::GenEvent, 83
    HepMC::GenEvent::particle_
        const_iterator, 98
    HepMC::GenEvent::particle_
        iterator, 101
    HepMC::GenEvent::vertex_const_
        iterator, 104
    HepMC::GenEvent::vertex_
        iterator, 107
    HepMC::GenParticle, 116
    HepMC::GenVertex, 133
    HepMC::GenVertex::edge_
        iterator, 143
    HepMC::GenVertex::particle_
        iterator, 146
    HepMC::GenVertex::vertex_
        iterator, 150
    HepMC::HeavyIon, 156
    HepMC::PdfInfo, 223
    HepMC::Polarization, 234
    HepMC::ThreeVector, 256
    HepMC::WeightContainer, 264
operator==
    HepMC::Flow, 57
    HepMC::FourVector, 63
    HepMC::GenCrossSection, 71
    HepMC::GenEvent::particle_
        const_iterator, 98
    HepMC::GenEvent::particle_
        iterator, 101
    HepMC::GenEvent::vertex_const_
        iterator, 104
    HepMC::GenEvent::vertex_
        iterator, 107
    HepMC::GenParticle, 117
    HepMC::GenVertex, 133
    HepMC::GenVertex::edge_
        iterator, 143
    HepMC::GenVertex::particle_
        iterator, 146
    HepMC::GenVertex::vertex_
        iterator, 150
    HepMC::HeavyIon, 156
    HepMC::PdfInfo, 223
    HepMC::Polarization, 234
    HepMC::ThreeVector, 256
    HepMC::WeightContainer, 265
operator[]
    HepMC::WeightContainer, 265
order_begin
    HepMC::TempParticleMap, 252
order_end
    HepMC::TempParticleMap, 252
orderIterator
    HepMC::TempParticleMap, 251
output
    HepMC::detail, 37, 38

p
    PythiaWrapper6_4.h, 350
parent_event
    HepMC::GenParticle, 117
    HepMC::GenVertex, 134
parents
    HepMC, 27
parf
    PythiaWrapper6_4.h, 350
pari
    PythiaWrapper6_4.h, 350
parj
    PythiaWrapper6_4.h, 350
parp
    PythiaWrapper6_4.h, 350
PART1
    HerwigWrapper.h, 314
PART2
    HerwigWrapper.h, 314
particle_const_iterator
    HepMC::GenEvent, 94
    HepMC::GenEvent::particle_
        const_iterator, 97
particle_iterator
    HepMC::GenEvent, 94
    HepMC::GenEvent::particle_
        iterator, 100
    HepMC::GenVertex, 140
    HepMC::GenVertex::particle_
        iterator, 145
particle_owner

```

- HepMC::Flow, 57
- particle_range
 - HepMC::GenEvent, 84
- particles
 - HepMC::GenVertex, 134
- particles_begin
 - HepMC::GenEvent, 84
 - HepMC::GenVertex, 134
- particles_empty
 - HepMC::GenEvent, 84
- particles_end
 - HepMC::GenEvent, 84, 85
 - HepMC::GenVertex, 134
- particles_in
 - HepMC::GenParticle, 117
 - HepMC::GenVertex, 134, 135
- particles_in_const_begin
 - HepMC::GenVertex, 135
- particles_in_const_end
 - HepMC::GenVertex, 135
- particles_in_const_iterator
 - HepMC::GenVertex, 130
- particles_in_size
 - HepMC::GenVertex, 135
- particles_out
 - HepMC::GenParticle, 117
 - HepMC::GenVertex, 135
- particles_out_const_begin
 - HepMC::GenVertex, 136
- particles_out_const_end
 - HepMC::GenVertex, 136
- particles_out_const_iterator
 - HepMC::GenVertex, 130
- particles_out_size
 - HepMC::GenVertex, 136
- particles_size
 - HepMC::GenEvent, 85
- particleTypes
 - testHepMCMethods.cc, 366
 - testHepMCMethods.h, 367
- paru
 - PythiaWrapper6_4.h, 351
- PBEAM1
 - HerwigWrapper.h, 314
- PBEAM2
 - HerwigWrapper.h, 314
- pdf1
 - HepMC::PdfInfo, 223
- pdf2
 - HepMC::PdfInfo, 224
- pdf_id1
 - HepMC::PdfInfo, 224
- pdf_id2
 - HepMC::PdfInfo, 224
- pdf_info
 - HepMC::GenEvent, 85
- PdfInfo
 - HepMC::PdfInfo, 222
- PdfInfo.cc, 334
- PdfInfo.h, 335
- pdg_id
 - HepMC::GenParticle, 117
- PDIQK
 - HerwigWrapper.h, 314
- perp
 - HepMC::FourVector, 63
 - HepMC::ThreeVector, 256
- perp2
 - HepMC::FourVector, 63
 - HepMC::ThreeVector, 256
- PGSMX
 - HerwigWrapper.h, 315
- PGSPL
 - HerwigWrapper.h, 315
- PH3MIX
 - HerwigWrapper.h, 315
- phi
 - HepMC::FourVector, 63
 - HepMC::Polarization, 234
 - HepMC::ThreeVector, 256
- PHIMIX
 - HerwigWrapper.h, 315
- PIFAC
 - HerwigWrapper.h, 315
- pin3, 227
 - isig, 227
 - sigh, 227
 - xsfx, 227
- pin5, 228
 - ngen, 228
 - ngenpd, 228
 - xsec, 228
- pin7, 229
 - sigt, 229
- pin8, 230
 - xpanh, 230
 - xpanl, 230
 - xpbeh, 230
 - xpdir, 230
 - xpvmd, 230
- pin9, 231
 - vxpanh, 231
 - vxpanl, 231
 - vxpdbg, 231
 - xpvmd, 231
- pmas
 - PythiaWrapper6_4.h, 351
- point3d

HepMC::GenVertex, 136
 Polarization
 HepMC::Polarization, 233
 polarization
 HepMC::GenParticle, 118
 Polarization.cc, 336
 Polarization.h, 337
 pop_back
 HepMC::WeightContainer, 265
 position
 HepMC::GenVertex, 136
 precision
 HepMC::IO_GenEvent, 186
 print
 HepMC::Flow, 57
 HepMC::GenEvent, 85
 HepMC::GenParticle, 118
 HepMC::GenVertex, 136
 HepMC::IO_AsciiParticles, 177
 HepMC::IO_BaseClass, 180
 HepMC::IO_GenEvent, 186
 HepMC::IO_HEPEVT, 191
 HepMC::IO_HERWIG, 196
 HepMC::Polarization, 235
 HepMC::WeightContainer, 265
 print_hepevt
 HepMC::HEPEVT_Wrapper, 166
 print_hepevt_particle
 HepMC::HEPEVT_Wrapper, 166
 print_inconsistency_errors
 HepMC::IO_HEPEVT, 191
 HepMC::IO_HERWIG, 196
 print_legend
 HepMC::HEPEVT_Wrapper, 166
 print_version
 HepMC::GenEvent, 86
 PrintChildren, 237
 PrintChildren, 237
 PrintChildren
 operator(), 237
 PrintChildren, 237
 PrintDescendants, 238
 PrintDescendants, 238
 PrintDescendants
 operator(), 238
 PrintDescendants, 238
 PrintParticle, 239
 PrintParticle, 239
 PrintParticle
 operator(), 239
 PrintParticle, 239
 PrintPhoton, 240
 PrintPhoton, 240
 PrintPhoton
 operator(), 240
 PrintPhoton, 240
 PRNDEC
 HerwigWrapper.h, 315
 PRNDEF
 HerwigWrapper.h, 315
 PRNTEX
 HerwigWrapper.h, 315
 PRNWEB
 HerwigWrapper.h, 315
 production_vertex
 HepMC::GenParticle, 118
 PRSOF
 HerwigWrapper.h, 315
 prvnv, 241
 ab, 241
 dcmass, 241
 idr, 241
 idr2, 241
 kfr, 241
 res, 241
 rms, 241
 prvpm, 243
 a, 243
 b, 243
 mflag, 243
 resm, 243
 resw, 243
 rm, 243
 PRVTX
 HerwigWrapper.h, 315
 pseudoRapidity
 HepMC::FourVector, 63
 PSPLT
 HerwigWrapper.h, 315
 pssm, 244
 imss, 244
 rmss, 244
 PTRMS
 HerwigWrapper.h, 316
 push_back
 HepMC::WeightContainer, 266
 px
 HepMC::FourVector, 63
 HepMC::HEPEVT_Wrapper, 166
 PXRMS
 HerwigWrapper.h, 316
 py
 HepMC::FourVector, 64
 HepMC::HEPEVT_Wrapper, 167
 pydat1
 PythiaWrapper6_4.h, 345
 pydat1_
 PythiaWrapper6_4.h, 351

pydat2
 PythiaWrapper6_4.h, 345
 pydat2_
 PythiaWrapper6_4.h, 351
 pydat3
 PythiaWrapper6_4.h, 345
 pydat3_
 PythiaWrapper6_4.h, 351
 pydata
 PythiaWrapper6_4.h, 345
 pydatr
 PythiaWrapper6_4.h, 345
 pydatr_
 PythiaWrapper6_4.h, 351
 pyevnt
 PythiaWrapper6_4.h, 345
 pyg2dx
 PythiaWrapper6_4.h, 345
 pyg2dx_
 PythiaWrapper6_4.h, 351
 pyhepc
 PythiaWrapper6_4.h, 345
 pyinit
 PythiaWrapper6_4.h, 345
 pyint1
 PythiaWrapper6_4.h, 345
 pyint1_
 PythiaWrapper6_4.h, 351
 pyint2
 PythiaWrapper6_4.h, 345
 pyint2_
 PythiaWrapper6_4.h, 351
 pyint3
 PythiaWrapper6_4.h, 346
 pyint3_
 PythiaWrapper.cc, 339
 PythiaWrapper6_4.h, 351
 pyint4
 PythiaWrapper6_4.h, 346
 pyint4_
 PythiaWrapper6_4.h, 351
 pyint5
 PythiaWrapper6_4.h, 346
 pyint5_
 PythiaWrapper.cc, 339
 PythiaWrapper6_4.h, 351
 pyint7
 PythiaWrapper6_4.h, 346
 pyint7_
 PythiaWrapper.cc, 339
 PythiaWrapper6_4.h, 351
 pyint8
 PythiaWrapper6_4.h, 346
 pyint8_
 PythiaWrapper.cc, 339
 PythiaWrapper6_4.h, 351
 pyint9
 PythiaWrapper6_4.h, 346
 pyint9_
 PythiaWrapper.cc, 339
 PythiaWrapper6_4.h, 351
 pyints
 PythiaWrapper6_4.h, 346
 pyints_
 PythiaWrapper6_4.h, 351
 pyjets
 PythiaWrapper6_4.h, 346
 pyjets_
 PythiaWrapper6_4.h, 351
 pyjets_maxn
 PythiaWrapper6_4.h, 351
 pylist
 PythiaWrapper6_4.h, 346
 pymsrv
 PythiaWrapper6_4.h, 346
 pymsrv_
 PythiaWrapper6_4.h, 351
 pypars
 PythiaWrapper6_4.h, 346
 pypars_
 PythiaWrapper6_4.h, 352
 pyrvnv
 PythiaWrapper6_4.h, 347
 pyrvnv_
 PythiaWrapper.cc, 340
 PythiaWrapper6_4.h, 352
 pyrvpm
 PythiaWrapper6_4.h, 347
 pyrvpm_
 PythiaWrapper.cc, 340
 PythiaWrapper6_4.h, 352
 pyssm
 PythiaWrapper6_4.h, 347
 pyssm_
 PythiaWrapper.cc, 340
 PythiaWrapper6_4.h, 352
 pyssmt
 PythiaWrapper6_4.h, 347
 pyssmt_
 PythiaWrapper6_4.h, 352
 pystat
 PythiaWrapper6_4.h, 347
 pysubs
 PythiaWrapper6_4.h, 347
 pysubs_
 PythiaWrapper6_4.h, 352
 pythia_in
 example_MyPythia.cc, 273

pythia_in_out
 example_MyPythia.cc, 274
pythia_out
 example_MyPythia.cc, 274
pythia_particle_out
 example_MyPythia.cc, 274
PythiaHelper.h, 338
PythiaHelper.h
 initPythia, 338
PythiaWrapper.cc, 339
PythiaWrapper.cc
 pyint3_, 339
 pyint5_, 339
 pyint7_, 339
 pyint8_, 339
 pyint9_, 339
 pyrvnv_, 340
 pyrvpm_, 340
 pyssm_, 340
PythiaWrapper.h, 341
PythiaWrapper6_4.h, 342
PythiaWrapper6_4.h
 brat, 348
 ckin, 348
 coef, 348
 icol, 348
 initpydata, 345, 348
 iset, 348
 k, 348
 kchg, 348
 kfdp, 348
 kfin, 348
 kfpr, 348
 mdcy, 348
 mdme, 349
 mint, 349
 mrpy, 349
 msel, 349
 mselpd, 349
 msti, 349
 mstj, 349
 mstp, 349
 mstu, 349
 msub, 349
 mwid, 349
 n, 349
 npad, 350
 p, 350
 parf, 350
 pari, 350
 parj, 350
 parp, 350
 paru, 351
 pmas, 351
 pydat1, 345
 pydat1_, 351
 pydat2, 345
 pydat2_, 351
 pydat3, 345
 pydat3_, 351
 pydata, 345
 pydatr, 345
 pydatr_, 351
 pyevnt, 345
 pyg2dx, 345
 pyg2dx_, 351
 pyhepc, 345
 pyinit, 345
 pyint1, 345
 pyint1_, 351
 pyint2, 345
 pyint2_, 351
 pyint3, 346
 pyint3_, 351
 pyint4, 346
 pyint4_, 351
 pyint5, 346
 pyint5_, 351
 pyint7, 346
 pyint7_, 351
 pyint8, 346
 pyint8_, 351
 pyint9, 346
 pyint9_, 351
 pyints, 346
 pyints_, 351
 pyjets, 346
 pyjets_, 351
 pyjets_maxn, 351
 pylist, 346
 pysrv, 346
 pysrv_, 351
 pypars, 346
 pypars_, 352
 pyrvnv, 347
 pyrvnv_, 352
 pyrvpm, 347
 pyrvpm_, 352
 pyssm, 347
 pyssm_, 352
 pyssmt, 347
 pyssmt_, 352
 pystat, 347
 pysubs, 347
 pysubs_, 352
 rrpy, 352
 rvlam, 352
 rvlamb, 352

- rvlamp, 352
- sfmix, 352
- smw, 352
- smz, 352
- umix, 352
- umixi, 352
- upevnt, 347
- upinit, 347
- v, 352
- vckm, 353
- vint, 353
- vmix, 353
- vmixi, 353
- wids, 353
- x1, 353
- xxm, 353
- zmix, 353
- zmixi, 353
- PythiaWrapper6_4_WIN32.h, 355
- pz
 - HepMC::FourVector, 64
 - HepMC::HEPEVT_Wrapper, 167
- QCDL3
 - HerwigWrapper.h, 316
- QCDL5
 - HerwigWrapper.h, 316
- QCDLAM
 - HerwigWrapper.h, 316
- QDIQK
 - HerwigWrapper.h, 316
- QFCH
 - HerwigWrapper.h, 316
- QG
 - HerwigWrapper.h, 316
- QSPAC
 - HerwigWrapper.h, 316
- QV
 - HerwigWrapper.h, 316
- r
 - HepMC::ThreeVector, 257
- random_states
 - HepMC::GenEvent, 86
- range
 - HepMC::GenVertex::vertex_
 - iterator, 150
- rdstate
 - HepMC::IO_AsciiParticles, 177
 - HepMC::IO_GenEvent, 186
- read
 - HepMC::GenCrossSection, 71
 - HepMC::GenEvent, 86
- read_next_event
 - HepMC::IO_BaseClass, 180
- read_particle
 - HepMC::detail, 37
- read_units
 - HepMC::detail, 38
- read_vertex
 - HepMC::detail, 37
- reading_event_header
 - HepMC::StreamInfo, 248
- readPythiaStreamIO
 - example_PythiaStreamIO.cc, 277
- relatives
 - HepMC, 27
- remove_barcode
 - HepMC::GenEvent, 86, 87
- remove_gaps_in_hepevt
 - HepMC::IO_HERWIG, 196
- remove_particle
 - HepMC::GenVertex, 137
- remove_particle_in
 - HepMC::GenVertex, 137
- remove_particle_out
 - HepMC::GenVertex, 137
- remove_vertex
 - HepMC::GenEvent, 87
- repair_hepevt
 - HepMC::IO_HERWIG, 197
- repairUnits
 - testHepMCMethods.cc, 366
 - testHepMCMethods.h, 367
- res
 - prvnv, 241
- resm
 - prvpm, 243
- resw
 - prvpm, 243
- rho
 - HepMC::FourVector, 64
- rm
 - prvpm, 243
- rms
 - prvnv, 241
- rmss
 - pssm, 244
- rrpy
 - PythiaWrapper6_4.h, 352
- rvlam
 - PythiaWrapper6_4.h, 352
- rvlamb
 - PythiaWrapper6_4.h, 352
- rvlamp
 - PythiaWrapper6_4.h, 352
- SCABI

HerwigWrapper.h, 316
scalePDF
 HepMC::PdfInfo, 224
SearchVector.cc, 356
SearchVector.h, 357
set
 HepMC::FourVector, 64
 HepMC::ThreeVector, 257
set_alphaQCD
 HepMC::GenEvent, 87
set_alphaQED
 HepMC::GenEvent, 87
set_barcode
 HepMC::GenEvent, 87
set_barcode_
 HepMC::GenParticle, 118
 HepMC::GenVertex, 137
set_beam_particles
 HepMC::GenEvent, 88
set_children
 HepMC::HEPEVT_Wrapper, 167
set_cross_section
 HepMC::GenCrossSection, 71
 HepMC::GenEvent, 88
set_cross_section_error
 HepMC::GenCrossSection, 72
set_eccentricity
 HepMC::HeavyIon, 157
set_end_vertex_
 HepMC::GenParticle, 118
set_event_number
 HepMC::GenEvent, 88
 HepMC::HEPEVT_Wrapper, 167
set_event_plane_angle
 HepMC::HeavyIon, 157
set_event_scale
 HepMC::GenEvent, 89
set_finished_first_event
 HepMC::StreamInfo, 249
set_flow
 HepMC::GenParticle, 119
set_generated_mass
 HepMC::GenParticle, 119
set_has_key
 HepMC::StreamInfo, 249
set_heavy_ion
 HepMC::GenEvent, 89
set_icode
 HepMC::Flow, 57
set_id
 HepMC::GenVertex, 138
 HepMC::HEPEVT_Wrapper, 167
set_id1
 HepMC::PdfInfo, 224
set_id2
 HepMC::PdfInfo, 224
set_impact_parameter
 HepMC::HeavyIon, 157
set_input_units
 HepMC, 30
set_io_type
 HepMC::StreamInfo, 249
set_mass
 HepMC::HEPEVT_Wrapper, 168
set_max_number_entries
 HepMC::HEPEVT_Wrapper, 168
set_momentum
 HepMC::GenParticle, 119
 HepMC::HEPEVT_Wrapper, 168
set_mpi
 HepMC::GenEvent, 89
set_N_Nwounded_collisions
 HepMC::HeavyIon, 157
set_Ncoll
 HepMC::HeavyIon, 157
set_Ncoll_hard
 HepMC::HeavyIon, 157
set_no_gaps_in_barcodes
 HepMC::IO_HERWIG, 197
set_normal3d
 HepMC::Polarization, 235
set_Npart_proj
 HepMC::HeavyIon, 157
set_Npart_targ
 HepMC::HeavyIon, 158
set_number_entries
 HepMC::HEPEVT_Wrapper, 168
set_Nwounded_N_collisions
 HepMC::HeavyIon, 158
set_Nwounded_Nwounded_collisions
 HepMC::HeavyIon, 158
set_parent_event_
 HepMC::GenVertex, 138
set_parents
 HepMC::HEPEVT_Wrapper, 169
set_pdf1
 HepMC::PdfInfo, 224
set_pdf2
 HepMC::PdfInfo, 224
set_pdf_id1
 HepMC::PdfInfo, 225
set_pdf_id2
 HepMC::PdfInfo, 225
set_pdf_info
 HepMC::GenEvent, 89
set_pdg_id
 HepMC::GenParticle, 119
set_phi

- HepMC::Polarization, 235
- set_polarization
 - HepMC::GenParticle, 119
- set_position
 - HepMC::GenVertex, 138
 - HepMC::HEPEVT_Wrapper, 169
- set_print_inconsistency_errors
 - HepMC::IO_HEPEVT, 191
 - HepMC::IO_HERWIG, 198
- set_production_vertex_
 - HepMC::GenParticle, 119
- set_random_states
 - HepMC::GenEvent, 89
- set_reading_event_header
 - HepMC::StreamInfo, 249
- set_scalePDF
 - HepMC::PdfInfo, 225
- set_sigma_inel_NN
 - HepMC::HeavyIon, 158
- set_signal_process_id
 - HepMC::GenEvent, 90
- set_signal_process_vertex
 - HepMC::GenEvent, 90
- set_sizeof_int
 - HepMC::HEPEVT_Wrapper, 169
- set_sizeof_real
 - HepMC::HEPEVT_Wrapper, 169
- set_spectator_neutrons
 - HepMC::HeavyIon, 158
- set_spectator_protons
 - HepMC::HeavyIon, 158
- set_status
 - HepMC::GenParticle, 120
 - HepMC::HEPEVT_Wrapper, 169
- set_theta
 - HepMC::Polarization, 235
- set_theta_phi
 - HepMC::Polarization, 235
- set_trust_beam_particles
 - HepMC::IO_HEPEVT, 191
- set_trust_both_mothers_and_
 - daughters
 - HepMC::IO_HEPEVT, 191
 - HepMC::IO_HERWIG, 198
- set_trust_mothers_before_daughters
 - HepMC::IO_HEPEVT, 192
 - HepMC::IO_HERWIG, 198
- set_undefined
 - HepMC::Polarization, 235
- set_unique_icode
 - HepMC::Flow, 57
- set_x1
 - HepMC::PdfInfo, 225
- set_x2
 - HepMC::PdfInfo, 225
- setE
 - HepMC::FourVector, 65
- setGeneratedMass
 - HepMC::GenParticle, 120
- setPhi
 - HepMC::ThreeVector, 257
- setPrecision
 - HepMC::IO_AsciiParticles, 178
- setPx
 - HepMC::FourVector, 65
- setPy
 - HepMC::FourVector, 65
- setPz
 - HepMC::FourVector, 65
- setT
 - HepMC::FourVector, 65
- setTheta
 - HepMC::ThreeVector, 257
- setX
 - HepMC::FourVector, 66
 - HepMC::ThreeVector, 257
- setY
 - HepMC::FourVector, 66
 - HepMC::ThreeVector, 258
- setZ
 - HepMC::FourVector, 66
 - HepMC::ThreeVector, 258
- sfmix
 - PythiaWrapper6_4.h, 352
- sigh
 - pin3, 227
- sigma_inel_NN
 - HepMC::HeavyIon, 158
- signal_process_id
 - HepMC::GenEvent, 90
- signal_process_vertex
 - HepMC::GenEvent, 90
- sigt
 - pin7, 229
- SimpleVector.h, 358
- size
 - HepMC::Flow, 57
 - HepMC::WeightContainer, 266
- size_type
 - HepMC::WeightContainer, 262
- sizeof_int
 - HepMC::HEPEVT_Wrapper, 170
- sizeof_real
 - HepMC::HEPEVT_Wrapper, 170
- smw
 - PythiaWrapper6_4.h, 352
- smz
 - PythiaWrapper6_4.h, 352

SOFTME
 HerwigWrapper.h, 316
spectator_neutrons
 HepMC::HeavyIon, 159
spectator_protons
 HepMC::HeavyIon, 159
status
 HepMC::GenParticle, 120
 HepMC::HEPEVT_Wrapper, 170
stream_id
 HepMC::StreamInfo, 249
StreamHelpers.cc, 359
StreamHelpers.h, 360
StreamInfo
 HepMC::StreamInfo, 246
StreamInfo.cc, 361
StreamInfo.h, 362
suggest_barcode
 HepMC::GenParticle, 120
 HepMC::GenVertex, 138
swap
 HepMC::Flow, 57
 HepMC::FourVector, 66
 HepMC::GenCrossSection, 72
 HepMC::GenEvent, 90
 HepMC::GenParticle, 120
 HepMC::GenVertex, 138
 HepMC::HeavyIon, 159
 HepMC::PdfInfo, 225
 HepMC::Polarization, 236
 HepMC::ThreeVector, 258
 HepMC::WeightContainer, 266
SWEIN
 HerwigWrapper.h, 317
t
 HepMC::FourVector, 66
 HepMC::HEPEVT_Wrapper, 170
TempMap
 HepMC::TempParticleMap, 251
TempMapIterator
 HepMC::TempParticleMap, 251
TempOrderMap
 HepMC::TempParticleMap, 251
TempParticleMap
 HepMC::TempParticleMap, 252
TempParticleMap.h, 363
testFlow.cc, 364
testFlow.cc
 FlowVec, 364
 main, 364
testHepMCIteration.h, 365
testHepMCIteration.h
 IsPhoton, 365
 IsWBoson, 365
testHepMCMethods.cc, 366
testHepMCMethods.cc
 findPiZero, 366
 particleTypes, 366
 repairUnits, 366
testHepMCMethods.h, 367
testHepMCMethods.h
 findPiZero, 367
 particleTypes, 367
 repairUnits, 367
testHerwigCopies.cc, 368
testHerwigCopies.cc
 main, 368
testPolarization.cc, 369
testPolarization.cc
 main, 369
testPrintBug.cc, 370
testPrintBug.cc
 main, 370
testPythiaCopies.cc, 371
testPythiaCopies.cc
 main, 371
testSimpleVector.cc, 372
testSimpleVector.cc
 main, 372
testUnits.cc, 373
testUnits.cc
 main, 373
testWeights.cc, 374
testWeights.cc
 main, 374
theta
 HepMC::FourVector, 67
 HepMC::Polarization, 236
 HepMC::ThreeVector, 258
ThreeVector
 HepMC::ThreeVector, 255, 256
TLOUT
 hwgev, 174
TMTOP
 HerwigWrapper.h, 317
translate_herwig_to_pdg_id
 HepMC::IO_HERWIG, 198
trust_beam_particles
 HepMC::IO_HEPEVT, 192
trust_both_mothers_and_daughters
 HepMC::IO_HEPEVT, 192
 HepMC::IO_HERWIG, 198
trust_mothers_before_daughters
 HepMC::IO_HEPEVT, 192
 HepMC::IO_HERWIG, 198
type

- HepMC::detail::disable_if<false, T >, 49
- HepMC::detail::enable_if<true, T >, 51
- umix
 - PythiaWrapper6_4.h, 352
- umixi
 - PythiaWrapper6_4.h, 352
- Units, 41
- Units.h, 375
- upevnt
 - PythiaWrapper6_4.h, 347
- upinit
 - PythiaWrapper6_4.h, 347
- use_input_units
 - HepMC::IO_GenEvent, 187
 - HepMC::StreamInfo, 249
- use_units
 - HepMC::GenEvent, 91
- v
 - PythiaWrapper6_4.h, 352
- valid_beam_particles
 - HepMC::GenEvent, 91
- value
 - HepMC::detail::is_arithmetic, 200
 - HepMC::detail::is_arithmetic<char >, 201
 - HepMC::detail::is_arithmetic<double >, 202
 - HepMC::detail::is_arithmetic<float >, 203
 - HepMC::detail::is_arithmetic<int >, 204
 - HepMC::detail::is_arithmetic<long >, 205
 - HepMC::detail::is_arithmetic<long double >, 206
 - HepMC::detail::is_arithmetic<short >, 207
 - HepMC::detail::is_arithmetic<signed char >, 208
 - HepMC::detail::is_arithmetic<unsigned char >, 209
 - HepMC::detail::is_arithmetic<unsigned int >, 210
 - HepMC::detail::is_arithmetic<unsigned long >, 211
 - HepMC::detail::is_arithmetic<unsigned short >, 212
- VCKM
 - HerwigWrapper.h, 317
- vckm
 - PythiaWrapper6_4.h, 353
- VectorConversion.h, 376
- VectorConversion.h
 - convertTo, 376
- version
 - HepMC, 32
- Version.h, 377
- versionName
 - HepMC, 32
- vertex_const_iterator
 - HepMC::GenEvent, 94
 - HepMC::GenEvent::vertex_const_iterator, 103
- vertex_iterator
 - HepMC::GenEvent, 95
 - HepMC::GenEvent::vertex_iterator, 106
 - HepMC::GenVertex, 140
 - HepMC::GenVertex::vertex_iterator, 148
- vertex_range
 - HepMC::GenEvent, 91
- vertex_root
 - HepMC::GenVertex::edge_iterator, 143
 - HepMC::GenVertex::vertex_iterator, 150
- vertices_begin
 - HepMC::GenEvent, 92
 - HepMC::GenVertex, 139
- vertices_empty
 - HepMC::GenEvent, 92
- vertices_end
 - HepMC::GenEvent, 92
 - HepMC::GenVertex, 139
- vertices_size
 - HepMC::GenEvent, 93
- VFCH
 - HerwigWrapper.h, 317
- VGCUT
 - HerwigWrapper.h, 317
- vint
 - PythiaWrapper6_4.h, 353
- vmix
 - PythiaWrapper6_4.h, 353
- vmixi
 - PythiaWrapper6_4.h, 353
- VPCUT
 - HerwigWrapper.h, 317
- VQCUT
 - HerwigWrapper.h, 317
- vxpanh
 - pin9, 231

- vxpanl
 - pin9, 231
- vxdgm
 - pin9, 231
- vxpvm
 - pin9, 231
- WBGST
 - hwgev, 175
- WeightContainer
 - HepMC::WeightContainer, 262, 263
- WeightContainer.cc, 378
- WeightContainer.h, 379
- weights
 - HepMC::GenEvent, 93
 - HepMC::GenVertex, 139
- WGTMAX
 - hwgev, 175
- WGTSUM
 - hwgev, 175
- wids
 - PythiaWrapper6_4.h, 353
- write
 - HepMC::GenCrossSection, 72
 - HepMC::GenEvent, 93
 - HepMC::WeightContainer, 266
- write_byte_num
 - HepMC::HEPEVT_Wrapper, 170
- write_comment
 - HepMC::IO_AsciiParticles, 178
 - HepMC::IO_GenEvent, 187
- write_cross_section
 - HepMC::GenEvent, 94
- write_end_listing
 - HepMC::IO_AsciiParticles, 178
- write_event
 - HepMC::IO_AsciiParticles, 178
 - HepMC::IO_BaseClass, 181
 - HepMC::IO_GenEvent, 187
 - HepMC::IO_HEPEVT, 192
- write_HepMC_IO_block_begin
 - HepMC, 30
- write_HepMC_IO_block_end
 - HepMC, 30
- write_units
 - HepMC::GenEvent, 94
- writePythiaStreamIO
 - example_PythiaStreamIO.cc, 277
- writeVersion
 - HepMC, 32
- WrongFileType
 - HepMC::IO_Exception, 183
- WSQSUM
 - hwgev, 175
- x
 - HepMC::FourVector, 67
 - HepMC::HEPEVT_Wrapper, 171
 - HepMC::ThreeVector, 258
- x1
 - HepMC::PdfInfo, 225
 - PythiaWrapper6_4.h, 353
- x2
 - HepMC::PdfInfo, 226
- xpanh
 - pin8, 230
- xpanl
 - pin8, 230
- xpbh
 - pin8, 230
- xpdir
 - pin8, 230
- xpvm
 - pin8, 230
- xsec
 - pin5, 228
- xsfx
 - pin3, 227
- xxm
 - PythiaWrapper6_4.h, 353
- Y
 - HepMC::FourVector, 67
 - HepMC::HEPEVT_Wrapper, 171
 - HepMC::ThreeVector, 259
- z
 - HepMC::FourVector, 67
 - HepMC::HEPEVT_Wrapper, 171
 - HepMC::ThreeVector, 259
- ZBINM
 - HerwigWrapper.h, 317
- zero_everything
 - HepMC::HEPEVT_Wrapper, 171
- zero_hepevt_entry
 - HepMC::IO_HERWIG, 198
- zmix
 - PythiaWrapper6_4.h, 353
- zmixi
 - PythiaWrapper6_4.h, 353
- ZPRIME
 - HerwigWrapper.h, 317